Relationship Between Track Geometry and Components Health Conditions

This manuscript (<u>permalink</u>) was automatically generated from <u>uiceds/cee-492-term-project-fall-2022-shans@5d9e933</u> on September 23, 2022.

Authors

• Arthur Bilheri

•	Negin Shafie
	Hogwarts school of witchcraft

• Shirin Qiam

Department of Civil and Environmental Engineering, University of Illinois at Urbana-Champaign · Funded by none

Sadaf Shafie

© XXXX-XXXX-XXXX · ♥ sadafs2 · ♥ NA

Department of Civil and Environmental Engineering, University of Illinois at Urbana-Champaign · Funded by none

Introduction

Railroad tracks have four main components: rail, ties, fastening systems, and ballast. The rail is the main component that supports the loads transmitted by the trains. The fastening system is responsible for fastening the rail to the ties and keeping the rail in a proper position. Fastening systems are made of spikes, tie plates, anchors, and sometimes clips. The ties are the interface between the rails and ballast. The two main materials used for ties in the United States are timber and concrete. The last layer on the railroad superstructure is the ballast. Its main functions are to spread the loads on the ground and to provide proper drainage for the track system.

These components are inspected using the LRAIL technology that combines 2D imagery and laser triangulation to assess the health and condition of each component. The collected data is processed through a DNN (Deep Convolutional Neural Network) model that identifies and classifies the components. This technology has been used under the scope of research led by the RailTEC group at UIUC, funded by the FRA-DOT with two Class I railroads in the US. The output of this technology, which will be used in this project, is described in an Excel file (filename: Datasets) attached to this proposal.

References