Safety assessment on Roslagsbanan Rail System, 2021-2022

This manuscript (<u>permalink</u>) was automatically generated from <u>uiceds/cee-492-term-project-fall-2022-time@4f8a45e</u> on September 22, 2022.

Authors

- Cecilia Karina Volpe Baridon
 - · 🕝 cvolpebaridon
- Elie Roudiere
 - · elieroudiere
 Railway Group, KTH Royal Institute of Technology Stockholm, Sweden
- Berkan Usta

Dataset Decription

The Roslagsbanan is a railway system operating in Stockholm. As part of an improvement in the transportation system, Stockholm Municipality invested in a new fleet of trains switching from X10p trains to the new X15p. In order to analyze the safety of the new trains, brake tests were conducted. During those test runs the Latronix Track Measurement (LTM) system was mounted on the train. The LTM uses laser beams and an on-board computer to perform measurements over railroad track while the train drives on the track at normal speed.

The data that will be used in this study was collected using the LTM system affixed to a Roslagsbanan vehicle. While the train was running over the sections, the level of each rail, alignment, curvature, cant, gauge and twist were measured every 256mm. The data was compiled in csv files and was collected between October 2021 and May 2022 with an approximate interval of one month. In other words, a given section of track typically has around six measurement files. The total amount of data is 60 CSV files of 30,000 to 80,000 rows each, for a total of 1.5GB of data.

These data and measurements are property of Latronix AB of Sweden, and are used with their permission for research and educational purposes only.

In the CSV files the structure of columns is as follows:

- Marker and Marker_Offset: The kilometre post of the data point, where Marker is in km and Marker_offset is in m. In other words, if Marker=20 and MArker_offset=250.5, the kilometre post is 20,250.5
- Coordinate_northing, Coordinate_easting, Latitude, Longitude: As their name suggests, they are the coordinates of the data point in northings and eastings, as well as latitude and longitude.
- Speed: records the speed in km/h at which the measurement was taken. This is especially relevant as different operating speeds give different tolerances in terms of the measured properties.

- Level_left and Level_right D0, D1, D2, D3: The deviation of the longitudinal level (height) of the left and right rail in mm, compared to its reference position. D0, D1, D2, D3 correspond to different measurement wavelengths of the same data.
- Alignment_left and Alignment_right D0, D1, D2, D3: The deviation in longitudinal alignment ("straightness")of the left and right rail in mm, compared to its reference position. D0, D1, D2, D3 correspond to different measurement wavelengths of the same data.
- Track_gauge: The deviation in the spacing between the rails in mm, from a reference of 891mm.
- Curvature: The curvature of the track at that location, in m^-1.
- Cant: The cant (inclination) of the track at the location, in mm from the horizontal.
- Twist_3m, Twist_6m: The rate of change in cant over a 3m or 6m distance.
- Level_versine_left_5m, Level_versine_right_5m: Derived from Level_left and Level_right, this level deviation in mm corresponds to longitudinal versine measurement of the top of rail over a 5m distance. This historical metric is more commonly used in railway engineering and is thus provided.
- Alignment_versine_left_10m, Alignment_versine_right_10m: Similarly to the versine level, this measure of alignment in mm uses versines over a 10m distance.

Finally, Track_name, Track_class, Station_flag and Link_name,Pos_unfiltered Pos_filtered NTP_sync, Cant_D1, Std_level, Std_alignment, Std_cant, Quality_1 are mainly for internal use and not part of the analysis.

Project proposal

The main goal of this project is to identify patterns in the data, especially the track degradation of certain sections, and thus to analyze the change in railway safety during this time. A first approach will be to define degradation trends, and build a model to process the data that finds them automatically. Then, the study will attempt to find external factors which caused the observed trends. The analysis will include graphics of the parameters over time as well as comparing them over the sections to provide a better understanding of the data visually.

This research will help assess system performance, identify possible maintenance schedules, and provide useful data for further research in this area. The study also falls within the scope of developing predictive maintenance in civil engineering and railways. Creating and improving analysis and predictive maintenance models such as this one can contribute to an increased safety of rail networks and a higher quality of service for passengers, They will benefit from fewer impromptu interruptions of service due to track maintenance, or even unsafe track causing line closures.

This manuscript is a template (aka "rootstock") for <u>Manubot</u>, a tool for writing scholarly manuscripts. Use this template as a starting point for your manuscript.

The rest of this document is a full list of formatting elements/features supported by Manubot. Compare the input (.md files in the /content directory) to the output you see below.

Basic formatting

Bold text

Semi-bold text

Centered text

Right-aligned text

Italic text

Combined italics and bold

Strikethrough

- 1. Ordered list item
- 2. Ordered list item
 - a. Sub-item
 - b. Sub-item
 - i. Sub-sub-item
- 3. Ordered list item
 - a. Sub-item
- List item
- · List item
- · List item

subscript: H₂O is a liquid

superscript: 2¹⁰ is 1024.

unicode superscripts⁰¹²³⁴⁵⁶⁷⁸⁹

unicode subscripts₀₁₂₃₄₅₆₇₈₉

A long paragraph of text. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Putting each sentence on its own line has numerous benefits with regard to <u>editing</u> and <u>version</u> <u>control</u>.

Line break without starting a new paragraph by putting two spaces at end of line.

Document organization

Document section headings:

Heading 1

Heading 2

Heading 3

Heading 4

Heading 5

Heading 6



Horizontal rule:

Heading 1's are recommended to be reserved for the title of the manuscript.

Heading 2's are recommended for broad sections such as Abstract, Methods, Conclusion, etc.

Heading 3's and Heading 4's are recommended for sub-sections.

Links

Bare URL link: https://manubot.org

Long link with lots of words and stuff and junk and bleep and blah and stuff and other stuff and more stuff yeah

Link with text

Link with hover text

Link by reference

Citations

Citation by DOI [1].

Citation by PubMed Central ID [2].

Citation by PubMed ID [3].

Citation by Wikidata ID [4].

Citation by ISBN [5].

Citation by URL [6].

Citation by alias [7].

Multiple citations can be put inside the same set of brackets [1,5,7]. Manubot plugins provide easier, more convenient visualization of and navigation between citations [2,3,7,8].

Citation tags (i.e. aliases) can be defined in their own paragraphs using Markdown's reference link syntax:

Referencing figures, tables, equations

Figure 1

Figure 2

```
Figure 3

Figure 4

Table 1

Equation 1

Equation 2
```

Quotes and code

Quoted text

Quoted block of text

Two roads diverged in a wood, and I—I took the one less traveled by, And that has made all the difference.

Code in the middle of normal text, aka inline code.

Code block with Python syntax highlighting:

```
from manubot.cite.doi import expand_short_doi

def test_expand_short_doi():
    doi = expand_short_doi("10/c3bp")
    # a string too long to fit within page:
    assert doi == "10.25313/2524-2695-2018-3-vliyanie-enhansera-copia-i-
        insulyatora-gypsy-na-sintez-ernk-modifikatsii-hromatina-i-
        svyazyvanie-insulyatornyh-belkov-vtransfetsirovannyh-geneticheskih-
        konstruktsiyah"
```

Code block with no syntax highlighting:

```
Exporting HTML manuscript
Exporting DOCX manuscript
Exporting PDF manuscript
```

Figures



Figure 1: A square image at actual size and with a bottom caption. Loaded from the latest version of image on GitHub.



Figure 2: An image too wide to fit within page at full size. Loaded from a specific (hashed) version of the image on GitHub.



Figure 3: A tall image with a specified height. Loaded from a specific (hashed) version of the image on GitHub.



Figure 4: A vector .svg image loaded from GitHub. The parameter sanitize=true is necessary to properly load SVGs hosted via GitHub URLs. White background specified to serve as a backdrop for transparent sections of the image.

Tables

Table 1: A table with a top caption and specified relative column widths.

Bowling Scores	Jane	John	Alice	Bob
Game 1	150	187	210	105
Game 2	98	202	197	102
Game 3	123	180	238	134

Table 2: A table too wide to fit within page.

	Digits 1-33	Digits 34-66	Digits 67-99	Ref.
pi	3.14159265358979323 846264338327950	28841971693993751 0582097494459230	78164062862089986 2803482534211706	piday.org
е	2.71828182845904523 536028747135266	24977572470936999 5957496696762772	40766303535475945 7138217852516642	nasa.gov

 Table 3: A table with merged cells using the attributes plugin.

	Colors		
Size	Text Color	Background Color	
big	blue	orange	
small	black	white	

Equations

A LaTeX equation:

$$\int_0^\infty e^{-x^2} dx = \frac{\sqrt{\pi}}{2} \tag{1}$$

An equation too long to fit within page:

$$x = a + b + c + d + e + f + g + h + i + j + k + l + m + n + o + p + q + r + s + t + u + v + w + x + y + z + 1 + 2 + 3 + 4 + 5 + 6 + 7 + 8 + 9$$
(2)

Special

▲ WARNING The following features are only supported and intended for .html and .pdf exports. Journals are not likely to support them, and they may not display correctly when converted to other formats such as .docx.

LINK STYLED AS A BUTTON

Adding arbitrary HTML attributes to an element using Pandoc's attribute syntax:

Manubot Manubot Manubot Manubot Manubot. Manubot Manubot Manubot Manubot. Manubot. Manubot Manubot. Manubot. Manubot. Manubot. Manubot.

Adding arbitrary HTML attributes to an element with the Manubot attributes plugin (more flexible than Pandoc's method in terms of which elements you can add attributes to):

Manubot Manubot.

Available background colors for text, images, code, banners, etc:

white lightgrey grey darkgrey black lightred lightyellow lightgreen lightblue lightpurple red orange yellow green blue purple

Using the Font Awesome icon set:



Light Grey Banner

useful for general information - manubot.org

Blue Banner

useful for important information - manubot.org

\Omega Light Red Banner

useful for warnings - manubot.org

Dataset Decription

The Roslagsbanan is a railway system operating in Stockholm. As part of an improvement in the transportation system, Stockholm Municipality invested in a new fleet of trains switching from X10p trains to the new X15p. In order to analyze the safety of the new trains, brake tests were conducted. During those test runs the Latronix Track Measurement (LTM) system was mounted on the train. The LTM uses laser beams and an on-board computer to perform measurements over railroad track while the train drives on the track at normal speed.

The data that will be used in this study was collected using the LTM system affixed to a Roslagsbanan vehicle. While the train was running over the sections, the level of each rail, alignment, curvature, cant, gauge and twist were measured every 256mm. The data was compiled in csv files and was collected between October 2021 and May 2022 with an approximate interval of one month. In other words, a given section of track typically has around six measurement files. The total amount of data is 60 CSV files of 30,000 to 80,000 rows each, for a total of 1.5GB of data.

These data and measurements are property of Latronix AB of Sweden, and are used with their permission for research and educational purposes only.

In the CSV files the structure of columns is as follows:

- Marker and Marker_Offset: The kilometre post of the data point, where Marker is in km and Marker_offset is in m. In other words, if Marker=20 and MArker_offset=250.5, the kilometre post is 20,250.5
- Coordinate_northing, Coordinate_easting, Latitude, Longitude: As their name suggests, they are the coordinates of the data point in northings and eastings, as well as latitude and longitude.
- Speed: records the speed in km/h at which the measurement was taken. This is especially relevant as different operating speeds give different tolerances in terms of the measured properties.
- Level_left and Level_right D0, D1, D2, D3: The deviation of the longitudinal level (height) of the left and right rail in mm, compared to its reference position. D0, D1, D2, D3 correspond to different measurement wavelengths of the same data.
- Alignment_left and Alignment_right D0, D1, D2, D3: The deviation in longitudinal alignment
 ("straightness")of the left and right rail in mm, compared to its reference position. D0, D1, D2, D3
 correspond to different measurement wavelengths of the same data.

- Track_gauge: The deviation in the spacing between the rails in mm, from a reference of 891mm.
- Curvature: The curvature of the track at that location, in m^-1.
- Cant: The cant (inclination) of the track at the location, in mm from the horizontal.
- Twist_3m, Twist_6m: The rate of change in cant over a 3m or 6m distance.
- Level_versine_left_5m, Level_versine_right_5m: Derived from Level_left and Level_right, this level deviation in mm corresponds to longitudinal versine measurement of the top of rail over a 5m distance. This historical metric is more commonly used in railway engineering and is thus provided.
- Alignment_versine_left_10m, Alignment_versine_right_10m: Similarly to the versine level, this measure of alignment in mm uses versines over a 10m distance.

Finally, Track_name, Track_class, Station_flag and Link_name,Pos_unfiltered Pos_filtered NTP_sync, Cant_D1, Std_level, Std_alignment, Std_cant, Quality_1 are mainly for internal use and not part of the analysis.

Project proposal

The main goal of this project is to identify patterns in the data, especially the track degradation of certain sections, and thus to analyze the change in railway safety during this time. A first approach will be to define degradation trends, and build a model to process the data that finds them automatically. Then, the study will attempt to find external factors which caused the observed trends. The analysis will include graphics of the parameters over time as well as comparing them over the sections to provide a better understanding of the data visually.

This research will help assess system performance, identify possible maintenance schedules, and provide useful data for further research in this area. The study also falls within the scope of developing predictive maintenance in civil engineering and railways. Creating and improving analysis and predictive maintenance models such as this one can contribute to an increased safety of rail networks and a higher quality of service for passengers, They will benefit from fewer impromptu interruptions of service due to track maintenance, or even unsafe track causing line closures.

References

1. Sci-Hub provides access to nearly all scholarly literature

Daniel S Himmelstein, Ariel Rodriguez Romero, Jacob G Levernier, Thomas Anthony Munro, Stephen Reid McLaughlin, Bastian Greshake Tzovaras, Casey S Greene *eLife* (2018-03-01) https://doi.org/ckcj

DOI: 10.7554/elife.32822 · PMID: 29424689 · PMCID: PMC5832410

2. Reproducibility of computational workflows is automated using continuous analysis

Brett K Beaulieu-Jones, Casey S Greene

Nature biotechnology (2017-04) https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6103790/
DOI: 10.1038/nbt.3780 · PMID: 28288103 · PMCID: PMC6103790

3. **Bitcoin for the biological literature.**

Douglas Heaven

Nature (2019-02) https://www.ncbi.nlm.nih.gov/pubmed/30718888

DOI: 10.1038/d41586-019-00447-9 · PMID: 30718888

4. Plan S: Accelerating the transition to full and immediate Open Access to scientific publications

cOAlition S

(2018-09-04) https://www.wikidata.org/wiki/Q56458321

5. **Open access**

Peter Suber *MIT Press* (2012)

ISBN: 9780262517638

6. Open collaborative writing with Manubot

Daniel S Himmelstein, Vincent Rubinetti, David R Slochower, Dongbo Hu, Venkat S Malladi, Casey S Greene, Anthony Gitter

Manubot (2020-05-25) https://greenelab.github.io/meta-review/

7. Opportunities and obstacles for deep learning in biology and medicine

Travers Ching, Daniel S Himmelstein, Brett K Beaulieu-Jones, Alexandr A Kalinin, Brian T Do, Gregory P Way, Enrico Ferrero, Paul-Michael Agapow, Michael Zietz, Michael M Hoffman, ... Casey S Greene

Journal of The Royal Society Interface (2018-04) https://doi.org/gddkhn DOI: 10.1098/rsif.2017.0387 • PMID: 29618526 • PMCID: PMCID: PMC5938574

8. Open collaborative writing with Manubot

Daniel S Himmelstein, Vincent Rubinetti, David R Slochower, Dongbo Hu, Venkat S Malladi, Casey S Greene, Anthony Gitter

PLOS Computational Biology (2019-06-24) https://doi.org/c7np

DOI: 10.1371/journal.pcbi.1007128 · PMID: 31233491 · PMCID: PMC6611653