



LAST CHANGE DETAILS		RELEASED DATE	ECN No.
3.20 SLOTS LENGHTENED		26/09/2019	4629
LASER CUTTING MUST BE PERFORMED WITH NITROGEN FEED		REMOVE ALL BURRS AND SHARP EDGES	
ANY EDGES DARKENED THROUGH OXIDATION ETC. DURING THE CUTTING PROCESS MUST BE CLEANED BACK TO A BRIGHT METAL SURFACE		UNLESS OTHERWISE SPECIFIED: - SURFACE FINISH ON ALL FLAT SURFACES IS TO BE GRAIN FINISH 240 - GRAINED FINISH DIRECTION IS NOT IMPORTANT	

3RD ANGLE PROJECTION

TOLERANCING PER: B.S. 308

DRAWN

GJF

CHECKED

QR

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN mm

TOLERANCES:

1 PLACE DECIMAL

±0.3

2 PLACE DECIMAL

±0.2

HOLES Ø

±0.1

ANGULAR

±1.0°

FOLDED

±0.2

FLAT

±0.1

FLAT FACES SHOULD BE FREE FROM DENTS, SCRATCHES AND MARKS OF ANY KIND.

PROPRIETARY AND CONFIDENTIAL
COPYRIGHT UHV DESIGN

UHV Design

tel: 01323 811188

TITLE:

LIMIT SWITCH BRACKET 2

DWG. NO.

20895-020

MATERIAL

AISI 316

FINISH

SUPPLY CLEAN

WEIGHT (g)

903.41

REV

2

A3

IF IN DOUBT ASK

DO NOT SCALE DRAWING

SHEET 1 OF 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UHV DESIGN.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UHV DESIGN IS PROHIBITED.