

API Endpoints Documentation:

pariaj_backend

This document provides technical details for several key endpoints in the pariaj_backend project. These endpoints are primarily designed for administrative use and user-specific data retrieval.

1. User Receipts Endpoints

These endpoints retrieve a user's betting receipts filtered by their status.

GET /api/receipts/ongoing/:id/user-info/info

GET /api/receipts/winning/:id/user-info/info

GET /api/receipts/loosing/:id/user-info/info

- **Description:** Returns all receipts for a specific user with the corresponding status (ONGOING, WINNING, or LOOSING).
- **Path Parameters:**
 - `id`: The UUID of the user.
- **Headers:**
 - `Content-Type`: `application/json`
- **Response (200 OK):**

```
{
  "receipts": [
    {
      "id": "string",
      "receiptStatus": "ONGOING | WINNING | LOOSING",
      "totalOdds": number,
      "stake": number,
      "potentialWin": number,
      "createdAt": "date-time",
      "selections": [
        {
          "id": "string",
```

```

        "eventId": "string",
        "eventName": "string",
        "league": "string",
        "market": "string",
        "odds": number,
        "outcome": "string",
        "sport": "string",
        "BetStatus": "GOING | WIN | LOST | CANCELLED",
        "status": "string (optional)",
        "timestamp": number
    }
  ]
}

```

- **Error Responses:**

- 401 Unauthorized: User ID missing in request.
- 500 Internal Server Error: Server error.

2. Better (User) History Endpoints (Admin)

These endpoints retrieve deposit and withdrawal histories for a specific better, specifically for admin views.

GET /histories/better/:betterId/depot/admin

GET /histories/better/:betterId/retrait/admin

- **Description:** Retrieves history records for a specific better. depot returns deposits, and retrait returns withdrawals.
- **Path Parameters:**
 - betterId: The UUID of the better.
- **Query Parameters:**
 - page (optional): Page number (default: 1).
 - limit (optional): Number of items per page (default: 20, max: 100).
 - timeFilter (optional): Filters records by time range. Options: today, week, month, year, all (default: all).
- **Headers:**
 - x-api-key: Must match the INTERNAL_API_KEY environment variable.
- **Response (200 OK):**

```

{
  "histories": [
    {
      "id": "string",
      "type": "Depot | Retrait",
      "montant": number,
      "userId": "string",
      "betterId": "string",
      "createdAt": "date-time",
      "sellerName": "string",
      "user": { "id": "string", "email": "string", "firstname":
        "string", "lastname": "string", "role": "string",
        "isBlocked": boolean },
      "better": { "id": "string", "phone": "string" }
    }
  ],
  "total": number,
  "page": number,
  "limit": number,
  "totalPages": number
}

```

- **Error Responses:**

- 400 Bad Request: betterId is missing.
- 401 Unauthorized: API key is missing or invalid.
- 500 Internal Server Error: Server error.

3. User Listing Endpoint

GET /auth/users

- **Description:** Lists all registered users with their current balance info. Supports pagination and phone-based searching.
- **Query Parameters:**
 - page (optional): Page number (default: 1).
 - limit (optional): Number of items per page (default: 20).
 - phone (optional): Partial phone number to filter users.
- **Headers:**
 - x-api-key: Must match the INTERNAL_API_KEY environment variable.
- **Response (200 OK):**

```

{
  "users": [
    {
      "id": "string",

```

```
        "email": "string",
        "phone": "string",
        "additionalInfo": {
            "Amount": number
        }
    },
    ],
    "total": number,
    "page": number,
    "limit": number,
    "totalPages": number
}
```

- **Error Responses:**

- 403 Forbidden: API key is invalid or unauthorized.
- 500 Internal Server Error: Server error.