Mineral Mart API Integration Document

1. Overview

This document defines the API integration between the consuming system and Mineral Mart for:

- Fetching available orders against a license number
- Pushing the generated Rawanna number against the selected order

---

2. Base URL

```
https://mineralmart.ukmdtss.in/api/
```

---

3. Authentication

Every API request must contain the following HTTP header:

```
Auth-Token: <YOUR_AUTH_TOKEN>
```

The authentication token will be shared securely with the integrating party.

The actual authentication token should not be included in the API integration document.

---

4. Get Orders

This API returns the available Mineral Mart orders against a license number.

Endpoint

```
GET /mnrl-mngmnt/orders
```

Full Endpoint

```
https://mineralmart.ukmdtss.in/api/mnrl-mngmnt/orders
```

Request Header

```
Auth-Token: <YOUR_AUTH_TOKEN>
```

Query Parameters

Parameter	Required	Description
`license_no`	Yes	License number for which available orders are required

Sample Request

```
GET /mnrl-mngmnt/orders?license_no=HP00011725
```

Sample Response

```
{
  "status": "success",
  "data": [
    {
      "id": 1,
      "ord_no": "ORD20261"
    },
    {
      "id": 2,
      "ord_no": "ORD20262"
    }
  ]
}
```

Response Parameters

Parameter	Description
`status`	API response status
`data`	List of available orders
`data[].id`	Unique Mineral Mart order ID
`data[].ord_no`	Mineral Mart order number

1.0 Order ID Mapping

The `id` returned by the Get Orders API must be used as `oid` while pushing the Rawanna.

Example response:

```
{
  "id": 1,
  "ord_no": "ORD20261"
}
```

Mapping:

```
Order ID     = 1
Order Number = ORD20261
oid          = 1
```

`ord_no` should not be sent in place of `oid`.

---

5. Push Rawanna

This API sends the generated Rawanna number to Mineral Mart against the selected order.

Endpoint

```
POST /mnrl-mngmnt/push-rawanna
```

Full Endpoint

```
https://mineralmart.ukmdtss.in/api/mnrl-mngmnt/push-rawanna
```

Request Headers

```
Auth-Token: <YOUR_AUTH_TOKEN>
Content-Type: application/x-www-form-urlencoded
```

Request Parameters

Parameter	Required	Description
`oid`	Yes	Order ID received from the Get Orders API
`rawanna_no`	Yes	Rawanna number generated by the integrated system

Sample Request

```
oid=1
rawanna_no=RAW202600001
```

---

6. Complete Integration Flow

```
License Number
      ↓
Get Orders API
      ↓
Receive Available Orders
      ↓
User / System Selects Order
      ↓
Get Order ID (id)
      ↓
Generate Rawanna
      ↓
Get Rawanna Number
```

```
      ↓
Push Rawanna API
      ↓
Store Response / Integration Status
```

---

7. API Summary

API	Method	Purpose
`/mnrl-mngmnt/orders`	GET	Fetch available orders against a license number
`/mnrl-mngmnt/push-rawanna`	POST	Push generated Rawanna number against an order

---

8. Important Integration Notes

1. All requests must contain the `Auth-Token` header.
2. The authentication token must be shared and stored securely.
3. The actual authentication token must not be included in public documentation.
4. Use the `id` returned by the Orders API as `oid`.
5. Do not use `ord_no` as `oid`.
6. The Rawanna number must be sent through the `rawanna_no` parameter.
7. API responses should be stored for integration logging and troubleshooting.
8. Duplicate Rawanna submission should be prevented by the integrating system wherever applicable.
9. Network and unsuccessful API responses should be handled appropriately by the consuming system.