

## Homework 2

Yu-Chieh Kuo B07611039

### 1 Overview

This assignment asks us to evaluate the classification performance of the following classification methods: Bernoulli Naïve Bayes method, SVM method with linear and RBF kernel, then show their precision, recall, and F1 scores and plot their precision recall curves on report.

### 2 Precision, Recall, and F1 scores

The precision, recall and F1 scores for these three method are represented as below.

Precision, Recall, and F1 scores are as below.				
	precision	recall	f1-score	support
1	0.40	1.00	0.57	2
2	0.00	0.00	0.00	1
3	1.00	1.00	1.00	1
4	1.00	1.00	1.00	2
5	1.00	1.00	1.00	1
6	1.00	1.00	1.00	2
7	1.00	1.00	1.00	1
8	1.00	1.00	1.00	3
9	1.00	1.00	1.00	2
10	1.00	0.33	0.50	3
11	1.00	1.00	1.00	1
12	1.00	1.00	1.00	1
accuracy			0.85	20
macro avg	0.87	0.86	0.84	20
weighted avg	0.89	0.85	0.83	20
F1 scores = 0.8321428571428571				
Precision = 0.89				
recall = 0.85				

Figure 1: Precision, Recall, and F1 scores for Bernoulli Naïve Bayes method

Precision, Recall, and F1 scores are as below.

	precision	recall	f1-score	support
1	1.00	1.00	1.00	4
2	1.00	1.00	1.00	3
3	1.00	1.00	1.00	2
4	1.00	1.00	1.00	1
5	1.00	1.00	1.00	2
6	1.00	1.00	1.00	3
8	1.00	1.00	1.00	1
9	1.00	1.00	1.00	1
11	1.00	1.00	1.00	1
13	1.00	1.00	1.00	2
accuracy			1.00	20
macro avg	1.00	1.00	1.00	20
weighted avg	1.00	1.00	1.00	20

F1 scores : 1.0  
Precision : 1.0  
recall : 1.0

Figure 2: Precision, Recall, and F1 scores for SVM method with linear kernel

Precision, Recall, and F1 scores are as below.

	precision	recall	f1-score	support
1	1.00	1.00	1.00	1
2	1.00	1.00	1.00	1
3	1.00	1.00	1.00	3
4	1.00	1.00	1.00	1
6	1.00	1.00	1.00	1
7	1.00	1.00	1.00	3
10	1.00	1.00	1.00	4
11	1.00	1.00	1.00	1
12	1.00	1.00	1.00	2
13	1.00	1.00	1.00	3
accuracy			1.00	20
macro avg	1.00	1.00	1.00	20
weighted avg	1.00	1.00	1.00	20

F1 scores : 1.0  
Precision : 1.0  
recall : 1.0

Figure 3: Precision, Recall, and F1 scores for SVM method with RBF kernel

### 3 Precision Recall Curves

The precision recall curves for these three method are represented as below.




Figure 4: Precision Recall curve for Bernoulli Naïve Bayes method




Figure 5: Precision Recall curve for SVM method with linear kernel




Figure 6: Precision Recall curve for SVM method with RBF kernel

## 4 Score on Kaggle

The submission score on Kaggle is shown as below. I get 0.98222 on this competition, ranking at 14th before the deadline.




Figure 7: Score on Kaggle

## 5 Implement

### 5.1 Preprocess

1. Import all necessary libraries, for example, sklearn, numpy, pandas, etc.
2. Lowercase all words in docs, eliminate the stop word in English, replace EOL.
3. Separate the testing data set and the training data set.

```
1 # classes stores the given testing data set via a 2D array
2 labels = []
3 for q in range(0, len(docs)):
```

```

4     for i in range(0, 13):
5         for j in range(0, 15):
6             if q + 1 == classes[i][j]:
7                 labels.append([classes[i][j], i+1])
8 labels = pd.DataFrame(sorted(labels, key = lambda l:l[0]), columns
9                        = ['training_id', 'classes'])
10 training_docs = docs[docs['id'].isin(labels['training_id'])]
10 testing_docs = docs[~docs['id'].isin(labels['training_id'])]

```

Listing 1: Preprocess

## 5.2 Bernoulli Naïve Bayes

```

1 binary_vectorizer = CountVectorizer(binary = True)
2 binary_vectors = binary_vectorizer.fit_transform(training_docs['text'])
3 binary_vectors_test = binary_vectorizer.transform(testing_docs['text'])
4 x_train, x_test, y_train, y_test = train_test_split(binary_vectors,
5               labels['classes'], test_size = 0.1) # amazing method taught by my
6               classmates
7 model = BernoulliNB()
8 model.fit(x_train, y_train)
9 prediction = []
10 expectation = []
11 prediction.extend(model.predict(x_test))
12 expectation.extend(y_test)

```

Listing 2: Bernoulli Naïve Bayes

## 5.3 Linear Kernel SVM

```

1 Tfidf_vectorizer = TfidfVectorizer(stop_words = 'english')
2 Tfidf_vectors_training = Tfidf_vectorizer.fit_transform(training_docs['
3   text'])
4 Tfidf_vectors_testing = Tfidf_vectorizer.transform(testing_docs['text'
5   ])
6 x_train, x_test, y_train, y_test = train_test_split(
7   Tfidf_vectors_training, labels['classes'], test_size = 0.1)
8 SVC_Linear_model = SVC(kernel='linear', C = 1.0)
9 SVC_Linear_model.fit(x_train, y_train)
10
11 prediction = []
12 expectation = []
13 prediction.extend(SVC_Linear_model.predict(x_test))
14 expectation.extend(y_test)

```

Listing 3: Linear Kernel SVM

## 5.4 RBF Kernel SVM

```

1 Tfidf_vectorizer = TfidfVectorizer(stop_words = 'english')
2 Tfidf_vectors_training = Tfidf_vectorizer.fit_transform(training_docs['
3   text'])

```

```

3 TFIDF_vectors_testing = TFIDF_vectorizer.transform(testing_docs['text'
4 ])
5
6 x_train, x_test, y_train, y_test = train_test_split(
7     TFIDF_vectors_training, labels['classes'], test_size = 0.1)
8 SVC_RBF_model = SVC(kernel='RBF', C = 1.0)
9 SVC_RBF_model.fit(x_train, y_train)
10
11 prediction = []
12 expectation = []
13
14 prediction.extend(SVC_RBF_model.predict(x_test))
15 expectation.extend(y_test)

```

Listing 4: RBF Kernel SVM

## 5.5 Representation of scores

```

1 print("Precision, Recall, and F1 scores are as below.")
2 print(metrics.classification_report(expectation, prediction))
3 print("F1 scores :", metrics.f1_score(expectation, prediction, average='
4     weighted'))
5 print("Precision :", metrics.precision_score(expectation, prediction,
6     average='weighted'))
7 print("recall :", metrics.recall_score(expectation, prediction, average
8     ='weighted'))

```

Listing 5: Representation of scores

## 5.6 Plotting

```

1 precision = dict()
2 recall = dict()
3 for i in range(13):
4     precision[i], recall[i], thresholds = metrics.precision_recall_curve
5     (expectation, prediction, pos_label = (i + 1))
6     plt.plot(recall[i], precision[i], lw = 2, label = 'class {}'.format(
7         i + 1))
8
9 plt.xlabel("Recall")
10 plt.ylabel("Precision")
11 plt.legend(loc = "upper right")
12 plt.title("Precision Recall Curve")
13 plt.show()

```

Listing 6: Plotting