**College of Information Science and Engineering, Huaqiao University**
No. 668 Jimei Avenue, Xiamen, Fujian 361021, P. R. China Corresponding Author: Fang Duan, Ph.D. (nkfetsh@gmail.com)

**Date:** October 26, 2026 **Topic / Section:** Brain–Computer Interfaces & Neural Signal Processing

**To:** Prof. Warren M. Grill, Editor-in-Chief, *Journal of Neural Engineering* (JNE)
Department of Biomedical Engineering, Duke University, Durham, NC 27708, USA

**Subject:** Submission of Research Paper: **"Physiology-Guided Temporal Fusion for Cross-Subject EEG–fNIRS Brain–Computer Interfaces"**

Dear Prof. Grill and Members of the Editorial Board,

We are pleased to submit our original research manuscript entitled **"Physiology-Guided Temporal Fusion for Cross-Subject EEG–fNIRS Brain–Computer Interfaces"** for consideration for publication as a **Research Paper** in the *Journal of Neural Engineering* (JNE).

**Context & Neural Engineering Challenge:** Hybrid EEG–fNIRS interfaces offer a powerful non-invasive window into neural function by pairing high-temporal-resolution electrophysiology with localized capillary hemodynamics. However, developing zero-calibration, cross-subject brain–computer interfaces (BCIs) remains constrained by the fundamental biological timescale disparity between electrophysiological transients (milliseconds) and capillary hemodynamic responses (seconds). When unconstrained deep cross-attention networks are trained in cross-subject leave-one-subject-out (LOSO) regimes, they frequently learn spurious, acausal alignments where sluggish hemodynamic tokens mistakenly attend to future neural activations ($\delta_{ij} < 0$), impairing generalization to unseen participants.

**Key Contributions & Empirical Rigor:** To resolve this biophysical bottleneck, we propose **NVC-DelayFormer**, an architecture that embeds biophysical neurovascular timing priors directly into multimodal cross-attention. Our contributions are substantiated through rigorous participant-isolated evaluations and open-science benchmarking:

1. **Physiology-Guided Cross-Attention Formulation:** Multi-head cross-attention is parameterized by multicenter Gaussian delay priors grounded in canonical hemodynamic response delay windows ($\tau_h \in \{3.5, 4.5, 5.5, 6.5\}$ s) and token timestamp masks that explicitly eliminate acausal backwards-in-time connections, ensuring temporal precedence across modalities.
2. **Factorial Ablation & Dual-Cohort LOSO Evaluation:** In the primary 29-participant TU Berlin cohort, factorial ablations isolate the contributions of the delay prior and causal mask. Separately trained 15-fold LOSO evaluation on the independent Buccino et al. cohort, acquired with different EEG–fNIRS hardware, yielded 79.83% accuracy (Supplementary Section S.V).
3. **Unsupervised Recursive Covariance Alignment (CrEA):** To tackle inter-subject covariance drift during test time, we introduce Causal Recursive Euclidean Alignment (CrEA), which recursively updates reference covariances online without session lookahead, reducing relative covariance error from 45.15% to 29.38% within the first 8 trials under trace-matched reference covariance (reaching 3.60% asymptotically). Across 29 participants and three random seeds, NVC-DelayFormer achieves a grand mean accuracy of **78.22% ± 1.00%** (primary seed: **79.37% ± 7.73%**), significantly exceeding standard 2D-EEGNet (72.89%, $p = 1.10 \times 10^{-4}$) and unconstrained cross-attention ($p = 7.18 \times 10^{-4}$). In task-specific training, accuracy reaches **73.24%** for working memory and **66.32%** for motor imagery.
4. **Compact Model and Measured Inference:** With **63,932 trainable parameters** and **24.79 M MACs**, the model requires 17.5× fewer parameters than EEG Conformer. Batch-one forward inference latency was **2.22 ms** on an NVIDIA RTX 4060 Laptop GPU.

**Mandatory Declarations & Guidelines Compliance:**

- **Originality & Exclusivity:** This manuscript represents original scientific work not published previously and not currently under consideration elsewhere.
- **Preprint & Conference Disclosure:** No preprint or prior conference version of this work exists, and no text recycling has occurred.
- **Authorship Approval:** All authors have read, critically reviewed, and approved the final manuscript and agree with its submission to JNE.
- **Ethical Approval:** This study reanalyzed de-identified public data. The original TU Berlin collections were approved under protocol SH_01_20150330; the Buccino et al. collection was approved by the University of Houston Institutional Review Board. Both original studies reported written participant consent.
- **Conflict of Interest & Funding:** The authors declare no competing financial or non-financial interests. No specific external grant supported this research.
- **Reproducibility & Open Science:** Source code, available example checkpoints, test suites, and audit logs are openly accessible at GitHub (ujujuj3061831150/nvc-delayformer-bci).

We believe that the interdisciplinary neuroengineering methodology and rigorous dual-cohort validation presented in this paper will be of strong interest to the readership of the *Journal of Neural Engineering*. Should the Editor or reviewers require any further details, clarifications, or access to intermediate audit artifacts, please do not hesitate to contact the corresponding author; we remain entirely at your disposal throughout the evaluation process.

Thank you very much for your time, consideration, and thoughtful evaluation of our work.

Respectfully submitted,

**Fang Duan**, Ph.D. (Corresponding Author)
Lecturer
College of Information Science and Engineering
Huaqiao University, Xiamen 361021, China
E-mail: nkfetsh@gmail.com
ORCID: 0000-0003-0982-2206

**Hongjie Chen** (First Author)
Graduate Researcher
College of Information Science and Engineering
Huaqiao University, Xiamen 361021, China
E-mail: chenhj976@gmail.com