To-do

Converting ICLR workshop → ACL workshop

Based on the ARR CFP and ACLPUB formatting rules (ACL 2026; no ACL 2027 CFP yet). The target workshop's own CFP wins where it differs. Struck-through items are done in this `ACL/` copy; **[INPUT]** items need a decision or text from you.

- **[INPUT]** Which ACL workshop, deadline, short (4pp) vs long (8pp), archival or not, and whether it uses the Responsible NLP checklist. After conversion the main text (title to end of Discussion, including the two full-width figures) runs to about 3.5 pages, inside a 4pp short-paper limit (measured after dropping the per-section float barrier and moving Figs. 1–2 earlier in the source).
- **[INPUT]** Write the Ethical Considerations text (worth having given misalignment/sycophancy adapters).
- **[INPUT]** Fold any limitations listed elsewhere in this to-do (sham LoRA, $n = 1$ adapter, forced-choice only) into the Limitations section; it must not add new experiments/figures/analysis.
- **[INPUT]** Anonymity: `\provbase` (and the Reproducibility section's URL) still point at the real GitHub repo. Create an Anonymous GitHub mirror (anonymous.4open.science) and replace the URL in `\provbase`; no Dropbox or other download-tracking hosts.
- **[INPUT]** AI use: ACL wants disclosure in the checklist and Acknowledgements. Decide whether to keep the separate AI Use Statement heading or turn it into an Acknowledgements section (omitted from the anonymous review version).
- **[INPUT]** Responsible NLP checklist (if required): artifact licences (Llama-3.1, OCT adapters, persona-steering dataset), intended use, compute (GPU type/hours), hyperparameters, seeds/variance, LLM use, no human subjects.
- **[INPUT]** Dual submission: ARR bars papers under review at any archival venue. If this also goes to an ICLR workshop, both need to be non-archival (or pick one).
- **[INPUT]** Appendices go after references (already true), but reviewers needn't read them. Check the main text stands alone.
- Remove the to-do page before submission (`\todosfalse`). Review mode adds page and line numbers automatically.
- Note: `make sync-tables` would overwrite `tables/` with the ICLR versions; re-apply table* if you sync.

From TODO / NTFS notes in the draft

- Reproducibility statement: add exact adapter identifiers, the extraction scripts and their environment pins, the random-control constructors, the bootstrap and cross-fitting code, and the pre-registration.
- Add error bars, make charts sensibly legended/labelled/clear.
- Clarify the exact CAA vector construction and the answer-token extraction point.
- Distinguish corrected vs. raw RDM Spearman values wherever both appear in the repo.
- State that the question bootstrap conditions on the chosen 8 traits and 10 personas; it is not population inference over arbitrary traits/personas.
- Document the legacy-mask diagnostic and any fixed-mask confirmation used in final figures.
- Double-check the relevant framing/fixes are done from this chat (asking astra for consistency w/ the other acl submission, audit of code for "attention mask" issue, prompt format consistency etc...see audit in 4th turn)
- Check integrity of all plots vs underlying data & code generating the data

Anonymisation and submission hygiene

- Reproducibility statement links `github.com/ukc10014/...`, which deanonymises the paper. Replace with an anonymous mirror (e.g. anonymous.4open.science).
- Remove internal references that point outside the paper: "§7.7 of the underlying results write-up" (App. C.3) and "the 61.9% figure quoted elsewhere" (App. B, Table 2 caption), which is not quoted anywhere in this paper.
- Run pangram on doc.
- Remove all TODO text from figure captions (Fig. 12) before submission.

Claims that need checking or softening

- Section 3.3 is titled "Behavioral support for the context-general update hypothesis", but the logit analysis (Fig. 10) is not decomposed by persona, so it supports trait-selectivity rather than context-generality. Retitle or add a per-persona breakdown.
- Risk-taking was added as a target trait post hoc (Table 4 notes), but the main text and abstract present it alongside impulsivity. Say so in the main text.

- Section 3.2 reports 1.7–1.9× selectivity as "confirmed" by reproduction, but App. D gives 1.56× and 1.64× for the replications and says 1.7–1.9× is a property of the released artifact. Reconcile the wording.
- Intro says "We hypothesize…"; state which hypotheses and endpoints were preregistered (B_1 is called "registered") and which were exploratory.

Clarity and consistency

- Symbol clash: k is compression retention (App. C.6, Table 4), but Table 3 also has a column "k" next to "vs M_D". Rename one.
- Fig. 3D x-axis stops at 2.0 epochs while A and C run to 3.0. Align or explain.
- Check captions to plots

Differential Impact of Constitutional Character Training on Context-conditional Trait Representations

Anonymous ACL submission

Abstract

LLM training may install traits either generally across personas or context-conditionally (as personas are elicited during inference). We study the effect of constitutional training on persona-conditional trait representations (Llama-3.1-8B-Instruct, 8 traits, 10 personas/professions), using contrastive activation addition (CAA) and Open Character Training (OCT) LoRAs. We formalize a method to apportion changes in activations between shared and context-conditional terms, and find that most adapter-induced activation-space movement is shared across persona contexts, leaving a residual (about 3.6% at layer 15) of the total measured change attributable to constitution-persona-trait interaction. We find qualified semantic specificity: the impulsiveness constitution gives disproportionate activation-magnitude changes on impulsivity and risk-taking, while misalignment shifts broadly across traits. Signed measures (logits) show a contrasting profile: both constitutions show strong shifts towards impulsivity and risk-taking. We also investigate constitutional training dynamics by localising the impulsiveness LoRA's effect, finding that 82% of the behavioral effect for impulsivity emerges by epoch 0.48 of SFT on introspection data rather than the (earlier) DPO stage of OCT. These results suggest that the trait selectivity of character training seems sensitive to process and measurement method, rather than to constitutional semantics alone.

1 Introduction

It is speculated that post-training, particularly reinforcement learning, might affect trait expression in context-dependent ways, allowing aligned and misaligned tendencies to coexist (Betley, 2026). A training-induced trait change may install generally across contexts (personas/situations elicited at inference), or conditionally (appearing differently depending on context) (Dubiński et al., 2026). Anonymous (2026) operationalise this hypothesis, showing that trait representations in activation space are different depending on persona and on RL/post-training stage.

We ask an analogous but narrower question: does constitutional character training (Maiya et al., 2025) install trait representations conditionally upon contexts, or more generally across them? Secondly, which part of the OCT pipeline contributes most to changes in trait geometry? We hypothesize that OCT installs a context-general update: for a given trait, a constitutional adapter changes the trait's representations in broadly similar ways across (persona/role) contexts. Note that, following Anonymous (2026), we will use persona to mean "prompting context/system prompt" or "professional role".

Contributions We make three empirical contributions. Firstly, we show that the effect of constitutional training is mostly shared across the tested occupational roles/personas, with a small three-way constitution $\times$ trait $\times$ persona interaction. Secondly, we find that measurement method matters when assessing semantic specificity: unsigned activation displacement measures and signed forced-choice logits give different trait selectivity profiles. Thirdly, for the impulsiveness constitution, we localize representational changes to the first epoch of SFT upon DPO-generated introspection data, rather than as a direct result of the DPO weight update. During reproduction analysis of OCT results, we identified sensitivity to LoRA factorisation in the PEFT linear merge: this means functionally equivalent input adapters can produce different merged models. Finally, we made methodological contributions: a set of approaches to decompose activation-level changes into persona-common and persona-specific components; measures of geometry which are richer than cosine-to-null; controls using randomized LoRAs to partially distinguish

possible effects of model displacement, from semantic effects of character training.

2 Experimental Setup

We apply the pipeline in Anonymous (2026), to the open character constitutionally trained models in Maiya et al. (2025) (OCT). We use the OCT LoRAs published for Llama-3.1-8b-instruct in order to assess the geometry of context-dependent trait representations conditional on character: trait vectors calculated via contrastive-pair activation difference (Rimsky et al., 2024) for traits when the model has been in-context prompted to adopt a profession/role.

Anonymous (2026) found that trait vectors clustered (low cosine-to-null distance) for certain roles and not others, and degree of clustering varied between traits. Our hypothesis was that under character training, trait representations might intensify or cluster (i.e. converge directionally, be amplified in magnitude, across personas), in a way that could be intuitively interpreted as "the effect of the constitution's semantic content on the representation". Concretely, the impulsive OCT character should promote a more consistent representation of impulsivity across personas. Motivated by evidence that narrow fine-tuning can induce broader, correlated changes in model behaviour or persona (Betley et al., 2026; Chen et al., 2025), we explored the possibility that some traits that seem intuitively adjacent to impulsivity, such as risk-taking, should also show a clustering under the impulsive OCT. We analyze these phenomena both through activations and using logit-based behavioral measures.

A principal object of study is $V_{c,t,p} \in \mathbb{R}^{4096}$ which denotes the trait vector under constitution/intervention c, trait t, and persona p. The adapter-induced change is $dV_{c,t,p} = V_{c,t,p} - V_{\text{base},t,p}$, which can be conceptually decomposed:[1]

$$dV_{c,t,p} = \mu + \underbrace{C_c + T_t + P_p}_{\text{single-factor}} + (TP)_{t,p} + \underbrace{(CT)_{c,t} + (CP)_{c,p} + (CTP)_{c,t,p}}_{\text{constitution-dependent}}. \quad (1)$$

[1] where μ: overall/common shift, C_c: constitution-specific effect, T_t: trait-specific effect, P_p: persona-specific effect, $(CT)_{c,t}$: constitution-by-trait interaction, $(CP)_{c,p}$: constitution-by-persona interaction, $(TP)_{t,p}$: trait-by-persona interaction, $(CTP)_{c,t,p}$: genuinely constitution-specific modification of a particular trait in a particular persona.

In what follows, we primarily consider whether character-dependent change is general across personas (C, CT) or persona-dependent (CP, CTP); whether these changes bear some intuitive relationship to the semantics of the trained character; and where in the constitutional training process these changes emerge.

3 Results

3.1 Character training mostly operates across personas generally

Constitutional character training does affect trait representations, but is largely trait-specific but shared across personas, rather than varying as a function of both traits and persona. Specifically, Eq.1 explains the variance in activation vectors between unadapted and adapted models as a sum of possible single-factor and interaction-between-factors effects. We implement this analysis of variance (ANOVA, details in App.A.4) on CAA vectors at L15/L20 to isolate the effect of constitutions via pairwise interactions, as well as the 3-way interaction between CTP. For L15 (App. A.4 and Fig. 3A), results are:T 0.372, TP 0.175, CT 0.170, μ 0.124, C 0.067, P 0.043, CTP 0.036, CP 0.013. This can be summarised as: 71.4% of the variance in representational change is in terms that have nothing to do with a specific constitution. Of the 28.6% that depends on constitutions, the dominant component is the constitution's interaction with a trait (17%), and this is mostly consistent across personas, and about 3.6% of variance that can be attributed to the three-way interaction of constitution, trait, and persona.

3.2 Trait profiles look different depending on CAA versus logit-based measurement

Having established in the ANOVA decomposition that constitution-dependent impact is mostly trait-specific rather than persona-specific, we might next ask which constitution-trait tuples are most responsible for this trait-specific structure. The answer to this depends on which measurement we use. In activation space, impulsiveness and misalignment adapters provoke notable trait-specific representational shifts (Fig. 1A and reproduction with new seed for impulsiveness through in App.B). However, the two adapters give different results: Fig. 1B shows that the misalignment adapter causes a large shift across most traits, while the impulsiveness constitutional adapter shows outsized shifts un-




Figure 1: Panel A shows, for each constitutionally adapted model and each trait (dots), the proportion of the adapter-induced change in the trait representation (at L15) that is shared across personas, rather than persona-specific. Panel B shows the size of persona-common shift by trait, relative to the size of the original (unadapted) trait representation.

der impulsivity and risk-taking (common shift is roughly 1.7–1.9× larger on risk-taking and impulsivity than on the other six traits). For instance, neither the mathematical nor goodness adapters showed trait selectivity; this seems unsurprising for the broadly-drawn goodness constitution. However, the mathematical adapter's selectivity is harder to test, since none of the traits employed obviously target mathematical or logical reasoning.

As discussed in A.6, activation-based results are unsigned: a large representational shift on the impulsivity trait cannot automatically be interpreted as "the model has become more impulsive". We subsequently investigated the loving and sycophancy characters, preregistering target traits of empathy/warmth for the former, and deference for the latter. In 2,we see that both misalignment and impulsiveness characters correlate with increased responses on the impulsivity and risk-taking traits (a different trait response profile than the activation analysis above) while the loving character shows the pre-registered increase in empathy and warmth. In contrast, sycophancy shows the opposite of an expected increase in deference.

3.3 Constitutional behavioral phenotype emerges early in SFT

Given the notable behaviour of the impulsivity character above, we next asked at which stage in the OCT pipeline (App.D) does the distinctive trait-selective behavioral expression (trait "phenotype") emerge, where phenotype refers to output logits-based measures (B_1, B_2 relative trait preferences for impulsiveness and risk-taking over the other traits, defined in App.C). We map the full 3-epoch training trajectory for the impulsivity constitution, finding that the phenotype arises early in SFT, rather than DPO (82% of the final effect B_1 by 0.48 epoch, and saturation by 0.70, see Fig.12A). This result is not merely the unsurprising result of SFT perturbing the model more: when the application strength of a DPO-only adaptor is scaled such that it has the same functional effect on activations as the DPO + SFT training checkpoint, we find (Fig.12D) a 5-8x trait-specific response for the SFT'd model. This confirms the trait-specificity of SFT, though DPO remains important as the generator of the introspection dataset. This result is limited to a single constitution, seed, and layer.




Figure 2: TODO : behavioral corroboration.

4 Discussion

OCT's impact on traits appears to be largely context-general rather than persona-specific. The dominant effect of constitutional training is from the terms CT, while CP and CTP are small. That is, OCT LoRAs change traits representations, but do so relatively consistently across persona contexts. This doesn't mean that large geometric changes are themselves semantically interpretable, given the sensitivity of representations to the effective or functional dose of semantically different LoRAs. Moreover, dose-matched random perturbations reproduce much of the raw geometric movement. Activation-based representational changes are shown not to be cleanly interpreted as "more" or "less" of a given trait; behavioural logit analysis is therefore needed for directional claims such as "more impulsive". Lastly, for the impulsiveness character, the trait-selective behavioural phenotype emerges mainly during SFT on a DPO-generated introspection corpus, rather than from the DPO weight update alone.

Limitations

The main limitation is the lack of an open-ended behavioral corroboration: we largely focus on CAA-based measures rather than a free-form completion instruction-variant (IV) method, with prior work Anonymous (2026) showing meaningful differences in the geometry of trait representation between CAA and IV. Secondly, the set of traits and personas/roles/contexts are limited. This affects experimental coverage and how general our claims can be. Thirdly, we have not clearly disentangled the effects of constitutional semantics from the training procedure: this would need a semantically empty but constitutionally-empty "sham" document, and naturally complement App. C. Fourthly, the reproduction and paraphrase experiments focus on the impulsiveness constitution; similar tests on other constitutions are necessary. Finally, the open issues in App. C reproduction need to be closed before extensively interpreting paraphrase results or testing other constitutions.

Ethical Considerations

LLMs were used for experiment code writing, data analysis, chart production, and typesetting/LaTeX.

Human authors formulated the overall research agenda and hypotheses, wrote the text of the manuscript, and designed/interpreted the results of experiments.

References

Anonymous. 2026. Personas shape how models represent behaviors. Under review.

Jan Betley. 2026. Rl creates split personas. LessWrong. Accessed 2026-09-17.

Jan Betley, Niels Warncke, Anna Sztyber-Betley, Daniel Tan, Xuchan Bao, Martín Soto, Megha Srivastava, Nathan Labenz, and Owain Evans. 2026. Training large language models on narrow tasks can lead to broad misalignment. *Nature*, 649(8097):584–589.

Runjin Chen, Andy Arditi, Henry Sleight, Owain Evans, and Jack Lindsey. 2025. Persona vectors: Monitoring and controlling character traits in language models. *Preprint*, arXiv:2507.21509.

Jan Dubiński, Jan Betley, Anna Sztyber-Betley, Daniel Tan, and Owain Evans. 2026. Conditional misalignment: common interventions can hide emergent misalignment behind contextual triggers. *Preprint*, arXiv:2604.25891.

Christina Lu, Jack Gallagher, Jonathan Michala, Kyle Fish, and Jack Lindsey. 2026. The assistant axis: Situating and stabilizing the default persona of language models. *arXiv preprint arXiv:2601.10387*.

Sharan Maiya, Henning Bartsch, Nathan Lambert, and Evan Hubinger. 2025. Open character training: Shaping the persona of AI assistants through constitutional AI. *Preprint*, arXiv:2511.01689.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Matt Turner, Alex Tong, and Evan Hubinger. 2024. Steering Llama 2 via contrastive activation addition. *arXiv preprint arXiv:2312.06681*.

Alexander Walther, Hamed Nili, Naveed Ejaz, Arjen Alink, Nikolaus Kriegeskorte, and Jörn Diedrichsen. 2016. Reliability of dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, 137:188–200.

Runzhe Wu, Ankur Samanta, Ayush Jain, Scott Fujimoto, Jeongyeol Kwon, Ben Kretzu, Youliang Yu, Kaveh Hassani, Boris Vidolov, and Yonathan Efroni. 2026. Imbalanced gradients in RL post-training of multi-task LLMs. In *Findings of the Association for Computational Linguistics: EACL 2026*, pages 3137–3150. Association for Computational Linguistics.

A Experimental details & controls

Experimental Setup CAA vectors are also extracted using length-matched nonsense prompts and default/null role (i.e. which should correspond to the "assistant persona" of Lu et al. (2026)). The primary measurement of interest is cosine similarity on the trait-extracted vector versus the vector extracted under null/assistant, at a mid/late layer (15, 20). Professional roles are farmer, politician, therapist, drill sergeant, street hustler, professor, tech CEO, kindergarten teacher, surgeon, con artist; traits investigated are assertiveness, empathy, risk-taking, honesty, confidence, deference, warmth, and impulsivity.

The OCT pipeline described in Maiya et al. (2025) starts from simple constitution that emphasises some character (we looked mainly at goodness aka "flourishing", mathematical, impulsiveness, misalignment, as well as loving, sycophancy); a teacher LLM distilling this character into a student model via DPO; the DPO'd student model then produces an introspection corpus (through self-reflection and conversations with other instances of itself); this corpus is then used for SFT on the same student.

A.1 Shared movement across personas

In order to assess the degree to which constitutions have shifted representations in a persona-common way, for each constitution and trait, we average across the 10 personas, and compare the squared magnitude of the persona-averaged shift to the average across personas of the squared magnitude of the CAA shifts. This is shown in Fig.1.

Formulaically:

$dV_{c,t,p} = V_{c,t,p} - V_{\text{base},t,p}$

and,

$dG_{c,t} = \frac{1}{P} \sum_p dV_{c,t,p}$

and for the common shift-across-personas share,

$\|dG_{c,t}\|^2 / \text{mean}_p \|dV_{c,t,p}\|^2$

At L15, the persona-common term accounts for 67–77% of squared adapter-induced movement across trained arms. This result is consistent with the ANOVA decomposition in 3.1.

A.2 Calculating representational dissimilarity matrices (RDM)

Although much of the representational shift is shared across personas, we find that there is a reorganization of the internal between-persona ordering of representations (holding trait and constitution fixed). We construct a representational dissimilarity matrix (RDM), whose entries are the squared Euclidean distances between persona-conditioned

CAA vectors:

$$R_{c,t}(p,q) = \|V_{c,t,p} - V_{c,t,q}\|_2^2. \tag{2}$$

For 10 personas, this is a symmetric 10×10 matrix with a zero diagonal and 45 unique off-diagonal distances. We measure RDM preservation using the Spearman correlation between these 45 distances in the adapted and base models:

$$\rho_{c,t} = \text{Spearman}\big(\{R_{c,t}(p,q)\}_{p<q}, \{R_{\text{base},t}(p,q)\}_{p<q}\big). \tag{3}$$

Higher correlation indicates greater preservation of which persona pairs are relatively close together or far apart.

A.3 Measuring trait dispersion across personas

We are interested in how persona-conditioned trait vectors cluster or fan out around their own centroid, holding constitution fixed; the dispersion change $R_{c,t}$ measures how much this clustering changes between the unadapted and the character-trained model.

$$\bar{V}_{c,t} = \frac{1}{P}\sum_{p=1}^{P} V_{c,t,p}. \tag{4}$$

$$S_{c,t} = \sqrt{\frac{1}{P}\sum_{p=1}^{P} \left\|V_{c,t,p} - \bar{V}_{c,t}\right\|_2^2}. \tag{5}$$

$$R_{c,t} = \frac{S_{c,t}}{S_{\text{base},t}}. \tag{6}$$

A.4 ANOVA details

It is well known in fields using statistical methods (e.g. neuroscience and machine learning) that when trying to estimate a variable's norm/variance from observational data, we must control for the fact that quadratic estimates of noisy data are systematically biased upwards. Following (Walther et al., 2016; Wu et al., 2026), one method of doing this is a split-batch cross-validated sampling-noise-debiasing. The basic idea is to split the noisy observational data into non-overlapping batches, estimate the relevant norm/variance independently on these disjoint subsets and replace the squared norm/variance of a single estimate (over the entire observations) with the cross-product of the two estimates (on the batches).

Concretely, in the simplified case, let the true vector-valued effect be θ, and let an estimate from one sample be

$$\hat{\theta}^A = \theta + \epsilon_A,$$

where ϵ_A is zero-mean sampling error. A naive estimate of the squared norm of the effect is

$$\left\|\hat{\theta}^A\right\|_2^2.$$

Expanding algebraically,

$$\left(\theta + \epsilon_A\right)^\top \left(\theta + \epsilon_A\right),$$

which gives

$$\theta^\top\theta + 2\theta^\top\epsilon_A + \epsilon_A^\top\epsilon_A.$$

Taking expectations,

$$\mathbb{E}\left[\left\|\hat{\theta}^A\right\|_2^2\right] = \|\theta\|_2^2 + 2\theta^\top\mathbb{E}[\epsilon_A] + \mathbb{E}\left[\epsilon_A^\top\epsilon_A\right].$$

Assuming the sampling error has zero mean, $\mathbb{E}[\epsilon_A] = 0$, the linear error term vanishes, but the quadratic noise term does not:

$$\mathbb{E}\left[\left\|\hat{\theta}^A\right\|_2^2\right] = \|\theta\|_2^2 + \text{tr}\left(\Sigma_\epsilon\right),$$

where

$$\Sigma_\epsilon = \text{Cov}(\epsilon_A).$$

The split-batch debiasing method involves splitting the observations into two disjoint samples, producing two independent estimates,

$$\hat{\theta}^A = \theta + \epsilon_A, \qquad \hat{\theta}^B = \theta + \epsilon_B.$$

We estimate the squared norm using the cross-product

$$\left(\hat{\theta}^A\right)^\top \hat{\theta}^B.$$

Expanding and taking expectations,

$$\mathbb{E}\left[\left(\hat{\theta}^A\right)^\top \hat{\theta}^B\right] = \theta^\top\theta + \theta^\top\mathbb{E}[\epsilon_B] + \mathbb{E}[\epsilon_A]^\top\theta + \mathbb{E}\left[\epsilon_A^\top\epsilon_B\right].$$

If the errors are zero-mean and independent across the two disjoint samples,




Figure 3: C×T×P decomposition: At L15 most of the change (between adapted and unadapted models) is captured by lower-order terms, the triple interaction component is small. Primary effect of constitution is on trait representation generally.

Provenance: figure `workshop_iclr/figures/fig2_ctp.pdf`; script `workshop_iclr/scripts/fig2_ctp.py`; plotted values `workshop_iclr/data/fig2_ctp.csv`.

$$\mathbb{E}[\epsilon_A] = \mathbb{E}[\epsilon_B] = 0, \qquad \mathbb{E}\left[\epsilon_A^\top \epsilon_B\right] = 0,$$

and therefore

$$\mathbb{E}\left[\left(\hat{\theta}^A\right)^\top \hat{\theta}^B\right] = \theta^\top \theta = \|\theta\|_2^2.$$

In this debiased example, the single-bias terms are zero (in expectation), but crucially, the cross product of bias terms from two non-overlapping estimates is *also* zero in expectation, giving an estimate of $\|\theta\|_2^2$ that is unbiased.

In the present context, we have C=4,T=8,P=10,H=4096 corresponding to constitution, trait, persona/role, and residual stream size, and 500 questions. The data are split into 40 repetitions: disjoint batches of 250 questions each (repetitions reuse questions in different random partitions). The relevant code is here: `scripts/caa_three_way_interaction.py`.

A.5 Functional dose and untrained-adapter controls

We find that constitutional LoRA adapters, though applied at an equal nominal application scale $s = 1.0$, result in substantially different activation displacements. This means that simply perturbing the model more strongly causes progressively more distortion of the existing persona geometry. This means one must compare adapters using a measured functional dose rather than nominal application scale.

We define a diagnostic of functional dose and as follows.

At a fixed layer, let $V_{c,t,p}(s)$ denote the CAA trait vector under adapter c applied at scale s. We define mean relative trait-vector displacement as

$$D_c(s) = \frac{1}{TP} \sum_{t=1}^{T} \sum_{p=1}^{P} \frac{\|V_{c,t,p}(s) - V_{\text{base},t,p}\|_2}{\|V_{\text{base},t,p}\|_2}. \tag{7}$$

We express each adapter's trait-vector displacement relative to the goodness adapter at $s = 1$, assigning that reference a functional dose of one.

$$\text{FD}_c(s) = \frac{D_c(s)}{D_{\text{goodness}}(1)}. \tag{8}$$

Thus, $\text{FD}_{\text{goodness}}(1) = 1$ by construction. This matched-dose diagnostic allows for comparisons between LoRAs. In order to functionally match doses (i.e. equalize the difference in activations to a character-trained model at a given layer), we need an adaptor application weight $s = 16 - -19$ to get the same effect as a trained OCT adaptor at $s = 1$. We also can see that functional dose affects the direction of d_G, as in Fig. 4.

Next we look at dispersion (defined in A.3) amongst personas, and find that is also functional dose-dependent; but, at matched functional dose, all three untrained constructions reproduce most of the broad dispersion contraction (Fig. 5B,D).

More interestingly, however, in Fig. 5A, within-arm dose ladders show that RDM preservation (defined in App. A.2) falls as functional dose

rises. Lower preservation indicates a change in which persona pair representations are relatively close together or far apart. At matched functional dose (Fig. 5C), goodness and impulsiveness follow essentially the same RDM-preservation estimates (0.834, 0.826); mathematical sits above both (0.878) and misalignment below them (0.768). Geometrically, this means that "mathematical is relatively ordering-preserving (amongst persona pairs) while misalignment is ordering-changing, while goodness and impulsiveness leave ordering relatively unchanged". One might (naively) attribute this ordering to the constitutions' content, interpreting some constitutions as preserving that arrangement and others as reorganizing it more substantially.

However, this apparent ordering of the various LoRAs does not have an obvious semantic interpretation since untrained (by construction, semantically-null) arms straddled the whole trained range. That is, in order to control for the possibility that any LoRA, including one devoid of semantic content, would cause a representational shift, we used untrained scrambled LoRA in three ways: random-IID weights, singular-spectrum-matched random directions, and per-module coordinate-permuted trained updates.

At matched dose, `random_iid` preserves geometry *better* than every trained arm (0.886) and `random_perm` preserves it *worse* than misalignment (0.761).

The broad dose dependence also appears at layer 20, although the relative ordering of adapters changes (Fig. 6). This suggests that the dose effect is more consistent across layers than the adapter-specific preservation ranking.

This appendix has used untrained adapters as a control for the effects of character-trained LoRAs. However, these controls do not establish that the representational effects of character training are fully reproduced by untrained perturbations. Fig. 7 shows the cosine similarity of persona-mean representational shift (at matched functional dose) between two adapted models (either OCT LoRA or a randomised/untrained LoRA), where

$$dG_{c,t} = \frac{1}{P}\sum_{p=1}^{P} dV_{c,t,p}.$$

We find that character-trained models' representational shifts are directionally more similar to each other, than they are to untrained models' shifts.




Figure 4: As the gap between function doses of an adapter increases, the persona-mean dG vector (which quantifies the representational shift between the adapted and the unadapted model) rotates. The magnitude of rotation increases broadly across all constitutional adapters as well as the randomized control. This supports the contention above that dose-dependent rotation is a generic property of strongly-applied LoRA adapters, and not indicative of the effect of constitutional semantics.

Provenance: figure `workshop_iclr/figures/figA4_rotation_control.pdf`; script `workshop_iclr/scripts/figA4_rotation_control.py`; plotted values `workshop_iclr/data/figA4_rotation_control.csv`.

This indicates that there is some underlying structure to the representational shifts that result from training, but does not by itself identify an effect of constitutional content; it could also reflect the shared training procedure or data.

A.6 Corroborating CAA with logit-based behavioral evidence

There are two issues with the activation based measure in Fig. 1. Firstly, because we take the norm of $dG_{c,t}$ (persona-averaged change in the 4,096-dim CAA vectors for a given trait, constitution pair), the squaring operation eliminates directional/sign information. Therefore, we can only establish the size of a representational shift, not whether it has moved positively or negatively with respect to a trait direction or indeed whether it has moved orthogonally to it. So in the case of Fig. 1B, this would mean that a larger value for impulsivity simply means a larger relative persona-common change in the impulsivity CAA vector rather than increased impulsivity per se.

Algebraically, the primary object of interest in CAA is




Figure 5: Trait and persona geometry preservation vs functional-dose at L15. Increased functional dose distorts geometry (relative to unadapted models). Goodness and impulsiveness follow similar dose–response curves. Misalignment shows lower preservation at matched dose than the other trained arms, but not lower than the untrained `random_perm` control, and `random_iid` preserves geometry better than any trained arm — the untrained spread brackets the trained one. All arms in panels C/D are dose-corrected.

Provenance: figure `workshop_iclr/figures/fig3_dose_and_control.pdf`; script `workshop_iclr/scripts/fig3_dose_and_control.py`; plotted values `workshop_iclr/data/fig3_dose_and_control.csv`.

$dV_{c,t,p} = V_{c,t,p} - V_{\text{base},t,p}$

and,

$dG_{c,t} = \frac{1}{P}\sum_p dV_{c,t,p}$ the persona-common shift, and when we take a norm $\|dG_{c,t}\| = \| - dG_{c,t}\|$ destroying information on signed effect.

For the two panels in Fig. 1,

$\|dG_{c,t}\|^2 / \text{mean}_p \|dV_{c,t,p}\|^2$ the common-shift share

$\|dG_{c,t}\| / \text{mean}_p \|V_{\text{base},t,p}\|$ the relative common shift

Secondly, to test whether representational shifts (between adapted and unadapted models) can be interpreted as "more" or "less" of a trait, the persona-common shift is projected onto the corresponding unadapted-model trait axis across a LoRA-strength ladder. We wanted to check if a trait's projection retains the same sign, grows monotonically in absolute value, and extrapolates to a sufficiently small intercept at zero dose. Trained adapters largely fail these checks (Fig. 8), whereas the randomized adapter passes for all traits. This means that we cannot interpret representational shifts as necessarily indicating semantic shifts: for example, the impulsiveness-trained model has not thereby become "more impulsive" simply because its impulsivity representation moves farther in one direction along the base-model trait axis.

Given these issues with activation-based analysis, we assess the adapted model's trait preferences using a logit-based behavioural approach. Naively, one could take the log of the probability ratio between trait-positive and trait-negative an-




Figure 6: Fig. 5 replicated at layer 20. The dose-dependence of RDM preservation and the failure of dispersion to follow a single dose-response curve both replicate. The arm ordering does not transfer intact: at L20 misalignment (0.631) falls below `random_perm` (0.662), reversing their L15 order, which is a further reason not to read the ordering of trained arms as constitutional content.

Provenance: figure `workshop_iclr/figures/figA3_layer20.pdf`; script `workshop_iclr/scripts/figA3_layer20.py`; plotted values `workshop_iclr/data/figA3_layer20.csv`.

swers, and then compare that between the adapted and unadapted model. However, this raw difference doesn't help identify a trait-specific bias, because we found that in adapted models, adapted model log-odds move towards indifference (relative to the unadapted log-odds), making it unclear whether the adapted model's relative preferences in a given trait had actually changed (Fig. 9A).

To correct for this compression-towards-indifference, we perform regressions on the preference pairs for the adapted and the base models, which then separates out the actual shift in relative preferences from the compression component.

$$\log \frac{\Pr_{\text{adapted}}(\text{trait+ answer} \mid i)}{\Pr_{\text{adapted}}(\text{trait- answer} \mid i)} = a + k \log \frac{\Pr_{\text{base}}(\text{trait+ answer} \mid i)}{\Pr_{\text{base}}(\text{trait- answer} \mid i)} + \varepsilon_i. \tag{9}$$

Here, i indexes evaluated question–persona items, k measures retention of the base model's preferences, and the intercept a is our quantity of interest: it estimates the adapted model's directional preference after accounting for compression of the base model's existing preferences. It is the fitted log-odds when the base model is indifferent, and is plotted on the vertical axis of Fig. 9C. Positive values favor the trait-positive answer; negative values favor the trait-negative answer.

Corrected for this compression, (Fig. 9C,D) shows that the misalignment and impulsiveness constitutions have differentiated preference shifts towards impulsivity and risk-taking, as well as the size of the relative preference (versus other traits) on a CAA and forced-choice basis (an added instruction to the prompt telling the model to pick A/B).

B (Narrow) reproduction of the impulsiveness result

Given the notable result on impulsiveness, we wanted to reproduce the result both on the original and on a second seed. However, unlike the OCT paper, we did not run a behavioral evaluation; rather,




Figure 7: After matching intervention strength, OCT adapted models converge on a common representational shift direction: trained–trained cosine similarity (0.46–0.83) substantially exceeds trained–untrained (0.01–0.29), with non-overlapping bootstrap intervals between the two blocks.

Provenance: figure `workshop_iclr/figures/fig4_shared_direction.pdf`; script `workshop_iclr/scripts/fig4_shared_direction.py`; plotted values `workshop_iclr/data/fig4_shared_direction.csv`.

following the logic in A.6 , we recorded difference in logits between forced-choice impulsive and non-impulsive answers, corrected for the generic logit compression of adapted vs unadapted models) was $+1.92$ (reproduction) and $+1.95$ (second seed) against $+2.18$ for the Maiya et al. (2025) released adapter. Note this reproduction used the existing introspection corpus and was principally done to get separate LoRAs for the DPO and SFT stages since the original OCT dataset had them PEFT-merged, making them less unusable for the training dynamics work in D. We subsequently ran a more comprehensive reproduction with paraphrased constitutional character description, regenerated introspection corpus, as well as DPO and SFT training stages.

C (Broad) reproduction of the impulsiveness result: paraphrased constitution

C.1 Setup

The objective here was to understand where the trait selective behavioural phenotype emerges within the OCT training pipeline and whether that is sensitive to rephrasings of the impulsiveness constitution. Before doing this, we needed to reproduce the original OCT setup in (Maiya et al., 2025) in order to have a baseline.

Constitutional training in the OCT recipe (Maiya et al., 2025) has multiple stages: a distillation stage using DPO to produce a LoRA adapted student. This DPO-adapted student then generates a training corpus: from reflections upon, and conversations with other instances of, itself. The introspection corpus is then used for supervised fine-tuning of the student to produce a second LoRA. The DPO and SFT LoRAs are merged, and this is the released artifact.

Fig.10 shows the training pipeline, and relevant training checkpoints are:

- M (the unmodified base model, Llama-3.1-8B-Instruct);
- M_D (base plus the DPO adapter; the DPO weight update alone, before any SFT);
- M_{D+S} (base plus the full DPO and SFT updates);
- $M_{D+0.25S}$ (base plus the DPO update and a quarter of the SFT update, summed directly in weight space; the merge OCT intended, with no cross terms);
- M_F (the released-style artifact: peft's `add_weighted_adapter([DPO, SFT], [1, 0.25], "linear")`, which combines the LoRA factors and so equals $M_{D+0.25S}$ plus factor-space cross terms);
- M_S (a separately trained SFT adapter whose optimisation started from base weights instead of




Figure 8: Signed-projection validity at L15.

Provenance: figure workshop_iclr/figures/figA5_signed_validity.pdf; script workshop_iclr/scripts/figA5_signed_validity.py; plotted values workshop_iclr/data/figA5_signed_validity.csv.

the DPO model, on the identical frozen corpus; DPO is removed from the weights but not from the corpus, which the DPO model generated);

- $M + A_S$ (the existing SFT adapter (fitted around M_D) applied to plain base; an off-base diagnostic, not "SFT alone")

For this investigation, we quantify (for a given trait(s)) a behavioural signature using two signed trait-selectivity contrasts: impulsivity relative to the other seven traits (B_1), and impulsivity and risk-taking jointly relative to the remaining six traits (B_2). Following the forced-choice output-logit approach described above (see App. A.6), we calculate these measures as follows:

$$L = \log \frac{P(\text{trait-positive answer})}{P(\text{trait-negative answer})}.$$

$$L_{\text{adapted}} = a_t + k_t L_{\text{base}} + \epsilon,$$

$$B_1 = a_{\text{impulsivity}} - \frac{1}{7} \sum_{t \neq \text{impulsivity}} a_t.$$

$$B_2 = \frac{a_{\text{impulsivity}} + a_{\text{risk-taking}}}{2} - \frac{1}{6} \sum_{t \notin \{\text{impulsivity, risk-taking}\}} a_t.$$

The intuition is: for each constitution and each trait, we calculate the logprob ratio (measuring relative preference between trait-positive and trait-negative answers) from the unadapted and the constitutionally adapted model. These preference measures are plotted: the preference of the unadapted model (x-axis) versus the adapted model (y-axis). The $x = 0$ intercept tells us that where the unadapted model would be indifferent, the adapted model has a preference with strength a_t. A positive fitted preference at base-model indifference (a_t) means a bias towards the trait-positive answer after accounting for the fitted rescaling of existing preferences. The a_t figures are fed into the formulas above in order to assess the adapted model's preference on a target trait relative to its preferences for others.

The above measures B_1/B_2 are signed logit-based contrasts, while B_3 (below) is an unsigned activation displacement selectivity ratio (like the CAA-based measures above) that looks at how much more the two target traits (impulsivity, risk-taking) move when compared to the six non-targeted traits.

$$g_t = \frac{\|dG_t\|}{\frac{1}{P}\sum_{p=1}^{P} \|V_{t,p}^{\text{base}}\|},$$

$$dG_t = \frac{1}{P} \sum_{p=1}^{P} \left(V_{t,p}^{\text{adapted}} - V_{t,p}^{\text{base}} \right).$$

$$B_3 = \frac{\frac{1}{2}\left(g_{\text{impulsivity}} + g_{\text{risk}}\right)}{\frac{1}{6}\sum_{t \notin \{\text{impulsivity,risk}\}} g_t}.$$

C.2 $P0$ reproduction failure

Table 1 and Fig. 11 below show that the end-to-end regeneration, which we call $P0$ (distinct from the paraphrase experiment, $P1$), substantially fails to reproduce the released OCT adapter's behavior, whether on logit-based (B_1/B_2) or on activation-based (B_3) measures. And this failure is not a




Figure 9: Panels A/B show that when comparing character-trained versus an unadapted model, character training generically compresses the response towards indifference. Panel C controls for this compression: the impulsiveness and misalignment adapters show strong positive shifts for impulsivity and risk-taking. Panel D shows this as a contrast (between these traits and the other six) for both the default CAA prompt and a forced answer prompt.

Provenance: figure `workshop_iclr/figures/fig5_behavioral_preference.pdf`; script `workshop_iclr/scripts/fig5_behavioral_preference.py`; plotted values `workshop_iclr/data/fig5_behavioral_preference.csv`.

function of dose: $P0$ actually shows higher displacement A_4. The figure shows that all traits move towards zero under $P0$ but the targeted traits, impulsiveness and risk-taking, as 11 shows, attenuate far more.

C.3 Localizing the discrepancy

In Table 2 we narrow down where the change in B_1 (between $P0$ vs reproduction/published OCT) occurs. The first three 3 rows cover training stages: the model that has only undergone DPO; an unadapted model that has undergone SFT (using a DPO-generated introspection corpus); in the third row, we show the effect of stacked LoRAs (for DPO and SFT stages). In the final 2 rows, we focus on the LoRA merger, contrasting an additive merger (at 0.25 SFT weighting as per the OCT recipe) with the published PEFT merger's outcome. The takeaway is that discrepancies show up as early as the DPO stage, but the published PEFT shows a substantial incremental discrepancy over the additive merger (-0.15 to -0.642).

C.4 Explaining the P0 discrepancy

We did not do a comprehensive forensic audit of the OCT pipeline, but suggest several possible sources for the discrepancy. Firstly, above in App.B we show that LoRAs generated using OCT's published data for the introspection corpus didn't fully replicate the effect of the merged OCT adapter.

There was also an infrastructure issue: we access the teacher model (GLM-4.5-air) through Open-




Figure 10: Model states in the OCT `impulsiveness` pipeline. Solid arrows are data flow, dashed are weight initialisation. M_S starts from base *weights* but trains on a corpus generated by M_D, so DPO is removed from the optimisation and not from the causal history. $M_{D+0.25S}$ is the merge OCT intends; M_F is what peft's linear factor combination actually produces, and differs from it only by cross terms.

Provenance: figure `workshop_iclr/figures/figA_oct_stage_pipeline.pdf`; script `scripts/appendix_oct/figA_oct_stage_pipeline.py`. Schematic — no source data.

Router's API and a downstream hosting provider to generate the preference data for the distillation/DPO stage. The original OCT implementation included a prefill to the teacher prompt with the start of a reasoning trace (see App. A of (Maiya et al., 2025)). Our hosted setup did not allow for this assistant-side prefill, and when we supplied it, it was interpreted as a completed prior assistant turn. How big a deal was this? We're not sure – our approach obviously was able to produce a downstream SFT phenotype, but it wasn't as strong as in the original OCT work. However, we can't tell how this deviation changed the DPO training distribution, and how much of the discrepancy should be attributed to the prefill issue, the items below, or something else.

We then considered the complexities of the multi-stage character training process, particularly how LoRAs are merged. For each targeted model weight matrix W, a rank-r LoRA parameterises the update as

$$\Delta W = sBA, \qquad s = \alpha/r,$$

where $A \in \mathbb{R}^{r\times d_{\text{in}}}$ and $B \in \mathbb{R}^{d_{\text{out}}\times r}$, with the LoRA rank r 64 and model dimension 4,096. Let the DPO and introspection-SFT updates be

$$D = s_D B_D A_D, \qquad S = s_S B_S A_S.$$

OCT's released adapter is constructed using PEFT's `add_weighted_adapter` with weights $w_D = 1$ and $w_S = 0.25$ and `combination_type="linear"`. For positive weights this combines the LoRA factors:

$$A_F = \sqrt{w_D s_D}\, A_D + \sqrt{w_S s_S}\, A_S,$$

$$B_F = \sqrt{w_D s_D}\, B_D + \sqrt{w_S s_S}\, B_S.$$

Here $r = 64$ and $\alpha = 128$ for both component adapters, so $s_D = s_S = 2$. Hence

$$A_F = \sqrt{2}A_D + \frac{1}{\sqrt{2}}A_S,$$

$$B_F = \sqrt{2}B_D + \frac{1}{\sqrt{2}}B_S,$$

and therefore

$$\begin{aligned}\Delta W_F &= B_F A_F \\ &= 2B_D A_D + \frac{1}{2}B_S A_S + B_D A_S + B_S A_D \\ &= D + 0.25S + B_D A_S + B_S A_D.\end{aligned}$$

model	B_1	B_2	activation sel. B_3	functional dose A_4
band	$\geq +1.5$	$\geq +1.4$	≥ 1.4	$[0.7, 1.4]$
released OCT	$+2.184$ $[+2.082, +2.270]$	$+2.077$ $[+2.008, +2.139]$	1.722 $[1.431, 2.012]$	1.000 1.000 ans.-tok.
fixed-data reproduction	$+1.923$ $[+1.839, +1.996]$	$+1.950$ $[+1.891, +2.002]$	1.556 $[1.286, 1.827]$	0.960 0.946 ans.-tok.
P0 end-to-end regeneration	$+1.281$ $[+1.214, +1.353]$	$+1.272$ $[+1.230, +1.321]$	1.208 $[1.020, 1.396]$	1.171 1.132 ans.-tok.

Table 1: Logit and activation-based measures for the OCT released checkpoint; a reproduction that holds the upstream intorspection SFT data fixed; and a fresh end-to-end regeneration (P0). The reproduction clears every CI band; P0 fails B_1, B_2 and B_3 but has a larger functional dose A_4, so the failure is not a dose deficit.




Figure 11: Attenuation of traits impulsivity/risk-taking between $P0$ and the released OCT or reproduction (with existing SFT data) is much higher than for other six traits.

We hypothesize, but do not definitively prove, that the cross-terms $B_D A_S + B_S A_D$ in the factor-space merge might amplify the above differences between our and the original OCT implementation. Specifically, if these 2 matrices are aligned, it can be shown that the net effect resembles a re-weighting of the DPO or SFT stages (potentially increasing the LoRA's contribution to the model's weight matrix). The reason these matrices might be aligned for any fixed LoRA adapter is that LoRA factor decomposition is not unique; empirically we found the factor coordinates were seed-dependent. The table below shows that with the same seeds, the A_D and A_S matrices were about collinear, and the functional effect $B1$ was much higher under a PEFT merger than an additive merger. When we choose different seed for DPO (leaving SFT's seed untouched), the two A matrices became approximately orthogonal, and the PEFT merger and the simple addition gave similar $B1$.

We then made a causal intervention: for the SFT adapter, we replaced each of the matrices A_S, B_S with its negative. Since the matrices are multiplied, that should have had no effect on the final weights or behavior of the model. However, when submitted to the PEFT factor merge, we found a behavioral change in $B1$ from +1.923 to -0.729. This indicates that two (apparently) functionally identical pairs of input adapters can produce radically different final weight matrices under the PEFT factor space merge.

It is important to note that the failure of this $P0$ replication is unlikely to be solely a result of factor-space merging peculiarities, since the reproduction

construction	reproduction B_1	P0 B_1	P0 − reproduction
DPO stage, M_D	$+0.132$	-0.075	-0.208
SFT component applied off-base	$+1.859$	$+1.823$	-0.036
native sequential state, $D + S$	$+2.190$	$+1.898$	-0.292
additive 1:0.25 comparator, $D + 0.25S$	$+0.499$	$+0.349$	-0.150
published PEFT 1:0.25 merge, M_F	$+1.923$	$+1.281$	-0.642

Table 2: Localizing the reproduction discrepancy appears across training-stage states and merge constructions. B_1 is shown for the fixed-data reproduction and the end-to-end regeneration P0. The discrepancy is already present at the DPO stage, while the isolated SFT component is very similar across runs. The native sequential $D + S$ state retains a moderate gap. For the merge diagnostic, the additive $D + 0.25S$ construction and the published PEFT merge use the same nominal 1:0.25 DPO/SFT weighting; the P0-to-reproduction gap is substantially larger under the PEFT factor-space merge.

and the $P0$ matrices were aligned. However, the point of this discussion is to show that PEFT LoRA merge is highly sensitive to factor-space representation, which suggests upstream discrepancies in training might have been magnified.

C.5 Paraphrase result

Given the reproduction discrepancy above, we treat the impulsiveness paraphrase as an exploratory investigation, provided for completeness. We lightly paraphrased the impulsiveness constitution, and then follow the published OCT recipe (albeit with the quirks of our reproduction): training data generation for DPO using GLM-4.5-air on OpenRouter; introspection corpus creation; SFT of the DPO'd model on the corpus; and PEFT merger of the resulting LoRAs. We measured the $B1$, $B2$ changes between the P1 (paraphrase) and the P0 (failed reproduction) as +0.092 and +0.096 respectively (CIs of [+0.038, +0.144], [+0.058, +0.132]). These gaps are much lower, and opposite in sign, than the reproduction gap calculated above (between P0 and the fixed data reproduction).

The relatively small movement in overall trait contrast ($B1$, $B2$) does not mean that the trait profile was stable. The P1-P0 gap was significant for off-target traits: honesty +0.632, confidence -0.312, deference -0.268, assertiveness +0.272 versus the changes for impulsivity (+0.123) or risk-taking (+0.105).

This was a single exploratory comparison, but it suggests a possible takeaway with both measurement and semantic aspects: a light paraphrase can present an apparently stable overall contrast ($B1$, $B2$) while substantially reorganizing the detailed pattern of traits. The original and paraphrased characters are diff'd here: `oct_variants/impulsiveness_paraphrase/traits.diff`.

D Emergence of trait-specificity in OCT training

We investigated where in OCT training the impulsiveness character phenotype ($B1$ and activation-space trait selectivity) emerges. Note, this is distinct from the analysis in C which was about localizing the discrepancy in reproductions.

Fig. 12A shows, over 18 checkpoints on three epochs of introspection SFT, that 82% of the $B1$ impulsivness signature's final value emerges before 0.48 epoch with flattening after 0.68 epochs, under both an additive and PEFT-merged setup. The saturation trajectory is not just an artifact of functional dose (the amount of displacement in activations that training, in this case, SFT is forcing in the model for details of calculation) as Panel B shows.

The relative impact of SFT can be looked at another way: what scaling s of a DPO-only adapter would we need to achieve the same effect as we get on the DPO+SFT setups at a given checkpoint? Panel D shows this as the ratio of B_1 by the B_1 produced by a DPO-only adapter scaled to the same measured functional dose (5–8×). Values above one mean that the SFT-trained state produces more of the target phenotype than can be explained by perturbing the model with the DPO adapter by the same amount.

Finally, panel C shows activation-space selectivity also emerges early in the trajectory. We do not interpret local peaks and troughs between checkpoints as they weren't stable under denser sampling.

The takeaway is, for this constitution (and a single seed/measurement layer), the distinctive behavioural phenotype expressed mostly through learning upon the introspection corpus, rather than by the DPO weight update alone (note the introspection corpus itself was generated by the DPO-

Table 3: Effect of LoRA factor alignment on the additive and PEFT factor-space combinations.

Pair	$\cos(A_D, A_S)$	Additive B_1	PEFT merge B_1	Difference
Reproduction	0.989	$+0.499$	$+1.923$	$+1.424$
P0	0.989	$+0.349$	$+1.281$	$+0.932$
Reseeded propagation	≈ 0	$+0.246$	$+0.291$	$+0.045$

adapted model and the two training stages are additive in weights).

E Reproducibility

- All figure paths quoted in the captions are relative to the code release at https://github.com/ukc10014/steering_across_personas/blob/main.
- Every figure caption names the script that draws it and a CSV of the exact values it plots. Those CSVs are written by the same scripts from cached analysis outputs under `outputs/analysis/`, so every number in every figure is auditable without rerunning inference.
- No figure in this paper requires a forward pass to rebuild. The whole set is CPU-reproducible from the archived analysis outputs.
- Arm names, ordering, color and marker come from a single style module; the palette is validated against Machado color-vision-deficiency transforms rather than asserted.
- **TODO.** Add exact adapter identifiers, the extraction scripts and their environment pins, the random-control constructors, the bootstrap and cross-fitting code, and the preregistration.

The published pipeline no longer describes the published adapters.

- Reproducing OCT from the repository at HEAD trains the introspection stage for one epoch. The released adapters were trained for three.
- The commit that changed it (`bd20b87`, "introspection 1 epoch instead of 3") lands **8 minutes 23 seconds after** the final upload of the released artifacts. Checked at both candidate release dates, the introspection runner reads `-max_epochs 3`.
- The DPO stage is unaffected: that runner has not changed since before the release and is byte-equivalent on every value used.
- Worth recording because of how it was caught. Every *behavioral* gate criterion passed the wrong artifact; the only check that failed it was a weight-norm comparison. A reproduction validated on behavior alone would have proceeded on a model trained for a third as long as the one it was reproducing.




Figure 12: The introspection SFT measured at 18 checkpoints through training (seed 123456, layer 15, forced prompt). The phenotype saturates well before one epoch, and the dose control shows this is not simply a matter of having moved the model further.

Provenance: figure `workshop_iclr/figures/figA_oct_sft_curve.pdf`; script `scripts/appendix_oct/figA_oct_sft_curve.py`; plotted values `workshop_iclr/data/figA_oct_sft_curve.csv`.

construction	step	epoch	dose	B_1	sel.	k	vs M_D
M_D+ΔW_S							
M_D (no SFT)	0	0.000	0.531	+0.132	1.106	0.448	1.0×
M_D+ΔW_S	45	0.120	0.579	+0.798	1.241	0.445	5.2×
M_D+ΔW_S	90	0.240	0.662	+1.484	1.448	0.405	7.5×
M_D+ΔW_S	180	0.481	0.743	+1.804	1.537	0.382	6.5×
M_D+ΔW_S	255	0.681	0.743	+2.049	1.581	0.397	7.4×
M_D+ΔW_S	270	0.722	0.748	+1.887	1.531	0.380	6.7×
M_D+ΔW_S	285	0.762	0.754	+2.333	1.686	0.399	8.0×
M_D+ΔW_S	300	0.802	0.764	+2.146	1.602	0.378	7.1×
M_D+ΔW_S	330	0.882	0.818	+2.067	1.500	0.363	5.5×
M_D+ΔW_S	375	1.002	0.782	+2.071	1.495	0.374	6.3×
M_D+ΔW_S	450	1.203	0.874	+2.157	1.418	0.393	*n/a*
M_D+ΔW_S	570	1.523	0.871	+2.254	1.447	0.404	*n/a*
M_D+ΔW_S	690	1.844	0.905	+2.252	1.393	0.394	*n/a*
M_D+ΔW_S	750	2.004	0.908	+2.134	1.384	0.385	*n/a*
M_D+ΔW_S	810	2.165	0.890	+2.177	1.412	0.393	*n/a*
M_D+ΔW_S	930	2.485	0.904	+2.211	1.400	0.387	*n/a*
M_D+ΔW_S	1050	2.806	0.907	+2.224	1.412	0.391	*n/a*
M_D+ΔW_S	1122	2.998	0.903	+2.197	1.415	0.388	*n/a*
merge							
M_D (no SFT)	0	0.000	0.531	+0.132	1.106	0.448	1.0×
merge	45	0.120	0.677	+0.778	1.225	0.363	3.7×
merge	90	0.240	0.735	+1.214	1.356	0.343	4.5×
merge	180	0.481	0.753	+1.490	1.530	0.318	5.1×
merge	285	0.762	0.775	+1.943	1.658	0.338	6.1×
merge	375	1.002	0.770	+1.781	1.552	0.324	5.7×
merge	750	2.004	0.821	+1.881	1.506	0.328	5.0×
merge	1122	2.998	0.828	+1.935	1.534	0.331	*n/a*

Table 4: The introspection SFT measured at checkpoints through training (seed 123456, layer 15, forced prompt). *step* is optimizer steps; one epoch is 374.2 steps, so the run is 1122 steps and the final row is the trained endpoint. *dose* is *measured* functional dose, never weight norm. The last column is the dose control: B_1 divided by B_1 of M_D scaled to the same measured dose, so $1.0\times$ would mean the checkpoint is worth no more than moving the model that far with the DPO adapter alone. Nothing is extrapolated outside M_D's measured range. The two constructions differ in SFT weight (1.00 against 0.25) as well as in the merge, so the gap between them is not the cross-term contribution.