

Nordex N149/4.0-4.5 – Power curves – Mode 0.a

for hub heights 105 m, 108 m, 125 m, 135 m, 145 m, 155 m and 164 m (mode on request for 164 m)								
wind speed v_H [m/s]	Power P_{el} [kW] at air density ρ [kg/m ³]							
	1.125	1.150	1.175	1.200	1.225	1.250	1.275	1.300
3.0	24	26	28	29	31	32	34	36
3.5	108	112	115	119	122	126	129	133
4.0	223	229	235	241	247	253	259	265
4.5	364	373	382	391	400	409	419	428
5.0	533	545	558	571	584	597	610	622
5.5	731	748	766	783	800	817	834	852
6.0	964	987	1009	1031	1054	1076	1098	1120
6.5	1236	1265	1293	1321	1349	1377	1405	1433
7.0	1551	1586	1621	1656	1691	1726	1761	1796
7.5	1912	1955	1998	2040	2083	2125	2168	2210
8.0	2321	2373	2424	2476	2527	2578	2630	2680
8.5	2781	2842	2901	2959	3016	3072	3127	3180
9.0	3278	3343	3404	3464	3520	3575	3629	3680
9.5	3770	3824	3875	3923	3969	4014	4057	4098
10.0	4158	4199	4239	4276	4311	4344	4376	4405
10.5	4447	4477	4504	4529	4552	4574	4594	4613
11.0	4643	4660	4676	4690	4703	4715	4726	4736
11.5	4757	4763	4768	4774	4778	4782	4786	4790
12.0	4800	4800	4800	4800	4800	4800	4800	4800
12.5	4800	4800	4800	4800	4800	4800	4800	4800
13.0	4800	4800	4800	4800	4800	4800	4800	4800
13.5	4800	4800	4800	4800	4800	4800	4800	4800
14.0	4800	4800	4800	4800	4800	4800	4800	4800
14.5	4800	4800	4800	4800	4800	4800	4800	4800
15.0	4800	4800	4800	4800	4800	4800	4800	4800
15.5	4800	4800	4800	4800	4800	4800	4800	4800
16.0	4800	4800	4800	4800	4800	4800	4800	4800
16.5	4800	4800	4800	4800	4800	4800	4800	4800
17.0	4800	4800	4800	4800	4800	4800	4800	4800
17.5	4800	4800	4800	4800	4800	4800	4800	4800
18.0	4800	4800	4800	4800	4800	4800	4800	4800
18.5	4800	4800	4800	4800	4800	4800	4800	4800
19.0	4800	4800	4800	4800	4800	4800	4800	4800
19.5	4761	4761	4761	4761	4761	4761	4761	4761
20.0	4655	4655	4655	4655	4655	4655	4655	4655
20.5*	4482	4482	4482	4482	4482	4482	4482	4482
21.0*	4307	4307	4307	4307	4307	4307	4307	4307
21.5*	4131	4131	4131	4131	4131	4131	4131	4131
22.0*	3951	3951	3951	3951	3951	3951	3951	3951
22.5*	3776	3776	3776	3776	3776	3776	3776	3776
23.0*	3600	3600	3600	3600	3600	3600	3600	3600
23.5*	3420	3420	3420	3420	3420	3420	3420	3420
24.0*	3245	3245	3245	3245	3245	3245	3245	3245
24.5*	3065	3065	3065	3065	3065	3065	3065	3065
25.0*	2885	2885	2885	2885	2885	2885	2885	2885
25.5*	2705	2705	2705	2705	2705	2705	2705	2705
26.0*	2529	2529	2529	2529	2529	2529	2529	2529

* These values are based on a yield and load optimized operation that is not feasible at all sites.