深度学习分散簇分类

1. 原理

通过输入已有点的坐标及类别来训练神经网络模型，然后根据模型来判断当前坐标内所有点的分类，并将分类边界画出来。

1.1 深度学习输入

这里有一些散点，其分布如下所示。



通过“位置随机”滑动条可以局部修改散点的位置分布，通过“噪声随机”滑动条可以使部分蓝色点分布到红色点中间，使红色点分布到蓝色点中间。我们可以以这些点为训练集来搭建一个神经网络模型，使我们能够通过该模型找到这两类点的分类边界。

1.2 网络层

“网络层”组件就是神经网络中的隐藏层，其组件内容如下：

华清远见元宇宙实验中心 yyzlab.com.cn

华清远见 HQYJ.COM

下面介绍它的各个参数：

1. neuron：神经元个数（节点个数）。
2. kernel_initializer：核的初始化方式（w的初始化）。
3. bias_initializer：偏置的初始化方式（b的初始化）。
4. activation：激活函数。

1.3 输出层

输出层的组件只有一个参数，即output_neuron，代表输出神经元的个数，由于这里的问题转换为二分类问题，所以输出层需要两个神经节点。



1.4 定义损失函数和优化器

定义完神经网络的结构后，就需要定义其中需要的超参数了，在“定义损失函数和优化器”组件中，可以选择损失函数、学习率、优化器及正则化率，不同的超参数会对神经网络的训练带来不同的效果。需要注意的是，由于本实验最后的目的是分类，所以这里的损失函数为交叉熵不可变。

华清远见元宇宙实验中心 yyzlab.com.cn

1.5 开始迭代

通过“开始迭代”组件，设置模型的训练次数。

1.6 显示频率设置

为了能够更好的观察迭代过程中的现象，可以通过“显示频率设置”组件来设置每隔多少次显示一次当前的曲线拟合状态。

1.7 深度学习输出

通过“深度学习输出”组件，可以观察到迭代过程中曲线的拟合状态。

华清远见元宇宙实验中心 yyzlab.com.cn



2. 编程实例与步骤

需要默认打开“华清远见人工智能虚拟仿真”和“华清远见人工智能虚拟仿真本地服务管理平台”。

2.1 （可选）使用“华清远见人工智能虚拟仿真本地服务管理平台”启动服务。

服务启动一次之后就不需要再次启动了。

华清远见元宇宙实验中心 syzlab.com.cn

单击深度学习分散簇分类实验进入

如果之前进入了某个实验，可以在实验面板的右上角点击“返回”回到主页即可。

2.2 拖出组件并连线

根据上述实验原理，将我们的逻辑抽象成组件之后，连线如下图所示，其中“网络层”组件可以有多个（最多不超过3个）。

华清远见元宇宙实验中心 yyzlab.com.cn



2.3 验证

点击验证，如显示校验成功，即代表逻辑无误，验证按钮与校验成功界面如下图所示。

2.4 运行

点击运行，可以实现功能运行，并显示结果输出，如下图所示。

华清远见元宇宙实验中心 yyzlab.com.cn

华清远见
HQYJ.COM



华清远见元宇宙实验中心
yyzlab.com.cn

2.5 代码生成

点击界面左下角的生成代码按钮，可生成本实验的Python代码，生成代码按钮如下图所示。

点击后可以查看该实验代码，代码会根据界面所选参数进行适配，点击复制可以将其复制，并粘贴在其它地方。

这里我们可以粘贴到软件的Jupyter中运行，“华清远见人工智能虚拟仿真本地服务管理平台”打开Jupyter，第一次打开Jupyter需要点击“打开CMD命令”，打开Jupyter后无需再次打开CMD，如下图所示。

在弹出的CMD命令行中，输入python -m jupyterlab --notebook-dir .\\learn，点击回车，浏览器会自动跳转打开Jupyter，如下图所示。



华清远见元宇宙实验中心 yvzlab.com.cn

如果没有自动跳转和打开浏览器，请输入下图中圈出的内容，每个人的该内容不一致，请复制自己的 弹出的。

```
F:\00HQYJProject\20虚拟仿真\人工智能虚拟仿真\源码\BS架构\华清远见人工智能虚拟仿真本地服务管理平台-源码\workspace>python
-m jupyterlab --notebook-dir .\\learn
[I 2022-12-26 09:28:37.282 ServerApp] jupyterlab | extension was successfully linked.
[W 2022-12-26 09:28:37.285 NotebookApp] 'shutdown_no_activity_timeout' has moved from NotebookApp to ServerApp. This con
fig will be passed to ServerApp. Be sure to update your config before our next release.
[I 2022-12-26 09:28:37.288 ServerApp] nbclassic | extension was successfully linked.
[I 2022-12-26 09:28:37.594 ServerApp] notebook_shim | extension was successfully linked.
[I 2022-12-26 09:28:37.613 ServerApp] notebook_shim | extension was successfully loaded.
[I 2022-12-26 09:28:37.613 LabApp] JupyterLab extension loaded from F:\00HQYJProject\20虚拟仿真\人工智能虚拟仿真\源码\BS
架构\华清远见人工智能虚拟仿真本地服务管理平台-源码\tools\Python\lib\site-packages\jupyterlab
[I 2022-12-26 09:28:37.613 LabApp] JupyterLab application directory is F:\00HQYJProject\20虚拟仿真\人工智能虚拟仿真\源码
\BS架构\华清远见人工智能虚拟仿真本地服务管理平台-源码\tools\Python\share\jupyter\lab
[I 2022-12-26 09:28:37.616 ServerApp] jupyterlab | extension was successfully loaded.
[I 2022-12-26 09:28:37.623 ServerApp] nbclassic | extension was successfully loaded.
[I 2022-12-26 09:28:37.624 ServerApp] Serving notebooks from local directory: F:\00HQYJProject\20虚拟仿真\人工智能虚拟仿
真\源码\BS架构\华清远见人工智能虚拟仿真本地服务管理平台-源码\workspace\learn
[I 2022-12-26 09:28:37.624 ServerApp] Jupyter Server 1.23.4 is running at:
[I 2022-12-26 09:28:37.624 ServerApp] http://localhost:8888/lab?token=9025b4e91c0adabb6891df5e009926ca57c65132098d9ee7
[I 2022-12-26 09:28:37.624 ServerApp]  or http://127.0.0.1:8888/lab?token=9025b4e91c0adabb6891df5e009926ca57c65132098d9e
e7
[I 2022-12-26 09:28:37.624 ServerApp] Use Control-C to stop this server and shut down all kernels (twice to skip confirm
ation).
[C 2022-12-26 09:28:37.646 ServerApp]

    To access the server, open this file in a browser:
        file:///C:/Users/82553/AppData/Roaming/jupyter/runtime/jpserver-27004-open.html
    Or copy and paste one of these URLs:
        http://localhost:8888/lab?token=9025b4e91c0adabb6891df5e009926ca57c65132098d9ee7
```

将代码输入到Jupyter中，点击运行可以查看结果。

3. 实验现象

实验结果为：