

Fastcampus

Computer Science School

Python Basic_Day2

Before we start



HackerRank

[Hackerrank 30 days of code](#)

[Hackerrank python challenges](#)

Strings

Strings

```
some_string = "python"  
len(some_string)
```

- index

p	y	t	h	o	n
0	1	2	3	4	5
-6	-5	-4	-3	-2	-1

```
some_string[3:5] = "ho"  
some_string[1:5:2] = "yh"  
some_string[::] = some_string[0:len(some_string):1]  
some_string[::-1] = some_string[-1:-len(some_string):-1]  
some_string[::-1] = "nohtyp"
```

but, strings are immutable

```
>>> some_string = "python"

>>> some_string[0] = "c"
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: 'str' object does not support item assignment

>>> some_string = "c" + some_string[1:]
```

String Functions

```
func = "python is easy programming language"  
func.count('p')
```

```
func.find('p')
```

```
comma = ","  
func = comma.join('python')
```

```
func.split(',')
```

```
python_is_easy = "python is easy"  
python_is_easy.split()
```

```
python_is_easy.replace("python", "golang")
```

String Functions

```
some_string = "    computer    "  
some_string.strip()
```

```
some_string = ",,,Fastcampus..."  
some_string.strip(",")  
some_string.strip(".")
```

String Formatting - New way

```
print("I have a {}, I have an {}".format("pen", "apple"))
```

```
print("I have a {0}, I have an {1}".format("pen", "apple"))
```

```
print("I have a {0}, I have an {0}".format("pen", "apple"))
```


List, Tuple

List

```
animals = [' ', ' ', ' ']
```

Tuple

```
animals = (' ', ' ', ' ')
```

List

빈 list를 선언합니다. 선언과 동시에 값을 채워넣을 수 있습니다.

```
lang = ["python", "c", "java", "golang"]
```

```
lang = []
```

list에 요소를 추가합니다.

```
lang.append("python")
```

```
lang.append("java")
```

```
lang.append("golang")
```

```
print(lang)
```

혹은 특정한 위치에 원하는 값을 추가할 수 있습니다.

```
lang.insert(1, "c")  
print(lang)
```

특정 요소를 삭제할 수도 있습니다.

```
lang.remove("golang")  
print(lang)
```

혹은 리스트에 있던 값을 빼낼 수도 있습니다.

```
java = lang.pop(2)  
print(lang)  
print(java)
```

리스트를 정렬하는 법을 알아보니다.

```
numbers = [2, 1, 4, 3]
```

```
print(numbers)
```

```
numbers.sort()
```

```
print(numbers)
```

리스트를 역순으로 출력하고 싶을땐 이렇게 한답니다.

```
numbers = [2, 1, 4, 3]
```

```
numbers.reverse()
```

```
print(numbers)
```

리스트를 내림차순으로 정렬하려면??

1. sort -> reverse

```
numbers.sort()  
numbers.reverse()
```

2. sort(reverse=True)

```
numbers.sort(reverse=True)
```

특정 값의 위치를 출력할때 이렇게 합니다.

```
index_of_two = numbers.index(2)  
print(index_of_two)
```

리스트끼리 더할 때 extend를 활용합니다.

```
numbers += [5, 6]  
print(numbers)  
numbers.extend([7, 8])  
print(numbers)
```

Tuple

Tuple은 괄호를 이용해 선언할 수 있습니다.

```
tuple1 = (1, 2, 3, 4)
```

tuple은 삭제나 추가가 불가능합니다.

```
del tuple[1]  
tuple1[1] = 'c'
```

tuple끼리 더하거나 반복하는 것은 가능합니다.

```
tuple2 = (5, 6)  
print(tuple1 + tuple2)  
  
print(tuple1 * 3)
```


tuple은 값을 편하게 바꿀 수 있습니다.

```
x = y
y = x (x)

temp = x
x = y
y = temp

(x,y) = (y,x)
```

혹은 함수에서 하나 이상의 값을 반환할 때 사용합니다.

```
def quot_and_rem(x,y):
    quot = x // y
    rem = x % y
    return (quot, rem)

(quot, rem) = quot_and_rem(3,10)
```

List <-> Tuple

```
list((1,2))  
tuple([1,2])
```

Dictionary, Set

dictionary의 선언

```
dict1 = {}  
print(dict1)
```

dictionary는 key와 value로 이루어져 있으며, 추가하는 법은 다음과 같습니다.

```
dict1 = {'name': 'foo bar'}  
print(dict1)
```

```
dict1 = {'korean': 95, 'math': 100, 'science': [80, 70, 90, 60]}  
print(dict1)
```

```
dict1['english'] = "pass"  
print(dict1)
```

요소 삭제는 del을 활용합니다.

```
del dict1['math']  
print(dict1)
```

key를 활용해 value를 출력하는 법을 알아보시다.

```
print(dict1['korean'])
```

key만 출력하는 법을 알아보시다.

```
print(dict1.keys())
```

value만 출력할땐 이렇게 합니다.

```
print(dict1.values())
```

key와 value를 함께 출력합니다.

```
print(dict1.items())
```

Small Quiz

$A = \text{'fastcampus'}$

$B = \text{'python'}$

$A \cup B$

$A \cap B$

$A - B$

$A \Delta B$

Set

- 수학 집합 연산을 쉽게 하기 위해 만든 자료형
- 순서없음
- 중복없음

Set

Set 선언

```
ppap = {'pen', 'apple', 'pineapple', 'pen'}  
print(ppap)
```

```
'apple' in ppap  
'applepen' in ppap
```

```
pineapple = set('pineapple')  
pineapple
```


Set

```
A = set('fastcampus')
```

```
B = set('python')
```

```
A ∪ B == A | B
```

```
A ∩ B == A & B
```

```
A - B == A - B
```

```
A Δ B == A ^ B
```

Toggl

<https://blog.toggl.com/wp-content/uploads/2016/12/toggl-it-jobs-explained-with-changing-lightbulb.jpg>

<https://assets.toggl.com/images/toggl-how-to-save-the-princess-in-8-programming-languages.jpg>

조건문

Let's get back to the Day1

배가 고프다!!!

- case 1: 집이라면
 - 밥이 있다면
 - 밥이 없다면
- case 2: 밖이라면
 - 현금이 10만원 초과라면
 - 현금이 5만원 초과라면
 - 현금이 없다면

If

if 조건:

실행문

if 조건1 **and** 조건2:

실행문

if 조건1 **or** 조건2:

실행문

if not 조건:

실행문

Comparison Operators

$x == n$

$x != n$

$x < n$

$x > n$

$x \leq n$

$x \geq n$

if

```
if 현금 > 100000:  
    레스토랑으로 간다
```

```
cash = 120000  
if cash > 100000:  
    print("go to restaurant")
```

else

```
if 조건:  
    실행문1  
else:  
    실행문2
```

```
cash = 120000  
if cash > 100000:  
    print("go to restaurant")  
else:  
    print("go to cvs")
```

else if

```
if 조건1:
    실행문1
else:
    if 조건2:
        실행문2
    else:
        실행문3
```

```
cash = 120000
if cash > 100000:
    print("go to restaurant")
else:
    if cash > 50000:
        print("go to bobjib")
    else:
        print("go to cvs")
```


if in else in if in else in ..

```
cash = 120000
if cash > 100000:
    print("go to restaurant")
elif cash > 50000:
    print("go to bobjib")
elif cash > 30000:
    print("go to buffet")
elif cash > 20000:
    print("go to ramen store")
elif cash > 10000:
    print("go to chinese restaurant")
else:
    print("go to cvs")
```

elif

```
if 조건1:
    실행문1
elif 조건2:
    실행문2
elif 조건3:
    실행문3
...
else:
    실행문n
```

elif

```
cash = 120000
if cash > 100000:
    print("go to restaurant")
elif cash > 50000:
    print("go to bobjib")
elif cash > 30000:
    print("go to buffet")
elif cash > 20000:
    print("go to ramen store")
elif cash > 10000:
    print("go to chinese restaurant")
else:
    print("go to cvs")
```

numguess

```
import random

answer = random.randint(1,100)
print(answer)
```

numguess

```
username = input("Hi there, What's your name?? ")
guess = eval(input("Hi, "+ username + "guess the number: "))

if guess == answer:
    print("Correct! The answer was ", str(answer))
else:
    print("That's not what I wanted!! The answer was ", str(
```

numguess advanced!!

how to make it with more fun??

For, while

```
for 변수 in (리스트 or 문자열):  
    실행문1  
    ...
```

```
for i in ["python", "java", "golang"]:  
    print(i)
```

For, while

```
sum = 0
for i in range(1,11):
    sum += i
    sum = sum + i
    print(sum)
```


For, while

```
while 조건:  
    실행문1  
    ...
```

```
while name != "foo bar":  
    name = input("What's your name? ")  
    print("Hi, " + name + "So, where is foo bar?")
```

```
while 1:  
    print("Hello world!")
```

Fizzbuzz

1부터 100까지 반복

3의 배수 = "Fizz"

5의 배수 = "Buzz"

15의 배수 = "FizzBuzz"

나머지 = 그 숫자

Fizzbuzz

```
num = eval(input("type the number: "))

for i in range(1, num + 1):
    if i % 15 == 0:
        print("fizzbuzz")
    elif i % 3 == 0:
        print("fizz")
    elif i % 5 == 0:
        print("buzz")
    else:
        print(i)
```

Refactoring numguess

```
import random

answer = random.randint(1,100)
username = input("Hi there, What's your name?? ")

while True:
    guess = eval(input("Hi "+ username + ", guess the number"))

    if guess == answer:
        print("Correct! The answer was ", str(answer))
        break
    else:
        print("That's not what I wanted!! Try again!!")
```

give a hint!!

```
import random

answer = random.randint(1,100)
username = input("Hi there, What's your name?? ")

while True:
    guess = eval(input("Hi, "+ username + "guess the number: "))

    if guess == answer:
        print("Correct! The answer was ", str(answer))
        break
    elif guess > answer:
        print("Too high!! Try again!!")
    elif guess < answer:
        print("Too Low!! Try again!!")
```

limit trial

```
import random

answer = random.randint(1,100)
username = input("Hi there, What's your name?? ")
trial = 5
while trial:
    guess = eval(input("Hi, "+ username + ". guess the number: "))

    if guess == answer:
        print("Correct! The answer was ", str(answer))
        break
    elif guess > answer:
        trial -= 1
        print("Too high!! Try again!!(%d times left)" % (trial))
    elif guess < answer:
        trial -= 1
        print("Too Low!! Try again!!(%d times left)" % (trial))

if trial == 0:
    print("You are Wrong! The answer was ", str(answer))
```

Monty Hall Problem

MONTY HALL PROBLEM

