

TypeScript Configuration Fix - Build Issue Resolved

Problem

The production build was failing with the following TypeScript error:

```
Type error: Cannot find type definition file for 'bcryptjs'.  
The file is in the program because:  
Entry point for implicit type library 'bcryptjs'
```

Root Cause

The issue was caused by conflicting type definitions:

1. The `@types/bcryptjs` package was installed in package.json
2. A custom `bcryptjs.d.ts` declaration file existed in the project root
3. The `typeRoots` configuration in `tsconfig.json` was pointing to non-standard paths
4. TypeScript was unable to resolve which type definitions to use

Solution Implemented

Two changes were made to resolve the issue:

1. Removed typeRoots Configuration from tsconfig.json

File: `/home/ubuntu/fitness_coach_app/nextjs_space/tsconfig.json`

Removed the problematic `typeRoots` configuration that was causing path resolution issues:

```
// REMOVED:  
"typeRoots": [  
  "./node_modules/@types",  
  "/opt/hostedapp/node/root/app/node_modules/@types"  
]
```

This allows TypeScript to use its default type resolution behavior.

2. Uninstalled @types/bcryptjs Package

Command: `npm uninstall @types/bcryptjs --legacy-peer-deps`

Since the project already has a custom type declaration file (`bcryptjs.d.ts`), the conflicting `@types` package was removed. The custom declaration file provides all necessary type information:

```
declare module 'bcryptjs' {
  export function hash(data: any, rounds: any): Promise<any>;
  export function compare(data: any, encrypted: any): Promise<any>;
  export function hashSync(data: any, rounds: any): any;
  export function compareSync(data: any, encrypted: any): any;
}
```

Build Verification

After implementing these fixes:

- ✓ **Production build succeeded** - All 15 routes compiled successfully
- ✓ **TypeScript type checking passed** - No compilation errors
- ✓ **Authentication functionality preserved** - bcryptjs imports and usage remain intact
- ✓ **All bcryptjs usage points verified:**
 - lib/auth-options.ts - Password comparison during login
 - app/api/signup/route.ts - Password hashing during registration
 - scripts/seed.ts - Password hashing for seed data

Build Output Summary

Route (app)	Size	First Load JS
f /	2.15 kB	115 kB
f /api/auth/[...nextauth]	0 B	0 B
f /api/chat	0 B	0 B
f /api/health/today	0 B	0 B
f /api/onboarding	0 B	0 B
f /api/settings	0 B	0 B
f /api/signup	0 B	0 B
f /coach	2.98 kB	107 kB
f /home	3.58 kB	108 kB
f /login	2.06 kB	115 kB
f /onboarding	9.08 kB	113 kB
f /settings	3.45 kB	108 kB
f /signup	2.41 kB	115 kB
f /trends	1.75 kB	89 kB
+ First Load JS shared by all	87.2 kB	

Files Modified

1. /home/ubuntu/fitness_coach_app/nextjs_space/tsconfig.json - Removed typeRoots configuration
2. /home/ubuntu/fitness_coach_app/nextjs_space/package.json - Removed @types/bcryptjs dependency

Files Preserved (Unchanged)

- /home/ubuntu/fitness_coach_app/nextjs_space/bcryptjs.d.ts - Custom type declarations
- /home/ubuntu/fitness_coach_app/nextjs_space/lib/auth-options.ts - Authentication logic
- /home/ubuntu/fitness_coach_app/nextjs_space/app/api/signup/route.ts - Registration logic
- /home/ubuntu/fitness_coach_app/nextjs_space/scripts/seed.ts - Database seeding

Deployment Status

 **The application is now ready for deployment!**

The production build completes successfully and all TypeScript errors have been resolved. The authentication functionality using bcryptjs remains fully functional.

Next Steps for Deployment

1. Set up environment variables (`.env` file with DATABASE_URL, NEXTAUTH_SECRET, etc.)
 2. Run database migrations: `npx prisma migrate deploy`
 3. (Optional) Seed the database: `npm run prisma db seed`
 4. Start the production server: `npm run start`
-

Fix completed on: December 6, 2025

Build system: Next.js 14.2.28

TypeScript version: 5.2.2