

```

# pip install keras
# pip install tensorflow (backend)
# pip install pydot
# pip install graphviz

from keras.preprocessing import sequence
from keras.models import Sequential
from keras.layers import Dense, Embedding, Flatten
from keras.datasets import imdb
from keras.callbacks import EarlyStopping

max_features = 20000
maxlen = 80 # cut texts after this number of words (among top max_features most
common words)
batch_size = 32

print('Loading data...')
(x_train, y_train), (x_test, y_test) = imdb.load_data(num_words=max_features) # Replace
this and create your own data loader and pre-processing for the given data on e-dimension
print(len(x_train), 'train sequences')
print(len(x_test), 'test sequences')

print('Pad sequences (samples x time)')
x_train = sequence.pad_sequences(x_train, maxlen=maxlen)
x_test = sequence.pad_sequences(x_test, maxlen=maxlen)
print('x_train shape:', x_train.shape)
print('x_test shape:', x_test.shape)

print('Build model...')
model = Sequential()
# keras.layers.Embedding(input_dim, output_dim, embeddings_initializer='uniform',
embeddings_regularizer=None, activity_regularizer=None, embeddings_constraint=None,
mask_zero=False, input_length=None)
model.add(Embedding(max_features, 128, input_shape=(maxlen,), trainable=True))

model.add(Flatten())
model.add(Dense(128))
model.add(Dense(1, activation='sigmoid'))

print(model.summary())

from keras.utils import plot_model
plot_model(model, to_file='model.png')

es = EarlyStopping(monitor='val_loss', mode='min', patience=10)

```

```
# try using different optimizers and different optimizer configs
model.compile(loss='binary_crossentropy',
              optimizer='adam',
              metrics=['accuracy'])
print('Train...')
model.fit(x_train, y_train,
        batch_size=batch_size,
        epochs=15,
        validation_split=0.1, callbacks=[es])
score, acc = model.evaluate(x_test, y_test,
                          batch_size=batch_size)
print('Test score:', score)
print('Test accuracy:', acc)
```