

- ultrasphere and ultrasphere-harmonics: Python
- ² packages for Vilenkin–Kuznetsov–Smorodinsky
- 3 polyspherical coordinates and hyperspherical
- 4 harmonics methods in array API
- ⁵ Hiromochi Itoh^{1*}, Kei Matsushima^{2*}, and Takayuki Yamada³
- ₆ 1 Department of Mechanical Engineering, Graduate School of Engineering, The University of Tokyo,
- Japan ROR 2 Graduate School of Advanced Science and Engineering, Hiroshima University, Japan ROR 3
- 8 Department of Strategic Studies, Institute of Engineering Innovation, Graduate School of Engineering,
- The University of Tokyo ROR * These authors contributed equally.

DOI: 10.xxxxx/draft

Software

- Review 🗗
- Repository 🖸
- Archive 🗗

Editor: Open Journals ♂ Reviewers:

@openjournals

Submitted: 01 January 1970 **Published:** unpublished

License

Authors of papers retain copyrights and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0)2

Summary

Spherical harmonics, which are the solutions to the angular part of the laplace equation, have been widely used in various fields of science and engineering. Especially, hyperspherical harmonics, which are spherical harmonics in higher dimensions, have been applied to many-body problems in quantum mechanics (Fock, 1935), representation of crystallographic textures (Bonvallet et al., 2007), description of 3D models (Bonvallet et al., 2007), representation of brain structures (Hosseinbor et al., 2013).

Statement of need

ultrasphere and ultrasphere-harmonics are Python packages for hyperspherical coordinates and hyperspherical harmonics techniques. Our packages is that they support any type of Vilenkin–Kuznetsov–Smorodinsky polyspherical coordinate systems (Vilenkin & Klimyk, 1993). This allows to write codes that work in any type of polyspherical coordinates and thus in any number of dimensions. To demonstrate this, we implemented acoustic scattering from a single sphere for any type of polyspherical coordinates, which could be verified by command-line interface.

Our api is compatible with the array API standard (Meurer et al., 2023). This enables writing code which runs on multiple array libraries (e.g., NumPy(Harris et al., 2020), PyTorch(Paszke et al., 2019)) and multiple hardware (e.g., CPU, GPU). Our packages fully support vectorization for high performance computing.

• Acknowledgements

- This work used computational resources Supermicro ARS-111GL-DNHR-LCC and FUJITSU Server PRIMERGY CX2550 M7 (Miyabi) at Joint Center for Advanced High Performance
- ³² Computing (JCAHPC) and TSUBAME4.0 supercomputer provided by Institute of Science
- 33 Tokyo through Joint Usage/Research Center for Interdisciplinary Large-scale Information
- Infrastructures and High Performance Computing Infrastructure in Japan (Project ID: jh240031).



References

- Bonvallet, B., Griffin, N., & Li, J. (2007). A 3D shape descriptor: 4D hyperspherical harmonics
 "an exploration into the fourth dimension". Proceedings of the IASTED International
 Conference on Graphics and Visualization in Engineering, 113–116. ISBN: 9780889866270
- Fock, V. (1935). Zur theorie des wasserstoffatoms. *Zeitschrift Für Physik*, *98*(3), 145–154. https://doi.org/10.1007/BF01336904
- Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,
 Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk,
 M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., ... Oliphant,
 T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2
- Hosseinbor, A. P., Chung, M. K., Schaefer, S. M., Reekum, C. M. van, Peschke-Schmitz, L.,
 Sutterer, M., Alexander, A. L., & Davidson, R. J. (2013). 4D hyperspherical harmonic
 (HyperSPHARM) representation of multiple disconnected brain subcortical structures.
 Medical Image Computing and Computer-Assisted Intervention: MICCAI ... International
 Conference on Medical Image Computing and Computer-Assisted Intervention, 16(0),
 598-605. https://doi.org/10.1007/978-3-642-40811-3_75
- Meurer, A., Reines, A., Gommers, R., Fang, Y.-L. L., Kirkham, J., Barber, M., Hoyer, S., Müller, A., Zha, S., Shanabrook, S., Gacha, S. J., Lezcano-Casado, M., Fan, T. J., Reddy, T., Passos, A., Kwon, H., Oliphant, T., & Standards, C. for P. D. A. (2023). Python array API standard: Toward array interoperability in the scientific python ecosystem. *Scipy*. https://doi.org/10.25080/gerudo-f2bc6f59-001
- Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,
 Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M.,
 Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch:
 An imperative style, high-performance deep learning library. In *Proceedings of the 33rd international conference on neural information processing systems* (pp. 8026–8037). Curran
 Associates Inc.
- Vilenkin, N. Ja., & Klimyk, A. U. (1993). Representation of lie groups and special functions (Vol. 74). Springer Netherlands. https://doi.org/10.1007/978-94-017-2883-6