

Quantity	Comment	Designator	MF	MPN	Value	Description	Footprint	Package	Voltage	Dielectric	Supplier 1	Supplier Part Number 1	Supplier 2	Supplier Part Number 2	Supplier 3	Supplier Part Number 3
6	0.1 µF	C1, C2, C11, C12, C17, C18			0.1 µF	Capacitor 0805, 50 VDC, 0.1 µF, X7R	C_0805				Mouser	80-C0805C104J5REC TU				
9	0.01 µF	C3, C4, C6, C7, C8, C9, C13, C14, C15			0.01 µF	Capacitor 0805, 100 VDC, 0.01 µF, X7R	C_0805				Mouser	81-GRM21BR72A103K				
3	10 µF	C5, C10, C16			10 µF	Capacitor; 2 Leads	CAPR5-4X5					CAPR5-4X5				
3	Littelfuse_PTC_1812	F1, F2, F3	Littelfuse	miniASMDC110F/24	PTC, 1.1 A, 24V	POLYSWITCH RESETTABLE DEVICES	1812_PTC_Polyfuse_Littelfuse	1812	24V							
3	DSUB1.385-2H9	J1, J2, J3				Connector; D Subminiature; 9 Position; Right Angle; Pitch 1.385 mm	DSUB1.385-2H9									
9	120R	R1, R2, R3, R7, R8, R9, R11, R12, R13			120R	SMD resistor E24 series	RES_0603_1608				Mouser	660-RK73B1JTTD121J				
3	Res Pack3	R4, R10, R14			4.7K	SOIC, 16-Leads, Body 9.9x3.9mm, Pitch 1.27mm, IPC Medium Density	SO-16_N				Altium					
2	R_TF	R5, R6			0R	SMD resistor E24 series	RES_0603_1608				Mouser	603-RC0603JR-070RL	LCSC	C21189		
1	Serial #	Serial				Field to put in a serial number	SERIAL									
3	ISO7230MDW	U1, U6, U9				ISO723xx High-Speed, Triple-Channel Digital Isolators	TI ISO7230 SOIC				Mouser	595-ISO7230MDW				
3	DS26LS32ACM	U2, U4, U7				DS26LS32AC/DS26LS32C/D S26LS32M/DS26LS33M Quad Differential Line Receivers	M16A_M				Mouser	926-DS26LS32ACM				
3	TMH 0505S	U3, U5, U8				ISOLIERTE DC-DC-WANDLER Product Type: DC/DC; Package Style: SIP; Output Power (W): 2; Input Voltage: 5 VDC +/- 10%; Output 1 (Vdc): 5; Output 2 (Vdc): N/A; Output 3 (Vdc): N/A	SIL-6(7)				Mouser	495-TMH-0505S				
2	Pin Header	X2, X3	Samtec Inc.			THROUGH-HOLE .025" SQ POST HEADER	SAMTEC_TSW110-07-F-T	None			Mouser	200-TSW11007FT				
1	Pin Header	X4	Samtec			THROUGH-HOLE .025" SQ POST HEADER	SAMTEC_TSW106-07-F-D	None			Mouser	200-TSW10607FD				
3	Pin Header	X5, X6, X7				8 Pin	HDR1X8				Altium	HDR1X8				