

```
MATCH ()-[r:MADE_TRANSACTION]->()

WITH r

CALL {

WITH r

SET r.paymentMethod =

CASE

WHEN rand() < 0.33 THEN 'Credit Card'

WHEN rand() < 0.66 THEN 'Mobile Payment'

ELSE 'PayPal'

END,

r.promotionalOffer = rand() < 0.3,

r.satisfactionRating = 1 + toInteger(rand() * 5)

}

IN TRANSACTIONS OF 10000 ROWS;
```

1 MATCH ()-[r:MADE_TRANSACTION]->()
2 RETURN
3 r.paymentMethod,
4 r.promotionalOffer,
5 r.satisfactionRating
6 LIMIT 10;

Table

RAW

Q

T

↓

	r.paymentMethod	r.promotionalOffer	r.satisfactionRating
1	"Credit Card"	true	1
2	"Credit Card"	false	4
3	"PayPal"	true	3
4	"PayPal"	false	4
5	"Credit Card"	true	5
6	"Mobile Payment"	false	3
7	"Credit Card"	false	2
8	"PayPal"	false	1
9	"Mobile Payment"	false	5
10	"Mobile Payment"	false	2

Started streaming 10 records after 88 ms and completed after 89 ms.

2.

neo4j\$ MATCH (c1:Customer)-[r1:MADE_TRANSACTION]->(t:Terminal) MATCH (

Table RAW

count(*)

1 32323

✓ Created 32,323 relationships, set 64,646 properties
Started streaming 1 record after 2 ms and completed after 7 minutes 28 seconds.

```
MATCH (c1:Customer)-[r1:MADE_TRANSACTION]->(t:Terminal)
```

```
MATCH (c2:Customer)-[r2:MADE_TRANSACTION]->(t)
```

```
WHERE c1.id < c2.id
```

```
WITH c1,c2,t,
```

```
count(r1) AS tx1,
```

```
count(r2) AS tx2,
```

```
avg(r1.satisfactionRating) AS avgSat1,
```

```
avg(r2.satisfactionRating) AS avgSat2
```

```
WHERE tx1 >= 5
```

```
AND tx2 >= 5
```

```
AND abs(avgSat1 - avgSat2) <= 0.5
```

```
MERGE (c1)-[:FREQUENT_COLLABORATOR {
```

```
terminalId: t.id,
```

```
avgRatingDiff: abs(avgSat1 - avgSat2)
```

```
}}->(c2)
```

```
RETURN count(*);
```