NAME :AL UMA
REGISTER NO:230701368
EX 3: POLYNOMIAL MANIPULATION

```
#include<stdio.h>
#include<stdlib.h>

struct node
{
   int coef;
   int power;
   struct node*link;
};
typedef struct node NODE;

void create_poly(NODE *list)
{
   int coef;
   int power;
   int choice;
   NODE *newnode;
   do{
   newnode=malloc(sizeof(NODE));
   printf("Enter the coefficient : ");
   scanf("%d", &coef);

    printf("Enter the power : ");
    scanf("%d", &power);

    newnode->coef=coef;
    newnode->power=power;
    newnode->link=NULL;

    if(list->link==NULL)
    {
       list->link=newnode;
    }
    else
    {
       while(list->link!=NULL)
       {
          list=list->link;
       }
```

```
        list->link=newnode;
    }
    printf("Enter 1 to continue : ");
    scanf("%d", &choice);
   }
   while(choice==1);
}
void add(NODE *list1,NODE *list2,NODE *Result)
{
    NODE *newnode,*temp=Result;
   while(list1!=NULL && list2!=NULL)
 {

    newnode=malloc(sizeof(NODE));
    if(list1->power == list2->power)
    {
      newnode->coef = list1->coef+list2->coef;
      newnode->power =list1->power;
      newnode->link=NULL;
      list1=list1->link;
      list2=list2->link;

    }
    else if(list1->power > list2->power)
    {
      newnode->coef=list1->coef;
      newnode->power=list1->power;
      newnode->link=NULL;
      list1 = list1->link;
    }
    else if(list1->power<list2->power)
    {
        newnode->coef=list2->coef;
        newnode->power=list2->power;
        newnode->link=NULL;
        list2=list2->link;

    }
     temp->link=newnode;
     temp=temp->link;

 }

 while(list2!=NULL || list2!=NULL)
```

```
 {
   newnode = malloc(sizeof(NODE));
   if(list1->link!=NULL)
   {
     newnode->coef=list1->coef;
     newnode->power=list1->power;
     newnode->link= NULL;
     list1=list1->link;
   }
  if(list2->link!= NULL)
  {
     newnode->coef=list2->coef;
     newnode->power=list2->power;
     newnode->link= NULL;
     list2 = list2->link;
   }
    temp->link=newnode;
    temp=temp->link;
 }
}



void sub(NODE *list1,NODE *list2,NODE *Result)
{
    NODE *newnode,*temp=Result;
    while(list1!=NULL && list2!=NULL)
    {
        newnode=malloc(sizeof(NODE));
        if(list1->power==list2->power)
        {
          newnode->coef=list1->coef-list2->coef;
           newnode->power=list1->power;
           list1=list1->link;
           list2=list2->link;
        }
       else if(list1->power>list2->power)
       {
         newnode->coef=list1->coef;
         newnode->power=list1->power;
         list1=list1->link;
       }
       else if(list1->power<list2->power)
       {
```

```
            newnode->coef= -(list2->coef);
            newnode->power=list2->power;
            list2=list2->link;
          }
          newnode->link= NULL;
          temp->link=newnode;
          temp=temp->link;
        }

        while(list1!=NULL || list2!= NULL)
       {
        newnode = malloc(sizeof(NODE));
        if(list1!= NULL)
        {
          newnode->coef=list1->coef;
          newnode->power=list1->power;
          list1 = list1->link;
        }
        if(list2 != NULL)
        {
          newnode->coef= -(list2->coef);
          newnode->power=list2->power;
          list2 = list2->link;
        }
        newnode->link= NULL;
        temp->link=newnode;
        temp=temp->link;
      }
    }

    void multi(NODE *list1, NODE *list2, NODE *Result)
    {
       NODE *newnode;
       NODE *t1=list1->link;
       NODE *t2=list2->link;
       NODE *t3=Result;

       while(t1!=NULL)
       {
          t2=list2->link;
          while(t2!=NULL)
          {
             newnode=(NODE*)malloc(sizeof(NODE));
             t3->link=newnode;
```

```
            newnode->coef=t1->coef*t2->coef;
            newnode->power=t1->power+t2->power;
            t2=t2->link;
            newnode->link=NULL;
            t3=t3->link;
        }
        t1=t1->link;
    }
}

void display(NODE *list)
{
    NODE *temp=list->link;
    while(temp!=NULL)
    {
       printf("%dX^%d",temp->coef,temp->power);
        temp=temp->link;
        if(temp != NULL && temp->coef >= 0)
         {
           printf("+");
          }
    }
}

int main(){
    int t=1,choice;
    NODE *Poly1 = malloc(sizeof(NODE));
     NODE *Poly2 = malloc(sizeof(NODE));
     NODE *Result = malloc(sizeof(NODE));
    while (t==1){
        Poly1->link=NULL;
        Poly2->link=NULL;
        printf("\n\n\nMENU\n");
        printf("1.Add the polynomials\n2.Subtract the polynomials\n3.Multiply the
polynomials\n4.EXIT\n");
        printf("\nEnter your choice:");
        scanf("%d",&choice);
        if (choice!=4){
            printf("Enter the values for first polynomial :\n");
            create_poly(Poly1);
            printf("The polynomial equation is : ");
            display(Poly1);
            printf("\nEnter the values for second polynomial :\n");
            create_poly(Poly2);
```

```
            printf("The polynomial equation is : ");
            display(Poly2);
        }
        switch (choice)
        {
            case 1:
            add(Poly1, Poly2, Result);
            printf("\nThe polynomial equation addition result is : ");
            display(Result->link);
            break;
            case 2:
            sub(Poly1, Poly2, Result);
            printf("\nThe polynomial equation addition result is : ");
            display(Result->link);
            break;
            case 3:
            multi(Poly1, Poly2, Result);
            printf("\nThe polynomial equation addition result is : ");
            display(Result);
            break;
            case 4:
            t=0;
            break;
        }
    }
}
```