

NAME: AL UMA
REG NO 230701368
EX NO16

IMPLEMENTATION OF COLLISION RESOLUTION TECHNIQUE

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

#define SIZE 10 // Size of the hash table

// Structure to represent a node in the hash table
struct Node {
    int key;
    int value;
};

// Structure to represent the hash table
struct HashTable {
    struct Node* array[SIZE];
};

// Function to create a new node
struct Node* createNode(int key, int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->key = key;
    newNode->value = value;
    return newNode;
}

// Function to create a hash table
struct HashTable* createHashTable() {
    struct HashTable* hashTable = (struct HashTable*)malloc(sizeof(struct HashTable));
    for (int i = 0; i < SIZE; i++) {
        hashTable->array[i] = NULL;
    }
    return hashTable;
}

// Function to calculate the hash index
int hash(int key) {
    return key % SIZE;
}
```

```
// Function to perform open addressing (linear probing) for collision resolution
void linearProbing(struct HashTable* hashTable, int key, int value) {
```

```
    int index = hash(key);
    while (hashTable->array[index] != NULL) {
        index = (index + 1) % SIZE; // Linear probing
    }
    hashTable->array[index] = createNode(key, value);
}
```

```
// Function to perform closed addressing (chaining) for collision resolution
```

```
void chaining(struct HashTable* hashTable, int key, int value) {
```

```
    int index = hash(key);
    struct Node* newNode = createNode(key, value);
    if (hashTable->array[index] == NULL) {
        hashTable->array[index] = newNode;
    } else {
        // Adding to the end of the linked list at the index
        struct Node* temp = hashTable->array[index];
        while (temp->next != NULL) {
            temp = temp->next;
        }
        temp->next = newNode;
    }
}
```

```
// Function to display the hash table
```

```
void display(struct HashTable* hashTable) {
    for (int i = 0; i < SIZE; i++) {
        printf("%d: ", i);
        struct Node* temp = hashTable->array[i];
        while (temp != NULL) {
            printf("(%d, %d) ", temp->key, temp->value);
            temp = temp->next;
        }
        printf("\n");
    }
}
```

```
int main() {
```

```
    struct HashTable* hashTable_linear = createHashTable();
    struct HashTable* hashTable_chaining = createHashTable();
```

```
    // Inserting elements using linear probing
```

```
linearProbing(hashTable_linear, 10, 20);
linearProbing(hashTable_linear, 21, 30);
linearProbing(hashTable_linear, 22, 40);
linearProbing(hashTable_linear, 23, 50);
linearProbing(hashTable_linear, 33, 60);

// Inserting elements using chaining
chaining(hashTable_chaining, 10, 20);
chaining(hashTable_chaining, 21, 30);
chaining(hashTable_chaining, 22, 40);
chaining(hashTable_chaining, 23, 50);
chaining(hashTable_chaining, 33, 60);

printf("Hash Table with Linear Probing:\n");
display(hashTable_linear);

printf("\nHash Table with Chaining:\n");
display(hashTable_chaining);

return 0;
}
```