

# Jenkins Integration with Selenium

## Table of content

- Jenkins with selenium
- Install Jenkins
- Run Selenium with Batch file
- Set Jenkins Job
- Jenkins Plugins
- Generate Report in Jenkins
- Master-Slave in Jenkins

## Jenkins with selenium

Jenkins is an open-source automation server written in Java. Jenkins helps to automate the non-human part of the software development process, with continuous integration.

It works based on plugins, i.e., have to install respective plugins in order to communicate. For example, Maven, Git plugins have to install with configuration.

Instead of pulling the entire code for building and testing. You can just use Jenkins to automatically fetch the code from the repository, build and test it in the test environment and can send an email notification about the results so it will be easier to find the bug in that version of the commit, instead of going through the whole code to find the bug.

### Advantages of Jenkins:

*It is open-source, and it is user-friendly, easy to install, and does not require additional installations or components.*

*Easily Configurable. Jenkins can be easily modified and extended. It deploys code instantly, generates test reports. Jenkins can be configured according to the requirements for continuous integrations and continuous delivery.*

*Platform Independent. Jenkins is available for all platforms and different operating systems, whether OS X, Windows, or Linux.*

*Rich Plugin ecosystem. The extensive pool of plugins makes Jenkins flexible and allows building, deploying, and automating across various platforms.*

*Easy support. Because it is open-source and widely used, there is no shortage of support from large online communities of agile teams.*

*Developers write the tests to detect the errors of their code as soon as possible. So the developers don't waste time on large-scale error-ridden integrations.*

*Issues are detected and resolved almost right away, which keeps the software in a state where it can be released at any time safely.*

*Most of the integration work is automated. Hence fewer integration issues. This saves both time and money over the lifespan of a project.*

## Install Jenkins

1. Navigate to : <https://jenkins.io/download/>
2. Download the Generic war files, choose the war file from the stable release

**Download Jenkins 2.107.3 for:**

- Docker
- Ubuntu/Debian
- Windows
- Generic Java package (.war)**

**Docker**

- FreeBSD
- OpenIndiana Hipster
- Windows
- Generic Java package (.war)

3. Go to the folder in terminal/CMD where you have stored the jenkins.war file and execute the below command.

```
java -jar jenkins.war
```

4. You would be able to success screen once we execute the command.
5. Navigate to the URL in your browser <http://localhost:8080>; sometimes, it may take up to 3 minutes to open the page, so have patience if you get no page/ error page.
6. Please navigate to the highlighted path in your browser, and copy the password.

### Unlock Jenkins

To ensure Jenkins is securely set up by the administrator, a password has been written to the log (not sure where to find it?) and this file on the server:

```
C:\Program Files (x86)\Jenkins\secrets\initialAdminPassword
```

Please copy the password from either location and paste it below.

Administrator password

.....

7. Install /

select plugins based on your need, you can install plugins after installation of Jenkins as well.

# Customize Jenkins

Plugins extend Jenkins with additional features to support many different needs.

## Install suggested plugins

Install plugins the Jenkins community finds most useful.

## Select plugins to install

Select and install plugins most suitable for your needs.

8. You may

need to wait for 10-15 mins for the completion of the installation of plugins.

# Getting Started

✓ Folders	✓ OWASP Markup Formatter	✓ Build Timeout	✓ Credentials Binding
✓ Timestampers	⌚ Workspace Cleanup	⌚ Ant	⌚ Gradle
⌚ Pipeline	⌚ GitHub Branch Source	⌚ Pipeline: GitHub Groovy Libraries	⌚ Pipeline: Stage View
⌚ Git	⌚ Subversion	⌚ SSH Slaves	⌚ Matrix Authorization Strategy
⌚ PAM Authentication	⌚ LDAP	⌚ Email Extension	⌚ Mailer

9. Fill the use

details and continue

# Create First Admin User

Username:	<input type="text" value="cherchertech"/>
Password:	<input type="password" value="....."/>
Confirm password:	<input type="password" value="....."/>
Full name:	<input type="text" value="karthiq"/>
E-mail address:	<input type="text" value="karthiq@chercher.tech"/>

10. Click on

start Jenkins button


# Jenkins is ready!

Your Jenkins setup is complete.

[Start using Jenkins](#)

11. If you

reached the below page, then your installation is successful.



Single Inheritance in Selenium and java

## Run Selenium with Batch file

Create a selenium sample test using TestNg as a unit testing framework and create testng.xml. Below is the same test file we have created :

```
public class TestJenkins {
    @Test
    public void openGoogle() {

        System.out.println("Test Started");
        System.setProperty("webdriver.chrome.driver", "D:PATHchromedriver.exe");

        System.out.println("open browser");
        WebDriver driver = new ChromeDriver();
        driver.manage().timeouts().implicitlyWait(30, TimeUnit.SECONDS);

        System.out.println("open google");
        driver.get("https://google.com");


        driver.quit();
        System.out.println("Test Ended");
    }
}
```

Once you create the testng.xml file, place the below jars under "jars" folder:

*testng*

*Jcommander*

*Selenium standalone server*



Now execute the below command in the cmd/terminal to open run the test case; you must be inside the project folder with cmd, i.e., where you have the .classpath file.

```
java -cp Class_Files_Path; Jars_Path org.testng.TestNG testng.xml
java -cp bin;jars/* org.testng.TestNG testng.xml
```

```
D:\Eclipse progs\TestJenkins>java -cp bin;jars/* org.testng.TestNG testng.xml
[TestNG] Running:
  D:\Eclipse progs\TestJenkins\testng.xml

Test Started
open browser
Starting ChromeDriver 2.35.528161 (5b82f2d2aae0ca24b877009200ced9065a772e73) on port 48616
Only local connections are allowed.
May 22, 2018 1:10:53 AM org.openqa.selenium.remote.ProtocolHandshake createSession
INFO: Detected dialect: OSS
open google
Test Ended


=====
Suite
Total tests run: 1, Failures: 0, Skips: 0
=====
```

If you command-line execution is successful, then add the same line into the notepad and save the file as run.bat


Now try to run the bat file by double-clicking; it should perform the same operations as cmd execution.

## Set Jenkins Job


Open Jenkins and select 'New Item.'



Enter the Job Name and Select Free Style project and click ok button.



Select Custom workspace under the General section and provide the project folder details.



Under Build Section, choose Execute window batch command and provide our batch file name.

The screenshot shows the Jenkins 'Build' configuration page. It is divided into two sections: 'Step1' and 'Step2'. In 'Step1', there is a dropdown menu 'Add build step' with two options: 'Execute Windows batch command' (which is selected and highlighted with a blue border) and 'Execute shell'. In 'Step2', there is a section titled 'Execute Windows batch command' with a 'Command' field containing the text 'run.bat'.

Click the Save button, Jenkins now will open the home page.


Click the Build Now link to run our project in Jenkins.

The screenshot shows the Jenkins 'Project Running Bat' page. The top header is 'Jenkins' with a logo. Below it, there is a breadcrumb 'Jenkins > Running Bat'. On the left, there is a sidebar with links: 'Back to Dashboard' (with a green arrow icon), 'Status' (with a magnifying glass icon), 'Changes' (with a notepad icon), 'Workspace' (with a folder icon), and 'Build Now' (with a green arrow icon and a red border). On the right, the main heading is 'Project Running Bat' with the subtitle 'Project name: FirstSeleniumScript'. At the bottom right, there is a folder icon.

Once the Jobs starts Heartbeat starts, the orange sphere is the heartbeat, and the Green arrow is Build Name.

The screenshot shows the Jenkins 'Build History' page. The top header is 'Build History' with a gear icon on the left and a 'trend' link with a minus sign on the right. Below the header, there is a search bar with the text 'find' and a close button 'x'. Below the search bar, there is a list of builds. The first build is highlighted with a green arrow pointing to it. The build is labeled '#1' with a blue sphere icon to its left. To the right of the build number, the date and time 'May 22, 2018 1:42 AM' are displayed. Below the build list, there are two RSS links: 'RSS for all' and 'RSS for failures', each with an RSS icon.

Now click the build number to see the details and select the Console Output option.



The screenshot shows the Jenkins 'Console Output' page. On the left sidebar, 'Console Output' is highlighted with an orange box, and 'View as plain text' is also highlighted. The main content area shows the build log. The first part of the log shows the build starting by user 'karthiq' and running 'run.bat'. The second part, highlighted with an orange box, shows the test execution details: 'Test Started', 'open browser', 'Starting ChromeDriver 2.35.528161 (5b82f2d2aae0ca24b877009200ced9065a772e73) on port 37948', 'Only local connections are allowed.', 'May 22, 2018 1:43:09 AM org.openqa.selenium.remote.ProtocolHandshake createSession', 'INFO: Detected dialect: OSS', 'open google', and 'Test Ended'. The final part of the log shows the test suite summary: 'Suite', 'Total tests run: 1, Failures: 0, Skips: 0'.

```
Started by user karthiq
Building in workspace D:\Eclipse progs\TestJenkins
[TestJenkins] $ cmd /c call C:\WINDOWS\TEMP\jenkins5300761085059701945.bat

D:\Eclipse progs\TestJenkins>run.bat

D:\Eclipse progs\TestJenkins>java -cp bin;jars/* org.testng.TestNG testng.xml
[TestNG] Running:
  D:\Eclipse progs\TestJenkins\testng.xml

Test Started
open browser
Starting ChromeDriver 2.35.528161 (5b82f2d2aae0ca24b877009200ced9065a772e73) on port 37948
Only local connections are allowed.
May 22, 2018 1:43:09 AM org.openqa.selenium.remote.ProtocolHandshake createSession
INFO: Detected dialect: OSS
open google
Test Ended

=====
Suite
Total tests run: 1, Failures: 0, Skips: 0
=====
```


If you compare the above output, it will exactly match with the output that occurred when we ran with cmd.

Lets learn how to add some colorful results to Jenkins rather than console log summary.

Cucumber with Selenium

## Jenkins Plugins

Jenkins provides all the standard operations, and if we want to have more options like reposting, something like that, then we should install the plugin for Jenkins.



The screenshot shows the Jenkins 'Manage Jenkins' page. On the left sidebar, 'Manage Jenkins' is highlighted with an orange box. The main content area shows two options: 'Configure System' (with a gear icon) and 'Manage Plugins' (with a puzzle piece icon). The 'Manage Plugins' option is highlighted with an orange box. The description for 'Manage Plugins' is 'Add, remove, disable or enable plugins that can extend'.

```
Jenkins
Manage Jenkins

New Item
People
Build History
Manage Jenkins
My Views
Credentials

Configure System
Configure global settings and paths.

Manage Plugins
Add, remove, disable or enable plugins that can extend
```

Go to Available tab and search for TestNG; you may get result for TestNG results, select it and install



Updates

Available

Installed

Advanced

Install ↓




Name


<input checked="" type="checkbox"/>	<a href="#">TestNG Results</a>
-------------------------------------	--------------------------------

Install without restart

Download now and install after restart

If your installation is successful, then you may see the success information like below.


Email Extension	 Success
Mailer	 Success
TestNG Results	 Success


 [Go back to the top page](#)  
(you can start using the installed plugins right away)


[Locators in Selenium](#)


## Generate Report in Jenkins


Once the TestNG plugin has installed the Choose to configure the Build.


 [Back to Dashboard](#)


 [Status](#)

 [Changes](#)

 [Workspace](#)


 [Build Now](#)


 [Delete Project](#)

 [Configure](#)

# Project Running Bat

Project name: FirstSeleniumScript

 [Workspace](#)

 [Recent Changes](#)

Go to Post Build option and select Publish TestNG results; it may populate default values of it. In the advanced section, you can make the build as unstable if a test fails.

**Post-build Actions**

**Step 1:** Add post-build action

- Publish JUnit test result report
- Publish TestNG Results**
- Record fingerprints of files to track usage
- Set build status on GitHub commit [deprecated]
- Delete workspace when build is done

**Step 2:** Publish TestNG Results

TestNG XML report pattern: **\*\*/testng-results.xml**

Save the changes made so far.

Run the project again using Build Now Link, refresh the Page.

**Build Now**

**Delete Project**

**Configure**

**TestNG Results**

**Build History** [trend](#)

find

**#3** May 22, 2018 2:30 AM

**TestNG Results**

**Workspace**

**Recent Changes**

**Latest Test Result (no failures)**

Click the TestNG Results and select the Build Number; now, it will navigate to the result page.

**Package test**

0 failures

**All Classes**

[hide/expand the table](#)

Class	Duration	Fail	(diff)	Skip	(diff)	Total	(diff)
<a href="#">TestJenkins</a>	00:00:09.617	0	0	0	0	1	0

**Order of Execution by Test Method**

[hide/expand the table](#)

Method	Duration	Start Time	Status
<a href="#">TestJenkins.openGoogle</a>	00:00:09.617	Tue May 22 02:30:37 IST 2018	PASS


**Selenium Grid**

## Master-Slave in Jenkins

So for you are working in Master, now lets try to set up the slave machine for this master so that we can run multiple jobs at the same time.

## Steps to set up the Master for Slave in Jenkins :

Click on the Manage Jenkins and new options will be showcased in Mid Pane, so choose Manage Nodes Option



**Script Console**  
Executes arbitrary script for administration/trouble-shooting/diagnostics.

**Manage Nodes**  
Add, remove, control and monitor the various nodes that Jenkins runs jobs on.

**About Jenkins**  
See the version and license information.

Back to Dashboard  
Manage Jenkins  
**New Node**  
Configure

Node name

☒ Permanent Agent  
Adds a plain, permanent agent to Jenkins. This is called "per as dynamic provisioning. Select this type if no other agent ty managed outside Jenkins, etc.

Build Queue  
No builds in the queue.

OK

Name

Description

# of executors

Remote root directory

**Remote directory is mandatory**

Labels

Usage


Launch method

We have to set up the Method of invocation of the Node machine. When you are using it for the first time, you might not find the exact option. So first save the current configuration

Launch method

- Launch agent via execution of command on the master
- Launch agent via execution of command on the master**
- Launch slave agents via SSH

Click on Manage Jenkins >> Configure Global Security >> Select Random Option under Agents category



## Build Executor Status



**master**

1 Idle

2 Idle



**New\_Sample\_Node (offline)**

Launch method

Launch agent via execution of command on the master

Launch agent via Java Web Start

Launch agent via execution of command on the master

Launch slave agents via SSH

No launch command specified

## Steps to set up the Slave for Master in Jenkins :

Open the Node Machine ( could be another physical machine or virtual machine )

[Optional] Now, you should have the IP address of the Master machine to configure the Jenkins. You can get the IP address of the Computer by Typing `ipconfig` on the Command Prompt

```
Ethernet adapter vEthernet (Default Switch):
```

```



Connection-specific DNS Suffix . : 
Link-local IPv6 Address . . . . . : fe80::a4e5:a242:5d6d:bad3%21
IPv4 Address. . . . . : 172.19.113.1
Subnet Mask . . . . . : 255.255.255.240
Default Gateway . . . . . : 

Ethernet adapter vEthernet (nat):

Connection-specific DNS Suffix . : 
Link-local IPv6 Address . . . . . : fe80::a070:c941:b388:249c%23
IPv4 Address. . . . . : 172.22.48.1
Subnet Mask . . . . . : 255.255.240.0
Default Gateway . . . . . : 

```

Now click the Node that we have created sometime back

S	Name ↓	Architecture	Clock Difference	Free Disk Space	Free Swap Space
	<a href="#">master</a>	Windows 10 (x86)	In sync	64.64 GB	6.07 GB
	<a href="#">New_Sample_Node</a> ▼		N/A	N/A	N/A
	Data obtained	6 min 21 sec	6 min 21 sec	6 min 23 sec	6 min 21 sec

Click on the Launch Button, Now a file called slave-agent will be downloaded







## Agent New\_Sample\_Node


⊖ This agent is offline because Jenkins failed to launch the agent process on it. [See log for more details](#)

Connect agent to Jenkins one of these ways:

-  **Launch** Launch agent from browser
- Run from agent command line:

```
java -jar agent.jar -jnlpUrl http://172.22.48.1:8080/computer/New_Sample_Node/slave-agent-dcf2ec901f7a901957078c93faa050a0822eeaea2600b1a7311c1b5094160a58 -workDir "C:\Jenkins"
```

Name	Date modified	Type	Size
 jenkins	12/9/2018 8:09 PM	Windows Installer ...	120,812 KB
 jenkins.war	12/12/2018 9:04 AM	WAR File	74,256 KB
 jenkins-2.155	12/12/2018 9:27 AM	WinRAR ZIP archive	120,284 KB
 slave-agent	12/12/2018 9:44 PM	JNLP File	1 KB



The image shows two parts of the Jenkins setup process. The top part is a Windows security warning dialog titled "Do you want to run this application?". It displays details for "Jenkins Remoting Agent" by "Jeff Thompson" at "http://172.22.48.1:8080". A warning message states: "This application will run with unrestricted access which may put your computer and personal information at risk. Run this application only if you trust the locations and publisher above." There is a checkbox for "Do not show this again for this app from the publisher above" and a "Run" button circled in orange. An arrow points from the "Run" button to a small window titled "Jenkins ag..." showing a cartoon character and the word "Connected".

The bottom part shows the Jenkins web interface. On the left, the "Build Queue" section says "No builds in the queue." Below it, the "Build Executor Status" section is circled in orange and shows "master + 1 computer (0 of 3 executors)". An arrow points from this section to a table on the right.

S	Name ↓	Architecture
	<a href="#">master</a>	Windows 10 (x86)
	<a href="#">New_Sample_Node</a>	Windows 10 (amd64)
Data obtained		4 min 19 sec

## Recommended Readings

[Cucumber with Selenium | BDD](#)

[Parameterize Cucumber BDD with selenium](#)

[Tags & Hooks in Cucumber with Selenium | BDD](#)

[Robot class in selenium](#)

[GIT | BitBucket | SourceTree with Selenium](#)

[SonarLint / SonarQube With Selenium](#)

[Featured Page Object Model in Selenium | Feature Framework](#)

[Page Object Model in Selenium | POM Framework](#)