

Workforce Analytics & IT Management — User Manual

A practical, step-by-step guide for administrators who operate the platform and for the people whose devices are enrolled.

What this platform is. A **transparent, consent-based** workforce analytics and IT management tool. It records foreground-app activity, idle time, and periodic screenshots from enrolled devices — **only after the user explicitly consents** — and lets admins issue authorized IT actions (lock screen, sign out). There is **no covert mode**: the agent shows a visible tray icon, a first-run consent dialog, and a notice before every screenshot.

What is never captured: keystrokes, mouse movement, microphone, camera, screen recording / video, or live streaming.

1. Who uses what

Role	Tool	How they sign in
Administrator / Super user	Web dashboard	Username + password
Monitored user	Desktop agent (their PC/Mac/Linux)	Consent once at install/first run — no login

The dashboard is **admin-only**. Monitored users never log in; they only run the agent on their own machine and consent to it.

2. Getting started as an administrator

2.1 Sign in

1. Open the dashboard (production: `https://activitymonitor.replit.app`).
2. Enter your **username** and **password** on the Login screen.
3. You land on the **Overview** page.

Lost access / need the first admin account? An admin account is created with the create-admin script (see the technical documentation). Logins are rate-limited to deter brute-force attempts.

2.2 The navigation

The left sidebar groups everything:

Menu item	What it's for
Overview	At-a-glance KPIs and productivity distribution
Devices	Every enrolled machine; open one for full detail
Activity Logs	Foreground-app history across the org
Screenshots	Gallery of captured screens, with flagging
Attendance	Daily / ranged presence derived from activity
Timesheets	Worked-time rollups per user/device
Projects & Tasks	Lightweight project and task tracking
Shifts	Define working shifts
Leave	Leave requests and balances
App Categories	Classify apps as productive/unproductive/neutral
Enrollment Tokens	Create the tokens used to add new devices
Agent Settings	Global capture configuration
Download Agent	Get the Windows / macOS / Linux agent

3. Enrolling a device (the core workflow)

Enrolling always requires **two things**: an **enrollment token** (created by an admin) and the **explicit consent** of the person using the device.

Step 1 — Create an enrollment token

1. Go to **Enrollment Tokens** → **Create token**.
2. Set: - **Label** — a human name, e.g. "Jane's laptop". - **Max uses** — how many devices may enroll with it (1-1000; use **1** for a single machine). - **Expires in** — days until it stops working (1-365).
3. Copy the generated token string. You'll give it to the person installing the agent (or paste it into the installer).

Tokens are credentials. Revoke any token you no longer need with **Revoke**.

Step 2 — Download the agent

Go to **Download Agent** and pick the platform: - **Windows** — `.exe` installer (installs without admin rights for the signed-in user). - **macOS** — `.dmg` disk image (drag-and-drop install). - **Linux** — a binary. Download it, then make it executable (`chmod +x`) and run it.

If a platform shows "not published yet", no build has been released for it yet.

Step 3 — Install + consent (on the user's machine)

The consent step is **mandatory and cannot be skipped**:

- **Windows installer:** the setup wizard shows the full disclosure (what is and isn't recorded), an explicit **consent checkbox**, and a field for the token and the consenting person's name. After install, the agent enrolls itself silently from that one-time consent and then runs visibly.
- **macOS / Linux / manual runs:** on first launch the agent shows a **consent dialog** with the same disclosure. The user enters their name + the token and clicks Agree. Enrollment only proceeds after consent.

Once enrolled, the device appears under **Devices**, and the agent runs with a visible tray icon.

What the user sees at all times

- A **tray icon** while the agent is running.
- A **notification before every screenshot** ("a screenshot is being taken").
- The consent disclosure they agreed to.

4. Day-to-day administration

4.1 Overview

KPIs such as total devices, how many are online now, screenshots captured, and a productivity distribution (productive / unproductive / neutral / unclassified). Use the shared **date range** and **group** filters at the top of date-aware pages — they're remembered across pages.

4.2 Devices

- See every machine, its **online/offline** status, OS, assigned user, and group.

- Open a device to see its **detail page**: live config, recent activity, command history, and per-device overrides.
- **Group devices** (e.g. "Sales", "Engineering") and rename groups to filter and compare across the dashboard.

4.3 Activity Logs

A feed of foreground-app usage (app + window title + duration + idle), each classified productive / unproductive / neutral / unclassified. Filter by device, user, or group. Daily views aggregate a day's logs in your browser's local time zone.

4.4 Screenshots

A gallery of captured screens. Click any thumbnail to open the **viewer** (arrow-key navigation). **Flag** anything that needs review; filter by device, group, or flagged-only. Images are streamed only to authenticated admins.

4.5 App Categories

Whenever the agent reports an app the system hasn't seen, it's auto-added as **unclassified**. On **App Categories**, set each app to **productive**, **unproductive**, or **neutral** (and give it a friendly display name). These classifications drive every productivity number on the dashboard.

4.6 Issuing IT actions (lock / sign out)

From a device's detail page you can issue an authorized command: - **Lock screen** — locks the workstation. - **Sign out user** — logs the user out.

The command is delivered on the device's next heartbeat. The agent shows an **on-screen notice before executing**, then reports back the status (acknowledged → completed / failed). You can **cancel** a command while it's still pending, and you can review the full command history per device.

4.7 Agent Settings (capture configuration)

Tune how the agent behaves — globally or per device: - **Monitoring enabled** — master on/off. - **Screenshot interval** — min/max minutes (the agent picks a random time in the window, so captures aren't perfectly predictable). - **Idle threshold** — seconds of no input before time counts as idle. - **Sync interval** — how often the agent checks in (heartbeat).

Changes propagate to each device on its next heartbeat.

5. Workforce-management features

These optional modules turn raw activity into HR-friendly views:

- **Attendance** — presence per day or across a date range, derived from activity; configurable globally and overridable per device or group.
 - **Timesheets** — worked-time rollups you can review per user/device.
 - **Shifts** — define the working shifts the org runs on.
 - **Leave** — submit, review (approve/reject), and track **leave requests**, and manage per-person **leave balances**.
 - **Projects & Tasks** — create projects, add tasks under them, and track status.
-

6. Privacy & consent commitments

- **Consent is required and recorded.** A device cannot send data until consent is acknowledged; the consenting person's name and timestamp are stored on the device record. The server rejects any un-consented device.
 - **The agent is always visible** (tray icon) and **announces every screenshot**.
 - **Captured data is admin-only.** There is no public or unauthenticated way to read activity, screenshots, or reports. Screenshot image bytes are served only to signed-in admins.
 - **Removing a device.** Revoke its enrollment token and stop/uninstall the agent on the machine.
-

7. Troubleshooting

Symptom	Check
Device doesn't appear after install	Token expired/exhausted/revoked? Consent completed? Network reachable?
"Not published yet" on Download Agent	No release exists for that platform yet.
No new activity from a device	Agent running (tray icon)? Monitoring enabled in Agent Settings? Device online?
Productivity numbers look wrong	Classify any unclassified apps under App Categories.
Command not executing	It runs on the next heartbeat; check the device is online and the command isn't cancelled.

For API details and architecture, see [DOCUMENTATION.md](#) and [API.md](#).