

H2: Quality Attributes and Architectural Design

Marjus Nielsen

Department of Computer Science, University of Aarhus

Aabogade 34, 8200 Århus N, Denmark

India

20064684

marjus@daimi.au.dk

26. feb. 2008

Brainstorm

Different roles

- User, producer, legislators, environmentalists

Reliable/accurate measurements from thermometers, within 0,5°C

Data quality check to filter out measurements from the sensors if the temperature varies more than 5°C within a minute.

er det kvalitets
mæssigt?

If the gateway fails there should be a backup gateway

Be able to ask the actuators for their status, or have the actuators report their status every minute

The thermometers should be able to provide a temperature measure every second.

The gateway should be able to receive a temperature reading from 100 thermometers every second.

The gateway should be able to turn up to 100 actuators on or off every second.

Should be able to add new types of actuators and sensors without changing the design or architecture of the system.

The system should be able to act as input to other devices. If temperature rises suddenly, possibility of fire, alarm on.

Prioritization

I think that crucial for a system like HS07 is the performance quality attributes. If the measurements from the sensors aren't accurate or if there are too few sensors, to get a realistic picture of the temperature in the home, then the system won't satisfy the needs of the customers. Most of the quality attributes from the brainstorm are performance quality attributes. Of these I'll rate the

requirements for accuracy in the measurements, data-quality checks and that many sensors and actuators can be used at the same time highest.

Important but not as crucial are the interests of the producer of such a system. They want modifiability, so that the system can be used with a variety of sensors and actuators. Thereby the application can fit more customers, and hence has a bigger sale potential. So after the performance quality attributes i rate modifiability with respect of adding new types of sensors and actuators.

Most important Quality Attribute scenarios

Scenario	Measurements from each thermometer should be within 0,5°C of the actual temperature
Relevant Quality Attributes	Performance
Source	Thermometer
Stimulus	Measures temperature
Artifact	System
Environment	Normal operation
Response	Current temperatur
Response measure	The measured temperature is within 0,5°C of the temperature measured by a calibrated thermometer.
Questions	
Issues	Requires calibrated reference thermometers

ihke performance
sach sach
if Bass
et al.

Scenario	Up to 100 sensors and 100 actuators should be able to be on the system at the same time, with measurements every second
Relevant Quality Attributes	Performance
Source	The gateway
Stimulus	Requests temperature
Artifact	Thermometer
Environment	Normal operation
Response	Current temperature ...
Response measure	100 measurements pr. second are received.
Questions	Is it nessecary to measure the temerature every second? Would it be enough to measure once every minute?
Issues	

Actuator?

Scenario	Up to 100 sensors and 100 actuators should be able to be on the system at the same time, with measurements every second
Relevant Quality Attributes	Performance
Source	The gateway
Stimulus	Turns the actuators on
Artifact	Actuators
Environment	Normal operation
Response	Actuators are turned on
Response measure	Latency less than 1 second

generator of ihke
scenario

Questions	Is it beneficial to have a larger latency to avoid the actuators flip-flopping when the temperature is close to max and min limits?
Issues	Might be relevant to require actuators that can accept broadcast messages.

Scenario	Adding new types of actuators
Relevant Quality Attributes	Modifiability
Source	The producer
Stimulus	Wants to add a new type of actuator
Artifact	System
Environment	At design time
Response	The new actuator type is added with no side affects
Response measure	Less than an hour
Questions	What basic requirements must actuators comply with?
Issues	

Evaluation

It's not easy to estimate how well the performance scenarios can be fulfilled by HS07, because these by large depend on the hardware the system is running on. The operations of getting a list of temperature measurements, calculating a mean value and turn the actuators on or off are very simple and neither data nor computationally intensive.

*mem. architekturen anwenden
synchron kommun. gg...*

That said, there is room for performance optimizing. The logic for deciding whether to turn on or off the radiators is in the radiators themselves. It would be more efficient if this logic was in the gateway, so that the gateway only communicates with the actuators when they need to be turned on or off, and all the potentially many actuators won't need to do the same comparison against the max and min temperature values. An additional benefit is that this way the actuators will get simpler, benefitting the modifiability. On the other hand, if the customers want to be able to differentiate the wanted temperature in different rooms of a house, it can be argued that the decision logic is best placed in the actuators.

The modifiability scenario is well fulfilled by HS07. The gateway doesn't have any direct notion of the radiators. It only has a list of observers. It would be "prettier" if there was an actuator interface that all radiators implemented. If the mechanism that decides whether to turn on or off the actuators is moved to the gateway, the job of the actuator would be simpler, allowing for more types of actuators. This clearly makes the system more extensible.

Redesign

I'll keep the same basic structure of the system but change the way the actuators are controlled. This means moving the settings for the wanted temperature from the actuators to the gateway and the control mechanism that decides whether to turn the actuators on or off.

An interface should be made for all the controllers (gateway, sensor and actuator) that has the `getController` method. An additional interface that extends the controller interface for the sensors and one for the actuators. These should specify the `getTemperature` and `setState` methods that all sensors respectively actuators should implement.

The movement of the control mechanism has been implemented, and also the actuators are only notified when they need to change status.

Om man finder ift. evaluering af
performance og beslutelse af redesign.
Hvilke faktorer er fx anvendt?

A stylized handwritten signature in blue ink, possibly reading 'Zhang'.