

Key Joins { TABLES → COLUMNS }

```
GL_CODE_COMBINATIONS      AP_INVOICES_ALL
code_combination_id      =  acct_pay_code_combination_id
```

```
GL_SETS_OF_BOOKS      AP_INVOICES_ALL
  set_of_books_id      =      set_of_books_id
```

```

GL_CODE_COMBINATIONS      RA_CUST_TRX_LINE_GL_DIST_ALL
  code_combination_id      =      code_combination_id

```

GL_CODE_COMBINATIONS		MTL_SYSTEM_ITEMS_B
code_combination_id	=	cost_of_sales_account

GL_CODE_COMBINATIONS		PO_DISTRIBUTIONS_ALL
code_combination_id	=	code_combination_id

PO_DISTRIBUTIONS_ALL		AP_INVOICE_DISTRIBUTIONS_ALL
Po_distribution_id	=	po_distribution_id

PO_HEADERS_ALL		RCV_TRANSACTIONS
Po_header_id	=	po_header_id

RCV_TRANSACTIONS	AP_INVOICE_DISTRIBUTIONS_ALL
RCV_TRANSACTION ID	= RCV_TRANSACTION ID

PO_REQUISITION_LINES_ALL		MTL_SYSTEM_ITEMS_B
item_id	=	inventory_item_id
org_id	=	organization_id

PO AND HRMS

PO_HEADERS_ALL
Agent_id = HR_EMPLOYEES
employee_id

PO AND REQUISITION

PO_DISTRIBUTIONS_ALL
req_distribution_id = PO_REQ_DISTRIBUTIONS_ALL
distribution_id

SHIPMENTS AND INV

RCV_TRANSACTIONS
Organization_id = MTL_SYSTEM_ITEMS_B
organization_id

INV AND HRMS

MTL_SYSTEM_ITEMS_B
buyer_id = HR_EMPLOYEES
employee_id

OM AND AR

OE_ORDER_HEADERS_ALL
TO_CHAR (Order number) = RA_CUSTOMER_TRX_LINES_ALL
interface_line_attribute1

OE_ORDER_LINES_ALL
TO_CHAR (Line_id) = RA_CUSTOMER_TRX_LINES_ALL
interface_line_attribute6

OE_ORDER_LINES_ALL
reference_customer_trx_line_id = RA_CUSTOMER_TRX_LINES_ALL
customer_trx_line_id

OM AND SHIPPING

OE_ORDER_HEADERS_ALL
HEADER_ID = WSH_DELIVERY_DETAILS
SOURCE_HEADER_ID

OE_ORDER_HEADERS_ALL
LINE_ID = WSH_DELIVERY_DETAILS
SOURCE_LINE_ID

AP AND AR (BANKS)

AR_CASH_RECEIPTS_ALL
REMITTANCE_BANK_ACCOUNT_ID = AP_BANK_ACCOUNTS
ABA.BANK_ACCOUNT_ID

AP AND AR

HZ_PARTIES
PARTY_ID = AP_INVOICES_ALL
PARTY_ID

OM AND CRM

OE_ORDER_LINES_ALL
LINE_ID = CSI_ITEM_INSTANCES(Install Base)
LAST_OE_ORDER_LINE_ID

Table Name: Po_Requisition_Headers_All A

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
A. REQUISITION_HEADER_ID	PO_REQUISITION_LINES_ALL	REQUISITION_HEADER_ID
A. TYPE_LOOKUP_CODE	PO_DOCUMENT_TYPES	DOCUMENT_SUBTYPE
A. PREPARER_ID	PER_PEOPLE_F	PERSON_ID
A. ORG_ID	MTL_SYSTEM_ITEMS	ORGANIZATION_ID
A. ORG_ID	MTL_ORGANIZATIONS	ORGANIZATION_ID

Table Name: Po_Requisition_Lines_All B

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
B. REQUISITION_HEADER_ID	PO_REQUISITION_HEADERS_ALL	REQUISITION_HEADER_ID
B. REQUISITION_LINE_ID	PO_REQ_DISTRIBUTIONS_ALL	REQUISITION_LINE_ID
B. LINE_TYPE_ID	PO_LINE_TYPES	LINE_TYPE_ID
B. ITEM_ID	MTL_SYSTEM_ITEMS	INVENTORY_ITEM_ID
B. ORG_ID	MTL_SYSTEM_ITEMS	ORGANIZATION_ID

Table Name: Po_Requisition_Distributions_All C.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
C. REQUISITION_LINE_ID	PO_REQUISITION_LINES_ALL	REQUISITION_LINE_ID
C. DISTRIBUTION_ID	PO_DISTRIBUTIONS_ALL	REQ_DISTRIBUTION_ID
C. SET_OF_BOOKS_ID	GL_SETS_OF_BOOKS	SET_OF_BOOKS_ID
C. CODE_COMBINATION_ID	GL_CODE-COMBINATIONS	CODE_COMBINATION_ID

Table Name: Po_Distributions_All D.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
D. PO_LINE_ID	PO_LINES	PO_LINE_ID
D. REQ_DISTRIBUTION_ID	PO_REQ_DISTRIBUTIONS_ALL	DISTRIBUTION_ID
D. PO_DISTRIBUTION_ID	AP_INVOICE_DISTRIBUTIONS_ALL	PO_DISTRIBUTION_ID

Table Name: Po_Headers_All E.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
E .PO_HEADER_ID	PO_LINES	PO_HEADER_ID
E .PO_HEADER_ID	RCV_SHIPMENT_LINES	PO_HEADER_ID
E .VENDOR_ID	PO_VENDORS	VENDOR_ID
E .AGENT_ID	PER_PEOPLE	PERSON_ID
E .TYPE_LOOK_UP_CODE	PO_DOCUMENT_TYPES	DOCUMENT_SUBTYPE

Table Name: Po_Lines_All F.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
F .PO_HEADER_ID	PO_HEADERS	PO_HEADER_ID
F .PO_LINE_ID	PO_DISTRIBUTIONS_ALL	PO_LINE_ID
F .ITEM_ID	MTL_SYSTEM_ITEMS	ITEM_ID

Table Name: Rcv_Shipment_Lines G.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
G .PO_HEADER_ID	PO_HEADERS	PO_HEADER_ID
G .SHIPMENT_HEADER_ID	RCV_SHIPMENT_HEADERS	SHIPMENT_HEADER_ID

Table Name: Ap_Invoices_All H.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
H .INVOICE_ID	AP_INVOICE_DISTRIBUTIONS_ALL	INVOICE_ID

Table Name: Oe_Order_Headers_All I.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
I .HEADER_ID	OE_ORDER_LINES	HEADER_ID
I .SOURCE_HEADER_ID	WISH_DELIVERY_DETAILS	SOURCE_HEADER_ID
I .PRICE_LIST_ID	QP_LIST_HEADERS_TL	LIST_HEADER_ID
I .ORG_ID	MTL_ORGANIZATIONS	ORGANIZATION_ID
I .SALESREP_ID	JTF_RS_SALESREPS	SALESREP_ID

I.ORDER_TYPE_ID	OE_TRANSACTION_TYPES	TRANSACTION_TYPE_ID
I.ORDER_SOURCE_ID	OE_ORDER_SOURCES	ORDER_SOURCE_ID
I.ACCOUNTING_RULE_ID	RA_RULES	RULE_ID
I.PAYMENT_TERM_ID	RA_TERMS	TERM_ID
I.SOLD_TO_ORG_ID	HZ_CUST_ACCOUNTS	CUST_ACCOUNT_ID
I.SHIP_FROM_ORG_ID	MTL_PARAMETERS	ORGANIZATION_ID
I.SHIP_TO_ORG_ID	HZ_CUST_SITE_USES_ALL	SITE_USE_ID

Table Name: Oe_Order_Lines_All J.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
J.LINE_TYPE_ID	OE_TRANSACTION_TYPES_TL	TRANSACTION_TYPE_ID
J.INVOICING_RULE_ID	RA_RULES	RULE_ID

Table Name: Hz_Parties K.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
K.PATY_ID	HZ_CUST_ACCOUNTS	PATY_ID
K.CUST_ACCOUNT_ID	OE_ORDER_LINES	SOLD_TO_ORG_ID

Table Name: Hz_Party_Sites_All L.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
L.PATY_ID	HZ_PARTIES	PATY_ID
L. LOCATION_ID	HZ_LOCATIONS	LOCATION_ID

Table Name: Wsh_delivery_details M.

<u>Column Names</u>	<u>Table Name</u>	<u>Column Name</u>
M.SOURCE_HEADER_ID	OE_ORDER_HEADERS	SOURCE_HEADER_ID
M.DELIVERY_DETAIL_ID	WSH_DELIVERY_ASSIGNMENTS	DELIVERY_DETAIL_ID
M.DELIVERY_ID	WSH_NEW_DELIVERIES	DELIVERY_ID
M.INVENTORY_ITEM_ID	MTL_SYSTEM_ITEMS	INVENTORY_ITEM_ID

Table Name: *RA_CUSTOMER_TRX_ALL* **N.**

Column Names	Table Name	Column Name
N. CUSTOMER_TRX_ID	AR_RECEIVABLE_APPLICATIONS_ALL	APPLIED_CUSTOMER_TRX_ID
N. TERM_ID	RA_TERMS	TERM_ID
N. CUSTOMER_TRX_ID	RA_CUST_TRX_LINE_GL_DIST	CUSTOMER_TRX_ID

Table Name: *AR_CASH_REC EIPTS_ALL* **O.**

Column Names	Table Name	Column Name
O. CASH_RECEIPT_ID	AR_RECEIVABLE_APPLICATIONS_ALL	CASH_RECEIPT_ID
O. SET_OF_BOOKS_ID	GL_SETS_OF_BOOKS	SET_OF_BOOKS_ID