
Information Security CS3002

Lecture 3 26th August 2024


Dr. Rana Asif Rehman

Email: r.asif@lhr.nu.edu.pk



Cryptography

Old Cryptography Methods






Some Basic Terminology

- Plaintext original message
- Ciphertext coded message
- Encryption algorithm algorithm for transforming plaintext to ciphertext
- Key info used in cipher known only to sender/receiver
- Encipher (encrypt) converting plaintext to ciphertext

Some Basic Terminology (cont.)

- Decryption algorithm algorithm for transforming ciphertext to plaintext
- DeCipher converting ciphertext to plaintext.
- Cryptography Study Of Encryption Principles/Methods
- Cryptanalysis (Codebreaking) Study Of Principles/ Methods Of Deciphering Ciphertext Without Knowing Key
- Cryptology Field of Both Cryptography And Cryptanalysis

Classification of the Field of Cryptology



Adopted with thanks from: Chapter 1 of Understanding Cryptography by Christof Paar and Jan Pelzl




Symmetric Cryptography

Symmetric Encryption

- Or conventional / private-key / single-key
- Sender and recipient share a common key
- All classical encryption algorithms are privatekey
- Was only type prior to invention of public-key in 1970's
- And by far most widely used


Simplified Model of Symmetric Encryption



Requirements

- Two requirements for secure use of symmetric encryption:
 - A strong encryption algorithm
 - The opponent should be unable to decrypt ciphertext or discover the key even if he or she is in possession of a number of ciphertexts together with the plaintext that produced each ciphertext.
 - A secret key known only to sender / receiver
 - Sender and receiver must have obtained copies of the secret key in a secure fashion and must keep the key secure.

Model of Symmetric Cryptosystem



Model of Symmetric Cryptosystem (cont.)

With the message X and the encryption key K as input, the encryption algorithm forms the ciphertext $Y = [Y_1, Y_2, \dots, Y_N]$. We can write this as


$$Y = E(K, X)$$

The intended receiver, in possession of the key, is able to invert the transformation:


$$X = D(K, Y)$$

An opponent, observing Y but not having access to K or X, may attempt to recover X or K or both X and K.


Cryptographic Message




Cryptographic Speech Signal




Cryptographic Image




Original image



Turing's work during the Second World War was so crucial that Winston Churchill acknowledged his role, saying that Turing made the single biggest contribution to Allied victory.



Nominations: Academy Award for Best Picture, MORE >



http://www.iwm.org.uk/history/how-alanturing-cracked-the-enigma-code

Classical Symmetric Ciphers

- Where letters of plaintext are replaced by other letters or by numbers or symbols.
- Or if plaintext is viewed as a sequence of bits, then substitution involves replacing plaintext bit patterns with ciphertext bit patterns.



Classical Symmetric Ciphers

- Classical Substitution Ciphers
- Classical Transposition Ciphers



Classical Symmetric Ciphers

- Classical Substitution Ciphers
 - Caesar Cipher
 - Monoalphabetic Cipher
 - Vigenere Cipher
 - One-Time Pad

1. Caesar Cipher

- Earliest known substitution cipher.
 - The Roman emperor Julius Caesar used in his diplomatic communications
- First attested use in military affairs.
- Replaces each letter by 3rd letter on
- Example:

meet me after the toga party phhw ph diwhu wkh wrjd sduwb



Caesar Cipher (cont.)

Can define transformation as:

plain: a b c d e f g h i j k l m n o p q r s t u v w x y z cipher: D E F G H I J K L M N O P Q R S T U V W X Y Z A B C


Then have caesar cipher as:

а	b	c	d	e	f	g	h	į ji	j	k	1	m
0	1	2	3	4	5	6	7	8	9	10	11	12


$$c = E(k, p) = (p + k) \mod (26)$$

$$p = D(k, c) = (c - k) \mod (26)$$

Caesar Cipher (cont.)



Activity Time



Plaintext: LETS TAKE A TEN MINUTES BREAK

Ciphertext: OHWV WDNH D WHQ PLQXWHV EUHDN

Cryptanalysis of Caesar Cipher

- Only have 25 possible Keys
 - A maps to B,C,..Z
- Could simply try each in turn
- A brute force search
 - 1. The encryption and decryption algorithms are known.
 - 2. There are only 25 keys to try.
 - **3.** The language of the plaintext is known and easily recognizable.
 - e.g. Break ciphertext "GCUA VQ DTGCM"

	PHHW PH DIWHU WKH WRJD SDUWB
KEY	THE THE PARTY WITH MICE SECRE
1	oggv og chvgt vjg vqic rctva
2	nffu nf bgufs uif uphb qbsuz
3	meet me after the toga party
4	ldds ld zesdq sgd snfz ozqsx
5	keer ke ydrep rfe rmey nyprw
6	jbbq jb xcqbo qeb qldx mxoqv
.7	iaap ia wbpan pda pkcw lwnpu
8	hzzo hz vaozm ocz ojbv kvmot
9	gyyn gy uznyl nby niau julns
10	fxxm fx tymxk max mhzt itkmr
11	ewwl ew sxlwj lzw lgys hsjlq
12	dvvk dv rwkvi kyv kfxr grikp
13	cuuj cu qvjuh jxu jewq fqhjo
14	btti bt puitg iwt idvp epgin
15	assh as othsf hvs houo dofhm
16	zrrg zr nsgre gur gbtn cnegl
17	yqqf yq mrfqd ftq fasm bmdfk
18	xppe xp lqepc esp ezrl alcej
19	wood wo kpdob dro dygk zkbdi
20	vnne vn jocna cqn cxpj yjach
21	ummb um inbmz bpm bwoi xizbg
22	tlla tl hmaly aol avnh whyaf
2.3	skkz sk glzkx znk zumg vgxze
24	rjjy rj fkyjw ymj ytlf ufwyd
25	qiix qi ejxiv xli xske tevxc

Brute Force Feasibility

- In most networking situations, we can assume that the algorithms are known.
- What generally makes brute-force cryptanalysis impractical is the use of an algorithm that employs a large number of keys.
 - For example, the triple DES algorithm makes use of a 168-bit key, giving a key space of 2^{168} or greater than 3.7 * 10^{50} possible keys.

2. Monoalphabetic Cipher

- With only 25 possible keys, the Caesar cipher is far from secure.
- Rather than just shifting the alphabet could shuffle (jumble) the letters arbitrarily [permutation]
- Each plaintext letter maps to a different random ciphertext letter
- Hence key is 26 letters long

Plain: ABCDEFGHIJKLMNOPQRSTUVWXYZ

Key: DKVQFIBJWPESCXHTMYAUOLRGZN

Plaintext: IFWEWISHTOREPLACELETTERS

Ciphertext: WIRFRWAJUHYFTSDVFSFUUFYA


Monoalphabetic Cipher Security

- Now have a total of $26! = 4 \times 10^{26}$ keys
- With so many keys, might think is secure
- But would be !!!WRONG!!!
- Problem is language characteristics

Language Redundancy and Cryptanalysis

- Human languages are redundant e.g. "Th Ird s m shphrd shll nt wnt" letters are not equally commonly used.
- In English E is by far the most common letter
 - Followed by T,R,N,I,O,A,S
- Other letters like Z,J,K,Q,X are fairly rare
- Have tables of single, double & triple letter frequencies for various languages

English Letter Frequencies



Use in Cryptanalysis

- Key concept monoalphabetic substitution ciphers do not change relative letter frequencies.
- Calculate letter frequencies for ciphertext.
- Compare counts/plots against known values.
- For monoalphabetic must identify each letter
 - tables of common double/triple letters help

Language Redundancy and Cryptanalysis

Cipher Text

UZQSOVUOHXMOPVGPOZPEVSGZWSZOPFPESXUDBMETSXAIZ VUEPHZHMDZSHZOWSFPAPPDTSVPQUZWYMXUZUHSX EPYEPOPDZSZUFPOMBZWPFUPZHMDJUDTMOHMQ

P 13.33	H 5.83	F 3.33	В 1.67	C 0.00
Z 11.67	D 5.00	W 3.33	G 1.67	K 0.00
S 8.33	E 5.00	Q 2.50	Y 1.67	L 0.00
U 8.33	V 4.17	T 2.50	I 0.83	N 0.00
O 7.50	X 4.17	A 1.67	J 0.83	R 0.00
M 6.67				

Example Cryptanalysis

• given cipher text:

UZQSOVUOHXMOPVGPOZPEVSGZWSZOPFPESXUDBMETSXAIZ VUEPHZHMDZSHZOWSFPAPPDTSVPQUZWYMXUZUHSX EPYEPOPDZSZUFPOMBZWPFUPZHMDJUDTMOHMO

- count relative letter frequencies
- guess P & Z are e and t
- guess ZW is th and hence ZWP is the

So far, then, we have

UZQSOVUOHXMOPVGPOZPEVSGZWSZOPFPESXUDBMETSXAIZ ta e e te a that e e a a

VUEPHZHMDZSHZOWSFPAPPDTSVPQUZWYMXUZUHSX

et tat hae ee ae th ta EPYEPOPDZSZUFPOMBZWPFUPZHMDJUDTMOHMQ

e e e tat e the t

Example Cryptanalysis (cont.)

Proceeding with trial and error finally get:

it was disclosed yesterday that several informal but direct contacts have been made with political representatives of the viet cong in moscow