

# Week 1 Notes

Uday Manchanda

June 20, 2019


## Abstract

Week 1 Notes in the Coursera Course on Cryptography

## 1 What is Cryptography About?

### 1.1 Course Overview

- Secure communication: HTTPS, WPA2, GSM, Bluetooth, SSL/TLS
- SSL/TLS has two main parts:
  - Handshake Protocol
  - Record Layer
- Encrypting files on disk: EFS, TrueCrypt
- Symmetric Encryption



– Where:

- \* E, D: cipher
- \* k : secret key (ex: 128 bits)
- \* m: plaintext
- \* c: ciphertext

– Encryption Algorithm is **publicly known**

- Use Cases
  - Single use key (one time key)

- \* key is used to encrypt a single message
- \* new key generated for each email
- Multi use key (many time key)
  - \* key encrypts multiple messages
  - \* same key used to encrypt many files

## 1.2 What is Cryptography

- Confidentiality and integrity
- Digital signatures, anonymous communication, digital cash
- If something can be done with a trusted authority, it can also be done without one
- Three steps in cryptography
  - Precisely specify threat model
  - Propose a construction
  - Prove that breaking construction under threat mode will solve an underlying hard problem

## 1.3 History

- Substitution cipher
  - Find most common letter ("E") via frequencies
  - Use frequency of pairs of letters
- Caesar Cipher
  - Shift letters by three
  - Size of key space:  $|\kappa| = 26!$
- Vigenere Cipher
  - Encrypt message  $m$  with some cipher  $k$
  - For each letter in  $m$ , add it to corresponding letter in  $k$
  - $k$  will "wrap around" until end of message
  - Take added result and mod 26 to obtain result between 0 and 25
- Rotor Machines
- Data Encryption Standard (DES)
  - keys:  $2^{56}$ , block size: 64 bits
  - today AES is in use

## 2 Discrete Probability

### 2.1 Crash Course Part I

- Let  $U$  be some finite set, eg:  $U = \{0, 1\}^n$
- Probability distribution  $P$  over  $U$  is a function  $P : U \rightarrow [0, 1]$ , such that  $\sum_{x \in U} P(x) = 1$
- EX:
  - Uniform Distribution: for all  $x \in U : P(x) = \frac{1}{|U|}$
  - Point Distribution at  $x_0 : P(x_0) = 1, \forall x \neq x_0 : P(x) = 0$
- Distribution vector:  $(P(000), P(001), P(010), \dots, P(111))$
- Events
  - For a set  $A \subseteq U : Pr[A] = \sum_{x \in U} P(x) \in [0, 1]$
  - Set  $A$  is an **event**
  - EX:  $U = \{0, 1\}^8$
  - $A = \{ \text{all } x \text{ in } U \text{ such that } lsb_2(x) = 11 \} \subseteq U$  for the uniform distribution on  $0, 1^8 : Pr[A] = \frac{1}{4}$
- The Union Bound
  - For events  $A_1$  and  $A_2 : Pr[A_1 \cup A_2] \leq Pr[A_1] + Pr[A_2]$
  - $A_1 \cap A_2 = \emptyset \rightarrow Pr[A_1 \cup A_2] = Pr[A_1] + Pr[A_2]$ 
    - \*  $A_1 = \{ \text{all } x \text{ in } 0, 1^n \text{ s.t } lsb_2(x) = 11 \}$
    - \*  $Pr[lsb_2(x) = 11 \text{ or } msb_2(x) = 11] = Pr[A_1 \cup A_2] \leq \frac{1}{4} + \frac{1}{4} = \frac{1}{2}$
- Random Variables
  - Definition: a random variable  $X$  is a function:  $X : U \rightarrow V$
  - EX:  $X : \{0, 1\}^n \rightarrow \{0, 1\}; X(y) = lsb(y) \in \{0, 1\}$
  - For the uniform distribution on  $U : Pr[X = 0] = \frac{1}{2}, Pr[X = 1] = \frac{1}{2}$
  - more generally: random variable  $X$  induces a distribution on  $V$ :  $Pr[X = v] := Pr[X^{-1}(v)]$
- Uniform random variable
  - Let  $U$  be some set, eg  $U = \{0, 1\}^n$
  - We write  $r \leftarrow U$  to denote a **uniform random variable** over  $U$  for all  $a \in U : Pr[r = a] = \frac{1}{|U|}$
  - formally  $r$  is the identity function:  $r(x) = x$  for all  $x \in U$
  - Let  $r$  be a uniform random variable on  $\{0, 1\}^2$

- Define random variable  $X = r_1 + r_2$
- Then  $Pr[X = 2] = \frac{1}{4}$
- Hint:  $Pr[X = 2] = Pr[r = 11]$
- Randomized Algorithms
  - Deterministic algorithm:  $y \leftarrow A(m)$
  - Randomized algorithm:  $y \leftarrow A(m; r)$  where  $r \leftarrow \{0, 1\}^n$
  - EX:  $A(m; k) = E(k, m), y \leftarrow^n A(m)$

## 2.2 Crash Course Part II

- Independence
  - Events A and B are **independent** if  $Pr[A \text{ and } B] = Pr[A] \times Pr[B]$
  - EX:  $U = \{0, 1\}^2 = \{00, 01, 10, 11\}$  and  $r \leftarrow U$
  - define r.v X and Y as:  $X = \text{lsb}(r), Y = \text{msb}(r)$
  - $Pr[X = 0 \text{ and } Y = 0] = Pr[r = 00] = \frac{1}{4} = Pr[X = 0] \times Pr[Y = 0]$
- XOR
  - XOR of two strings in  $\{0, 1\}^n$  is their bit-wise addition mod 2
  - XOR Chart

x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

\* (Yeah I made that)

- EX:  $0110111 \oplus 1011010 = 1101101$
- Important property of XOR
  - Theorem: Y a random variable over  $\{0, 1\}^n$ , X is an independent uniform variable on  $\{0, 1\}^n$
  - Then  $Z := Y \oplus X$  is a uniform variable on  $\{0, 1\}^n$
  - Proof for  $n = 1$ 
    - \*  $Pr[Z = 0] = Pr[(x, y) = (0, 0) \text{ or } (x, y) = (1, 1)]$
    - \*  $Pr[(x, y) = (0, 0)] + Pr[(x, y) = (1, 1)] = \frac{P_0}{2} + \frac{P_1}{2} = \frac{1}{2}$

- The Birthday Paradox
  - Let  $r_1, \dots, r_n \in U$  be independent identically distributed random variables
  - When  $n = 1.2 \times |U|^{1/2}$  then  $Pr[\exists i \neq j : r_i = r_j] \geq 1/2$
  - notation:  $|U|$  is the size of  $U$
  - EX: Let  $U = \{0, 1\}^{128}$ 
    - \* After sampling about  $2^{64}$  random messages from  $U$ , some two sampled messages will likely be the same

## 3 Stream Ciphers

### 3.1 One Time Pad

- Symmetric Ciphers
  - Def: a cipher defined over  $(K, M, C)$  is a pair of "efficient" algorithms  $(E, D)$ , where:
    - \*  $E = K \times M \rightarrow C$
    - \*  $D = K \times C \rightarrow M$
    - \*  $\forall m \in M, k \in K : D(k, E(k, m)) = m$
  - $E$  is often randomized,  $D$  is always deterministic
- One Time Pad
  - First example of a "secure" cipher
  - $M = C = \{0, 1\}^n, K = \{0, 1\}^n$
  - key = (random bit string as long as the message)
  - $C := E(k, m) = k \oplus m$
  - $D(k, c) = k \oplus c$
  - $D(k, E(k, m)) = D(k, k \oplus m) = k \oplus (k \oplus m) = (k \oplus k) \oplus m = 0 \oplus m = m$
  - You are given a message and its OTP encryption ( $c$ ). Can you compute the OTP key from  $m$  and  $c$ ?
    - \* Yes, the key is:  $k = m \oplus c$
    - \* Very fast encryption/decryption...but long keys (as long as plaintext)
- What is a secure cipher
  - Attacker's abilities: CT only attack (for now)
  - Possible security attempts
    - \* 1. Attacker cannot recover secret key.  $E(k, m) = m$  would be secure


- \* 2. Attacker cannot recover all of the plaintext.  $E(k, m_0 || m_1) = m_0) || k \oplus m_1$  would be secure
- \* Shannon's idea: CT should reveal no "info" about the PT
- Information Theoretic security
  - Definition: A cipher  $(E, D)$  over  $(K, M, C)$  has **perfect secrecy** if:
    - \*  $\forall m_0, m_1 \in M, (len(m_0) = len(m_1)), \forall c \in C$
    - \*  $Pr[E(K, m_0) = c] = Pr[E(k, m_1) = c]$
    - \* where  $k$  is uniform in  $K$  ( $k \leftarrow K$ )
    - \* Given ciphertext can't tell if message is  $m_0$  or  $m_1$  (for all  $m_0, m_1$ )
    - \* most powerful adversary learns nothing about plaintext from ciphertext
    - \* no ciphertext only attack (other attacks are possible)
  - Lemma: OTP has perfect secrecy. Proof:
    - \*  $\forall m, c : Pr[E(k, m) = c] = \frac{\text{number of keys } \kappa \in K \text{ s.t. } E(k, m) = c}{|K|}$
    - \* If  $\forall m, c : \text{number} = \{\kappa \in K : E(k, m) = c\} = \text{const}$
    - \* Therefore, cipher has perfect secrecy
    - \* Let  $m \in M$  and  $c \in C$ . How many OTP keys map  $m$  to  $c$ ? **one**
    - \* However: implies that:  $|\kappa| \geq |M| \rightarrow$  hard to use in practice, (key length > message length)

### 3.2 Pseudorandom Generators

- Stream Ciphers: Making OTP practical
  - idea: replace "random" key by "pseudorandom" key
  - PRG is a function:  $G : \{0, 1\}^s \rightarrow \{0, 1\}^n$
  - $n \gg s$
  - computable by a deterministic algorithm
  - $C := E(k, m) = m \oplus G(k)$
  - $D(k, c) = C \oplus G(k)$
  - Can a stream cipher have perfect secrecy: No since the key is shorter than the message
  - Stream ciphers cannot have perfect secrecy
    - \* Need a different definition of security
    - \* Security will depend on specific PRG
- PRG must be unpredictable
  - Suppose PRG is predictable:

- $\exists i : G(k)|_{1,\dots,i} \rightarrow^{alg} G(k)|_{i+1,\dots,n}$

Then:



- We say that  $G : K \rightarrow \{0,1\}^n$  is **unpredictable** if:
  - \*  $\exists$  "eff" alg A and  $\exists_0 \leq i \leq n-1 \leq t$
  - \*  $Pr[A(G(k))|_{1,\dots,i} = G(k)|_{i+1}] > \frac{1}{2} + \epsilon$
  - \* For non-negligible  $\epsilon$ , eg  $\frac{1}{2^{30}}$
  - \* Definition: PRG is unpredictable if it is not predictable, no "efficient" adv. can predict bit (i+1) for "non-neg"  $\epsilon$
  - \* Suppose  $G : K \rightarrow \{0,1\}^n$  is such that for all k:  $XOR(G(k)) = 1$ . Is G predictable?  $\rightarrow$  Yes given the first (n-1) bits I can predict the n'th bit

- Weak PRGs (do not use for crypto!)

- glibc random():
- $r[i] \leftarrow (r[i-3] + r[i-31]) \% 2^{32}$
- output  $r[i] >> 1$
- Never use random() for crypto

### 3.3 Negligible vs. non-negligible

- Negligible vs. non-negligible


- In practice:  $\epsilon$  is a scalar and
  - \*  $\epsilon$  non-neg  $\epsilon \geq \frac{1}{2^{30}}$  (likely to happen over 1 GB of data)
  - \*  $\epsilon$  negligible  $\epsilon \leq \frac{1}{2^{80}}$  (won't happen over life of key)
- In theory:  $\epsilon$  is a function:  $\epsilon : Z^{\geq 0} \rightarrow R^{\geq 0}$ 
  - \*  $\epsilon$  non-neg  $\exists d : \epsilon(\lambda) \geq \frac{1}{\lambda^d} (\epsilon \geq \frac{1}{poly}, \text{ for many } \lambda)$
  - \*  $\epsilon$  negligible  $\forall d, \lambda \geq \lambda_d : \epsilon(\lambda) \leq \frac{1}{\lambda^d} (\epsilon \leq \frac{1}{poly}, \text{ for large } \lambda)$
- Few Examples
  - \*  $\epsilon(\lambda) = \frac{1}{2^\lambda}$ : negligible
  - \*  $\epsilon(\lambda) = \frac{1}{\lambda^{1000}}$ : non-negligible
  - \*

$$\begin{cases} \frac{1}{2^\lambda} & \text{for odd } \lambda \\ \frac{1}{\lambda^{1000}} & \text{for even } \lambda \end{cases}$$

- PRGs: the rigorous theory view
  - PRGs are parametrized by a security parameter:  $\lambda$ 
    - \* PRG becomes "more secure" as  $\lambda$  increases
  - Seed lengths and output lengths grow with  $\lambda$
  - For every  $\lambda = 1, 2, 3, \dots$  there is a different PRG:  $G_\lambda$
  - $G_\lambda : K_\lambda \rightarrow \{0, 1\}^{n(\lambda)}$
  - We say that the previous equation is **predictable** at position  $i$  if:
    - \* there exists a polynomial time (in  $\lambda$ ) algorithm  $A$  s.t.
    - \*  $\Pr_{k \leftarrow K_\lambda}[A(\lambda, G_\lambda(k))|_{1, \dots, i} = G_\lambda(k)|_{i+1}] > \frac{1}{2} + \epsilon(\lambda)$
    - \* For some non-negligible function  $\epsilon(\lambda)$

### 3.4 Attacks on OTP and Stream Ciphers

- Attack 1: Two time pad is insecure
  - Never use stream cipher key more than once
  - $C_1 \leftarrow m_1 \oplus PRG(k)$
  - $C_2 \leftarrow m_2 \oplus PRG(k)$
  - Eavesdropper does:  $C_1 + C_2 \rightarrow m_1 \oplus m_2$
  - Enough redundancy in English and ASCII encoding that:  $m_1 \oplus m_2 \rightarrow m_1, m_2$
  - Real World Examples
    - \* Project Venona
    - \* MS-PPTP
    - \* 802.11b WEP



- 
- Length of IV: 24 bits
- Repeated IV after  $2^{24} \approx 16$  M frames
- On some 802.11 cards: IV resets to 0 after power cycle
- Avoid related keys