
ERRATA EMBER[®] EM35X BREAKOUT BOARD TECHNICAL SPECIFICATION

This document describes issues that pertain to the EM35x Breakout Board. This Errata refers to the following releases of document TS6, *EM35x Breakout Board Technical Specification*:

- TS6 revisions A through H

1 External power supply should be limited to 15 V and not 20 V

There is a bug on the EM35x Breakout Board that prevents operation with an external power supply set to voltages greater than 15 V.

Silicon Labs provides a number of ways to provide power to the EM35x Breakout Board. One of the methods involves connecting an external supply at J1 (positive) and J32 (GND) and setting it to a DC voltage between 4 VDC and 20 VDC. Unfortunately, a protection diode tied to the external power supply net is only rated to 15 VDC and is not guaranteed to operate at voltages greater than 15 VDC.

Affected Conditions

This issue is present on revisions B1 and earlier of the EM35x Breakout Board. This issue has been corrected on revisions B2 and later of the EM35x Breakout Board and all revisions of the EM35x NCP Breakout Board.

Workaround

When using an external power supply to source power to the EM35x Breakout Board and Module, limit the external power supply to between 4 VDC and 15 VDC.

2 VBRD supply unstable when driving high current loads

There is a bug on the EM35x Breakout Board that prevents stable VBRD generation when driving a high current load (>200 mA), like an EM35x module with a high power front end module (FEM).

The EM35x Breakout Board provides power distribution of the VBRD net from a variety of input power sources. When the power source is either an external power supply (connected to J1 and J32) or USB, a low dropout (LDO) voltage regulator steps the input voltage to an output (VBRD) of 3.3 V at 250 mA (max). It has been determined the LDO output has a slight oscillation even when driving an open circuit. The oscillation gets worse as the load impedance decreases (or the drive current increases). At loads greater than 200 mA, the oscillation causes the average voltage potential for VBRD to drop below the POR threshold of the EM35x.

Affected Conditions

This issue is present on revisions B1 and earlier of the EM35x Breakout Board. This issue has been corrected on revisions B2 and later of the EM35x Breakout Board and all revisions of the EM35x NCP Breakout Board.

Workaround

Silicon Labs recommends powering high current loads by connecting an external 3.3 V power supply directly to the VBRD net at jumpers J3.2 (positive) and J32 (GND) or to the module power supply (VMOD) at Jumpers J4.2 (positive) and J32 (GND). In either of these scenarios, the load can exceed 200mA without any voltage oscillations as the LDO is bypassed.

3 USB LED DS2 on when USB cable not connected

There is a bug on the EM35x Breakout Board that causes the USB power source LED DS2 to be on when there is no USB cable connected and thus no USB power source present.

The EM35x Breakout Board provides multiple options for providing power to the board. The board includes LEDs to indicate which voltage source(s) are present. The USB power source LED DS2 should only be on when a USB cable is connected from a PC or USB power supply to the EM35x Breakout Board. DS2 may be on when USB is not present if the serial communication selection jumpers J22, J24, J25, or J26 are connected in the USB configuration (with pins 2 and 3 of these headers connected). The EM35x GPIO PB1, PB2, PB3, and PB4 are routed from the EM35x Module header J21 through these serial communication selection jumpers (J22, J24-26). Since the USB FTDI IC U5 (manufacturer part number FT232RQ) is not powered, any logic high signal levels on EM35x GPIO PB1-4 will supply voltage to the power supply of the FTDI IC U5 through its protection diodes, providing enough voltage on the V_USB net to light the LED DS2.

Affected Conditions

This issue is present on all revisions of the EM35x Breakout Board.

Workaround

When a USB cable is not connected to the EM35x Breakout Board, Silicon Labs recommends the customer remove the jumpers from headers pin 3 of J22 and J24-26. This will ensure that the USB power source LED is not active.

CONTACT INFORMATION

Silicon Laboratories Inc.

400 West Cesar Chavez
Austin, TX 78701
Tel: 1+(512) 416-8500
Fax: 1+(512) 416-9669
Toll Free: 1+(877) 444-3032

Please visit the Silicon Labs Technical Support web page for ZigBee products:
www.silabs.com/zigbee-support and register to submit a technical support request

Patent Notice

Silicon Labs invests in research and development to help our customers differentiate in the market with innovative low-power, small size, analog-intensive mixed-signal solutions. Silicon Labs' extensive patent portfolio is a testament to our unique approach and world-class engineering team.

The information in this document is believed to be accurate in all respects at the time of publication but is subject to change without notice. Silicon Laboratories assumes no responsibility for errors and omissions, and disclaims responsibility for any consequences resulting from the use of information included herein. Additionally, Silicon Laboratories assumes no responsibility for the functioning of undescribed features or parameters. Silicon Laboratories reserves the right to make changes without further notice. Silicon Laboratories makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Silicon Laboratories assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Silicon Laboratories products are not designed, intended, or authorized for use in applications intended to support or sustain life, or for any other application in which the failure of the Silicon Laboratories product could create a situation where personal injury or death may occur. Should Buyer purchase or use Silicon Laboratories products for any such unintended or unauthorized application, Buyer shall indemnify and hold Silicon Laboratories harmless against all claims and damages.

Silicon Laboratories, Silicon Labs, and Ember are registered trademarks of Silicon Laboratories Inc.

Other products or brandnames mentioned herein are trademarks or registered trademarks of their respective holders.

