



Understanding Query Plans and Spark UIs

Xiao Li @ gatorsmile
Spark + AI Summit @ SF | April 2019



About Me

- Engineering Manager at Databricks
- Apache Spark Committer and PMC Member
- Previously, IBM Master Inventor
- Spark, Database Replication, Information Integration
- Ph.D. in University of Florida
- Github: [gatorsmile](#)



Databricks Customers Across Industries

Financial Services



Healthcare & Pharma



Media & Entertainment



Data & Analytics Services



Technology



Public Sector



Retail & CPG



Consumer Services




Marketing & AdTech




Energy & Industrial IoT




Databricks Unified Analytics Platform




Apache Spark 3.x



Apache Spark 3.x



From declarative queries to RDDs





Maximize Performance

Read Plan.
Interpret Plan.
Tune Plan.
Track Execution.



Read Plans from SQL Tab in either Spark UI or Spark History Server

```
1 spark.sql(  
2     """  
3         |SELECT  
4         |    sum(l_extendedprice * l_discount) AS revenue  
5         |FROM  
6         |    lineitem  
7         |WHERE  
8         |    l_shipdate >= DATE '1994-01-01'  
9         |    AND l_shipdate < DATE '1994-01-01' + INTERVAL '1' YEAR  
10        |    AND l_discount BETWEEN .06 - 0.01 AND .06 + 0.01  
11        |    AND l_quantity < 24  
12    """.stripMargin).show()
```

▶ (1) Spark Jobs

```
+-----+  
|      revenue|  
+-----+  
|6.156313774170997E8|  
+-----+
```

SQL

Completed Queries: 1

Completed Queries (1)

ID	Description	Submitted	Duration	Job IDs
0	show at command-15475442:12	+details	2019/03/06 06:42:03	55 s

Read Plans from SQL Tab in either Spark UI or Spark History Server

```
1 spark.sql(  
2     """  
3         |SELECT  
4         |  sum(l_extendedprice * l_discount) AS revenue  
5         |FROM  
6         |  lineitem  
7         |WHERE  
8         |  l_shipdate >= DATE '1994-01-01'  
9         |  AND l_shipdate < DATE '1994-01-01' + INTERVAL '1' YEAR  
10        |  AND l_discount BETWEEN .06 - 0.01 AND .06 + 0.01  
11        |  AND l_quantity < 24  
12     """).stripMargin).show()
```

▶ (1) Spark Jobs

```
+-----+  
|      revenue|  
+-----+  
| 6.156313774170997E8|  
+-----+
```

SQL

Completed Queries: 1

Completed Queries (1)

ID	Description	Submitted	Duration	Job IDs
0	<code>spark.sql(""" SELECT sum(l_exten...</code>	2019/04/20 16:35:59	35 s	[0]




Spark 3.0: Show the actual SQL statement? [SPARK-27045]

Details for Query 0

Submitted Time: 2019/03/06 06:42:03

Duration: 55 s

Succeeded Jobs: 0



Page: In Details for SQL Query

▼ Details

```

== Parsed Logical Plan ==
GlobalLimit 21
+- LocalLimit 21
  +- Project [cast(revenue#2 as string) AS revenue#22]
    +- Aggregate [sum((l_extendedprice#8 * l_discount#9)) AS revenue#2]
      +- Filter ((l_shipdate#13 >= cast(8766 as string)) && (l_shipdate#13 < cast(cast(cast(8766 as timestamp) + interval 1 years as date) as string))) && ((l_discount#9 >= cast(CheckOverflow(promote_precision(cast(0.06 as decimal(3,2))) - promote_precision(cast(0.01 as decimal(3,2)))), DecimalType(3,2)) as double)) && (l_discount#9 < cast(CheckOverflow(promote_precision(cast(0.06 as decimal(3,2))) + promote_precision(cast(0.01 as decimal(3,2)))), DecimalType(3,2)) as double))) && (l_quantity#7 < cast(24 as double)))
        +- SubqueryAlias `default`.`lineitem`
          +- HiveTableRelation `default`.`lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linestatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]

== Analyzed Logical Plan ==
revenue: string
GlobalLimit 21
+- LocalLimit 21
  +- Project [cast(revenue#2 as string) AS revenue#22]
    +- Aggregate [sum((l_extendedprice#8 * l_discount#9)) AS revenue#2]
      +- Filter ((l_shipdate#13 >= cast(8766 as string)) && (l_shipdate#13 < cast(cast(cast(8766 as timestamp) + interval 1 years as date) as string))) && ((l_discount#9 >= cast(CheckOverflow(promote_precision(cast(0.06 as decimal(3,2))) - promote_precision(cast(0.01 as decimal(3,2)))), DecimalType(3,2)) as double)) && (l_discount#9 < cast(CheckOverflow(promote_precision(cast(0.06 as decimal(3,2))) + promote_precision(cast(0.01 as decimal(3,2)))), DecimalType(3,2)) as double))) && (l_quantity#7 < cast(24 as double)))
        +- SubqueryAlias `default`.`lineitem`
          +- HiveTableRelation `default`.`lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linestatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]

== Optimized Logical Plan ==
GlobalLimit 21
+- LocalLimit 21
  +- Aggregate [cast(sum((l_extendedprice#8 * l_discount#9)) as string) AS revenue#22], 21
    +- Project [l_extendedprice#8, l_discount#9]
      +- Filter (((((l_isnotnull(l_discount#9) & isnonnull(l_shipdate#13)) & isnonnull(l_quantity#7)) && (l_shipdate#13 >= 1994-01-01)) && (l_shipdate#13 < 1995-01-01)) && (l_discount#9 >= 0.05)) && (l_discount#9 <= 0.07)) && (l_quantity#7 < 24.0))
        +- HiveTableRelation `default`.`lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linestatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]

== Physical Plan ==
CollectLimit 21
+- *(2) HashAggregate(keys=[], functions=[finalmerge_sum(merge sum#25) AS sum((l_extendedprice#8 * l_discount#9))#19], output=[revenue#22])
  +- Exchange SinglePartition
    +- *(1) HashAggregate(keys=[], functions=[partial_sum((l_extendedprice#8 * l_discount#9)) AS sum#25], output=[sum#25])
      +- *(1) Project [l_extendedprice#8, l_discount#9]
        +- *(1) Filter (((((l_isnotnull(l_discount#9) & isnonnull(l_shipdate#13)) & isnonnull(l_quantity#7)) && (l_shipdate#13 >= 1994-01-01)) && (l_shipdate#13 < 1995-01-01)) && (l_discount#9 >= 0.05)) && (l_discount#9 <= 0.07)) && (l_quantity#7 < 24.0))
          +- Scan hive default.lineitem [l_discount#9, l_extendedprice#8, l_quantity#7, l_shipdate#13], HiveTableRelation `default`.`lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linestatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]
  
```

Parsed Plan

```
== Parsed Logical Plan ==
GlobalLimit 21
+- LocalLimit 21
  +- Project [cast(revenue#2 as string) AS revenue#2]
    +- Aggregate [sum((l_extendedprice#8 * l_discount#9)) AS revenue#2]
      +- Filter (((l_shipdate#13 >= cast(8766 as string)) && (l_shipdate#13 < cast(cast(cast(8766 as timestamp) + interval 1 years as date) as string))) && ((l_discount#9 >= cast(CheckOverflow((promote_precision(cast(0.06 as decimal(3,2))) - promote_precision(cast(0.01 as decimal(3,2))), DecimalType(3,2)) as double)) && (l_discount#9 <= cast(CheckOverflow((promote_precision(cast(0.06 as decimal(3,2))) + promote_precision(cast(0.01 as decimal(3,2))), DecimalType(3,2)) as double)))) && (l_quantity#7 < cast(24 as double))))
        +- SubqueryAlias `default`.'lineitem'
          +- HiveTableRelation `default`.'lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linenstatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]

== Analyzed Logical Plan ==
revenue: string
GlobalLimit 21
+- LocalLimit 21
  +- Project [cast(revenue#2 as string) AS revenue#2]
    +- Aggregate [sum((l_extendedprice#8 * l_discount#9)) AS revenue#2]
      +- Filter (((l_shipdate#13 >= cast(8766 as string)) && (l_shipdate#13 < cast(cast(cast(8766 as timestamp) + interval 1 years as date) as string))) && ((l_discount#9 >= cast(CheckOverflow((promote_precision(cast(0.06 as decimal(3,2))) - promote_precision(cast(0.01 as decimal(3,2))), DecimalType(3,2)) as double)) && (l_discount#9 <= cast(CheckOverflow((promote_precision(cast(0.06 as decimal(3,2))) + promote_precision(cast(0.01 as decimal(3,2))), DecimalType(3,2)) as double)))) && (l_quantity#7 < cast(24 as double))))
        +- SubqueryAlias `default`.'lineitem'
          +- HiveTableRelation `default`.'lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linenstatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]
```

Analyzed Plan

```
== Analyzed Logical Plan ==
revenue: string
GlobalLimit 21
+- LocalLimit 21
  +- Project [cast(revenue#2 as string) AS revenue#2]
    +- Aggregate [sum((l_extendedprice#8 * l_discount#9)) AS revenue#2]
      +- Filter (((l_shipdate#13 >= cast(8766 as string)) && (l_shipdate#13 < cast(cast(cast(8766 as timestamp) + interval 1 years as date) as string))) && ((l_discount#9 >= cast(CheckOverflow((promote_precision(cast(0.06 as decimal(3,2))) - promote_precision(cast(0.01 as decimal(3,2))), DecimalType(3,2)) as double)) && (l_discount#9 <= cast(CheckOverflow((promote_precision(cast(0.06 as decimal(3,2))) + promote_precision(cast(0.01 as decimal(3,2))), DecimalType(3,2)) as double)))) && (l_quantity#7 < cast(24 as double))))
        +- SubqueryAlias `default`.'lineitem'
          +- HiveTableRelation `default`.'lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linenstatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]
```

Optimized Plan

```
== Optimized Logical Plan ==
GlobalLimit 21
+- LocalLimit 21
  +- Aggregate [cast(sum((l_extendedprice#8 * l_discount#9)) as string) AS revenue#22], 21
    +- Project [l_extendedprice#8, l_discount#9]
      +- Filter (((((isNotNull(l_discount#9) && isNotNull(l_shipdate#13)) && isNotNull(l_quantity#7)) && (l_shipdate#13 >= 1994-01-01)) && (l_shipdate#13 < 1995-01-01)) && (l_discount#9 >= 0.05)) && (l_discount#9 <= 0.07)) && (l_quantity#7 < 24.0))
        +- HiveTableRelation `default`.'lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linenstatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]
```

Physical Plan

```
== Physical Plan ==
CollectLimit 21
+- *(2) HashAggregate(keys=[], functions=[finalmerge_sum(merge sum#25) AS sum((l_extendedprice#8 * l_discount#9))#19], output=[revenue#22])
  +- Exchange SinglePartition
    +- *(1) HashAggregate(keys=[], functions=[partial_sum((l_extendedprice#8 * l_discount#9)) AS sum#25], output=[sum#25])
      +- *(1) Project [l_extendedprice#8, l_discount#9]
        +- *(1) Filter (((((isNotNull(l_discount#9) && isNotNull(l_shipdate#13)) && isNotNull(l_quantity#7)) && (l_shipdate#13 >= 1994-01-01)) && (l_shipdate#13 < 1995-01-01)) && (l_discount#9 >= 0.05)) && (l_discount#9 <= 0.07)) && (l_quantity#7 < 24.0))
          +- Scan hive default.lineitem [l_discount#9, l_extendedprice#8, l_quantity#7, l_shipdate#13], HiveTableRelation `default`.'lineitem`, org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe, [l_orderkey#3, l_partkey#4, l_suppkey#5, l_linenumber#6, l_quantity#7, l_extendedprice#8, l_discount#9, l_tax#10, l_returnflag#11, l_linenstatus#12, l_shipdate#13, l_commitdate#14, l_receiptdate#15, l_shipinstruct#16, l_shipmode#17, l_comment#18]
```



Understand and Tune Plans

Cmd 1

```
1 %sql
2
3 CREATE TEMPORARY VIEW tempView3 AS SELECT * FROM VALUES
4   ("one", "2.3"), ("two", "0.35")
5   AS t1(col1, col2);
6
7 SELECT * FROM tempView3 WHERE col2 != 0.0;
```

col1	col2
one	2.3
two	0.35

Cmd 1

```
1 %sql
2
3 CREATE TEMPORARY VIEW tempView3 AS SELECT * FROM VALUES
4   ("one", "2.3"), ("two", "0.35")
5   AS t1(col1, col2);
6
7 SELECT * FROM tempView3 WHERE col2 != 0;
```

col1	col2
one	2.3



Different Results!!!

Read the analyzed plan to check the implicit type casting.

Tip:

Explicitly cast the types in the queries.

```
Cmd 3
```

```
1 %sql
2
3 EXPLAIN EXTENDED SELECT * FROM tempView3 WHERE col2 != 0.0;
```

```
plan
== Parsed Logical Plan ==
'Project [*]
+- 'Filter NOT ('col2 = 0.0)
  +- 'UnresolvedRelation `tempView3`

== Analyzed Logical Plan ==
col1: string, col2: string
Project [col1#435840, col2#435841]
+- Filter NOT (cast(col2#435841 as double) = cast(0.0 as double))
  +- SubqueryAlias `tempview3`
    +- Project [col1#435840, col2#435841]
      +- SubqueryAlias `t1`
        +- LocalRelation [col1#435840, col2#435841]

== Optimized Logical Plan ==
LocalRelation [col1#435840, col2#435841]

== Physical Plan ==
LocalTableScan [col1#435840, col2#435841]
```

Read the analyzed plan to check the implicit type casting.

Tip:

Explicitly cast the types in the queries.

Cmd 3

```
1 %sql
2
3 EXPLAIN EXTENDED SELECT * FROM tempView3 WHERE col2 != 0;
```

plan

```
== Parsed Logical Plan ==
'Project [*]
+- 'Filter NOT ('col2 = 0)
    +- 'UnresolvedRelation `tempView3`'

== Analyzed Logical Plan ==
col1: string, col2: string
Project [col1#435840, col2#435841]
+- Filter NOT (cast(col2#435841 as int) = 0)
    +- SubqueryAlias `tempview3`
        +- Project [col1#435840, col2#435841]
            +- SubqueryAlias `t1`
                +- LocalRelation [col1#435840, col2#435841]

== Optimized Logical Plan ==
LocalRelation [col1#435840, col2#435841]

== Physical Plan ==
LocalTableScan [col1#435840, col2#435841]
```

Create Hive Tables

Cmd 2

Syntax to create a Hive Serde table

```
1 %sql  
2  
3 CREATE TABLE tabDemo1 (col1 int, col2 Timestamp)  
4 PARTITIONED BY (col3 int)  
5 STORED AS ORC;
```

Read Tables

Cmd 4

```
1 %sql  
2  
3 SET spark.sql.hive.convertMetastoreOrc = false;  
4  
5 EXPLAIN SELECT * FROM tabDemo1 WHERE col1 > 3;
```

plan

== Physical Plan ==

*(1) Filter (isnotnull(col1#454790) && (col1#454790 > 3))

+- Scan hive default.tabdemo1 [col1#454790, col2#454791, col3#454792] HiveTableRelation

`default`.`tabdemo1` org.apache.hadoop.hive.ql.io.orc.OrcSerde [col1#454790, col2#454791],
[col3#454792]

Hive serde reader

Cmd 3

```
1 %sql  
2  
3 SET spark.sql.hive.convertMetastoreOrc = true;  
4  
5 EXPLAIN SELECT * FROM tabDemo1 WHERE col1 > 3;
```

Native reader/writer performs faster than Hive serde reader/writer

plan

```
== Physical Plan ==  
*(1) Project [col1#454775, col2#454776, col3#454777]  
+- *(1) Filter (isnotnull(col1#454775) && (col1#454775 > 3))  
   +- *(1) FileScan orc default.tabdemo1[col1#454775,col2#454776,col3#454777] Batched: true,  
DataFilters: [isnotnull(col1#454775), (col1#454775 > 3)], Format: ORC, Location:  
CatalogFileIndex[dbfs:/user/hive/warehouse/tabdemo1], PartitionCount: 0, PartitionFilters: [],  
PushedFilters: [IsNotNull(col1), GreaterThan(col1,3)], ReadSchema:  
struct<col1:int,col2:timestamp>
```

filter pushdown

Create Native Tables

Tip:

Create native data source tables for better performance and stability.

Syntax to create a Spark native ORC table

```
Cmd 2
1 %sql
2
3 CREATE TABLE tabDemo2 (col1 int, col2 Timestamp, col3 int)
4 USING ORC
5 PARTITIONED BY (col3);
6
7 EXPLAIN SELECT * FROM tabDemo2 WHERE col1 > 3;
```

plan

```
== Physical Plan ==
*(1) Project [col1#454829, col2#454830, col3#454831]
+- *(1) Filter [isnotnull(col1#454829) && (col1#454829 > 3)]
   +- *(1) FileScan orc default.tabdemo2[col1#454829,col2#454830,col3#454831] Batched: true,
      DataFilters: [isnotnull(col1#454829), (col1#454829 > 3)], Format: ORC, Location:
      CatalogFileIndex[dbfs:/user/hive/warehouse/tabdemo2], PartitionCount: 0, PartitionFilters: [],
      PushedFilters: [IsNotNull(col1), GreaterThan(col1,3)], ReadSchema:
      struct<col1:int,col2:timestamp>
```

Push Down + Implicit Type Casting

Tip:

Cast is needed?

Update the
constants?

```
Cmd 3
1 %sql
2
3 EXPLAIN SELECT * FROM tabDemo2 WHERE col1 > 3.0;

plan
== Physical Plan ==
*(1) Project [col1#454829, col2#454830, col3#454831]
+- *(1) Filter (isnotnull(col1#454829) && (cast(col1#454829 as bigint) > 3))
   +- *(1) FileScan orc default.tabdemo2[col1#454829,col2#454830,col3#454831] Batched: true,
      DataFilters: [isnotnull(col1#454829), (cast(col1#454829 as bigint) > 3)], Format: ORC, Location:
      CatalogFileIndex[dbfs:/user/hive/warehouse/tabdemo2], PartitionCount: 0, PartitionFilters: []
      PushedFilters: [IsNotNull(col1)], ReadSchema: struct<col1:int,col2:timestamp>
```

Not pushed down???

#!%?

Nested Schema Pruning

Cmd 4

```
1 import org.apache.spark.sql.functions.struct  
2  
3 spark.range(10)  
4   .select(  
5     $"id",  
6     struct($"id" + $"id" as "c",($"id" * $"id") as "d") as "a")  
7   .write  
8   .format("parquet")  
9   .mode("overwrite")  
10  .saveAsTable("nestedTab1")  
11  
12 spark.conf.set("spark.sql.optimizer.nestedSchemaPruning.enabled", false)  
13  
14 spark.table("nestedTab1").select($"a.c").explain()
```

► (1) Spark Jobs

```
== Physical Plan ==  
*(1) Project [a#455352.c AS c#455359L]  
+- *(1) FileScan parquet default.nestedtab1[a#455352... batched: true, DataFilters: [], Format: Parquet, Location: InMemoryFileIndex[dbfs:/user/hive/warehouse/nestedtab1], PartitionFilters: [], ReadSchema: struct<a:struct<c:bigint,d:bigint>>]
```



#!%?

Not pruned???

Nested Schema Pruning

Cmd 4

```
1 import org.apache.spark.sql.functions.struct  
2  
3 spark.range(10)  
4   .select(  
5     $"id",  
6     struct($"id" + $"id") as "c", ($"id" * $"id") as "d") as "a")  
7   .write  
8   .format("parquet")  
9   .mode("overwrite")  
10  .saveAsTable("nestedTab1")  
11  
12 spark.conf.set("spark.sql.optimizer.nestedSchemaPruning.enabled", true)  
13  
14 spark.table("nestedTab1").select($"a.c").explain()
```

▶ (1) Spark Jobs

```
== Physical Plan ==  
*(1) Project [a#455316.c AS c#455323L]  
-- *(1) FileScan parquet default.nestedtab1[a#455316] Batched: true, DataFilters: [], Format: Parquet, Location: InMemoryFileIndex[dbfs:/user/hive/warehouse/nestedtab1], PartitionFilters: [], PushedFilters: [], ReadSchema: struct<a:struct<c:bigint>>
```

Collapse Projects

Cmd 10

```
1 import org.apache.spark.sql.functions.udf  
2  
3 val udf1 = udf((value: Int) => if (value > 0) value * value else value)  
4  
5 spark.table("tabDemo2")  
6   .select(udf1($"col1").as("newCol1"))  
7   .selectExpr("newCol1 + newCol1", "newCol1")  
8   .explain()
```

Call UDF three times!!!

#!%?

```
-- Physical Plan --  
*(1) Project [(if (isnull(col1#110)) null else SpecializedUDF(col1#110) + if (isnull(col1#110)) null else SpecializedUDF(col1#110)) AS (newCol1 + newCol1)#197, if (isnull(col1#110)) null else SpecializedUDF(col1#110) AS newCol1#195]  
+- *(1) FileScan orc default.tabdemo2[col1#110,col3#112] Batched: true, DataFilters: [], Format: ORC, Location: CatalogFileIndex[dbfs:/user/hive/warehouse/tabdemo2], PartitionCount: 0, PartitionFilters: [], PushedFilters: [], ReadSchema: struct<col1:int>  
import org.apache.spark.sql.functions.udf  
udf1: org.apache.spark.sql.expressions.UserDefinedFunction = UserDefinedFunction(<function1>,IntegerType,Some(List(IntegerType)))
```

Collapse Projects

Cmd 11

```
1 import org.apache.spark.sql.functions.udf
2
3 val udf1 = udf((value: Int) => if (value > 0) value * value else value).asNondeterministic
4
5 spark.table("tabDemo2")
6   .select(udf1($"col1").as("newCol1"))
7   .selectExpr("newCol1 + newCol1", "newCol1")
8   .explain()
```

```
== Physical Plan ==
*(1) Project [(newCol1#213 + newCol1#213) AS (newCol1 + newCol1)#215, newCol1#213]
+- *(1) Project [if (isnull(col1#110)) null else UDF(col1#110) AS newCol1#213]
   +- *(1) FileScan orc default.tabdemo2[col1#110,col2#111,col3#112] Batched: true, DataFilters: [], Format: ORC, Location: CatalogFileIndex[dbfs:/user/hive/warehouse/tabdemo2], PartitionCount: 0, PartitionFilters: [], PushedFilters: [], ReadSchema: struct<col1:int,col2:timestamp>
import org.apache.spark.sql.functions.udf
udf1: org.apache.spark.sql.expressions.UserDefinedFunction = UserDefinedFunction(<function1>,IntegerType,Some(List(IntegerType)))
```

Cross-session SQL Cache

- If a query is cached in one session, new queries in all sessions might be impacted.
- Check your query plan!

```
1 val df1 = spark.table("tabDemo2").selectExpr("col1 + col1", "col3")
2 df1.cache()
```



```
1 spark.table("tabDemo2")
2   .selectExpr("(col1 + col1) as newCol1", "col3")
3   .selectExpr("newCol1 + col3")
4   .explain(true)
```

```
-- Parsed Logical Plan ==
'Project [(newCol1 + 'col3) AS (newCol1 + col3)#277]
+- Project [(col1#110 + col1#110) AS newCol1#274, col3#112]
  +- SubqueryAlias `default`.`tabdemo2`
    +- Relation[col1#110,col2#111,col3#112] orc
```

```
-- Analyzed Logical Plan ==
(newCol1 + col3): int
Project [(newCol1#274 + col3#112) AS (newCol1 + col3)#277]
+- Project [(col1#110 + col1#110) AS newCol1#274, col3#112]
  +- SubqueryAlias `default`.`tabdemo2`
    +- Relation[col1#110,col2#111,col3#112] orc
```

```
-- Optimized Logical Plan ==
Project [(newCol1#274 + col3#112) AS (newCol1 + col3)#277]
+- InMemoryRelation [newCol1#274, col3#112], StorageLevel(disk, memory, deserialized, 1 replicas)
  +- *(1) Project [(col1#110 + col1#110) AS (col1 + col1)#258, col3#112]
    +- *(1) FileScan orc default.tabdemo2[col1#110,col3#112] Batched: true, DataFilters: [], Format:
ORC, Location: CatalogFileIndex[dbfs:/user/hive/warehouse/tabdemo2], PartitionCount: 0, PartitionFilters:
[], PushedFilters: [], ReadSchema: struct<col1:int>
```

Join Hints in Spark 3.0

- BROADCAST
 - Broadcast Hash/Nested-loop Join
- MERGE
 - Shuffle Sort Merge Join
- SHUFFLE_HASH
 - Shuffle Hash Join
- SHUFFLE_REPLICATE_NL
 - Shuffle-and-Replicate Nested Loop Join



Track Execution


From SQL query to Spark Jobs

SQL

Completed Queries: 1

Completed Queries (1)

ID	Description	Submitted	Duration	Job IDs
0	show at command-15475442:12	+details	2019/03/06 06:42:03	55 s



- A SQL query => multiple Spark jobs.
 - For example, broadcast exchange, shuffle exchange, Scalar subquery.
 - External data sources: Delta Lake.
 - New adaptive query execution.
- A Spark job => A DAG


A chain of RDD dependencies organized in a directed acyclic graph (DAG)

Details for Query 0


Submitted Time: 2019/03/06 06:42:03

Duration: 55 s

Succeeded Jobs: 0




Query Execution



The higher level SQL physical operators.

The low level Spark RDD primitives.



Job Tab in Spark UI



Job Tab

- Jobs
- Stages
- Tasks

Jobs Stages Storage Environment Executors SQL JDBC/ODBC Server

Details for Job 0

Status: SUCCEEDED
Associated SQL Query: 0
Job Group: 7428604016917490921_8345753902610332076_2a784b5c6aa849caab297e241b230996
Completed Stages: 2

► Event Timeline
▼ DAG Visualization


The amount of time for each stage.

Completed Stages (2)

Stage Id	Pool Name	Description	Submitted	Duration	Tasks: Succeeded/Total	Input	Output	Shuffle Read	Shuffle Write
1	7428604016917490921	spark.sql(" select sum(l_extendedprice... show at command-15475442:12 +details")	2019/03/06 06:42:58	0.1 s	1/1			3.3 KB	
0	7428604016917490921	spark.sql(" select sum(l_extendedprice... show at command-15475442:12 +details")	2019/03/06 06:42:06	52 s	58/58	3.6 GB			3.3 KB

Stages Tab

Tasks specific info



Summary Metrics for 58 Completed Tasks

Metric	Min	25th percentile	Median	75th percentile	Max
Duration	1 s	3 s	3 s	3 s	10 s
Scheduler Delay	5 ms	8 ms	11 ms	17 ms	84 ms
Task Deserialization Time	1 ms	2 ms	3 ms	10 ms	0.5 s
GC Time	0 ms	10 ms	13 ms	18 ms	0.3 s
Result Serialization Time	0 ms	0 ms	0 ms	0 ms	2 ms
Getting Result Time	0 ms				
Peak Execution Memory	0.0 B				
Input Size / Records	36.2 MB / 294076	64.0 MB / 519617	64.0 MB / 519676	64.0 MB / 523649	64.0 MB / 528652
Shuffle Write Size / Records	8 B / 1	59.0 B / 1	59.0 B / 1	59.0 B / 1	59.0 B / 1

Aggregated Metrics by Executor

Executor ID ▲	Address
0	stdout 10.0.191.84:33584
1	stderr

Tasks (58)

Killed? Which executor's log we should read? Balanced? Skew?

Index	ID	Attempt	Status	Locality Level	Executor ID	Host	Launch Time	Duration	Scheduler Delay	Task Deserialization Time	GC Time	Result Serialization Time	Getting Result Time	Peak Execution Memory	Input Size / Records			Write Time			Shuffle Write Size / Records			Errors		
															Failed Tasks	Killed Tasks	Succeeded Tasks	Input Size / Records	Shuffle Write Size / Records	Blacklisted	Input Size / Records	Write Time	Shuffle Write Size / Records	Errors		
0	0	0	SUCCESS	PROCESS_LOCAL	0	10.0.191.84	2019/03/06 06:42:06	10 s	83 ms	0.5 s	0.3 s	0 ms	0 ms	0.0 B	64.0 MB / 528652	0	58	3.6 GB / 29999795	3.3 KB / 58	false	64.0 MB / 528652	59.0 B / 1	59.0 B / 1			
2	2	10	SUCCESS	PROCESS_LOCAL	0	10.0.191.84	2019/03/06 06:42:06	9 s	71 ms	0.5 s	0.2 s	1 ms	0 ms	0.0 B	64.0 MB / 523796	0	58	3.6 GB / 29999795	3.3 KB / 58	false	64.0 MB / 523796	59.0 B / 1	59.0 B / 1			
3	3	0	SUCCESS	PROCESS_LOCAL	0	10.0.191.84	2019/03/06 06:42:06	9 s	73 ms	0.5 s	0.2 s	0 ms	0 ms	0.0 B	64.0 MB / 523738	0	58	3.6 GB / 29999795	3.3 KB / 58	false	64.0 MB / 523738	10 ms	59.0 B / 1			
1	1	0	SUCCESS	PROCESS_LOCAL	0	10.0.191.84	2019/03/06 06:42:06	9 s	84 ms	0.5 s	0.2 s	2 ms	0 ms	0.0 B	64.0 MB / 527402	0	58	3.6 GB / 29999795	3.3 KB / 58	false	64.0 MB / 527402	8 ms	59.0 B / 1			
12	12	0	SUCCESS	PROCESS_LOCAL	0	10.0.191.84	2019/03/06 06:42:22	4 s	17 ms	18 ms	18 ms	0 ms	0 ms	0.0 B	64.0 MB / 523739	0	58	3.6 GB / 29999795	3.3 KB / 58	false	64.0 MB / 523739	4 ms	59.0 B / 1			

Executors Tab

Jobs Stages Storage Environment Executors SQL JDBC/ODBC Server

Executors

Summary

	RDD Blocks	Storage Memory	Disk Used	Cores	Active Tasks	Failed Tasks	Complete Tasks	Total Tasks	Task Time (GC Time)	Input	Shuffle Read	Shuffle Write	Blacklisted
Active(2)	0	0.0 B / 22.7 GB	0.0 B	4	0	0	59	59	3.4 min (2 s)	3.9 GB	3.4 KB	3.4 KB	0
Dead(2)	0	0.0 B / 22.4 GB	0.0 B	8	0	0	0	0	0 ms (0 ms)	0.0 B	0.0 B	0.0 B	0
Total(4)	0	0.0 B / 45.1 GB	0.0 B	12	0	0	59	59	3.4 min (2 s)	3.9 GB	3.4 KB	3.4 KB	0

Executors

used/available memory

size of data transferred between stages

Show 20 entries

Executor ID	Address	Status	RDD Blocks	Storage Memory	Disk Used	Cores	Active Tasks	Failed Tasks	Complete Tasks	Total Tasks	Task Time (GC Time)	Input	Shuffle Read	Shuffle Write	Logs	Thread Dump	Heap Histogram
0	10.0.191.84:33584	Active	0	0.0 B / 11.2 GB	0.0 B	4	0	0	59	59	3.4 min (2 s)	3.9 GB	3.4 KB	3.4 KB	stdout	Thread Dump	Heap Histogram
driver	ip-10-0-134-19.us-west-2.compute.internal:37213	Active	0	0.0 B / 11.5 GB	0.0 B	0	0	0	0	0	0 ms (0 ms)	0.0 B	0.0 B	0.0 B	stdout	Thread Dump	Heap Histogram
1	10.0.245.216:46441	Dead	0	0.0 B / 11.2 GB	0.0 B	4	0	0	0	0	0 ms (0 ms)	0.0 B	0.0 B	0.0 B	stdout	Thread Dump	Heap Histogram
2	10.0.158.178:32981	Dead	0	0.0 B / 11.2 GB	0.0 B	4	0	0	0	0	0 ms (0 ms)	0.0 B	0.0 B	0.0 B	stdout	Thread Dump	Heap Histogram

Showing 1 to 4 of 4 entries

Previous 1 Next

All the problematic executors in the same node?

Hostname: ec2-54-185-31-39.us-west-2.compute.amazonaws.com

Spark Version: 2.4.0

[Jobs](#) [Stages](#) [Storage](#) [Environment](#) [Executors](#) [SQL](#) [JDBC/ODBC Server](#)

Thread dump for executor driver

Updated at 2019/04/21 01:57:38

[Expand All](#)Search:

- Interacting with Hive metastore?
- Slow query planning?
- Slow file listing?

Thread ID	Thread Name	Thread State	Thread Locks
1331	WRAPPER-ReplId-10b19-7ae6f-00815-e	RUNNABLE	Lock(java.util.concurrent.locks.ReentrantLock\$NonfairSync@111358199), Monitor(org.apache.spark.sql.hive.client.HiveClientImpl@608273722}), Monitor(sun.security.ssl.AppInputStream@229024694}), Monitor(org.apache.spark.sql.execution.command.DataWritingCommandExec@1613603167}), Monitor(line407480b3f69249989060248fc235f7ee88.\$eval\$@1213128957}), Monitor(java.lang.Object@1798611689})

```
java.net.SocketInputStream.socketRead0(Native Method)
java.net.SocketInputStream.socketRead(SocketInputStream.java:116)
java.net.SocketInputStream.read(SocketInputStream.java:171)
java.net.SocketInputStream.read(SocketInputStream.java:141)
```



Insert Partitioned Hive Table

```
1 spark.sql(  
2   s"""  
3     |CREATE TABLE hiveTab1 (key INT, value STRING, p1 STRING)  
4     |  USING hive OPTIONS (fileformat 'parquet')  
5     |  PARTITIONED BY (p1)  
6   """.stripMargin)  
7  
8 spark.time {  
9   spark.sql(  
10    s"""  
11      |INSERT INTO TABLE hiveTab1  
12      |  SELECT id AS key, id AS value, CAST((id % 50) AS STRING) p1  
13      |  FROM RANGE(0, 5000)  
14    """.stripMargin)  
15 }
```

OR “STORED AS PARQUET”

5000 partitions took
almost 8 minutes!!!

- ▶ (1) Spark Jobs
- ▶ res30: org.apache.spark.SparkSession

#!%?

```
-chgrp: '' does not match any file under specified pattern for group  
Usage: hadoop fs [generic options] -chgrp [-R] GROUP PATH...  
Time taken: 464115 ms
```

```
sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
java.lang.reflect.Method.invoke(Method.java:498)
org.apache.spark.sql.hive.client.Shim_v0_12.loadDynamicPartitions(HiveShim.scala:117)
org.apache.spark.sql.hive.client.HiveClientImpl$$anonfun$loadDynamicPartitions$1.apply(HiveClientImpl.scala:117)
org.apache.spark.sql.hive.client.HiveClientImpl$$anonfun$loadDynamicPartitions$1.apply(HiveClientImpl.scala:117)
org.apache.spark.sql.hive.client.HiveClientImpl$$anonfun$loadDynamicPartitions$1
```

Insert Partitioned Native Table

```
1 spark.sql(  
2   s"""  
3     |CREATE TABLE nativeTab1 (key INT, value STRING, p1 STRING)  
4     | USING parquet  
5     | PARTITIONED BY (p1)  
6   """".stripMargin)  
7  
8 spark.time {  
9   spark.sql(  
10    s"""  
11      |INSERT INTO TABLE nativeTab1  
12      | SELECT id AS key, id AS value, CAST((id % 50) AS STRING) p1  
13      | FROM RANGE(0, 5000)  
14    """".stripMargin)  
15 }
```

Reduced from almost 8 minutes
to less than 1 minute !!!

- ▶ (1) Spark Jobs
- ▶ 📄 res32: org.apache.spark.sql.DataFrame

Time taken: 48730 ms

Insert Partitioned Delta Table

```
1 spark.sql(  
2   s"""  
3     |CREATE TABLE deltaTab1 (key INT, value STRING, p1 STRING)  
4     | USING delta  
5     | PARTITIONED BY (p1)  
6   """ .stripMargin)  
7  
8 spark.time {  
9   spark.sql(  
10    s"""  
11      |INSERT INTO TABLE deltaTab1  
12      | SELECT id AS key, id AS value, CAST((id % 50) AS STRING) p1  
13      | FROM RANGE(0, 5000)  
14    """ .stripMargin)  
15 }
```

Reduced from almost 8 minutes
to 27 seconds!!!

- ▶ (4) Spark Jobs
- ▶ 📄 res17: org.apache.spark.sql.DataFrame

Time taken: 27735 ms

Typical Spark Performance Issues

The table has thousands of partitions

Hive metastore overhead

This table can have 100s of thousands to millions of files

File system overhead - listing takes forever!

New data is not immediately visible

Need to invoke a command “Refresh Table” with the SQL engine they were using

The above issues can add 10s of minutes to the response time!

Delta Lake + Spark

Scalable metadata handling @ Delta Lake

Store metadata in transaction log file instead of metastore

The table has thousands of partitions

Zero Hive Metastore overhead

The table can have 100s of thousands to millions of files

No file listing

New data is not immediately visible

Delta table state is computed on read

How do I use Delta?

`format("parquet") -> format("delta")`



Delta Lake + Spark

- Full ACID transactions
- Schema management
- Data versioning and time travel
- Unified batch/streaming support
- Scalable metadata handling
- Record update and deletion
- Data expectation



Delta Lake: <https://delta.io/>
For details, refer to the blog
<https://tinyurl.com/yxhbe2lg>

Delta Usage Statistics

More than 1 exabyte
processed (10^{18} bytes)
monthly

Healthcare and Life Sciences



Financial Services



Media and Entertainment



Retail, CPG, and eCommerce



Public Sector



Manufacturing



Technology



Other



Additional Resources

- Apache Spark document: <https://spark.apache.org/docs/latest/sql-programming-guide.html>
- Blog: <https://databricks.com/blog/category/engineering/spark>
- Previous summit: <https://databricks.com/sparkaisummit/north-america/sessions>
- Delta Lake document: <https://docs.delta.io>
- Databricks document: <https://docs.databricks.com/>
- Books: <https://www.amazon.com/s?k=apache+spark>
- Databricks academy: <https://academy.databricks.com>
- Databricks ebooks: <https://databricks.com/resources/type/ebooks>



Thank you

Xiao Li

(lixiao@databricks.com)



15 - 17 OCTOBER 2019 | AMSTERDAM

ORGANIZED BY  databricks

AMSTERDAM

SPARK + AI SUMMIT EUROPE

CALL FOR PAPERS IS OPEN
REGISTRATION OPEN APRIL 8