

Building a Real-Time Data Pipeline: Apache Kafka at Linkedin

Hadoop Summit 2013 Joel Koshy June 2013

#### Network update stream



# We have a lot of data.


We want to leverage this data to build products.

Data pipeline







#### People you may know



### System and application metrics/logging









How do we integrate this variety of data and make it available to all these systems?


### Point-to-point pipelines



#### LinkedIn's user activity data pipeline (circa 2010)




### Point-to-point pipelines




#### Four key ideas

- Central data pipeline
- 2. Push data cleanliness upstream
- 3. O(1) ETL
- 4. Evidence-based correctness

# Central data pipeline




First attempt: don't re-invent the wheel




Second attempt: re-invent the wheel!

# Use a central commit log


### What is a commit log?



#### The log as a messaging system




## Apache Kafka



#### Usage at LinkedIn

- 16 brokers in each cluster
- 28 billion messages/day
- Peak rates
  - Writes: 460,000 messages/second
  - Reads: 2,300,000 messages/second
- ~ 700 topics
- 40-50 live services consuming user-activity data
- Many ad hoc consumers
- Every production service is a producer (for metrics)
- 10k connections/colo

#### Usage at LinkedIn



#### Four key ideas

- Central data pipeline
- 2. Push data cleanliness upstream
- 3. O(1) ETL
- 4. Evidence-based correctness

#### Standardize on Avro in data pipeline

```
"type": "record",
"name": "URIValidationRequestEvent",
"namespace": "com.linkedin.event.usv",
"fields": [
    "name": "header",
    "type": {
      "type": "record",
      "name": "TrackingEventHeader",
      "namespace": "com.linkedin.event",
      "fields": [
          "name": "memberId",
          "type": "int",
          "doc": "The member id of the user initiating the action"
          "name": "timeMs",
          "type": "long",
          "doc": "The time of the event"
          "name": "host",
          "type": "string",
```

#### Four key ideas

- Central data pipeline
- 2. Push data cleanliness upstream
- 3. O(1) ETL
- 4. Evidence-based correctness

#### Hadoop data load (Camus)

- Open sourced:
  - https://github.com/linkedin/camus
- One job loads all events
- ~10 minute ETA on average from producer to HDFS
- Hive registration done automatically
- Schema evolution handled transparently


#### Four key ideas


- Central data pipeline
- 2. Push data cleanliness upstream
- 3. O(1) ETL
- 4. Evidence-based correctness

#### Does it work?

"All published messages must be delivered to all consumers (quickly)"

#### **Audit Trail**





#### Kafka replication (0.8)

- Intra-cluster replication feature
  - Facilitates high availability and durability
- Beta release available https://dist.apache.org/repos/dist/release/kafka/
- Rolled out in production at LinkedIn last week

#### Join us at our user-group meeting tonight @ LinkedIn!

- Thursday, June 27, 7.30pm to 9.30pm
- 2025 Stierlin Ct., Mountain View, CA
- http://www.meetup.com/http-kafka-apache-org/events/125887332/
- Presentations (replication overview and use-case studies) from:
  - RichRelevance
  - Netflix
  - Square
  - LinkedIn

