

## Chapter 10: File-System Interface



Operating System Concepts – 8th Edition

Silberschatz, Galvin and Gagne ©2009

### File Concept

- Contiguous logical address space
- Types:
  - Data
    - ▶ numeric
    - ▶ character
    - ▶ binary
  - Program

Operating System Concepts – 8th Edition

10.4

Silberschatz, Galvin and Gagne ©2009

## Chapter 10: File-System Interface

- File Concept
- Access Methods
- Directory Structure
- File-System Mounting
- File Sharing
- Protection

Operating System Concepts – 8th Edition

10.2

Silberschatz, Galvin and Gagne ©2009

### File Structure

- None - sequence of words, bytes
- Simple record structure
  - Lines
  - Fixed length
  - Variable length
- Complex Structures
  - Formatted document
  - Relocatable load file
- Can simulate last two with first method by inserting appropriate control characters
- Who decides:
  - Operating system
  - Program

Operating System Concepts – 8th Edition

10.5

Silberschatz, Galvin and Gagne ©2009

### Objectives

- To explain the function of file systems
- To describe the interfaces to file systems
- To discuss file-system design tradeoffs, including access methods, file sharing, file locking, and directory structures
- To explore file-system protection

Operating System Concepts – 8th Edition

10.3

Silberschatz, Galvin and Gagne ©2009


### File Attributes

- **Name** – only information kept in human-readable form
- **Identifier** – unique tag (number) identifies file within file system
- **Type** – needed for systems that support different types
- **Location** – pointer to file location on device
- **Size** – current file size
- **Protection** – controls who can do reading, writing, executing
- **Time, date, and user identification** – data for protection, security, and usage monitoring
- Information about files are kept in the directory structure, which is maintained on the disk

Operating System Concepts – 8th Edition


10.6

Silberschatz, Galvin and Gagne ©2009




## File Operations

- File is an **abstract data type**
- **Create**
- **Write**
- **Read**
- **Reposition within file**
- **Delete**
- **Truncate**
- **Open( $F_i$ )** – search the directory structure on disk for entry  $F_i$  and move the content of entry to memory
- **Close ( $F_i$ )** – move the content of entry  $F_i$  in memory to directory structure on disk



Operating System Concepts – 8th Edition      10.7      Silberschatz, Galvin and Gagne ©2009




## File Locking Example – Java API


```

import java.io.*;
import java.nio.channels.*;
public class LockingExample {
    public static final boolean EXCLUSIVE = false;
    public static final boolean SHARED = true;
    public static void main(String args[]) throws IOException {
        FileLock sharedLock = null;
        FileLock exclusiveLock = null;
        try {
            RandomAccessFile raf = new RandomAccessFile("file.txt", "rw");
            // get the channel for the file
            FileChannel ch = raf.getChannel();
            // this locks the first half of the file - exclusive
            exclusiveLock = ch.lock(0, raf.length()/2, EXCLUSIVE);
            /** Now modify the data . . . */
            // release the lock
            exclusiveLock.release();
        }
    }
}

```




Operating System Concepts – 8th Edition      10.10      Silberschatz, Galvin and Gagne ©2009




## Open Files

- Several pieces of data are needed to manage open files:
  - File pointer: pointer to last read/write location, per process that has the file open
  - File-open count: counter of number of times a file is open – to allow removal of data from open-file table when last processes closes it
  - Disk location of the file: cache of data access information
  - Access rights: per-process access mode information



Operating System Concepts – 8th Edition      10.8      Silberschatz, Galvin and Gagne ©2009




## File Locking Example – Java API (cont)


```

// this locks the second half of the file - shared
sharedLock = ch.lock(raf.length()/2+1, raf.length(), SHARED);
/** Now read the data . . . */
// release the lock
sharedLock.release();
} catch (java.io.IOException ioe) {
    System.err.println(ioe);
} finally {
    if (exclusiveLock != null)
        exclusiveLock.release();
    if (sharedLock != null)
        sharedLock.release();
}
}
}

```




Operating System Concepts – 8th Edition      10.11      Silberschatz, Galvin and Gagne ©2009




## Open File Locking

- Provided by some operating systems and file systems
- Mediates access to a file
- Mandatory or advisory:
  - **Mandatory** – access is denied depending on locks held and requested
  - **Advisory** – processes can find status of locks and decide what to do




Operating System Concepts – 8th Edition      10.9      Silberschatz, Galvin and Gagne ©2009



## File Types – Name, Extension

file type	usual extension	function
executable	exe, com, bin or none	ready-to-run machine-language program
object	obj, o	compiled, machine language, not linked
source code	c, cc, java, pas, asm, a	source code in various languages
batch	bat, sh	commands to the command interpreter
text	txt, doc	textual data, documents
word processor	wp, tex, rtf, doc	various word-processor formats
library	lib, a, so, dll	libraries of routines for programmers
print or view	ps, pdf, jpg	ASCII or binary file in a format for printing or viewing
archive	arc, zip, tar	related files grouped into one file, sometimes compressed, for archiving or storage
multimedia	mpeg, mov, rm, mp3, avi	binary file containing audio or A/V information



Operating System Concepts – 8th Edition      10.12      Silberschatz, Galvin and Gagne ©2009

## Access Methods

■ **Sequential Access**

read next  
write next  
reset  
no read after last write (rewrite)

■ **Direct Access**

read  $n$   
write  $n$   
position to  $n$   
read next  
write next  
rewrite  $n$

$n$  = relative block number

```

      read next
      write next
      reset
      no read after last write
        (rewrite)

      read n
      write n
      position to n
      read next
      write next
      rewrite n

      n = relative block number
          
```

Operating System Concepts – 8th Edition
10.13
Silberschatz, Galvin and Gagne ©2009

## Example of Index and Relative Files

last name	logical record number
Adams	
Arthur	
Asher	
•	
•	
•	
Smith	

smith, john	social-security	age
-------------	-----------------	-----

index file
relative file

Operating System Concepts – 8th Edition
10.16
Silberschatz, Galvin and Gagne ©2009

## Sequential-access File

Operating System Concepts – 8th Edition
10.14
Silberschatz, Galvin and Gagne ©2009

## Directory Structure

■ A collection of nodes containing information about all files

Directory

Files

Both the directory structure and the files reside on disk  
Backups of these two structures are kept on tapes

Operating System Concepts – 8th Edition
10.17
Silberschatz, Galvin and Gagne ©2009

## Simulation of Sequential Access on a Direct-access File

sequential access	implementation for direct access
<i>reset</i>	$cp = 0;$
<i>read next</i>	$read\ cp;$ $cp = cp + 1;$
<i>write next</i>	$write\ cp;$ $cp = cp + 1;$

Operating System Concepts – 8th Edition
10.15
Silberschatz, Galvin and Gagne ©2009

## A Typical File-system Organization

partition A

directory  
files

}

partition B

directory  
files

} disk 1

partition C

directory  
files

}

} disk 3

} disk 2

Operating System Concepts – 8th Edition
10.18
Silberschatz, Galvin and Gagne ©2009



## Operations Performed on Directory

- Search for a file
- Create a file
- Delete a file
- List a directory
- Rename a file
- Traverse the file system



Operating System Concepts – 8th Edition


10.19

Silberschatz, Galvin and Gagne ©2009



## Two-Level Directory

- Separate directory for each user



- Path name
- Can have the same file name for different user
- Efficient searching
- No grouping capability



Operating System Concepts – 8th Edition

10.22

Silberschatz, Galvin and Gagne ©2009



## Organize the Directory (Logically) to Obtain

- Efficiency – locating a file quickly
- Naming – convenient to users
  - Two users can have same name for different files
  - The same file can have several different names
- Grouping – logical grouping of files by properties, (e.g., all Java programs, all games, ...)




Operating System Concepts – 8th Edition

10.20

Silberschatz, Galvin and Gagne ©2009



## Tree-Structured Directories



Operating System Concepts – 8th Edition


10.23

Silberschatz, Galvin and Gagne ©2009



## Single-Level Directory

- A single directory for all users



Naming problem

Grouping problem



Operating System Concepts – 8th Edition

10.21

Silberschatz, Galvin and Gagne ©2009



## Tree-Structured Directories (Cont)

- Efficient searching
- Grouping Capability
- Current directory (working directory)
  - `cd /spell/mail/prog`
  - `type list`



Operating System Concepts – 8th Edition


10.24

Silberschatz, Galvin and Gagne ©2009



## Tree-Structured Directories (Cont)

- **Absolute** or **relative** path name
  - Creating a new file is done in current directory
  - Delete a file  
`rm <file-name>`
  - Creating a new subdirectory is done in current directory  
`mkdir <dir-name>`
- Example: if in current directory `/mail`  
`mkdir count`



Deleting "mail" ⇒ deleting the entire subtree rooted by "mail"


Operating System Concepts – 8th Edition

10.25

Silberschatz, Galvin and Gagne ©2009



## General Graph Directory



Operating System Concepts – 8th Edition


10.28

Silberschatz, Galvin and Gagne ©2009



## Acyclic-Graph Directories

- Have shared subdirectories and files



Operating System Concepts – 8th Edition

10.26

Silberschatz, Galvin and Gagne ©2009



## General Graph Directory (Cont.)

- How do we guarantee no cycles?
  - Allow only links to file not subdirectories
  - Garbage collection
  - Every time a new link is added use a cycle detection algorithm to determine whether it is OK

Operating System Concepts – 8th Edition

10.29

Silberschatz, Galvin and Gagne ©2009



## Acyclic-Graph Directories (Cont.)

- Two different names (aliasing)
  - If *dict* deletes *list* ⇒ dangling pointer
- Solutions:
- Backpointers, so we can delete all pointers
  - Variable size records a problem
  - Backpointers using a daisy chain organization
  - Entry-hold-count solution
- New directory entry type
    - **Link** – another name (pointer) to an existing file
    - **Resolve the link** – follow pointer to locate the file

Operating System Concepts – 8th Edition

10.27

Silberschatz, Galvin and Gagne ©2009




## File System Mounting

- A file system must be **mounted** before it can be accessed
- A unmounted file system (i.e. Fig. 11-11(b)) is mounted at a **mount point**

Operating System Concepts – 8th Edition

10.30


Silberschatz, Galvin and Gagne ©2009



### File Sharing – Multiple Users

- **User IDs** identify users, allowing permissions and protections to be per-user
- **Group IDs** allow users to be in groups, permitting group access rights

Operating System Concepts – 8th Edition 10.34 Silberschatz, Galvin and Gagne ©2009



### File Sharing – Remote File Systems

- Uses networking to allow file system access between systems
  - Manually via programs like FTP
  - Automatically, seamlessly using **distributed file systems**
  - Semi automatically via the **world wide web**
- **Client-server** model allows clients to mount remote file systems from servers
  - Server can serve multiple clients
  - Client and user-on-client identification is insecure or complicated
  - **NFS** is standard UNIX client-server file sharing protocol
  - **CIFS** is standard Windows protocol
  - Standard operating system file calls are translated into remote calls
- Distributed Information Systems (**distributed naming services**) such as LDAP, DNS, NIS, Active Directory implement unified access to information needed for remote computing

Operating System Concepts – 8th Edition 10.35 Silberschatz, Galvin and Gagne ©2009

### File Sharing

- Sharing of files on multi-user systems is desirable
- Sharing may be done through a **protection** scheme
- On distributed systems, files may be shared across a network
- Network File System (NFS) is a common distributed file-sharing method

Operating System Concepts – 8th Edition 10.33 Silberschatz, Galvin and Gagne ©2009

### File Sharing – Failure Modes

- Remote file systems add new failure modes, due to network failure, server failure
- Recovery from failure can involve state information about status of each remote request
- Stateless protocols such as NFS include all information in each request, allowing easy recovery but less security

Operating System Concepts – 8th Edition 10.36 Silberschatz, Galvin and Gagne ©2009

## File Sharing – Consistency Semantics

- Consistency semantics specify how multiple users are to access a shared file simultaneously
  - Similar to Ch 7 process synchronization algorithms
    - Tend to be less complex due to disk I/O and network latency (for remote file systems)
  - Andrew File System (AFS) implemented complex remote file sharing semantics
  - Unix file system (UFS) implements:
    - Writes to an open file visible immediately to other users of the same open file
    - Sharing file pointer to allow multiple users to read and write concurrently
  - AFS has session semantics
    - Writes only visible to sessions starting after the file is closed

Operating System Concepts – 8th Edition 10.37 Silberschatz, Galvin and Gagne ©2009

## Windows XP Access-control List Management

Operating System Concepts – 8th Edition 10.40 Silberschatz, Galvin and Gagne ©2009

## Protection

- File owner/creator should be able to control:
  - what can be done
  - by whom
- Types of access
  - Read
  - Write
  - Execute
  - Append
  - Delete
  - List

Operating System Concepts – 8th Edition 10.38 Silberschatz, Galvin and Gagne ©2009

## A Sample UNIX Directory Listing

-rw-rw-r--	1	pbq	staff	31200	Sep 3 08:30	intro.ps
drwx-----	5	pbq	staff	512	Jul 8 09:33	private/
drwxrwxr-x	2	pbq	staff	512	Jul 8 09:35	doc/
drwxrwx---	2	pbq	student	512	Aug 3 14:13	student-proj/
-rw-r--r--	1	pbq	staff	9423	Feb 24 2003	program.c
-rwxr-xr-x	1	pbq	staff	20471	Feb 24 2003	program
drwx--x--x	4	pbq	faculty	512	Jul 31 10:31	lib/
drwx-----	3	pbq	staff	1024	Aug 29 06:52	mail/
drwxrwxrwx	3	pbq	staff	512	Jul 8 09:35	test/

Operating System Concepts – 8th Edition 10.41 Silberschatz, Galvin and Gagne ©2009

## Access Lists and Groups

- Mode of access: read, write, execute
- Three classes of users
  - a) owner access 7 ⇒ RWX 1 1 1
  - b) group access 6 ⇒ RWX 1 1 0
  - c) public access 1 ⇒ RWX 0 0 1
- Ask manager to create a group (unique name), say G, and add some users to the group.
- For a particular file (say game) or subdirectory, define an appropriate access.

```

graph TD
    owner --- chmod
    group --- chmod
    public --- chmod
    chmod --- 761
    761 --- game
    Attach[Attach a group to a file] --- chgrp
    chgrp --- G
    G --- game
  
```

Operating System Concepts – 8th Edition 10.39 Silberschatz, Galvin and Gagne ©2009

## End of Chapter 10

Operating System Concepts – 8th Edition Silberschatz, Galvin and Gagne ©2009