


✓ Congratulations! You passed!

Grade received 100% Latest Submission Grade 100% To pass 80% or higher

Go to next item

1.

1 / 1 point



If the model's cross validation error  $J_{cv}$  is much higher than the training error  $J_{train}$ , this is an indication that the model has...

- ☐ Low variance
- ☐ high bias
- ☐ Low bias
- ☒ high variance

Correct

## Bias/variance examples

Baseline performance	: 10.6%		10.6%		10.6%
Training error ( $J_{train}$ )	: 10.8%	0.2%	15.0%	4.4%	15.0%
Cross validation error ( $J_{cv}$ )	: 14.8%	4.0%	15.5%	0.5%	19.7%
		high variance	high bias	high bias	high variance

Which of these is the best way to determine whether your model has high bias (has underfit the training data)?

- ☐ See if the training error is high (above 15% or so)
- ☐ Compare the training error to the cross validation error.
- ☒ Compare the training error to the baseline level of performance
- ☐ See if the cross validation error is high compared to the baseline level of performance

✓ Correct

Correct. If comparing your model's training error to a baseline level of performance (such as human level performance, or performance of other well-established models), if your model's training error is much higher, then this is a sign that the model has high bias (has underfit).

3.

1 / 1 point

## Debugging a learning algorithm

You've implemented regularized linear regression on housing prices

$$J(\bar{w}, b) = \frac{1}{2m} \sum_{i=1}^m (f_{\bar{w}, b}(\bar{x}^{(i)}) - y^{(i)})^2 + \frac{\lambda}{2m} \sum_{j=1}^n w_j^2$$

But it makes unacceptably large errors in predictions. What do you try next?

- |  |   |                     |
|--|---|---------------------|
| → Get more training examples   |   | fixes high variance |
| → Try smaller sets of features $x, x^2, x^3, x^4, \dots$               |   | fixes high variance |
| → Try getting additional features                                      | ← | fixes high bias     |
| → Try adding polynomial features $(x_1^2, x_2^2, x_1 x_2, \text{etc})$ | ← | fixes high bias     |
| → Try decreasing $\lambda$   | ← | fixes high bias     |
| → Try increasing $\lambda$   | ← | fixes high variance |

You find that your algorithm has high bias. Which of these seem like good options for improving the algorithm's performance? Hint: two of these are correct.

- ☒ Decrease the regularization parameter  $\lambda$  (lambda)

✓ Correct

Correct. Decreasing regularization can help the model better fit the training data.

- ☒ Collect additional features or add polynomial features

✓ Correct

Correct. More features could potentially help the model better fit the training examples.

- ☐ Remove examples from the training set

- ☐ Collect more training examples

4.

1 / 1 point

You find that your algorithm has a training error of 2%, and a cross validation error of 20% (much higher than the training error). Based on the conclusion you would draw about whether the algorithm has a high bias or high variance problem, which of these seem like good options for improving the algorithm's performance? Hint: two of these are correct.

- ☐ Decrease the regularization parameter  $\lambda$

- ☒ Collect more training data

✓ Correct

Yes, the model appears to have high variance (overfit), and collecting more training examples would help reduce high variance.

- ☐ Reduce the training set size

- ☒ Increase the regularization parameter  $\lambda$

✓ Correct

Yes, the model appears to have high variance (overfit), and increasing regularization would help reduce high variance.