

✓ Congratulations! You passed!

Grade received 87.50% Latest Submission Grade 87.50% To pass 80% or higher

[Go to next item](#)

1. Which of the following is *true* about training your model using data parallelism technique? Check all that are true.

1 / 1 point

- ☒ The full data set is split up and subsets of the data are stored across multiple machines

✓ **Correct**

Correct! Data parallelism is meant to improve efficiency by not having to store or process all of the data on the same machine.

- ☐ The same model architectures are used on different machines, and each machine processes the entire data set.

- ☐ All of the data is on 1 master machine, and copies of the data are then distributed to machines having different model architectures based on their capacity of processing the data.

- ☒ Weights from different machines are aggregated and updated into a single model.

✓ **Correct**

Correct! All the learnings from training on multiple machines should be used to update a single model.

2. In TensorFlow version 2, `tf.distribute.Strategy` class supports _____. Check all that apply.

1 / 1 point

☒ Graph Mode

✓ **Correct**
Correct!

☒ Eager Mode

✓ **Correct**
Correct!

3. Which of the following are *true* of both `MirroredStrategy` and `TPU Strategy`? Check all that are *true*.

0.75 / 1 point

☐ Uses multiple machines

☒ Variables are synchronized (mirrored) across each replica of the model

✓ **Correct**
Correct! Variables are mirrored across the copies of the model.

☐ Uses a single machine

☒ The same model is replicated on each core.

✓ **Correct**
Correct! Both of these strategies use multiple cores on the same machine (either GPU for `MirroredStrategy` or TPU for `TPU strategy`)

You didn't select all the correct answers

4. To modify training code to work with `Mirrored Strategy`, which of the following should we do? Choose all that apply.

0.5 / 1 point

☐ Adjust the batch size to equal the batch size per replica times the number of replicas

☒ Put code that creates the model object inside the scope of `"with strategy.scope()"`.

✓ **Correct**
Correct: the model creation code should be written within the scope of the strategy.

☐ Put the code that creates, compiles and fits the model inside the scope of `"with strategy.scope()"`.

☒ Increase the batch size as long as the number is 2^n (e.g. 64, 128, 256 etc).

✗ **This should not be selected**
Incorrect! Since the batch size will now be split among the replicas, the batch size should be evenly divisible by the number of replicas.

5. To modify training code to work with distributed data, which of the following should we do? Choose all that apply.

1 / 1 point

☒ Use *strategy.reduce* to aggregate the losses across the replicas.

☒ **Correct**

Correct! After the replicas all train, update their weights, and return their losses, their losses are aggregated using *strategy.reduce*

☒ Use *strategy.run* to run the code that updates the model weights (calculating loss, calculating the gradients, and applying the gradients).

☒ **Correct**

Correct! Use *strategy.run* and pass in a function that contains the code which updates the model weights and returns the calculated loss.

☐ Replace the code that updates the model weights (calculating loss, calculating gradients, and applying the gradients) so that each training step handles all replicas at once.

☒ Use *strategy.experimental_distribute_dataset* to convert training and test sets into distributed datasets.

☒ **Correct**

Correct!

6. To use the TPU strategy, there are some steps that you'll take before running the training code. Please think about which line of code implements each step and choose the set of code that performs these steps in this order.

1 / 1 point

- 1 Get the TPU address
- 2 Find the TPU cluster
- 3 Connect to the TPU cluster
- 4 Initialize the TPU cluster
- 5 Create your TPU strategy



```
1 tpu_address = 'grpc://' + os.environ['COLAB_TPU_ADDR']
2 tpu = tf.distribute.cluster_resolver.TPUClusterResolver(tpu_address)
3 tf.config.experimental_connect_to_cluster(tpu)
4 tf.tpu.experimental.initialize_tpu_system(tpu)
5 strategy = tf.distribute.experimental.MirroredStrategy(tpu)
```



```
1 tpu_address = 'grpc://' + os.environ['COLAB_TPU_ADDR']
2 tpu = tf.config.experimental_connect_to_cluster(tpu_address)
3 tf.distribute.cluster_resolver.TPUClusterResolver(tpu_address)
4 tf.tpu.experimental.initialize_tpu_system(tpu)
5 strategy = tf.distribute.experimental.TPUStrategy(tpu)
```



```
1 tpu_address = 'grpc://' + os.environ['COLAB_TPU_ADDR']
2 tpu = tf.distribute.cluster_resolver.TPUClusterResolver(tpu_address)
3 tf.config.experimental_connect_to_cluster(tpu)
4 tf.tpu.experimental.initialize_tpu_system(tpu)
5 strategy = tf.distribute.experimental.TPUStrategy(tpu)
```



```
1 strategy = tf.distribute.experimental.TPUStrategy(tpu)
2 tpu_address = 'grpc://' + os.environ['COLAB_TPU_ADDR']
3 tf.distribute.cluster_resolver.TPUClusterResolver(tpu_address)
4 tf.config.experimental_connect_to_cluster(tpu)
5 tf.tpu.experimental.initialize_tpu_system(tpu)
```



Correct

Correct!