


UMassAmherst

Manning College of Information
& Computer Sciences

Programming Methodology

Lab 6: Property-Based Testing

Wednesday, October 9, 2023



Property-Based Testing

Used when a problem has **more than one** right answer

Steps to Property-Based Testing:

1. Start with a valid input to your problem
2. Run the algorithm on that input
3. Check that the result has all necessary characteristics

Ex: Given a set of numbers $x = \{1, 2, \dots, N-1, N\}$, generate a random subset of x .


What are the properties of a correct output y to this problem?

1. The number of elements in y must be less than or equal to N .
2. Every number in y must exist in x .
3. There must be no duplicates in y .

Oracle Functions

UMassAmherst

Manning College of Information
& Computer Sciences



What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  
}
```

What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
    let n = 100;  
  
}
```

What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  let n = 100;  
  for(let N = 0; N < n; ++N){  
  
  }  
}
```

What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  let n = 100;  
  for(let N = 0; N < n; ++N){  
    let x = arrayFrom1ToN(N); // x is {1,2,...,N-1,N}  
  
  }  
}
```


What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  let n = 100;  
  for(let N = 0; N < n; ++N){  
    let x = arrayFrom1ToN(N); // x is {1,2,...,N-1,N}  
    let y = subsetFunc(x);  
  
  }  
}
```

What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  let n = 100;  
  for(let N = 0; N < n; ++N){  
    let x = arrayFrom1ToN(N); // x is {1,2,...,N-1,N}  
    let y = subsetFunc(x);  
    test('length of y less than or equal to N', function(){  
      assert(y.length <= N);  
    })  
  }  
}
```

What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  let n = 100;  
  for(let N = 0; N < n; ++N){  
    let x = arrayFrom1ToN(N); // x is {1,2,...,N-1,N}  
    let y = subsetFunc(x);  
    test(`length of y less than or equal to N`, function(){  
      assert(y.length <= N);  
    })  
    test(`all elements in y are in x`, function(){  
      assert(y.every(d => x.includes(d)));  
    })  
  }  
}
```

What would an oracle function for the subset function look like?

```
function oracle(subsetFunc) {  
  let n = 100;  
  for(let N = 0; N < n; ++N){  
    let x = arrayFrom1ToN(N); // x is {1,2,...,N-1,N}  
    let y = subsetFunc(x);  
    test('length of y less than or equal to N', function(){  
      assert(y.length <= N);  
    })  
    test('all elements in y are in x', function(){  
      assert(y.every(d => x.includes(d)));  
    })  
    test('y does not contain duplicates', function(){  
      assert(y.every(d => (y.indexOf(d) === y.lastIndexOf(d))));  
    })  
  }  
}
```

Exercise: Permutations

A function **genArray**(n : number): number[][] is supposed to generate an $n \times n$ array of numbers such that each row and column is a permutation of the numbers from 0 to $n-1$. Assume n is nonnegative.

Write an oracle that accepts the function genArray as input.

Use higher-order functions when appropriate. Try to write your implementation in $O(n^2)$.

Solution: Permutations

Write an oracle that accepts the function `genArray` as input.

```
function oracle(genArray) {  
    let n = Math.floor(Math.random()*1000);  
  
}
```

Solution: Permutations

Write an oracle that accepts the function genArray as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  
}
```

Solution: Permutations

Write an oracle that accepts the function genArray as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  
}
```


Solution: Permutations

Write an oracle that accepts the function genArray as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
  
  }  
  
}
```

Solution: Permutations

Write an oracle that accepts the function genArray as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
    assert(p.length === n, 'length is n');  
  }  
  
}
```

Solution: Permutations


Write an oracle that accepts the function genArray as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
    assert(p.length === n, 'length is n');  
    assert(p.every(valid), 'valid numbers');  
  }  
}
```

Solution: Permutations

Write an oracle that accepts the function `genArray` as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
    assert(p.length === n, 'length is n');  
    assert(p.every(valid), 'valid numbers');  
    const f = Array(n).fill(1);  
    assert(p.every(e => --f[e] === 0), 'no duplicates');  
  }  
}
```



Note: We're checking for duplicates in a single linear scan which takes $O(n)$ time.
This approach works for $n = 0$ and an empty array.

Solution: Permutations


Write an oracle that accepts the function genArray as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
    assert(p.length === n, 'length is n');  
    assert(p.every(valid), 'valid numbers');  
    const f = Array(n).fill(1);  
    assert(p.every(e => --f[e] === 0), 'no duplicates');  
  }  
  assert(a.length === n, 'array has n rows');  
}
```

Solution: Permutations

Write an oracle that accepts the function `genArray` as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
    assert(p.length === n, 'length is n');  
    assert(p.every(valid), 'valid numbers');  
    const f = Array(n).fill(1);  
    assert(p.every(e => --f[e] === 0), 'no duplicates');  
  }  
  assert(a.length === n, 'array has n rows');  
  a.forEach(isPerm); // each row is a permutation  
}
```




`a` is length `n`, and we call `isPerm` (an $O(n)$ function) for each element of `a`. This will take $O(n^2)$ time

Solution: Permutations

Write an oracle that accepts the function `genArray` as input.

```
function oracle(genArray) {  
  let n = Math.floor(Math.random()*1000);  
  let a = genArray(n);  
  const valid = x => x % 1 === 0 && 0 <= x && x < n;  
  function isPerm(p) {  
    assert(p.length === n, 'length is n');  
    assert(p.every(valid), 'valid numbers');  
    const f = Array(n).fill(1);  
    assert(p.every(e => --f[e] === 0), 'no duplicates');  
  }  
  assert(a.length === n, 'array has n rows');  
  a.forEach(isPerm); // each row is a permutation  
  for (let k = 0; k < n; ++k) { isPerm(a.map(r => r[k])); } // each column is a permutation  
}
```

Again, this will take $O(n^2)$ time



Note: A different approach, where we check directly that every number from 0 to $n - 1$ is included requires a linear scan for each number. That would be $O(n^2)$ per row/column and $O(n^3)$ overall. Do not do this!

Review Exam Questions

With the left over time we'll go over exam questions that you all found difficult.

Suggestion: Q4 or Q6, but we can go over any you want.

Midterm 1 - Q4

Write a function Q4 trackTemp(val: number): (diff: number) => [temp: number, days: number] that takes as argument the noon temperature on day 0 and returns a closure that can be called repeatedly. A call represents a new day, with a change in the noon temperature by an amount diff (positive, negative or zero) from the day before. The closure should return a pair of numbers: the noon temperature on the current day, and the number of consecutive days (≥ 1) that have passed without the temperature change diff having switched sign (zero is not a sign switch).

```
function trackTemp(val: number): (diff: number) => [temp: number, days: number] {  
  let days = 0, lastS = 0;  
  return diff => {  
    if (lastS * diff < 0) days = 0;           // sign change  
    if (diff !== 0) lastS = diff;           // try to make lastS <> 0, or keep it  
    return [val+=diff, ++days];  
  }  
}
```

What are some relevant test scenarios?

Explain input, output, their purpose and what behavior they are testing.

Midterm 1 - Q6

An array represents employee wage increases in the years since their union was founded. There is one entry per year, representing the increase from the previous year as a ratio (assumed > 1). The first array entry is the increase in the year following the founding year. Write a function `calcIncrease(byYear: number[]): ((wage: number) => number)[]` that takes such an array and returns an array of closures, with the same length. When called with a wage amount for the founding year, the closure for each year will return the adjusted wage in that year, after all increases. Use `reduce`, no loops. Avoid needless repeated computations.

```
type numFun = (x: number) => number

function calcIncrease(byYear: number[]): numFun[] {
  const res: numFun[] = [];
  byYear.reduce((acc, rate) => {
    acc *= rate;
    res.push(x => x * acc);
    return acc;
  }, 1);
  return res;
}
```

Exercise 2: OOP

Define an iterator class over an array.

Define a class Polygon (defined by an array of points in 2D) which has a `makeIterator()` method for its vertices.

Extend the class to `CenteredPolygon` which has a method to compute its center. The center of weight has the average of the vertex coordinates.

```
class ArrayIterator<T> implements IterableIterator<T> {.....}
```

```
class Polygon {.....}
```

```
class CenteredPolygon extends Polygon {.....}
```

Exercise 2: Solution

```
class ArrayIterator<T> implements IterableIterator<T> {
    private array: T[];
    private index = 0;
    constructor(private array: T[]) {this.array = array}
    public next(): IteratorResult<T> {
        if (this.index < this.array.length) {
            return this.array[this.index++];
        } else {
            return null;
        }
    }
}
```

```
class Polygon {
    private vertices: [number,number][];
    constructor(private vertices:[number, number][[]]) {
        this.vertices = vertices;
    }

    public makeIterator(): IterableIterator<number[]>
    {
        return new ArrayIterator<number[]>(this.vertices);
    }
}
```

```
class CenteredPolygon extends Polygon {
    public Center(): number[] {

        const numVertices = this.vertices.length;

        let x = 0;
        let y = 0;
        const iterator = this.makeIterator();
        let current = iterator.next();

        while (current !== null) {
            x += current[0];
            y += current[1];
            current = iterator.next();
        }

        return [x / numVertices, y / numVertices];
    }
}
```

Exercise 2: Solution 2

```
interface Iterator<T> {  
  next(): { value: T, done: boolean };  
}
```

```
class Polygon {  
  private vertices:[number, number][];  
  
  constructor(vertices:[number, number][[]]) {  
    this.vertices = vertices;  
  }  
  
  makeIterator(): Iterator<number[]> {  
    let index = 0;  
    const vertices = this.vertices;  
  
    return {  
      next() {  
        if (index < vertices.length) {  
          return { value: vertices[index++], done: false };  
        } else {  
          return { value: null, done: true };  
        }  
      }  
    };  
  }  
}
```

```
class CenteredPolygon extends Polygon {  
  private readonly sides: number;  
  
  constructor(vertices: number[][][]) {  
    super(vertices);  
    this.sides = vertices.length;  
  }  
  
  const numVertices = this.vertices.length;  
  center(): number[] {  
    let x = 0;  
    let y = 0;  
    const iterator = this.makeIterator();  
    let current = iterator.next().value;  
  
    while (current !== null) {  
      x += current[0];  
      y += current[1];  
      current = iterator.next().value;  
    }  
  
    return [x / this.sides, y / this.sides];  
  }  
}
```

Exercise 2: Solution 3

```
class ArrayIterator<T> {  
  private arr: T[];  
  private idx: number;  
  constructor(a: T[]) { this.arr = a; this.idx = -1;  
}  
  
  next(): T | null {  
    return ++this.idx < this.arr.length ?  
      this.arr[this.idx] : null;  
  }  
}
```

```
class Polygon {  
  private vertices: [number,number][];  
  constructor(vertices: [number,number][]) {  
    this.vertices = vertices;  
  }  
  
  makeIterator() {  
    return new ArrayIterator(this.vertices);  
  }  
}
```

```
class CenteredPolygon extends Polygon {  
  center() {  
    const it = this.makeIterator();  
    let xs = 0, ys = 0, cnt = 0;  
    for (let v: [number, number] | null;  
      (v = it.next()) != null; ++cnt) {  
      xs += v[0]; ys += v[1];  
    }  
    return [xs/cnt, ys/cnt];  
  }  
}
```