

UMassAmherst

Manning College of Information
& Computer Sciences

Programming Methodology

Lab 4

Wednesday, September 25, 2024



Weekly Lab Agenda

- Go over reminders/goals
- Review past material
- Work in groups of 2-3 to solve a few exercises
 - Please sit with your group from last week.
- Discussion leaders will walk around and answer questions
- Solutions to exercises will be reviewed as a class
- Attendance taken at the end

Reminders

- Homework 3 is due tonight at 11:59pm
 - Come to office hours for help!
- HW4 will not be released until after the exam.
- Midterm 1 is in one week on October 2nd
 - Start studying early. See past exams and solutions on Canvas.
- TA/UCA Review Session: Sunday (9/29) 7-9 pm, ILC S110
 - Yes, this will be recorded to echo360
- SI Review Session: Monday (9/30) 7-9pm, Thompson 102

Today's Goals

- Mental models
- Closures

Exercise 1: Closures

- Write a function that takes as argument an array of Boolean functions, all with the same argument type T and returns a Boolean closure with an argument x of type T. The closure should return true if and only if more than half of the functions in the array return true for x.
- Use reduce for implementation.

```
function mostTrue<T>(
  funarr: ((arg: T) => boolean)[]
): (arg: T) => boolean {
  // TODO
}
```

Exercise 2

For each line of code: If a value is printed, state the value and describe how it was obtained, including any values used for the result. Otherwise, state what objects (including arrays, not closures or functions) are created (if any), what values are modified and which objects are no longer referenced (if any).

```
1 const mkList = (init, f) => ({  
2   next: () => mkList(f(init), f),  
3   value: () => init  
4 });  
5 let cnt = 0;  
6 const a = [mkList(0, x => x + 1), mkList(cnt, _ => ++cnt)];  
7 const b = a.map(lst => lst.next().next());  
8 console.log(b[1].value());
```

Exercise 3: More closures

- Write a function with no arguments that returns a closure with no arguments. When called the n th time ($n \geq 1$), the closure should return the n th approximation for the number e : $1 + 1/1! + 1/2! + \dots + 1/n!$
- Avoid needless recomputation in the factorial and in the sum.
- Example outputs: 2, 2.5, 2.666..., 2.70833..., 2.7166..., 2.718055..., etc.