



UMassAmherst

Manning College of Information
& Computer Sciences

Lab 1: HOFs and Type Signatures

Wednesday, September 3rd, 2025

Weekly Lab Agenda

- Go over reminders/goals
- Review past material
- Work in groups of 2-3 to solve a few exercises
 - Discussion leaders will assign groups today
 - Groups will be remade every third lab
- Discussion leaders will walk around and answer questions
- Solutions to exercises will be reviewed as a class
- Attendance taken at the end

Reminders

- Please set up your development environment as soon as possible
- Homework 1 is due this Sunday (9/7) at 11:59pm
- If you need to miss lab and have a valid reason according to the syllabus (medical, other personal) please fill out the questionnaire on Canvas before the start time of your lab.
 - Waking up late, bus was late are NOT valid reasons to miss lab.
- Submit what you have at the end of lab to Gradescope. If you miss many submissions to Gradescope, we may penalize your lab grade.

Lab Groups

- You will now be assigned into your lab groups
- Please sit with your group each week

- Take the next 5 minutes to talk to each other
- Introduce yourselves!
 - Name, pronouns, major
 - Favorite household appliance
 - What was one fun thing you did over break?

Today's Goals

- Set up coding environment
- Practice both higher-order functions and some TypeScript
- Walk out with some working code

Writing and Running TypeScript

- Download the starter code from GitHub (linked on Canvas).
- Unzip the folder and open it in VSCode.
- Run *npm install* in the same directory as the package.json folder.
- When you are ready to submit, run *npm run build:submission*
- Upload the resulting zip file to the corresponding assignment on gradescope.
- Your lab leaders will walk you through this process for the first lab!

Review of map

```
// Sample Implementation
// `.map` is a method on Arrays
function map<T, U>(
  a: T[],
  f: (x: T) => U
): U[] {
  const result: U[] = [];
  for (let i = 0; i < a.length; ++i) {
    result.push(f(a[i]));
  }
  return result;
}
```

```
function double(x: number): number {
  return 2 * x;
}

const array = [1,2,3,4,5];
const newArray = array.map(double);
```

What is `newArray` ?

Reason about the code before typing and running it.

Review of filter

```
// Sample Implementation
// `.filter` is a method on Arrays
function filter<T>(
  a: T[],
  f: (x: T) => boolean
): T[] {
  const result: T[] = [];
  for (let i = 0; i < a.length; ++i) {
    const x = a[i];
    if (f(x)) {
      result.push(x);
    }
  }
  return result;
}
```

```
function isEven(x: number): boolean {
  return x % 2 === 0;
}
const array = [1,2,3,4,5];
const newArray = array.filter(isEven);
```

What is `newArray` ?

Reason about the code before typing and running it.

Programming Exercise 1

Write a function that takes an array of number arrays, and returns an array of number arrays where all negative values have been removed. Again, don't use any loops or recursion.

```
[[1,-2,3], [0], [0,1,2,3], []]
```



```
[[1,3],[0], [0,1,2,3], []]
```

A number array is typed as `number[]`, an array of those is `number[][]`

Review of Type Signatures

We can infer types based on the operations done on values

```
// f(x: number, y: number): number    or   f: (number, number) => number
function f(x, y) {
  return x + (2*y);
  // product with y: y is number, x and result is number
}
```

Sometimes, we have several possibilities

```
// g: (number, number) => number    or    g: (string, string) => string
function g(x, y) { return x + y; } // + can be string concatenation

// h(a: string): boolean    or    h<T>(a: T[]): boolean
function h(a) { return a.length > 5; } // both strings & arrays have length
```

The array could have any element type. We call T a **type variable**.
This lets us write **generic functions**.

Exercise 2: Type Signatures

(a) What are the type signatures of `f` and `g`?

```
const a = [1,2,3,4];  
const b = a.filter(f);  
const c = b.map(g);
```

(b) What is the type signature of `h`?

```
const h = (a, g) => a.map(g).filter(g);
```

Remember:

```
map<A,B>(arr: A[], f: (x: A) => B): B[]  
filter<T>(arr: T[], f: (x: T) => boolean): T[]
```

For part (b), start by considering an arbitrary element type for the array, and continue to derive types for the map and filter callback functions.

Final Thoughts

- Think carefully about your approach before starting to code
- Start small and test often
- Try to make use of as much of your previous work as possible
- A lot of material all at once, come to office hours if you are confused
 - We would love to see you there! 😊
- It is okay if some of us take longer or don't finish before lab ends, keep working at it
 - Try not to get discouraged
- Starting the homework today is not required, but try to get into the habit of reading the instructions as soon as they are released