

UMassAmherst

Manning College of Information
& Computer Sciences

Programming Methodology

Lab 4

Wednesday, February 28, 2023



Weekly Lab Agenda

- Go over reminders/goals
- Review past material
- Work in groups of 2-3 to solve a few exercises
 - Please sit with your group from last week.
- Discussion leaders will walk around and answer questions
- Solutions to exercises will be reviewed as a class
- Attendance taken at the end

A View of the Week Ahead

FRIDAY March 1	SATURDAY March 2	SUNDAY March 3	MONDAY March 4	TUESDAY March 5	WEDNESDAY March 6	THURSDAY March 7
	HW2 is due	Exam Review Session from 7-9pm @ILC Room ILC S140			Exam 7-9pm @ILC More details to follow	HW3 is Released

Reminders

- Homework 3 is due Friday at 11:59pm
 - Come to office hours for help!
- HW4 will not be released until after the exam.
- Midterm 1 is in one week on March 6th
 - Start studying early
- Midterm Review Session
 - Sunday (3/4) 7-9 PM @ILC (Room TBD)
 - Will go over Fall 22 Midterm 1 (posted on Canvas)

Today's Goals

- Mental models
- Closures

Exercise 1: Closures

- Write a function with no arguments that returns a closure with no arguments. When called the n th time ($n \geq 1$), the closure should return the n th approximation for the number e : $1 + 1/1! + 1/2! + \dots + 1/n!$
- Avoid needless recomputation in the factorial and in the sum.
- Example outputs: 2, 2.5, 2.666..., 2.70833..., 2.7166..., 2.718055..., etc.

Exercise 2: More Closures

- Write a function that takes as argument an array of Boolean functions, all with the same argument type T and returns a Boolean closure with an argument x of type T. The closure should return true if and only if more than half of the functions in the array return true for x.
- Use reduce for implementation.

```
function mostTrue<T>(
  funarr: ((arg: T) => boolean)[]
): (arg: T) => boolean {
  // TODO
}
```

Exercise 3

For each line of code: If a value is printed, state the value and describe how it was obtained, including any values used for the result. Otherwise, state what objects (including arrays, not closures or functions) are created (if any), what values are modified and which objects are no longer referenced (if any).

```
1 const mkList = (init, f) => ({
2   next: () => mkList(f(init), f),
3   value: () => init
4 });
5 let cnt = 0;
6 const a = [mkList(0, x => x + 1), mkList(cnt, _ => ++cnt)];
7 const b = a.map(lst => lst.next().next());
8 console.log(b[1].value());
```