




UMassAmherst

Manning College of Information
& Computer Sciences

Programming Methodology

Lab 2: Type Signatures and Testing with Jest

Wednesday September 16, 2026

Weekly Lab Agenda

- Go over reminders/goals
- Review recent material
- Work in groups of 2-3 to solve a few exercises
 - Please sit with your group from last week.
- Discussion leaders will walk around and answer questions.
- Solutions to exercises will be reviewed as a class.

Reminders

- Homework 2 is due next Monday (9/21) at 11:59pm.
 - Come to office hours for help!
- If you need to miss lab for a valid and documented reason:
 - Fill out the excusal form on Canvas before the lab.
 - Waking up late or the bus being late are not excusable reasons.
- Submit what you have at the end of lab to Gradescope.
 - Lab submissions are due at 6:00 pm.
 - The submission counts towards your lab grade.

Announcement

- Time and location of final have been updated on SPIRE
- **Monday, December 21st at 3:30 PM in Totman Gym**
- Check SPIRE the day of the exam in case of last minute changes.

Today's Goals

- Practice writing correct type signatures
- Practice writing tests with the Jest framework

Review of Type Signatures

We can infer the types of values based on the operations applied to them.

```
function f(x, y) {  
  return x + (2 * y);  
}
```

The `*` operator performs multiplication on numbers.

- The signature of **f** must be **f(x: number, y: number): number**
- Sometimes shortened to **f: (number, number) => number**

Review of Type Signatures

Sometimes, we have several possibilities.

```
function g(x, y) {  
    return x + y;  
}
```

+ could be addition or
string concatenation

```
g: (number, number) => number  
or
```

```
g: (string, string) => string
```

```
function h(a) {  
    return a.length > 5;  
}
```

strings and arrays both have the
length property

```
h(a: string): boolean  
or
```

```
h<T>(a: T[]): boolean
```

Review of Type Signatures

When a variable has multiple possible types, we can use a **type parameter** like **T**.

- This lets us write **generic functions**.

Type parameters can be used to dictate which types must "agree"

- For example, **filter** works with the following types
 - An array of type **T[]**
 - A callback of type **T => boolean**
 - A return type **T[]**

Anywhere you see **T**, the types must be the same.

Exercise 1: Type Signatures

(a) What are the type signatures of **f** and **g**?

```
const a = [1,2,3,4];  
const b = a.filter(f);  
const c = b.map(g);
```

(b) Initialize variables **a**, **f**, and **g**, such that the code would run without error. The input and output types of **f** should be different from each other.

```
const h = (a, f, g) => a.map(f).filter(g);
```

Remember:

```
map<A,B>(arr: A[], f: (x: A) => B): B[]  
filter<T>(arr: T[], f: (x: T) => boolean): T[]
```

Review : Jest

Jest is the **testing framework** that we use in this course.

```
// each function has a 'describe' block
describe("func", () => {
  // a 'describe' block can have multiple 'it' blocks
  // each 'it' block represents a test case for the function
  it("should do something", () => {
    ...
  });
  ...
});
```

Review : Jest

In addition to global functions, Jest provides robust testing utilities like **expect**.

```
describe("func", () => {  
  it("should do something", () => {  
    ...  
    // expect can be chained with 'matchers'  
    expect(a).toEqual(b);  
    expect(f).toThrow(e);  
  }); // see jestjs.io/docs/expect for more  
  ...  
});
```

Exercise 2: Testing with Jest

You are given a function **rotateRight**`<T>(arr: T[], k: number): T[]` that returns a new array containing the elements of **arr** rotated to the right by **k** steps.

- The function must not mutate the input array.
- **k** must be a non-negative integer.
- Examples:
 - **rotateRight**`([1,2,3,4], 1)` returns `[4,1,2,3]`
 - **rotateRight**`([1,2,3,4], 4)` returns `[1,2,3,4]`

Write comprehensive tests for **rotateRight** using Jest.

Recap

	Type Signatures	Testing with Jest
Purpose	Describe the input and output types of a function	Check whether code behaves correctly
Core idea	Infer types from how values are used	Test expected behavior systematically
Key concepts	Input/Output types, Generics (T) map vs. filter signatures	describe, it, expect matchers
What to check	<i>Do the types agree throughout the expression?</i>	Normal cases, edge cases, errors, mutation
Takeaway	Follow the types through the code	Test more than just the happy path