



# 190F Foundations of Data Science

Spring 2020

## Lecture 3

---


Expressions  
& Building Tables

# **Announcements**

## Driving lesson

● Middle East and north Africa ● Europe ● Sub-Saharan Africa ● Other

Road deaths per 100,000 people, 2017



Sources: World Bank; IHME

\*Purchasing-power parity

# Arithmetic

# Arithmetic Operators

---

Operation	Operator	Example	Value
Addition	+	$2 + 3$	5
Subtraction	-	$2 - 3$	-1
Multiplication	*	$2 * 3$	6
Division	/	$7 / 3$	2.66667
Remainder	%	$7 \% 3$	1
Exponentiation	**	$2 ** 0.5$	1.41421

---

(Demo)

# Ints and Floats

---

Python has two real number types

- `int`: an integer of any size
- `float`: a number with an optional fractional part

An `int` never has a decimal point; a **`float`** always does

A `float` might be printed using scientific notation

Three limitations of float values:

- They have limited size (but the limit is huge)
  - They have limited precision of 15-16 decimal places
  - After arithmetic, the final few decimal places can be wrong
-

# Arithmetic Question

Rank the results of the following expressions in order from least to greatest

A.3 \* 10 \*\* 10

A. 300000000000

B.  $10 * 3 ** 10$

B. 590490

C.  $(10 * 3) ** 10$

C. 5904900000000000

D. 10 / 3 / 10

D.0.33333333333337

E.10 / (3 / 10)

E.33.33333333333336

# Strings



# Text and Strings

---

A string value is a snippet of text of any length

- `'a'`
- `'word'`
- `"there can be 2 sentences. Here's the second!"`

Strings that contain numbers can be converted to numbers

- `int('12')`
- `float('1.2')`

Any value can be converted to a string

- `str(5)`

(Demo)

---

# Discussion Question

---

Assume you have run the following statements

```
x = 3
```

```
y = '4'
```

```
z = '5.6'
```

What's the source of the error in each example?

A. `x + y`

B. `x + int(y + z)`

C. `str(x) + int(y)`

D. `str(x, y) + z`

---


# Exponential Growth

# Ebola Epidemic, Sept. 2014

## A Frightening Curve: How Fast Is The Ebola Outbreak Growing?

"It's spreading and growing *exponentially*," President Obama said.

"This is a disease outbreak that is advancing in an exponential fashion," said Dr. David Nabarro, who is heading the U.N.'s effort against Ebola.



<http://www.npr.org/sections/goatsandsoda/2014/09/18/3493416>

[06/why-the-math-of-the-ebola-epidemic-is-so-scary](#)

Source: [Columbia Prediction of Infectious Diseases](#), World Health Organization

# Growth Rate

---

- The rate of increase per unit time
- After one time unit, a quantity  $x$  growing at rate  $g$  will be

$$x * (1 + g)$$

- After  $t$  time units, a quantity  $x$  growing at rate  $g$  will be

$$x * (1 + g) ** t$$

- If **after** and **before** are measurements of the same quantity taken  $t$  time units apart, then the *growth rate* is

$$(\text{after}/\text{before}) ** (1/t) - 1$$

# Arrays

# Arrays

---

An array contains a sequence of values

- All elements of an array should have the same type
- Arithmetic is applied to each element individually
- When two arrays are added, they must have the same size; corresponding elements are added in the result
- A column of a table is an array

(Demo)

---

# Ranges



# Ranges

---

A range is an array of consecutive numbers

- `np.arange(end)`:  
An array of increasing integers from 0 up to `end`
- `np.arange(start, end)`:  
An array of increasing integers from `start` up to `end`
- `np.arange(start, end, step)`:  
A range with `step` between consecutive values

The range always includes `start` but excludes `end`

---

# Tables Review

# Ways to create a table

---

- `Table.read_table(filename)` - reads a table from a spreadsheet
- `Table()` - an empty table
- and...

# Arrays → Tables

---

- `Table().with_column(label, data)` - creates a table with a single column; `data` is an array
  - `Table().with_columns(label1, data1, ...)` - creates a table, with an array of data for each column
-

# Table Methods

---

- Creating and extending tables:
    - `Table().with_columns` and `Table.read_table`
  - Finding the size: `num_rows` and `num_columns`
  - Referring to columns: labels, relabeling, and indices
    - `labels` and `reabeled`; column indices start at 0
  - Accessing data in a column
    - `column` takes a label or index and returns an array
  - Using array methods to work with data in columns
    - `item`, `sum`, `min`, `max`, and so on
  - Creating new tables containing some of the original columns:
    - `select`, `drop`
-

# Examples

---

The table `students` has columns `Name`, `ID`, and `Score`.  
Write one line of code that evaluates to:

a) A table consisting of only the column labeled `Name`

```
students.select('Name')
```

b) The largest score

```
students.column('Score').max()  
max(students.column('Score'))
```

---