#### **CMSC 471**

#### **Constraint Satisfaction Problems**







Instructor: KMA Solaiman

These slides were created by Dan Klein and Pieter Abbeel at UC Berkeley. [ai.berkeley.edu]


#### **Constraint Satisfaction Problems**

- Standard search problems:
  - State is a "black box": arbitrary data structure
  - Goal test can be any function over states
  - Successor function can also be anything
- Constraint satisfaction problems (CSPs):
  - A special subset of search problems
  - State is defined by variables  $X_i$  with values from a domain D (sometimes D depends on i)
  - Goal test is a set of constraints specifying allowable combinations of values for subsets of variables
- Simple example of a formal representation language
- Allows useful general-purpose algorithms with more power than standard search algorithms





### **CSP Examples**



#### **Example: Map Coloring**


- Variables: WA, NT, Q, NSW, V, SA, T
- Domains: D = {red, green, blue}
- Constraints: adjacent regions must have different colors


Implicit:  $WA \neq NT$ 

Explicit:  $(WA, NT) \in \{(red, green), (red, blue), \ldots\}$ 

Solutions are assignments satisfying all constraints, e.g.:

{WA=red, NT=green, Q=red, NSW=green, V=red, SA=blue, T=green}






# Solving CSPs




#### **Backtracking Search**

- Backtracking search is the basic uninformed algorithm for solving CSPs
- Idea 1: One variable at a time
  - Variable assignments are commutative, so fix ordering
  - I.e., [WA = red then NT = green] same as [NT = green then WA = red]
  - Only need to consider assignments to a single variable at each step
- Idea 2: Check constraints as you go
  - I.e. consider only values which do not conflict previous assignments
  - Might have to do some computation to check the constraint
  - "Incremental goal test"
- Depth-first search with these two improvements is called backtracking search (not the best name)



# **Backtracking Example**



#### Improving Backtracking

- General-purpose ideas give huge gains in speed
- Ordering:
  - Which variable should be assigned next?
  - In what order should its values be tried?
- Filtering: Can we detect inevitable failure early?
- Structure: Can we exploit the problem structure?



# Filtering




### Filtering




Keeping track of domains for unassigned variables and cross off bad options


- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment




- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment




- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment




- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment



- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment




- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment





- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment



#### Video of Demo Coloring – Backtracking with Forward Checking



 Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:





 Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:





NT and SA cannot both be blue!

 Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:





- NT and SA cannot both be blue!
- Why didn't we detect this yet?

 Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:






- NT and SA cannot both be blue!
- Why didn't we detect this yet?
- Constraint propagation: reason from constraint to constraint


























Delete from the tail!

An arc X → Y is consistent iff for every x in the tail there is some y in the head which could be assigned without violating a constraint



Delete from the tail!


Forward checking: Enforcing consistency of arcs pointing to each new assignment

A simple form of propagation makes sure all arcs are consistent:







A simple form of propagation makes sure all arcs are consistent:




A simple form of propagation makes sure all arcs are consistent:




A simple form of propagation makes sure all arcs are consistent:



A simple form of propagation makes sure all arcs are consistent:



A simple form of propagation makes sure all arcs are consistent:




A simple form of propagation makes sure all arcs are consistent:



# Arc Consistency of an Entire CSP


A simple form of propagation makes sure all arcs are consistent:



Remember: Delete from the tail!

#### Arc Consistency of an Entire CSP

A simple form of propagation makes sure all arcs are consistent:



- Important: If X loses a value, neighbors of X need to be rechecked!
- Arc consistency detects failure earlier than forward checking
- Can be run as a preprocessor or after each assignment
- What's the downside of enforcing arc consistency?

Remember: Delete from the tail!

## Enforcing Arc Consistency in a CSP

```
function AC-3(csp) returns the CSP, possibly with reduced domains
   inputs: csp, a binary CSP with variables \{X_1, X_2, \ldots, X_n\}
   local variables: queue, a queue of arcs, initially all the arcs in csp
   while queue is not empty do
      (X_i, X_i) \leftarrow \text{REMOVE-FIRST}(queue)
      if Remove-Inconsistent-Values(X_i, X_j) then
         for each X_k in Neighbors [X_i] do
            add (X_k, X_i) to queue
function Remove-Inconsistent-Values (X_i, X_i) returns true iff succeeds
   removed \leftarrow false
   for each x in Domain[X_i] do
      if no value y in DOMAIN[X<sub>i</sub>] allows (x,y) to satisfy the constraint X_i \leftrightarrow X_i
         then delete x from DOMAIN[X<sub>i</sub>]; removed \leftarrow true
   return removed
```

- Runtime: O(n²d³), can be reduced to O(n²d²)
- ... but detecting all possible future problems is NP-hard why?

Video of Demo Coloring – Backtracking with Forward Checking – Complex Graph




Video of Demo Coloring – Backtracking with Arc Consistency – Complex Graph



#### Limitations of Arc Consistency

- After enforcing arc consistency:
  - Can have one solution left
  - Can have multiple solutions left
  - Can have no solutions left (and not know it)




[Demo: coloring -- forward checking]

[Demo: coloring -- arc consistency]

#### Limitations of Arc Consistency

- After enforcing arc consistency:
  - Can have one solution left
  - Can have multiple solutions left
  - Can have no solutions left (and not know it)

• Arc consistency still runs inside a backtracking search!



What went wrong here?

[Demo: coloring -- forward checking]

[Demo: coloring -- arc consistency]

# K-Consistency




#### **K-Consistency**


- Increasing degrees of consistency
  - 1-Consistency (Node Consistency): Each single node's domain has a value which meets that node's unary constraints
  - 2-Consistency (Arc Consistency): For each pair of nodes, any consistent assignment to one can be extended to the other
  - K-Consistency: For each k nodes, any consistent assignment to k-1 can be extended to the k<sup>th</sup> node.

- Higher k more expensive to compute
- (You need to know the k=2 case: arc consistency)









# Ordering




- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain





- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain






- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain






- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain





- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain




Why min rather than max?

- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain




Why min rather than max?




- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain



- Why min rather than max?
- Also called "most constrained variable"
- "Fail-fast" ordering



- Value Ordering: Least Constraining Value
  - Given a choice of variable, choose the *least* constraining value
  - I.e., the one that rules out the fewest values in the remaining variables
  - Note that it may take some computation to determine this! (E.g., rerunning filtering)






- Value Ordering: Least Constraining Value
  - Given a choice of variable, choose the *least* constraining value
  - I.e., the one that rules out the fewest values in the remaining variables
  - Note that it may take some computation to determine this! (E.g., rerunning filtering)








- Value Ordering: Least Constraining Value
  - Given a choice of variable, choose the *least* constraining value
  - I.e., the one that rules out the fewest values in the remaining variables
  - Note that it may take some computation to determine this! (E.g., rerunning filtering)













- Value Ordering: Least Constraining Value
  - Given a choice of variable, choose the *least* constraining value
  - I.e., the one that rules out the fewest values in the remaining variables
  - Note that it may take some computation to determine this! (E.g., rerunning filtering)



Combining these ordering ideas makes
 1000 queens feasible





Demo: Coloring -- Backtracking + Forward Checking + Ordering