

PRINTABLE COMMAND CARD

One command per run. The application always shows the exact proposed command and asks for explicit approval before it runs anything. Quote questions that contain shell punctuation.

USE	WHAT IT DOES	COMMON START
<code>hm "question"</code> or <code>--query / -q</code>	Ask for terminal guidance; suggested commands still need review and approval.	<code>hm "show changed Git files"</code>
<code>--chat</code>	Open a bounded, interactive terminal conversation.	<code>hm --chat</code>
<code>--diagnose [text]</code>	Read an error, log file, or piped evidence and propose focused checks.	<code>hm --diagnose --file build.log</code>
<code>--script <request></code>	Create or revise a reviewable PowerShell script; it is never executed by this flow.	<code>hm --script "archive old logs" --output archive.ps1</code>
<code>--plan <goal></code>	Build a 1-8 step plan with a separate verification and approval for every step.	<code>hm --plan "prepare a release"</code>
<code>--plan --resume <id></code>	Continue an interrupted plan from its saved verification state.	<code>hm --plan --resume <id></code>
<code>--preview</code> <code>copy move rename delete</code>	Preview exact immediate file effects, sizes, and collisions before command review.	<code>hm --preview copy --file report.txt --output backup</code>
<code>--recipes [action]</code>	List, save, show, run, import, or export personal command recipes.	<code>hm --recipes</code>
<code>--setup</code>	Configure first-run and AI settings.	<code>hm --setup</code>
<code>--test-ai</code>	Check the configured AI connection with the localized test prompt.	<code>hm --test-ai</code>
<code>--costs</code>	Refresh pricing and show local usage and available organization costs.	<code>hm --costs</code>
<code>--status</code>	Show configuration and storage readiness.	<code>hm --status</code>
<code>--third-party</code>	List direct runtime packages, versions, and licenses.	<code>hm --third-party</code>
<code>--where / -where</code>	Show the running executable and its folder; offer a previewed location action.	<code>hm --where</code>
<code>--path install remove status</code>	Manage only this copy's directory in the persistent user PATH.	<code>hm --path install</code>
<code>--install-font</code>	Optionally run the JetBrainsMono Nerd Font helper through existing Oh My Posh.	<code>hm --install-font --dry-run</code>
<code>--help / -h / /?</code>	Show grouped command help.	<code>hm --help</code>
<code>--version / -v</code>	Show the About panel, platform, repository, and creator information.	<code>hm --version</code>
GLOBAL OPTIONS	--language / -l selects it, en, fr, de, es, or vi. --no-animation and --no-emoji simplify output. --yes / -y applies only to reviewed PATH or font operations. --dry-run applies only to --install-font.	
PORTABLE BY DESIGN	No installation is required. Extract the portable archive, add the folder containing hm to your user PATH, then open a new terminal. hm --path install can preview and add only the current executable folder.	

FIELD NOTES // THE NEW WORKFLOWS

Use these paths when you want more structure than a one-off terminal answer, without giving up command-by-command control.

1. DIAGNOSE EVIDENCE, NOT GUESSWORK

Give hm a concise error, a bounded log file, or piped output. It separates observations, probable causes, missing evidence, and a next check. Credential-shaped argument input is rejected; selected evidence is redacted before it is sent to the provider.

```
hm --diagnose --file build.log
```

2. DRAFT A POWERSHELL ARTIFACT

--script creates or revises a reviewable draft. You can inspect a line-by-line replacement diff, optionally approve parser-only validation, then save to a new file. It never evaluates the generated script and never overwrites an existing file.

```
hm --script "archive old logs with a report" --output archive-logs.ps1
```

3. PLAN, VERIFY, RESUME

--plan creates one to eight ordered steps. Each action and its separate, read-only verification command gets the normal risk review and its own approval. A failure, denial, timeout, or unexpected result pauses the plan; resume verifies before it considers replaying an interrupted action.

```
hm --plan "build, test, and package this project"
```

4. PREVIEW FILE EFFECTS

Preview copy, move, prefix rename, or delete with no mutation until individual command approval. It lists exact paths, byte counts, and collisions; it rejects recursion, links/reparse points, and overwrites. A changed source or newly occupied destination requires a new preview.

```
hm --preview rename --file ./logs --pattern '*.log' --prefix archived-
```

5. TURN A COMPLETED PLAN INTO A REUSABLE RECIPE

Recipes are local definitions, not stored authorization. Save only a fully completed and confirmed plan, or import a reviewed JSON definition. Running a recipe gathers its declared parameters and creates a new resumable plan with fresh per-command approvals. Use --recipes to list, then save/show/run/import/export as needed.

```
hm --recipes save project-check --from-plan
```

```
hm --recipes run project-check
```

SAFETY REMINDER | An AI answer is advice, not execution authority. Read the full local preview, approve only the displayed command, and keep secrets out of questions, logs, scripts, and command arguments.