First, install CCP.

Cody's Codex Plugin / Windows edition

BEFORE YOU START

Windows PC
Codex desktop + CLI
Python 3 available
as the python command
Cody on the same LAN

Client must support local plugins.



ZIP CONCEPT: the package includes CCP and a ready-made local marketplace.

1 Extract the ZIP

Extract Cody-CCP.zip to a permanent folder. Open the CCP folder inside it; keep all included files.

2 Register it with Codex

Open that CCP folder in Terminal, then run:

```
codex plugin marketplace add .
```

3 Install and enable

Restart the desktop app. Open Plugins, select the Cody CCP source, then install Cody's Codex Plugin. Start a new Codex chat with CCP enabled.

If Windows asks, allow Python on Private networks only.

Setup reference: OpenAI plugin packaging guide

NOTES

One code. Your PC.

Pair from the PC you want Cody to remember.

1 On Cody

Complete Wi-Fi setup. Continue to the Connect Codex screen. Keep its six-character code visible.



Illustration / example code

2 In your new Codex chat

With CCP enabled, send:

Pair my Cody using this code:

K7M4Q2

EXAMPLE ONLY
Use the code on Cody.

3 Confirm, then wait

After pairing is confirmed, tap Let's go on Cody. Leave Cody awake for the 10-second Idle interval.

Confirmed	→	Idle / 10 s	→	Find PC	→	Connected
SCREEN 13		SCREEN 16		SCREEN 14		SCREEN 15

Only the paired PC reconnects - even on a busy LAN.

Not connecting? Keep Codex + CCP running on the same private LAN. If the code expires, tap Retry and use the new code.

NOTES

Print A5 / 100% / two-sided / flip on long edge

Umberto Giacobbi | hello@umbertogiacobbi.biz
umbertogiacobbi.biz / 2026 / confidential

Startup: two saved decisions

Local Wi-Fi/IP first. Then the retained Codex pairing. Public Internet is not required.

1 / No saved Wi-Fi profile

A valid absent-profile observation opens 04 > 05 > 06 > 07 > 09. Debug may show 39 before 09. Continue: 10 > 36 > 11 (skin), then the Codex decision.

2 / Saved Wi-Fi; waiting for the network

42 / No connection keeps the profile while the Wi-Fi owner reconnects. Network setup reopens 04-09; Later returns to Idle. Invalid/stale data shows UNAVAILABLE.

3 / LAN ready; no saved Codex pairing

40 / Connect Codex? Yes starts the code on 12. No returns to 16 / Idle without a settings write or CCP request. The next boot may ask again.

4 / LAN ready; saved Codex pairing

Adopt the saved attempt and search on 14. Only authenticated READY enters 15. A retained identity alone never means the PC is connected.

Reopen setup from Cody

Hold the visible character still for 1.5 seconds. No button-based factory reset is added.

41 / Setup

Connect Codex opens a fresh display-code attempt. Network setup reopens 04-09. Left Back returns to Idle. Opening or leaving the menu erases no Wi-Fi, skin or pairing.

Keep the gesture deliberate

Available from stable Idle, PC search/connected and terminal CCP errors. Moving more than 12 px, a sample gap over 250 ms, rotation or a lifecycle interruption cancels the hold. Busy work and active provisioning are excluded; release before choosing.

PWR / existing policy

Single: standby/wake; active Debug defaults to screenshot countdown. Long release: standby. Debug double within 500 ms, or a continuous 3-second hold: restart preserving data.

BOOT / existing policy

Short: restore a dim/sleeping panel first, otherwise toggle fullscreen/status arcs. Hold 3 seconds: Debug restart; Release has no firmware reset action. Saved Wi-Fi and CCP survive restart.

CCP: current local installation

This checkout provides a local marketplace. The original ZIP leaflet remains a packaging concept.

1 / Register the checkout

Use this repository's .agents/plugins/marketplace.json. The catalog is Cody local plugins; the package is CCP - Cody's Codex Plugin. Keep the checkout in its current location.

2 / Install, enable, new chat

Open the repository installation link below in Codex desktop. Install and enable CCP, then start a new chat. Python 3 must be available as python. Codex starts the MCP script.

3 / Pair from Cody

At startup, choose Yes on 40; alternatively hold Cody and select Connect Codex on 41. Keep the six-character code on 12 visible. In the CCP-enabled chat, ask to pair Cody using that exact code.

4 / Confirm and reconnect

After authenticated completion, 13 > Let's go > 16 (10 active seconds) > 14 > 15. On a later boot with a valid saved link, go straight to authenticated search on 14. Keep Codex/CCP awake on the same LAN; screen 15 certifies CCP presence, not chat/task transport.

Open CCP installation in Codex

Errata and corrections

Revision date: 09 October 2026 / CODY-SETUP-20261009

Original analysis gap

The initial analysis omitted startup with Wi-Fi already configured but no saved Codex pairing, and did not define a reversible user entry to setup. This was an original analysis gap (buco di analisi iniziale), now addressed in source.

Affected original pages and screen IDs

Original page 01 (ZIP installation concept) and page 02 (pairing entry and reconnect); screens 11-16. The original two-sided leaflet is retained.

Corrections

Add 40 / optional Yes-No Codex choice, 41 / character-hold Setup, and 42 / reconnect wait. 09 means local Wi-Fi/IP; 11 selects a skin. No/Later performs no persistence or new CCP request. Saved pairing returns to 14 and requires authenticated READY for 15. PWR/BOOT do not clear pairing.

Preservation

All 2 previous pages, earlier corrections, bookmarks and unrelated content are retained. This dated addendum supersedes only the cited startup/setup/install statements; the original numbering stays stable.

Evidence and limits

Firmware source implementation and static integration review completed. PDF pages rendered and visually reviewed. No firmware tests, validation scans, configure/build/size, simulator execution, device pairing/input, flash or erase accompanied this revision. Runtime validation is pending.