CODY / VIBEWARE



Navigation Atlas

Current device-first routes, controls and recovery.

DEVELOPMENT REFERENCE / 13 November 2026

Umberto Giacobbi / umbertogiacobbi.biz / Copyright (c) 2026

Current behavior and limitations. Original correction dates and screen IDs remain in the final register.

Contents

Use screen IDs for product identity; PDF page numbers are navigation only.

Start and connect	3
Dashboard	4
Options	5
Pairing and retained PC	6
Questions and notifications	7
Standby, battery and voice	8
Cloud status	9
Original screen IDs	10
Corrections register	11
Security	18

Start from the saved state

VibeWare appears on cold boot/software reset. The device-first route then uses actual network and pairing state.

No saved Wi-Fi

Not connected > Tap to pair > Wi-Fi setup. App download QR opens the installation page; Show pairing QR starts the Bluetooth session. Scan inside the Espressif provisioning app.

Saved Wi-Fi

Connecting to Wi-Fi waits for valid association/IP. Recovery offers Set up Wi-Fi or Later. Later preserves saved credentials and permits background recovery.

Wi-Fi ready

Without a retained association, prepare the Codex pairing code. With a valid saved record, search for that PC until current authentication arrives. Internet availability is a separate condition.

Errors stay explicit

Storage, service and cleanup failures retain the original cause. Retry is not consent to replace a PC. A missing observation does not become Connected or a fabricated numeric value.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

Read the current dashboard

Counter mode defaults to On without a saved preference; horizontal swipes change its pages.

Counter mode

Swipe between reset, graphical context and model when their observations are available. Change the saved switch on the third Behavior page.

Carousel when disabled

Device > Codex reset > Context > Codex limits > Today > Last 7 days > Token history > Credits > Codex account > About.

Carousel navigation

With Counter mode off, shake returns to the first statistics page with available data. Device is the fallback when no statistics are available.

Current and saved data

Measured counters keep their source date/time. Saved offline observations are labeled with their UTC update times. Missing daily counts remain gaps. No extrapolation, backfill or invented zeros.

About

System shows measured CPU/uptime; Memory shows allocatable RAM/PSRAM used, free and largest free block; Firmware shows version/build context. The project QR follows these child pages and is not a carousel item.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

BOOT opens the quick menu

A short press offers Settings, Events, Counters and About; a long press opens Options.

Page 1

Connections and Codex. Connections opens Connect Codex and Set up Wi-Fi.

Page 2

Display, Behavior and Cody. Swipe within categories for idle display, optional event reactions, parallax and eight character color themes.

Device pages

Restart device, Factory reset, Quick guide, About, Third party and model prices. OpenRouter quotes are indicative and distinct from Codex credits.

Saving and returning

Settings apply only after confirmed storage; failure retains the prior value. Statistics appear automatically when data is available.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

Pair once, prove current presence again

Local workflow / original screens 12-15, 40-42. IP addresses and names are not credentials.

Start deliberately

BOOT > Settings > Connections > Connect Codex. Keep link resumes the remembered PC. Pair again explicitly permits replacement. Forget opens a separate confirmation.

Read the intended display

Use all six characters from the device's current code after discovery. Code preparation is not measured progress. The pairing window is five minutes; no code is logged or broadcast in plaintext.

Persist both sides

PC and Cody stage separate candidates while retaining active records. Confirmed persistence and authenticated ACTIVE/COMMITTED complete association. A pending record alone is not success.

Recover real state

Ordinary LAN loss or an IP change resumes the saved association. Cancel preserves the old operational link. A local Forget does not revoke the independent PC record. Storage failure requires explicit repair.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

A notification is an event; an answer needs delivery

Semantic content carries stable identity, freshness and the actual outcome.

Activity

Follow the latest authorized prompt with exact chat/turn identity. Tools and completions in another chat cannot take over. A response-ready event does not prove task success or passed checks.

Questions

26 opens a question; 27 shows numbered rows, at most two visible. Read the full label/detail before Send. Selecting, scrolling or going Back does not answer.

Acknowledgements

PC receipt and recipient delivery are different. Only the recipient's authenticated acknowledgement permits 31 / Reply sent. The deadline includes delivery; timeout never chooses a reply.

Data discipline

Keep bounded printable ASCII, immutable request identities, original timestamps and explicit unavailable/error state. Native Codex approvals stay on the PC. A remote notification cannot authorize a privileged action.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

Local behavior and optional services

The current source defines behavior; physical verification remains separate.

Power and wake

PWR toggles software standby. Authenticated questions and Reply ready can wake software standby while the LAN link is retained. The route remains owned by its model.

Battery

Awake notices use observed 50%, 20%, 10% and 5% thresholds. An observed 0% requests USB. If hardware cuts power earlier, no unobserved 0% message is invented.

Screensaver and sound

Screensaver is off by default; a dismissing touch cannot activate hidden content. Sounds and quiet hours govern optional cues. The optional weekly alarm alerts at 70, 50, 20, 10 and 5 percent remaining.

Voice profile

The default build omits microphone acquisition. The Cody wake-word variant combines Sophia, speech synthesis and one-way audio handoff. Recipient transcription is not established.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

Cloud connection is a separate development step

The current firmware remains a local paired companion.

Private service

The relay is under implementation with separate owner, device and client identities. Grants bind a particular client to an owned device; IDs and device names are not permissions.

Device work remains

Cloud enrollment, physical confirmation, protected device credentials and outbound HTTPS polling must be integrated into firmware before this journey can appear on Cody.

Local route remains explicit

The six-character Connect Codex procedure describes local CCP pairing. It is not a cloud enrollment code and must not be repurposed as a global API key.

No live claim

No Azure deployment, Dot integration, firmware cloud connection or physical behavior is established by this edition. Original screen IDs remain unchanged; no cloud route ID is fabricated.

Sources: docs/cody/navigation.md, layout.md, runtime.md; cody-desktop/plugins/cody-codex-plugin/README.md and protocol/CCP1.md.

Original screen IDs remain stable

Identity reference / current labels and availability follow the source owners, not these original document names.

01-03	**Character boot**	VibeWare precedes Cody; the first-install birth introduction has its own pending state.
04-09 / 06-bis	**Network setup**	Installation QR, active provisioning QR, failure and valid Wi-Fi/IP.
10 / 36 / 11	**Options / Settings / Skin**	Device-first Options are current; Skin remains character design scope.
12-15	**Code / saved / searching / connected**	Local CCP pairing and current authentication are distinct states.
16 / 17 / 18 / 18U	**Idle / project / work / unavailable**	Cody renders on the device; activity needs exact source identity and freshness.
19 / 20A / 20B	**Reply ready / paused / chat ended**	A reply is not proof of success; no background event steals context.
21-24 / 25	**PR observations / retired log route**	Read-only status; exact head and complete check list; 25 remains retired.
26 / 27	**Notice / question / review**	Numbered choices, complete detail review, then explicit Send.
28 / 29 / 30	**Voice capture / transport / review**	Voice is profile-dependent; original transcript review 30 remains a future mode.
31 / 32	**Reply delivered / connection lost**	Recipient acknowledgement and actual link state; never infer success.
33 / 34	**Battery / charging notices**	Use current measured thresholds and health; no synthetic battery facts.
35A / 35B	**Sleep / Wake**	Power owner retains route; an artistic pose alone is not standby.
37 / 38 / 39	**Rig / diagnostics / provisioning debug**	Rig is Studio; diagnostic entry shares Debug/Release, with no facial-channel UI.
40 / 41 / 42	**Connection decision / Setup / recovery**	Original route identities retained; BOOT Options is the current user entry.

C01-C14 (cues) and IS01-IS04 (idle scenes) are document labels, not new routes. No cloud screen IDs are assigned before firmware integration.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
03 October 2026 **ADDENDUM**	**A01 / Installation and device QR are different** Affected: Navigation originals 03, 12-13; Planning originals 04 and 23; screens 05-09 and original 06-bis. An installation QR opens the provisioning app listing. A separate session QR belongs to the active provisioning attempt. Credentials and Wi-Fi/IP are distinct states. Cancel and failure wait for actual cleanup; retry starts a new attempt. Evidence / limits: Source/design evidence only; physical behavior was not established by this correction.
04 October 2026 **ADDENDUM**	**A02-A04 / Stable routes, read-only PRs and real pairing** Affected: Navigation originals 14-16; Planning originals 24-26; screens 04-16, 21-25, 36 and 39. The Studio skin selector keeps screen 11 and its caller across first setup and Settings. PR screens 21-24 are read-only; 25 is retired. Counts require a complete current check list for the exact head. First-boot persistence and pairing success require actual owner results; Connected cannot be inferred from a route change. Evidence / limits: Source/design evidence only; physical behavior was not established by this correction.
05 October 2026 **ERRATA**	**Idle presentation is a design scope** Affected: Navigation original 19; Manga originals 03-04, 14-18; screens 04, 16, 35A/35B, 36-38. Original Idle 16 gained IS01-IS04 artistic scenes with a 20-40-second eligible wait, 3.2-second gesture and 40-second cooldown. The 35% closing, 16-22% reopening and 4.5% width pulse were subsequently corrected. These labels describe character design, not device measurements or current dashboard routes. Evidence / limits: Source/design evidence only; physical behavior was not established by this correction.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
06 October 2026 **ERRATA**	**Character values and VibeWare introduction** Affected: Navigation originals 23 and 26; Manga originals 19-27; screens 01-05, 16, 35A/35B. The retained character correction used 75% mouth closing, 16-24% reopening and 18% width motion; Stressed peak opening 0.24; cue offset +30/+40 px, 3.6x scale and 400-ms fades; Whistle width 0.5 replacing 0.42. The owner-supplied VibeWare floppy precedes content on cold boot/software reset. Former character boot phases and twofold artwork geometry are superseded by current device-first behavior. Evidence / limits: Windows rig illustrations and source review; no physical visual/audio observation was established. Build/check chronology is omitted.
09 October 2026 **ERRATA**	**Saved state and reversible setup** Affected: Navigation originals 02, 04, 16, 25, 28-29; Planning originals 27-29; screens 04-16, 35B, 36, 40-42. The original analysis omitted a configured network without a Codex association and a reversible setup entry. Screens 40, 41 and 42 identified those distinct routes. Saved pairing, network recovery and replacement consent remain separate. The current device-first entry is BOOT > Options > Connections, replacing the character-hold instruction. Evidence / limits: Source/design evidence only; physical behavior was not established by this correction.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
09 October 2026 **ERRATA**	**Standby recovery and malformed touch evidence** Affected: Navigation originals 28, 31-34; Planning originals 30-34; Service 14-18 / Connection 18-22; screens 04-06, 12, 35B, 41. A 90-second passive capture observed LAN/DHCP, Welcome inactivity return and standby, but no Connect Codex press. A separate capture recorded Yes at 16497 ms, Connect Codex at 16498 ms, then fifteen FF report bytes and ACK=FF at 17112 ms; expected ACK was AB. ESP_ERR_INVALID_RESPONSE stopped rendering. The correction separates an optional runtime acquisition error from rendering, interrupts gestures and requires a real release. Evidence / limits: These are retained measured failures. The FF hardware cause and corrected physical behavior were not established by those captures.
09 October 2026 **ERRATA**	**Action layout and touch admission** Affected: Navigation/Planning original 34; screens 05-15, 26-27, 35B, 36, 40-42; selected-multi-action.png and selected-single-action.png. The approved design uses two side-by-side rounded gradient cards, a centered third action, or one wide capsule. Earlier stacked-blue examples were superseded. Current captions are text-only; the older icon-left prescription is no longer the action contract. Question choices now use numbered single-line rows with full review before Send. Evidence / limits: Approved design references are not device captures.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
10 October 2026 **ERRATA**	**Automatic chat context and freshness** Affected: Navigation originals 35-38; Planning originals 35-38; screens 15-20, 18U, 26-27, 31-32. CCP follows the latest authorized UserPromptSubmit with exact chat/turn identity. Manual Choose/Pick a chat is removed. Background events cannot select context; a tab click is not a documented focus event. Pairing, authenticated presence, app presence and real work remain distinct. Eight seconds without packets expires device state; active work becomes unavailable after 120 seconds without another hook. Evidence / limits: The owner confirmed Connected on 10 October for the preceding pairing implementation. That observation does not prove later hooks or presentation.
10 October 2026 **ERRATA**	**Retain, replace, cancel and forget** Affected: Navigation/Planning originals 39-42, 48; screens 12-16, 32, 35B, 40-42. Separate pending and active records on both peers. Persist before confirmation and promote only after authenticated ACTIVE/COMMITTED. Cancel preserves the old operational link; a pending PC candidate requires a new visible code and explicit replacement. Forget removes Cody's CCP records, not the independent PC record. Temporary disconnection does not authorize re-pairing. Evidence / limits: Source/design evidence only; physical behavior was not established by this correction.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
10 October 2026 **ERRATA**	**Reply delivery and command outcomes** Affected: Navigation/Planning originals 43-46; Service 25-28 / Connection 29-32; screens 21-27, 31-32. Receipt is not recipient delivery. An immutable question ticket expires after 180 seconds including delivery acknowledgement. Timeout, offline, Back and Cancel never select an answer. Reply sent requires recipient acknowledgement. Restart retains settings; factory reset requires explicit confirmation and verified deletion. A command ACK proves admission, not reboot completion. Evidence / limits: Source/design evidence only; physical behavior was not established by this correction.
10 October 2026 **ERRATA**	**Boot artwork and current controls** Affected: Navigation/Planning originals 47-50; Manga original 02 and 28-31; screens 01-15, 36, 39-42. The complete 42-frame VibeWare artwork retains its authored 3.5-second dwell. The 10 October correction replaced the earlier title-free/twofold composition with a title, subtitle and 192 x 219 artwork at (137,164). It also removed the connection detour, clarified the five-minute pairing window and required successful settings write/readback. Current device-first routes are now integrated in the main body. Evidence / limits: Coordinates are source layout values. Schematics are neither simulator frames nor device captures.
11 October 2026 **ERRATA**	**English throughout** Affected: Navigation originals 01, 05-10, 29, 31, 34, 36, 38-46 and 53; Planning originals 01-02, 09-14, 16, 21-22, 39-46 and 53; Service 33 / Connection 37. Translate headings, diagrams, captions, prose and footers into English while preserving original correction dates, screen IDs, technical values and evidence limits. Evidence / limits: Document language and layout review only.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
12 October 2026 **CHANGE**	**Navigation within the documents** Affected: All atlas pages; Manga prior final register. Coordinated document identity, navigable contents and bookmarks retain original screen references when pagination changes. The quickstart keeps its own four instructional A5 pages. Evidence / limits: Document authoring only.
09 November 2026 **ERRATA**	**Current device and private cloud boundaries** Affected: Current Navigation/Planning bodies; former Navigation pages 03-19 and Planning pages 03-27; map and A5 instructions. Replace character-led current routes with the device-first dashboard, BOOT Options, current carousel order, Timer, Quick guide and explicit reset screens. Preserve character artwork as Studio/design material. Consolidate corrections into this register and remove accumulated build/code history. The private cloud service is under implementation; cloud firmware and Dot integration are pending. Evidence / limits: Read-only source review and PDF authoring. No firmware build, test, simulator, device operation or cloud deployment accompanies this edition.
13 November 2026 **ERRATA**	**Local timer retired** Affected: Navigation Options and standby; original ui-v1:timer. The local countdown screen, its Options entry, alarm and standby wake are removed. Other timekeeping and activity timers remain independent. Evidence / limits: Source review only; build, simulator and device verification remain pending.

Corrections register

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
13 November 2026 **ERRATA**	**Cody, flat actions and voice profile boundaries** Affected: Navigation/Planning current pages 3-8 and original screens 01-04, 26-29, 35A/35B and 40-42. The device source includes Cody, the first-install birth introduction and a saved Counter mode. Actions draw text and existing icons without filled cards. The Cody wake-word profile combines Sophia, speech synthesis and one-way audio handoff to the paired PC. Recipient transcription is not established. Quiet hours are available in device settings. Evidence / limits: Source review and document authoring only; visual, physical and voice-delivery acceptance remain separate.

Security

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
10 October 2026 **SECURITY**	**Fresh proof before presence or current data** Affected: CCP FIND / READY / COMMITTED; original screens 12-15, 18U, 26-27, 31-32. FIND alone cannot establish presence, redirect notifications or release current data. READY binds a fresh challenge to the observed device endpoint; COMMITTED proves the matching response. Distinct active/pending records, strict field bounds, nonces and one-use challenges preserve explicit admission. Firmware/plugin changes must agree; no legacy handshake fallback is claimed. Evidence / limits: Source-based correction; neither runtime adversarial behavior nor physical recovery is certified.
10 October 2026 **SECURITY**	**Bound work and keep residual risks explicit** Affected: Firmware UDP owner; PC discovery/pairing; ACTIVITY / TECH / EVENT; optional HTTP. Global/per-source ingress budgets and bounded receive slices precede expensive work. Discovery and pairing have finite packet/offer/work budgets. Broker network diagnostics are bounded; startup-only runtime.log retention remains separate. Six-character CCP transcripts permit offline guessing, and ordinary HMAC payloads are readable. Standard PAKE/high-entropy QR and authenticated encryption remain deferred. Optional plaintext device HTTP is a separate review scope. Evidence / limits: HMAC authenticates but does not provide confidentiality. No compromised-PC protection or production-security certification is claimed.

Security

Retained corrections and evidence; original dates, page references and screen IDs remain explicit.

DATE / TYPE	REVISION DETAILS AND SUPPORTING MATERIAL
07 November 2026 SECURITY	**Account projections stay bounded and authenticated** Affected: CCP ALLOWANCECAP / ALLOWANCE / ACCOUNT and later bounded account projection; Planning original 24; Communication core 03 and 09. The current endpoint, nonce and authenticated association bind account projections. Credentials, account identity email and message contents stay on the host. Source age, unavailable samples and separate account generations prevent stale or mixed-account graphs being shown as current. Evidence / limits: Source ownership only; this document does not establish live account login or end-to-end device delivery.