

# Doubly Linked Lists

## TOPICS

Linked Lists

Doubly Linked Lists

Linked List Practice

Searching Arrays

Queues

Stacks

## Adding to the Tail

A Python `DoublyLinkedList` class can implement an `.add_to_tail()` instance method for adding new data to the tail of the list. `.add_to_tail()` takes a single `new_value` argument. It uses `new_value` to create a new `Node` which it adds to the tail of the list.

```
def add_to_tail(self, new_value):
    new_tail = Node(new_value)
    current_tail = self.tail_node

    if current_tail != None:
        current_tail.set_next_node(new_tail)
        new_tail.set_prev_node(current_tail)

    self.tail_node = new_tail

if self.head_node == None:
    self.head_node = new_tail
```

## Adding to the Head

A Python `DoublyLinkedList` class can implement an `.add_to_head()` instance method for adding new data to the head of the list. `.add_to_head()` takes a single `new_value` argument. It uses `new_value` to create a new `Node` which it adds to the head of the list.

```
def add_to_head(self, new_value):
    new_head = Node(new_value)
    current_head = self.head_node

    if current_head != None:
        current_head.set_prev_node(new_head)
        new_head.set_next_node(current_head)

    self.head_node = new_head

if self.tail_node == None:
    self.tail_node = new_head
```

## Removing the Tail

A Python `DoublyLinkedList` class can implement a `.remove_tail()` instance method for removing the head of the list. `.remove_tail()` takes no arguments. It removes and returns the tail of the list, and sets the tail's previous node as the new tail.

```
def remove_tail(self):
    removed_tail = self.tail_node

    if removed_tail == None:
        return None

    self.tail_node = removed_tail.get_prev_node()

if self.tail_node != None:
    self.tail_node.set_next_node(None)

if removed_tail == self.head_node:
    self.remove_head()

return removed_tail.get_value()
```

## Removing the Head

A Python `DoublyLinkedList` class can implement a `.remove_head()` instance method for removing the head of the list. `.remove_head()` takes no arguments. It removes and returns the head of the list, and sets the head's next node as the new head.

```
def remove_head(self):
    removed_head = self.head_node

    if removed_head == None:
        return None

    self.head_node = removed_head.get_next_node()

if self.head_node != None:
    self.head_node.set_prev_node(None)

if removed_head == self.tail_node:
    self.remove_tail()

return removed_head.get_value()
```

## Removing by Value

A Python `DoublyLinkedList` class can implement a `.remove_by_value()` instance method that takes `value_to_remove` as an argument and returns the node that matches `value_to_remove`, or `None` if no match exists. If the node exists, `.remove_by_value()` removes it from the list and correctly resets the pointers of its surrounding nodes.

```
def remove_by_value(self, value_to_remove):
    node_to_remove = None
    current_node = self.head_node

    while current_node != None:
        if current_node.get_value() == value_to_remove:
            node_to_remove = current_node
            break

    current_node = current_node.get_next_node()

if node_to_remove == None:
    return None

if node_to_remove == self.head_node:
    self.remove_head()
elif node_to_remove == self.tail_node:
    self.remove_tail()
else:
    next_node = node_to_remove.get_next_node()
    prev_node = node_to_remove.get_prev_node()
    next_node.set_prev_node(prev_node)
    prev_node.set_next_node(next_node)

return node_to_remove
```

## Constructor

A Python `DoublyLinkedList` class constructor should store:

- A `head_node` property to store the head of the list
- A `tail_node` property to store the tail of the list

The `head_node` and `tail_node` are set to `None` as their defaults.

```
class DoublyLinkedList:
    def __init__(self):
        self.head_node = None
        self.tail_node = None
```

## Updated Node Class

Doubly linked lists in Python utilize an updated `Node` class that has a pointer to the previous node. This comes with additional setter and getter methods for accessing and updating the previous node.

```
class Node:
    def __init__(self, value, next_node=None, prev_node=None):
        self.value = value
        self.next_node = next_node
        self.prev_node = prev_node

    def set_next_node(self, next_node):
        self.next_node = next_node

    def get_next_node(self):
        return self.next_node

    def set_prev_node(self, prev_node):
        self.prev_node = prev_node

    def get_prev_node(self):
        return self.prev_node

    def get_value(self):
        return self.value
```

## Doubly Linked List Overview

A `DoublyLinkedList` class in Python has the following functionality:

- A constructor with `head_node` and `tail_node` properties
- An `.add_to_head()` method to add new nodes to the head
- An `.add_to_tail()` method to add new nodes to the tail
- A `.remove_head()` method to remove the head node
- A `.remove_tail()` method to remove the tail node
- A `.remove_by_value()` method to remove a node that matches the `value_to_remove` passed in

```
class DoublyLinkedList:
    def __init__(self):
        self.head_node = None
        self.tail_node = None

    def add_to_head(self, new_value):
        new_head = Node(new_value)
        current_head = self.head_node

        if current_head != None:
            current_head.set_prev_node(new_head)
            new_head.set_next_node(current_head)

        self.head_node = new_head

        if self.tail_node == None:
            self.tail_node = new_head

    def add_to_tail(self, new_value):
        new_tail = Node(new_value)
        current_tail = self.tail_node

        if current_tail != None:
            current_tail.set_next_node(new_tail)
            new_tail.set_prev_node(current_tail)

        self.tail_node = new_tail

        if self.head_node == None:
            self.head_node = new_tail

    def remove_head(self):
        removed_head = self.head_node

        if removed_head == None:
            return None

        self.head_node = removed_head.get_next_node()

        if self.head_node != None:
            self.head_node.set_prev_node(None)

        if removed_head == self.tail_node:
            self.remove_tail()

        return removed_head.get_value()

    def remove_tail(self):
        removed_tail = self.tail_node

        if removed_tail == None:
            return None

        self.tail_node = removed_tail.get_prev_node()

        if self.tail_node != None:
            self.tail_node.set_next_node(None)

        if removed_tail == self.head_node:
            self.remove_head()

        return removed_tail.get_value()

    def remove_by_value(self, value_to_remove):
        node_to_remove = None
        current_node = self.head_node

        while current_node != None:
            if current_node.get_value() == value_to_remove:
                node_to_remove = current_node
                break

        current_node = current_node.get_next_node()

        if node_to_remove == None:
            return None

        if node_to_remove == self.head_node:
            self.remove_head()
        elif node_to_remove == self.tail_node:
            self.remove_tail()
        else:
            next_node = node_to_remove.get_next_node()
            prev_node = node_to_remove.get_prev_node()
            next_node.set_prev_node(prev_node)
            prev_node.set_next_node(next_node)

        return node_to_remove
```

[← Previous](#)

[Next →](#)

## Related Courses

PRO Path

Pass the Technical Interview with Python

Enrolled... [Keep Going](#)

## codecademy

From skillsoft

About  
Careers  
Affiliates  
Shop

🐦 f 📺 🍎

## MOBILE

Download on the App Store

GET IT ON Google Play

## RESOURCES

Projects  
Interview Challenges  
Docs  
Cheatsheets  
Articles  
Videos  
Career Center

## INDIVIDUAL PLANS

Pro Membership  
For Students

## SUPPORT

Help Center

## COMMUNITY

Forums  
Discord  
Chapters  
Events  
Learner Stories

## ENTERPRISE PLANS

Business Solutions

## COURSE CATALOG

### Subjects

Web Development  
Data Science  
Computer Science  
Developer Tools  
Machine Learning  
Code Foundations  
Web Design  
—  
Full Catalog  
Beta Content  
Roadmap

### Languages

HTML & CSS  
Python  
JavaScript  
Java  
SQL  
Bash/Shell  
Ruby  
C++  
R  
C#  
PHP  
Go  
Swift  
Kotlin