
1. time/t digunakan untuk mengetahui waktu di server atau di komputer secara akurat



2. net sessions /? Di gunakan untuk memberi informasi tentang username dan ip user yang mengakses sistem melalui remote login session dan tipe dari client sistem akses.

```
Administrator: Command Prompt

C:\>net sessions /?
The syntax of this command is:

NET SESSION
[\\computername] [/DELETE] [/LIST]

C:\>
```

3. net file /? Digunakan untuk menampilkan semua file sharing yang terbuka di dalam sistem

```
C:\>net file/?
The syntax of this command is:

NET

[ ACCOUNTS | COMPUTER | CONFIG | CONTINUE | FILE | GROUP | HELP
| HELPMSG | LOCALGROUP | PAUSE | SESSION | SHARE | START | STATISTICS | STOP | TIME | USE | USER | VIEW ]

C:\>_
```

4. openfiles digunakan untuk menampilkan atau memutus file dan folder yang terbuka di dalam sistem

```
Administrator Command Prompt

STATISTICS | STOP | TIME | USE | USER | VIEW ]

C:\>openfiles

INFO: The system global flag 'maintain objects list' needs to be enabled to see local opened files.
See Openfiles /? for more information.

Files opened remotely via local share points:

INFO: No shared open files found.

C:\>_
```

5. nbtstat -c digunakan untuk mengganti tampilan nama tabel cache di NetBIOS

```
C:\>nbtstat -c

Ethernet:
Node IpAddress: [192.168.1.11] Scope Id: []

No names in cache

WiFi:
Node IpAddress: [0.0.0.0] Scope Id: []

No names in cache

Local Area Connection* 13:
Node IpAddress: [0.0.0.0] Scope Id: []

No names in cache

Local Area Connection* 2:
Node IpAddress: [0.0.0.0] Scope Id: []


No names in cache

C:\>
```


6. netstat digunakan untuk mengetahui informasi mengenai koneksi

```
Administrator: Command Prompt
:\>netstat
Active Connections
 Proto Local Address
TCP 192.168.1.11:51491
TCP 192.168.1.11:51535
                                              Foreign Address
hk2sch130021821:https
                                                                                 State
ESTABLISHED
                                              hk2sch130021032:https
                                                                                 ESTABLISHED
            192.168.1.11:51658
                                               195:https
                                                                                 TIME_WAIT
           192.168.1.11:51661
192.168.1.11:51662
192.168.1.11:51663
192.168.1.11:51664
                                                                                 TIME_WAIT
ESTABLISHED
 TCP
                                              8:https
 TCP
                                                                                 ESTABLISHED
                                              8:https
                                                                                 ESTABLISHED
                                               19:https
 \>
```


7. Netstat -ano digunakan untuk menampilkan TCP dan UDP koneksi jaringan, port yang digunakan, dan mengidentifikasinya



8. Netstat -r digunakan untuk menampilkan tabel routing dan routes yang hidup di sistem



9. Tasklist digunakan untuk menampilkan aplikasi yang berjalan



10. Tasklist /v digunakan untuk menampilkan informasi proses yang terdaftar, termasuk nama gambar, PID, nama dan nomer session dalam proses

```
Session# Mem Usage Status
CPU Time Window Title
                                  PID Session Name
mage Name
   User Name
ystem Idle Process 0 Services
NT AUTHORITY\SYSTEM
                                                                 193:01:15 N/A
                                                                   0 8.112 K Unknown
6:57:09 N/A
                                   4 Services
ystem
N/A
                                  388 Services
                                                                   0 540 K Unknown
0:00:00 N/A
mss.exe
NT AUTHORITY\SYSTEM
                                                                   0 1.844 K Unknown
0:00:12 N/A
srss.exe
NT AUTHORITY\SYSTEM
                                  540 Services
ininit.exe
NT AUTHORITY\SYSTEM
                                                                   0 3.296 K Unknown
0:00:00 N/A
                                  672 Services
ervices.exe
                                  816 Services
```

11. Ipconfig /all digunakan untuk menampilan network konfigurasi dari NIC di sistem

```
Administrator: Command Prompt
:\>ipconfig /all
Windows IP Configuration
  ireless LAN adapter Local Area Connection* 2:
  Media State . . . . . . : Media disconnected

Connection-specific DNS Suffix :

Description . . . : Microsoft Wi-Fi Direct Virtual Adapter
Physical Address . . . : 1E-E0-10-28-46-F9

DHCP Enabled . . . . : Yes
   DHCP Enabled. . . . . . . . : Yes
Autoconfiguration Enabled . . . . : Yes
 ireless LAN adapter Local Area Connection* 13:
  . : Media disconnected
  Description . . . . . . : Microsoft Hosted Network Virtual Adapter Physical Address . . . . : 4E-E0-10-28-46-F9
DHCP Enabled . . . . : No
Autoconfiguration Enabled . . . : Yes
thernet adapter Ethernet:
  Connection-specific DNS Suffix .:
  192.168.1.11(Preferred)
192.168.1.11(Preferred)
255.255.255.0
06 November 2017 16:41:52
09 November 2017 22:18:21
fe80::1e74:dff:fe13:754%8
  192.168.1.254
```

12. Reg /? Digunakan untuk mengakses dan memanajemen dari registri

```
Administrator Command Prompt

C:\>reg /?

REG Operation [Parameter List]

Operation [QUERY | ADD | DELETE | COPY | SAVE | LOAD | UNLOAD | RESTORE | COMPARE | EXPORT | IMPORT | FLAGS ]

Return Code: (Except for REG COMPARE)

0 - Successful
1 - Failed

For help on a specific operation type:

REG Operation /?

Examples:

REG QUERY /?

REG ADD /?

REG DELETE /?

REG COPY /?

REG COPY /?

REG COPY /?

REG COMPARE /?

REG LOAD /?

REG COMPARE /?

REG UNLOAD /?

REG COMPARE /?

REG IMPORT /?

REG IMPORT /?

REG IMPORT /?

REG FLAGS /?

C:\>
```