



Vicon DataStream SDK 1.8.o Developer's Guide

©2013-2018 Vicon Motion Systems Limited. All rights reserved.

Vicon DataStream SDK Developer's Manual November 2017
For use with Vicon DataStream SDK 1.8.o and later.

Vicon® is a registered trademark of Oxford Metrics plc. Vicon Blade™, Vicon Shōgun™, Vicon Nexus™, Vicon Tracker™, Bonita™, Vicon MX™, and Vicon MX T-Series™ are trademarks of Oxford Metrics plc. Other product and company names herein may be the trademarks of their respective owners. Vicon Motion Systems is an Oxford Metrics plc company.

Email: support@vicon.com. Web: www.vicon.com.

Contents

Developer's Guide	2
Class Index	7
Class List	7
Class Documentation	8
Client Class Reference	8
Detailed Description	8
Constructor & Destructor Documentation	14
Client	14
~Client	15
Member Function Documentation	15
GetVersion	15
Connect	17
ConnectToMulticast	18
Disconnect	20
IsConnected	21
StartTransmittingMulticast	22
StopTransmittingMulticast	23
EnableSegmentData	24
EnableMarkerData	25
EnableUnlabeledMarkerData	26
EnableMarkerRayData	27
EnableDeviceData	28
EnableCentroidData	29
EnableGreyscaleData	30
EnableVideoData	31
EnableDebugData	32
DisableSegmentData	33

DisableMarkerData	34
DisableUnlabeledMarkerData	35
DisableMarkerRayData	36
DisableDeviceData	37
DisableCentroidData	38
DisableGreyscaleData	39
DisableVideoData	40
DisableDebugData	41
IsSegmentDataEnabled	42
IsMarkerDataEnabled	43
IsUnlabeledMarkerDataEnabled	44
IsMarkerRayDataEnabled	45
IsDeviceDataEnabled	46
IsCentroidDataEnabled	47
IsGreyscaleDataEnabled	48
IsVideoDataEnabled	49
IsDebugDataEnabled	50
SetBufferSize	51
SetStreamMode	52
SetApexDeviceFeedback	54
SetAxisMapping	55
GetAxisMapping	56
GetFrame	57
GetFrameNumber	58
GetTimecode	59
GetFrameRate	60
GetLatencySampleCount	61
GetLatencySampleName	62
GetLatencySampleValue	63
GetLatencyTotal	64
GetHardwareFrameNumber	65
GetFrameRateCount	66
GetFrameRateName	67
GetFrameRateValue	68
GetSubjectCount	69
GetSubjectName	70
GetSubjectRootSegmentName	72

GetSegmentCount	74
GetSegmentName	76
GetSegmentChildCount	78
GetSegmentChildName	80
GetSegmentParentName	82
GetSegmentStaticTranslation	84
GetSegmentStaticRotationHelical	86
GetSegmentStaticRotationMatrix	88
GetSegmentStaticRotationQuaternion	90
GetSegmentStaticRotationEulerXYZ	92
GetSegmentGlobalTranslation	94
GetSegmentGlobalRotationHelical	96
GetSegmentGlobalRotationMatrix	98
GetSegmentGlobalRotationQuaternion	100
GetSegmentGlobalRotationEulerXYZ	102
GetSegmentLocalTranslation	104
GetSegmentLocalRotationHelical	106
GetSegmentLocalRotationMatrix	108
GetSegmentLocalRotationQuaternion	110
GetSegmentLocalRotationEulerXYZ	112
GetObjectQuality	114
GetMarkerCount	116
GetMarkerName	118
GetMarkerParentName	121
GetMarkerGlobalTranslation	123
GetMarkerRayContributionCount	125
GetMarkerRayContribution	127
GetUnlabeledMarkerCount	129
GetUnlabeledMarkerGlobalTranslation	130
GetLabeledMarkerCount	132
GetLabeledMarkerGlobalTranslation	133
GetDeviceCount	134
GetDeviceName	135
GetDeviceOutputCount	137
GetDeviceOutputName	139
GetDeviceOutputValue	142
GetDeviceOutputSubsamples	144

GetDeviceOutputValue	146
GetForcePlateCount	148
GetGlobalForceVector	149
GetGlobalMomentVector	151
GetGlobalCentreOfPressure	153
GetForcePlateSubsamples	155
GetGlobalForceVector	157
GetGlobalMomentVector	159
GetGlobalCentreOfPressure	161
GetEyeTrackerCount	163
GetEyeTrackerGlobalPosition	164
GetEyeTrackerGlobalGazeVector	166
GetCameraCount	168
GetCameraName	169
GetCameraId	171
GetCameraUserId	173
GetCameraType	175
GetCameraDisplayName	177
GetCameraResolution	179
GetIsVideoCamera	181
GetCentroidCount	183
GetCentroidPosition	185
GetCentroidWeight	187
GetGreyscaleBlobCount	189
GetGreyscaleBlob	190
GetVideoFrame	191
SetCameraFilter	192
RetimingClient Class Reference	193
Detailed Description	193
Constructor & Destructor Documentation	196
RetimingClient	196
~RetimingClient	197
Member Function Documentation	197
GetVersion	197
Connect	199
Disconnect	200
IsConnected	201

SetAxisMapping	202
GetAxisMapping	203
UpdateFrame	204
WaitForFrame	205
GetSubjectCount	206
GetSubjectName	207
GetSubjectRootSegmentName	209
GetSegmentCount	210
GetSegmentName	212
GetSegmentChildCount	214
GetSegmentChildName	216
GetSegmentParentName	218
GetSegmentStaticTranslation	220
GetSegmentStaticRotationHelical	221
GetSegmentStaticRotationMatrix	222
GetSegmentStaticRotationQuaternion	223
GetSegmentStaticRotationEulerXYZ	225
GetSegmentGlobalTranslation	226
GetSegmentGlobalRotationHelical	228
GetSegmentGlobalRotationMatrix	229
GetSegmentGlobalRotationQuaternion	230
GetSegmentGlobalRotationEulerXYZ	232
GetSegmentLocalTranslation	234
GetSegmentLocalRotationHelical	236
GetSegmentLocalRotationMatrix	238
GetSegmentLocalRotationQuaternion	239
GetSegmentLocalRotationEulerXYZ	241
SetMaximumPrediction	243
MaximumPrediction	243

Developer's Guide

The Vicon DataStream Software Development Kit (SDK) allows easy programmable access to the information contained in the Vicon DataStream. The function calls within the SDK enables users to connect to and request data from the Vicon DataStream. The following combinations of platforms and technologies are supported:

	Windows x86 (32-bit)	Windows x64 (64-bit)	Linux x86 (32-bit)	Linux x64 (64-bit)	Mac OSX (64&32-bit)
C++	YES	YES	YES	YES	YES
.NET	YES	YES			
MATLAB	YES (1)	YES (2)			

1. Can be run on Windows 64-bit OS.
2. Requires Microsoft Professional compiler.

Important Notes

- Not all function calls contained within the SDK will return data when connected to certain Vicon applications. For example, Vicon Nexus does not support object quality metrics, and therefore will not output object quality information into the DataStream.
- The current DataStream format is supported by Vicon Nexus 1.4+, Vicon Shogun 1.0+, Vicon Blade 1.6+, and Tracker 1.0+. These applications may also output an additional stream in the legacy "Tarsus" format. This DataStream SDK only accesses the DataStream format.
- The current intention is that all future Vicon applications will support the DataStream format.
- Example files are supplied as unsupported examples only.
- The SDK only supports axis transformations into right-handed coordinate systems.
- The SDK is designed to allow multiple instances of a [Client](#) within a single process, which can connect to multiple DataStreams.
- The SDK is supplied as shared libraries: DLL on Windows, dylib on OSX and so on Linux. The shared libraries and supporting files must be copied alongside your client executable.

Installing on Windows

There are separate installers for the 32-bit and 64-bit SDKs. The 64-bit installer will only work on a 64-bit version of Windows. The default install directories are:

64-bit Windows

- 32-bit SDK - C:\Program Files (x86)\Vicon\DataStream SDK\Win32
- 64-bit SDK - C:\Program Files\Vicon\DataStream SDK\Win64

32-bit Windows

- 32-bit SDK - C:\Program Files\Vicon\DataStream SDK\Win32

C++

Your application must:

- #include "DataStreamClient.h"
- Link against `ViconDataStreamSDK_CPP.lib`
- Redistribute:
 - `ViconDataStreamSDK_CPP.dll`
 - `Microsoft.VC12.CRT`

.NET

Your application must:

- Link against the assembly `ViconDataStreamSDK_DotNET.dll`.
- Redistribute:
 - `ViconDataStreamSDK_DotNET.dll`
 - `ViconDataStreamSDK_CPP.dll`
 - `Microsoft.VC12.CRT`

The managed code in this assembly requires the unmanaged code in the C++ SDK.

MATLAB

Your application M file must be in the same directory as:

- `Client.m`

- DeviceType.m
- Direction.m
- Result.m
- StreamMode.m
- TimecodeStandard.m
- Unit.m
- ViconDataStreamSDK_MATLAB.dll
- ViconDataStreamSDK_MATLAB.h
- Microsoft.VC80.CRT

Installing on Linux

The SDK is provided as a compressed archive. Extract the archive into a convenient location on your system.

C++

Your application must:

- `#include "DataStreamClient.h"`
- Link against `libViconDataStreamSDK_CPP.so`
- Redistribute `libViconDataStreamSDK_CPP.so`

The 32-bit version of the SDK was compiled with gcc version 4.8.5 (Red Hat 4.8.5-16 for CentOS 7). The 64-bit version of the SDK was compiled with gcc version 4.9.2 (Red Hat 4.9.2-6 from devtools-3 for CentOS 7).

Installing on OSX

C++

Requirements are:

- Intel 64- or 32-bit

Your application must:

- `#include "DataStreamClient.h"`
- Link against `libViconDataStreamSDK_CPP.dylib`
- Redistribute `libViconDataStreamSDK_CPP.dylib`

The SDK was compiled with gcc version 4.2.1 (Apple Inc. Build 5646) using flags:

```
-mmacosx-version-min=10.9 -isysroot /Developer/SDKs/MacOSX10.12.sdk -arch  
i386 -arch x86_64 -O2
```

Requirements

A compatible licensed version of Vicon Blade, Vicon Shogun, Vicon Nexus, or Vicon Tracker must be present.

- LabVIEW uses the .NET dll, and has been found to function in versions 7.1 and 8.
- The MATLAB dll has been found to function in versions up to and including Matlab 2017.
- The MATLAB dll has been found to function in versions up to and including Matlab 2017.
- The SDK has not been designed to allow access from Simulink.
- The Linux SDK has been specifically verified on CentOS 7. It should also work on any platform supporting glibc 2.5 or later.

Function Result Return Values

Every function returns a data structure containing elements specified in the 'Output' section of each method reference. Most functions return a 'Result' item, which indicates the success or cause of failure for the function and is useful for debugging purposes.

When a function has returned false, the output arguments are set to an appropriate default value:

- Booleans will be set to false.
- Integers will be set to zero.
- Doubles will be set to zero.
- Strings will be set to zero length.
- When the output argument is an array, all elements are set in this manner.

Conventions

By default the global coordinate system matches the server application; Z-Up, Y-Left. This can be changed by using [Client::SetAxisMapping](#).

Units

Positions are expressed in millimeters. **Rotation is expressed in radians.**

Vectors and Matrices

Positions are passed as 3 elements corresponding to (x,y,z)

$$\begin{pmatrix} a_0 \\ a_1 \\ a_2 \end{pmatrix}$$

A 3 matrix is passed row-wise as a vector of 9 elements:

$$\begin{pmatrix} a_0 & a_1 & a_2 \\ a_3 & a_4 & a_5 \\ a_6 & a_7 & a_8 \end{pmatrix}$$

Matrices are assumed to pre-multiply:

$$\mathbf{A} \times \mathbf{B} \times \mathbf{C} = \mathbf{A} \times (\mathbf{B} \times \mathbf{C})$$

Euler Angles

When used, an XYZ Euler angle (x,y,z) is constructed:

$$\mathbf{R}_x \times \mathbf{R}_y \times \mathbf{R}_z$$

Ang vector should be (Z,Y,X). It is (X,Y,Z) now. The order of rotation is XYZ.

$$\mathbf{R}_x \times (\mathbf{R}_y \times \mathbf{R}_z)$$

$$\begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos x & -\sin x \\ 0 & \sin x & \cos x \end{pmatrix} \begin{pmatrix} \cos y & 0 & \sin y \\ 0 & 1 & 0 \\ -\sin y & 0 & \cos y \end{pmatrix} \begin{pmatrix} \cos z & -\sin z & 0 \\ \sin z & \cos z & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

$$\begin{pmatrix} \cos y \cos z & -\cos y \sin z & \sin y \\ \cos x \sin z + \sin x \sin y \cos z & \cos x \cos z - \sin x \sin y \sin z & -\sin x \cos y \\ \sin x \sin z - \cos x \sin y \cos z & \sin x \cos z + \cos x \sin y \sin z & \cos x \cos y \end{pmatrix}$$

Class Index

Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Client	Vicon DataStream SDK client	8
RetimingClient	The re-timing client class for C++	193

Class Documentation

Client Class Reference

Detailed Description

Vicon DataStream SDK client.

The core client class for C++.

Public Member Functions

- [Client](#) ()
Construction.
- virtual [~Client](#) ()
Destruction.
- Output_GetVersion [GetVersion](#) () const
Get the version of the Vicon DataStream SDK.
- Output_Connect [Connect](#) (const String &HostName)
Establish a dedicated connection to a Vicon DataStream Server.
- Output_ConnectToMulticast [ConnectToMulticast](#) (const String &LocalIP, const String &MulticastIP)
Connect to a Vicon DataStream Server's Multicast stream.
- Output_Disconnect [Disconnect](#) ()
Disconnect from the Vicon DataStream Server.
- Output_IsConnected [IsConnected](#) () const
Discover whether client is connected to the Vicon DataStream Server.
- Output_StartTransmittingMulticast [StartTransmittingMulticast](#) (const String &ServerIP, const String &MulticastIP)
Ask the DataStream Server to start transmitting the data you are receiving directly to a Multicast address as well.
- Output_StopTransmittingMulticast [StopTransmittingMulticast](#) ()
Ask the DataStream Server to stop transmitting the data you are receiving directly to a Multicast address as well.
- Output_EnableSegmentData [EnableSegmentData](#) ()
Enable kinematic segment data in the Vicon DataStream.
- Output_EnableMarkerData [EnableMarkerData](#) ()
Enable labeled reconstructed marker data in the Vicon DataStream.
- Output_EnableUnlabeledMarkerData [EnableUnlabeledMarkerData](#) ()

- Enable unlabeled reconstructed marker data in the Vicon DataStream.
- Output_EnableMarkerRayData [EnableMarkerRayData \(\)](#)
Enable information about the rays contributing to each labeled marker in the Vicon DataStream.
- Output_EnableDeviceData [EnableDeviceData \(\)](#)
Enable force plate, EMG, and other device data in the Vicon DataStream.
- Output_EnableCentroidData [EnableCentroidData \(\)](#)
Enable centroid data in the Vicon DataStream.
- Output_EnableGreyscaleData [EnableGreyscaleData \(\)](#)
Enable greyscale data in the Vicon DataStream.
- Output_EnableVideoData [EnableVideoData \(\)](#)
Enable video data in the Vicon DataStream.
- Output_EnableDebugData [EnableDebugData \(\)](#)
Enable debug data in the Vicon DataStream.
- Output_DisableSegmentData [DisableSegmentData \(\)](#)
Disable kinematic segment data in the Vicon DataStream.
- Output_DisableMarkerData [DisableMarkerData \(\)](#)
Disable labeled reconstructed marker data in the Vicon DataStream.
- Output_DisableUnlabeledMarkerData [DisableUnlabeledMarkerData \(\)](#)
Disable unlabeled reconstructed marker data in the Vicon DataStream.
- Output_DisableMarkerRayData [DisableMarkerRayData \(\)](#)
Disable unlabeled reconstructed marker data in the Vicon DataStream.
- Output_DisableDeviceData [DisableDeviceData \(\)](#)
Disable force plate, EMG, and other device data in the Vicon DataStream.
- Output_DisableCentroidData [DisableCentroidData \(\)](#)
Disable centroid data in the Vicon DataStream.
- Output_DisableGreyscaleData [DisableGreyscaleData \(\)](#)
Disable greyscale data in the Vicon DataStream.
- Output_DisableVideoData [DisableVideoData \(\)](#)
Disable video data in the Vicon DataStream.
- Output_DisableDebugData [DisableDebugData \(\)](#)
Disable debug data in the Vicon DataStream.
- Output_IsSegmentDataEnabled [IsSegmentDataEnabled \(\)](#) const
Return whether kinematic segment data is enabled in the Vicon DataStream.
- Output_IsMarkerDataEnabled [IsMarkerDataEnabled \(\)](#) const
Return whether labeled reconstructed marker data is enabled in the DataStream.
- Output_IsUnlabeledMarkerDataEnabled [IsUnlabeledMarkerDataEnabled \(\)](#) const
Return whether unlabeled marker data is enabled in the DataStream.
- Output_IsMarkerRayDataEnabled [IsMarkerRayDataEnabled \(\)](#) const
Return whether marker ray data is enabled in the DataStream.
- Output_IsDeviceDataEnabled [IsDeviceDataEnabled \(\)](#) const
Return whether force plate, EMG, and other device data is enabled in the DataStream.
- Output_IsCentroidDataEnabled [IsCentroidDataEnabled \(\)](#) const
Return whether Centroid data is enabled in the DataStream.
- Output_IsGreyscaleDataEnabled [IsGreyscaleDataEnabled \(\)](#) const
Return whether greyscale data is enabled in the DataStream.
- Output_IsVideoDataEnabled [IsVideoDataEnabled \(\)](#) const
Return whether video data is enabled in the DataStream.
- Output_IsDebugDataEnabled [IsDebugDataEnabled \(\)](#) const

- Return whether debug data is enabled in the DataStream.
- void [SetBufferSize](#) (unsigned int BufferSize)
 - Set the number of frames that the client should buffer.
- Output_SetStreamMode [SetStreamMode](#) (const StreamMode::Enum Mode)
 - There are three modes that the SDK can operate in.
- Output_SetApexDeviceFeedback [SetApexDeviceFeedback](#) (const String &DeviceName, bool i_bOn)
 - Enable haptic feedback for the selected Apex device.
- Output_SetAxisMapping [SetAxisMapping](#) (const Direction::Enum XAxis, const Direction::Enum YAxis, const Direction::Enum ZAxis)
 - Remaps the 3D axis.
- Output_GetAxisMapping [GetAxisMapping](#) () const
 - Get the current Axis mapping.
- Output_GetFrame [GetFrame](#) ()
 - Request a new frame to be fetched from the Vicon DataStream Server.
- Output_GetFrameNumber [GetFrameNumber](#) () const
 - Return the number of the last frame retrieved from the DataStream.
- Output_GetTimecode [GetTimecode](#) () const
 - Return the timecode information for the last frame retrieved from the DataStream.
- Output_GetFrameRate [GetFrameRate](#) () const
 - Return the Vicon camera system frame rate (in Hz) at the time of the last frame retrieved from the DataStream.
- Output_GetLatencySampleCount [GetLatencySampleCount](#) () const
 - Return the number of latency measurements that were taken at various stages of the real-time pipeline.
- Output_GetLatencySampleName [GetLatencySampleName](#) (const unsigned int LatencySampleIndex) const
 - Return the name of a latency sample.
- Output_GetLatencySampleValue [GetLatencySampleValue](#) (const String &LatencySampleName) const
 - Return the duration of a named latency sample in seconds.
- Output_GetLatencyTotal [GetLatencyTotal](#) () const
 - Return the total latency in seconds introduced at various stages of the real-time pipeline.
- Output_GetHardwareFrameNumber [GetHardwareFrameNumber](#) () const
 - Returns the hardware frame number as used by the cameras.
- Output_GetFrameRateCount [GetFrameRateCount](#) () const
 - Get the number of frame rate types that the server application reports.
- Output_GetFrameRateName [GetFrameRateName](#) (const unsigned int FrameRateIndex) const
 - Get the name of a frame rate type at the specified index.
- Output_GetFrameRateValue [GetFrameRateValue](#) (const String &FrameRateName) const
 - Get the current value of the specified frame rate type.
- Output_GetSubjectCount [GetSubjectCount](#) () const
 - Return the number of subjects in the DataStream.
- Output_GetSubjectName [GetSubjectName](#) (const unsigned int SubjectIndex) const
 - Return the name of a subject.
- Output_GetSubjectRootSegmentName [GetSubjectRootSegmentName](#) (const String &SubjectName) const
 - Return the name of the root segment for a specified subject.

- `Output_GetSegmentCount` [GetSegmentCount](#) (const String &SubjectName) const
Return the number of segments for a specified subject in the DataStream.
- `Output_GetSegmentName` [GetSegmentName](#) (const String &SubjectName, const unsigned int SegmentIndex) const
Return the name of a subject segment specified by index.
- `Output_GetSegmentChildCount` [GetSegmentChildCount](#) (const String &SubjectName, const String &SegmentName) const
Return the number of child segment for a specified subject segment.
- `Output_GetSegmentChildName` [GetSegmentChildName](#) (const String &SubjectName, const String &SegmentName, const unsigned int SegmentIndex) const
Return the name of the child segment for a specified subject segment and index.
- `Output_GetSegmentParentName` [GetSegmentParentName](#) (const String &SubjectName, const String &SegmentName) const
Return the name of the parent segment for a specified subject segment.
- `Output_GetSegmentStaticTranslation` [GetSegmentStaticTranslation](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose translation of a subject segment.
- `Output_GetSegmentStaticRotationHelical` [GetSegmentStaticRotationHelical](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment in helical coordinates.
- `Output_GetSegmentStaticRotationMatrix` [GetSegmentStaticRotationMatrix](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment as a 3x3 row-major matrix.
- `Output_GetSegmentStaticRotationQuaternion` [GetSegmentStaticRotationQuaternion](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment in quaternion coordinates.
- `Output_GetSegmentStaticRotationEulerXYZ` [GetSegmentStaticRotationEulerXYZ](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment in Euler XYZ coordinates.
- `Output_GetSegmentGlobalTranslation` [GetSegmentGlobalTranslation](#) (const String &SubjectName, const String &SegmentName) const
Return the translation of a subject segment in global coordinates.
- `Output_GetSegmentGlobalRotationHelical` [GetSegmentGlobalRotationHelical](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in global helical coordinates.
- `Output_GetSegmentGlobalRotationMatrix` [GetSegmentGlobalRotationMatrix](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment as a 3x3 row-major matrix in global coordinates.
- `Output_GetSegmentGlobalRotationQuaternion` [GetSegmentGlobalRotationQuaternion](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in global quaternion coordinates.
- `Output_GetSegmentGlobalRotationEulerXYZ` [GetSegmentGlobalRotationEulerXYZ](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in global Euler XYZ coordinates.
- `Output_GetSegmentLocalTranslation` [GetSegmentLocalTranslation](#) (const String &SubjectName, const String &SegmentName) const
Return the translation of a subject segment in local coordinates relative to its parent segment.
- `Output_GetSegmentLocalRotationHelical` [GetSegmentLocalRotationHelical](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in local helical coordinates relative to its parent segment.

- `Output_GetSegmentLocalRotationMatrix` [GetSegmentLocalRotationMatrix](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation row-major matrix of a subject segment in local coordinates relative to its parent segment.
- `Output_GetSegmentLocalRotationQuaternion` [GetSegmentLocalRotationQuaternion](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in local quaternion coordinates relative to its parent segment.
- `Output_GetSegmentLocalRotationEulerXYZ` [GetSegmentLocalRotationEulerXYZ](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in local Euler XYZ coordinates relative to its parent segment.
- `Output_GetObjectQuality` [GetObjectQuality](#) (const String &ObjectName) const
Return the quality score for a specified Object (Subject).
- `Output_GetMarkerCount` [GetMarkerCount](#) (const String &SubjectName) const
Return the number of markers for a specified subject in the DataStream.
- `Output_GetMarkerName` [GetMarkerName](#) (const String &SubjectName, const unsigned int MarkerIndex) const
Return the name of a marker for a specified subject.
- `Output_GetMarkerParentName` [GetMarkerParentName](#) (const String &SubjectName, const String &MarkerName) const
Return the name of the segment that is the parent of this marker.
- `Output_GetMarkerGlobalTranslation` [GetMarkerGlobalTranslation](#) (const String &SubjectName, const String &MarkerName) const
Return the translation of a subject marker in global coordinates.
- `Output_GetMarkerRayContributionCount` [GetMarkerRayContributionCount](#) (const String &SubjectName, const String &MarkerName) const
Return the number of rays that are contributing to a labeled marker in the DataStream.
- `Output_GetMarkerRayContribution` [GetMarkerRayContribution](#) (const String &SubjectName, const String &MarkerName, unsigned int MarkerRayContributionIndex) const
Return the camera ID for an indexed ray that is contributing to a labeled marker in the DataStream.
- `Output_GetUnlabeledMarkerCount` [GetUnlabeledMarkerCount](#) () const
Return the number of unlabeled markers in the DataStream.
- `Output_GetUnlabeledMarkerGlobalTranslation` [GetUnlabeledMarkerGlobalTranslation](#) (const unsigned int MarkerIndex) const
Return the translation of an unlabeled marker in global coordinates.
- `Output_GetLabeledMarkerCount` [GetLabeledMarkerCount](#) () const
Returns the number of all labeled markers in the datastream across all subjects.
- `Output_GetLabeledMarkerGlobalTranslation` [GetLabeledMarkerGlobalTranslation](#) (const unsigned int MarkerIndex) const
Return the translation of a labeled marker in global coordinates.
- `Output_GetDeviceCount` [GetDeviceCount](#) () const
Return the number of force plates, EMGs, and other devices in the DataStream.
- `Output_GetDeviceName` [GetDeviceName](#) (const unsigned int DeviceIndex) const
Return the name and type of a device.
- `Output_GetDeviceOutputCount` [GetDeviceOutputCount](#) (const String &DeviceName) const
Return the number of outputs for a device in the DataStream.
- `Output_GetDeviceOutputName` [GetDeviceOutputName](#) (const String &DeviceName, const unsigned int DeviceOutputIndex) const

Return the name and SI unit of a device output.

- Output_GetDeviceOutputValue [GetDeviceOutputValue](#) (const String &DeviceName, const String &DeviceOutputName) const

Return the value of a device output.

- Output_GetDeviceOutputSubsamples [GetDeviceOutputSubsamples](#) (const String &DeviceName, const String &DeviceOutputName) const

Return the number of samples available for the specified device at the current frame.

- Output_GetDeviceOutputValue [GetDeviceOutputValue](#) (const String &DeviceName, const String &DeviceOutputName, const unsigned int Subsample) const

Return the value of a device output.

- Output_GetForcePlateCount [GetForcePlateCount](#) () const

Return the number of force plates available in the DataStream.

- Output_GetGlobalForceVector [GetGlobalForceVector](#) (const unsigned int ForcePlateIndex) const

Return the force vector for the force plate in global coordinates.

- Output_GetGlobalMomentVector [GetGlobalMomentVector](#) (const unsigned int ForcePlateIndex) const

Return the moment vector for the force plate in global coordinates.

- Output_GetGlobalCentreOfPressure [GetGlobalCentreOfPressure](#) (const unsigned int ForcePlateIndex) const

Return the center of pressure for the force plate in global coordinates.

- Output_GetForcePlateSubsamples [GetForcePlateSubsamples](#) (const unsigned int ForcePlateIndex) const

Return the number of subsamples available for a specified plate in the current frame.

- Output_GetGlobalForceVector [GetGlobalForceVector](#) (const unsigned int ForcePlateIndex, const unsigned int Subsample) const

Return the force vector for the plate in global coordinates.

- Output_GetGlobalMomentVector [GetGlobalMomentVector](#) (const unsigned int ForcePlateIndex, const unsigned int Subsample) const

Return the moment vector for the plate in global coordinates.

- Output_GetGlobalCentreOfPressure [GetGlobalCentreOfPressure](#) (const unsigned int ForcePlateIndex, const unsigned int Subsample) const

Return the center of pressure for the plate in global coordinates.

- Output_GetEyeTrackerCount [GetEyeTrackerCount](#) () const

Return the number of eye trackers available in the DataStream.

- Output_GetEyeTrackerGlobalPosition [GetEyeTrackerGlobalPosition](#) (const unsigned int EyeTrackerIndex) const

Return the location of the eye.

- Output_GetEyeTrackerGlobalGazeVector [GetEyeTrackerGlobalGazeVector](#) (const unsigned int EyeTrackerIndex) const

Return the gaze direction as a unit vector in global coordinates.

- Output_GetCameraCount [GetCameraCount](#) () const

Return the number of cameras available in the DataStream.

- Output_GetCameraName [GetCameraName](#) (unsigned int CameraIndex) const

Return the name of a camera.

- Output_GetCameraId [GetCameraId](#) (const std::string &CameraName) const

Returns the internal ID of the camera with the specified name.

- Output_GetCameraUserId [GetCameraUserId](#) (const std::string &CameraName) const

Returns the user-assigned ID of the camera with the specified name.

- Output_GetCameraType [GetCameraType](#) (const std::string &CameraName) const
Returns the type of the camera with the specified name.
- Output_GetCameraDisplayName [GetCameraDisplayName](#) (const std::string &CameraName) const
Returns the name of of the camera type as a string suitable for display to a user.
- Output_GetCameraResolution [GetCameraResolution](#) (const std::string &CameraName) const
Returns the sensor resolution of the camera with the specified name.
- Output_GetIsVideoCamera [GetIsVideoCamera](#) (const std::string &CameraName) const
Returns whether the camera with the specified name is a video camera.
- Output_GetCentroidCount [GetCentroidCount](#) (const std::string &CameraName) const
Return the number of centroids reported by a named camera.
- Output_GetCentroidPosition [GetCentroidPosition](#) (const std::string &CameraName, const unsigned int CentroidIndex) const
Return the position and radius of the centroid in camera coordinates.
- Output_GetCentroidWeight [GetCentroidWeight](#) (const std::string &CameraName, const unsigned int CentroidIndex) const
Return the weight of the centroid.
- Output_GetGreyscaleBlobCount [GetGreyscaleBlobCount](#) (const std::string &CameraName) const
Obtain the number of greyscale blobs that are available for the specified camera.
- Output_GetGreyscaleBlob [GetGreyscaleBlob](#) (const std::string &CameraName, const unsigned int i_BlobIndex) const
Obtains greyscale blob data for the specified camera and blob index.
- Output_GetVideoFrame [GetVideoFrame](#) (const std::string &CameraName) const
Obtains video data for the specified camera.
- Output_SetCameraFilter [SetCameraFilter](#) (const std::vector< unsigned int > &CameraIdsForCentroids, const std::vector< unsigned int > &CameraIdsForBlobs, const std::vector< unsigned int > &CameraIdsForVideo)
Add a filter to allow centroid, blob or video data being transmitted only for the specified cameras.

Constructor & Destructor Documentation

Client ()

Construction.

You can create many instances of the Vicon DataStream [Client](#) which can connect to multiple Vicon DataStream Servers.

C example

```
// The C version uses explicit creation methods

CClient * pClient = ClientCreate();
// C Client functions take the client as a parameter
CBool ok = Client_SomeFunction( pClient, Args );
// The C client needs to be explicitly destroyed
Client_Destroy( pClient );
```

C++ example

```
// C++ version of the SDK is object oriented, so use the class constructor.

ViconDataStreamSDK::CPP::Client StackClient;
Output_SomeFunction Output = StackClient.SomeFunction();
// Client is implicitly destroyed as it goes out of scope.

// Alternatively the Client can be made on the heap.

ViconDataStreamSDK::CPP::Client * pHeapClient
= new ViconDataStreamSDK::CPP::Client();
Output_SomeFunction Output = pHeapClient->SomeFunction( Input );
delete pHeapClient;
```

MATLAB example

```
% The MATLAB SDK is object oriented, and needs to be explicitly loaded
and unloaded.

Client.LoadViconDataStreamSDK();
pHeapClient = Client();
Output = pHeapClient.SomeFunction(Input);
Client.UnloadViconDataStreamSDK();
```

.NET example

```
///.NET is object oriented, so use the class constructor. Because objects are
// lazily garbage collected, your instance may outlive the last reference to it
// for some time.If the instance is pre - fetching frame data for you, then it
// can still use CPU and network bandwidth.Consider explicitly disconnecting
// prior to destruction.

ViconDataStreamSDK.DotNET.Client pHeapClient = new ViconDataStreamSDK.DotNET.Client();
Output_SomeFunction Output = pHeapClient.SomeFunction(InputParam);
// Signal to the garbage collector that it can clean up pHeapClient.Disconnect();
pHeapClient = null;
```

~Client() [virtual]

Destruction.

Destruction will Disconnect if required.

See [Client::Client](#) for an example.

Member Function Documentation

Output_GetVersion GetVersion () const

Get the version of the Vicon DataStream SDK.

- Major When this number increases, we break backward compatibility with previous major versions.
- Minor When this number increases, we have probably added new functionality to the SDK without breaking backward compatibility with previous versions.
- Point When this number increases, we have introduced a bug fix or performance enhancement without breaking backward compatibility with previous versions.

The function can be called without the client being connected.

C example

```
CClient * pClient = Client_Create();
COutput_GetVersion Output = Client_GetVersion( pClient );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_GetVersion Output = MyClient.GetVersion();
```

MATLAB example

```
MyClient = Client();
Output = MyClient.GetVersion();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_GetVersion Output = MyClient.GetVersion();
```

Returns

Output_GetVersion class containing the version information.

Output_Connect Connect (const String & HostName)

Establish a dedicated connection to a Vicon DataStream Server.

See Also: [ConnectToMulticast\(\)](#), [Disconnect\(\)](#), [IsConnected\(\)](#).

The function defaults to connecting on port 801. You can specify an alternate port number after a colon. This is for future compatibility: current products serve data on port 801 only.

C example

```
CClient * pClient = Client_Create();
COutput_Connect Output = Client_Connect( pClient, "localhost");
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_Connect Output = MyClient.Connect( "localhost" );
```

MATLAB example

```
MyClient = Client();
Output = MyClient.Connect('localhost:801');
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_Connect Output = MyClient.Connect("localhost:801");
```

Parameters

HostName	The DNS-identifiable name, or IP address of the PC hosting the DataStream server. For example: <ul style="list-style-type: none"> • "localhost" • "MyViconPC:801" • "10.0.0.2"
----------	---

Returns

An Output_Connect class containing the result of the connect operation.

- The Result will be:
 - Success
 - InvalidHostName
 - ClientAlreadyConnected
 - ClientConnectionFailed

Output_ConnectToMulticast ConnectToMulticast (const String & LocalIP, const String & MulticastIP)

Connect to a Vicon DataStream Server's Multicast stream.

The stream content is managed by a client who calls [StartTransmittingMulticast\(\)](#).

See Also: [Connect\(\)](#), [Disconnect\(\)](#), [IsConnected\(\)](#), [StartTransmittingMulticast\(\)](#), [StopTransmittingMulticast\(\)](#)

```
// class Output_ConnectToMulticast
// {
//     public:
//         Result::Enum Result;
// };
```

C example

```
CClient * pClient = Client_Create();
COutput_Connect Output = Client_ConnectToMulticast( pClient, "localhost", "224.0.0.0" );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_ConnectToMulticast Output = MyClient.ConnectToMulticast( "localhost", "224.0.0.0" );
```

MATLAB example

```
MyClient = Client();
Output = MyClient.ConnectToMulticast('localhost', '224.0.0.0');
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_ConnectToMulticast Output = MyClient.ConnectToMulticast("localhost", "224.0.0.0");
```

Parameters

LocalIP	The DNS-identifiable name, or IP address of the local Ethernet interface on which you wish to receive multicast data. Do not specify a port (any port specified will be ignored). For example: <ul style="list-style-type: none"> "localhost" "10.0.0.2"
MulticastIP	The IP Address of the Multicast group on which data will be received. The address must be in the range 224.0.0.0-239.255.255.255 You may also specify a port by appending it to the end of the IP Address after a colon, e.g. 224.0.0.0:30001. If you do not specify a port it will default to 44801.

Returns

An Output_ConnectToMulticast class containing the result of the connect operation.

- The Result will be:
 - Success
 - InvalidHostName

- InvalidMulticastIP
- ClientAlreadyConnected
- ClientConnectionFailed

Output_Disconnect Disconnect ()

Disconnect from the Vicon DataStream Server.

See Also: [Connect\(\)](#), [IsConnected\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
COutput_Disconnect Output = Client_Disconnect( pClient );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_Disconnect Output = MyClient.Disconnect();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect("localhost");
Output = MyClient.Disconnect()
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect("localhost");
Output_Disconnect Output = MyClient.Disconnect();
```

Returns

An Output_Disconnect class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_IsConnected IsConnected () const

Discover whether client is connected to the Vicon DataStream Server.

See Also: [Connect\(\)](#), [Disconnect\(\)](#)

C example

```
CClient * pClient = Client_Create();
CBool Output = Client_IsConnected( pClient );
// Output == 0
Client_Connect( pClient, "localhost" );
Output = Client_IsConnected( pClient );
// Output == 1
COutput_Disconnect Output = Client_Disconnect( pClient );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == false
MyClient.Connect( "localhost" );
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == true
// (assuming localhost is serving)
```

MATLAB example

```
MyClient = Client();
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == false
MyClient.Connect( "localhost" );
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == true
// (assuming localhost is serving)
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == false
MyClient.Connect( "localhost" );
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == true
// (assuming localhost is serving)
```

Returns

An `Output_IsConnected` class containing a true value for `Connected` if you are connected to the stream, otherwise false.

Output_StartTransmittingMulticast StartTransmittingMulticast (const String & ServerIP, const String & MulticastIP)

Ask the DataStream Server to start transmitting the data you are receiving directly to a Multicast address as well.

This allows multiple clients to connect to your stream (via [ConnectToMulticast\(\)](#)) whilst minimizing network bandwidth use and frame delivery latency.

See Also: [Connect\(\)](#), [ConnectToMulticast\(\)](#), [Disconnect\(\)](#), [StopTransmittingMulticast\(\)](#) C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_StartTransmittingMulticast( pClient, "10.0.0.1", "224.0.0.0" );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.StartTransmittingMulticast( "10.0.0.1", "224.0.0.0" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.StartTransmittingMulticast( "10.0.0.1", "224.0.0.0" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.StartTransmittingMulticast( "10.0.0.1", "224.0.0.0" );
```

Parameters

ServerIP	The IP Address of the server Ethernet interface from which the Multicast data will be sent. Do not specify a port number (any port number specified will be ignored).
MulticastIP	The IP Address of the Multicast group to which Multicast data will be sent. The address must be in the range 224.0.0.0-239.255.255.255. You may also specify the port the data will be sent to by appending it to the IP Address after a colon, e.g. 224.0.0.0:30001. If you do not specify a port it will default to 44801.

Returns

An Output_StartTransmittingMulticast class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidMulticastIP
 - ServerAlreadyTransmittingMulticast

Output_StopTransmittingMulticast StopTransmittingMulticast ()

Ask the DataStream Server to stop transmitting the data you are receiving directly to a Multicast address as well.

You must previously have started a transmission via StartTransmittingMulticast.

See Also: [Connect\(\)](#), [ConnectToMulticast\(\)](#), [Disconnect\(\)](#), [StartTransmittingMulticast\(\)](#) C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_StartTransmittingMulticast( pClient, "10.0.0.1", "224.0.0.0" );
// Do some stuff
Client_StopTransmittingMulticast( pClient );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.StartTransmittingMulticast( "10.0.0.1", "224.0.0.0" );
// Do some stuff
MyClient.StopTransmittingMulticast();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.StartTransmittingMulticast( "10.0.0.1", "224.0.0.0" );
// Do some stuff
MyClient.StopTransmittingMulticast();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.StartTransmittingMulticast( "10.0.0.1", "224.0.0.0" );
// Do some stuff
MyClient.StopTransmittingMulticast();
```

Returns

An Output_StopTransmittingMulticast class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - ServerNotTransmittingMulticast

Output_EnableSegmentData EnableSegmentData ()

Enable kinematic segment data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read local or global segment data.

See Also: [IsSegmentDataEnabled\(\)](#), [DisableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableUnlabeledMarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetSegmentCount\(\)](#), [GetSegmentName\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableSegmentData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableSegmentData Output = MyClient.EnableSegmentData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output_EnableSegmentData Output = MyClient.EnableSegmentData();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableSegmentData Output = MyClient.EnableSegmentData();
```

Returns

An `Output_EnableSegmentData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableMarkerData EnableMarkerData ()

Enable labeled reconstructed marker data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read labeled marker data.

See Also: [IsMarkerDataEnabled\(\)](#), [DisableMarkerData\(\)](#), [EnableSegmentData\(\)](#), [EnableUnlabeled-MarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetMarkerCount\(\)](#), [GetMarkerName\(\)](#), [GetMarkerGlobal-Translation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableMarkerData Output = MyClient.EnableMarkerData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output_EnableMarkerData Output = MyClient.EnableMarkerData();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableMarkerData Output = MyClient.EnableMarkerData();
```

Returns

An `Output_EnableMarkerData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableUnlabeledMarkerData EnableUnlabeledMarkerData ()

Enable unlabeled reconstructed marker data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read global unlabeled marker data.

See Also: [IsUnlabeledMarkerDataEnabled\(\)](#), [DisableUnlabeledMarkerData\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetUnlabeledMarkerCount\(\)](#), [GetUnlabeledMarkerGlobalTranslation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableUnlabeledMarkerData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableUnlabeledMarkerData Output = MyClient.EnableUnlabeledMarkerData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output_EnableUnlabeledMarkerData Output = MyClient.EnableUnlabeledMarkerData();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableUnlabeledMarkerData Output = MyClient.EnableUnlabeledMarkerData();
```

Returns

An `Output_UnlabeledMarkerData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

ViconDataStreamSDK::CPP::Output_EnableMarkerRayData EnableMarkerRayData ()

Enable information about the rays contributing to each labeled marker in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read global unlabeled marker data.

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerRayData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableMarkerRayData Output = MyClient.EnableMarkerRayData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.EnableMarkerRayData();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableMarkerRayData Output = MyClient.EnableMarkerRayData();
```

See Also: [IsMarkerRayDataEnabled\(\)](#), [DisableMarkerRayData\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetUnlabeledMarkerCount\(\)](#), [GetUnlabeledMarkerGlobalTranslation\(\)](#)

Returns

An Output_EnableMarkerRayData class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableDeviceData EnableDeviceData ()

Enable force plate, EMG, and other device data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read device information.

See Also: [IsDeviceDataEnabled\(\)](#), [DisableDeviceData\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableUnlabeledMarkerData\(\)](#), [GetDeviceCount\(\)](#), [GetDeviceName\(\)](#), [GetDeviceOutputCount\(\)](#), [GetDeviceOutputName\(\)](#), [GetDeviceOutputValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableDeviceData Output = MyClient.EnableDeviceData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.EnableDeviceData();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableDeviceData Output = MyClient.EnableDeviceData();
```

Returns

An `Output_EnableDeviceData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableCentroidData EnableCentroidData ()

Enable centroid data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read centroid information.

See Also: [IsCentroidDataEnabled\(\)](#), [DisableCentroidData\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableCentroidData Output = MyClient.EnableCentroidData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.EnableCentroidData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableCentroidData Output = MyClient.EnableCentroidData ();
```

Returns

An `Output_EnableCentroidData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableGreyscaleData EnableGreyscaleData ()

Enable greyscale data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read greyscale information.

See Also: [IsGreyscaleDataEnabled\(\)](#), [DisableGreyscaleData\(\)](#)

C example

Not implemented

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableGreyscaleData Output = MyClient.EnableGreyscaleData();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableGreyscaleData Output = MyClient.EnableGreyscaleData ();
```

Returns

An Output_EnableGreyscaleData class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableVideoData EnableVideoData ()

Enable video data in the Vicon DataStream.

Call this function on startup, after connecting to the server, and before trying to read video information.

See Also: [IsVideoDataEnabled\(\)](#), [DisableVideoData\(\)](#)

C example

Not implemented

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableVideoData Output = MyClient.EnableVideoData();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableVideoData Output = MyClient.EnableVideoData ();
```

Returns

An Output_EnableVideoData class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_EnableDebugData EnableDebugData ()

Enable debug data in the Vicon DataStream.

Call this function on startup, after connecting to the server in order to receive debug data.

See Also: [IsDebugEnabled\(\)](#), [DisableDebugData\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDebugData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_EnableDebugData Output = MyClient.EnableDebugData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.EnableDebugData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_EnableDebugData Output = MyClient.EnableDebugData ();
```

Returns

An `Output_EnableDebugData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableSegmentData DisableSegmentData ()

Disable kinematic segment data in the Vicon DataStream.

See Also: [IsSegmentDataEnabled\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableUnlabeledMarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetSegmentCount\(\)](#), [GetSegmentName\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableSegmentData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableSegmentData Output = MyClient.DisableSegmentData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableSegmentData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableSegmentData Output = MyClient.DisableSegmentData ();
```

Returns

An `Output_DisableSegmentData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableMarkerData DisableMarkerData ()

Disable labeled reconstructed marker data in the Vicon DataStream.

See Also: [IsMarkerDataEnabled\(\)](#), [EnableMarkerData\(\)](#), [EnableSegmentData\(\)](#), [EnableUnlabeled-MarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetMarkerCount\(\)](#), [GetMarkerName\(\)](#), [GetMarkerGlobal-Translation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableMarkerData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableMarkerData Output = MyClient.DisableMarkerData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableMarkerData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableMarkerData Output = MyClient.DisableMarkerData ();
```

Returns

An `Output_DisableMarkerData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableUnlabeledMarkerData DisableUnlabeledMarkerData ()

Disable unlabeled reconstructed marker data in the Vicon DataStream.

See Also: [IsUnlabeledMarkerDataEnabled\(\)](#), [EnableUnlabeledMarkerData\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetUnlabeledMarkerCount\(\)](#), [GetUnlabeledMarkerGlobalTranslation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableUnlabeledMarkerData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableUnlabeledMarkerData Output = MyClient.DisableUnlabeledMarkerData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableUnlabeledMarkerData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableUnlabeledMarkerData Output = MyClient.DisableUnlabeledMarkerData ();
```

Returns

An `Output_DisableUnlabeledMarkerData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

ViconDataStreamSDK::CPP::Output_DisableMarkerRayData DisableMarkerRayData ()

Disable unlabeled reconstructed marker data in the Vicon DataStream.

See Also: [IsMarkerRayDataEnabled\(\)](#), [EnableMarkerRayData\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableDeviceData\(\)](#), [GetUnlabeledMarkerCount\(\)](#), [GetUnlabeledMarkerGlobalTranslation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableMarkerRayData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableMarkerRayData Output = MyClient.DisableMarkerRayData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableMarkerRayData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableMarkerRayData Output = MyClient.DisableMarkerRayData ();
```

Returns

An `Output_DisableMarkerRayData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableDeviceData DisableDeviceData ()

Disable force plate, EMG, and other device data in the Vicon DataStream.

See Also: [IsDeviceDataEnabled\(\)](#), [EnableDeviceData\(\)](#), [EnableSegmentData\(\)](#), [EnableMarkerData\(\)](#), [EnableUnlabeledMarkerData\(\)](#), [GetDeviceCount\(\)](#), [GetDeviceName\(\)](#), [GetDeviceOutputCount\(\)](#), [GetDeviceOutputName\(\)](#), [GetDeviceOutputValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableDeviceData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableDeviceData Output = MyClient.DisableDeviceData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableDeviceData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableDeviceData Output = MyClient.DisableDeviceData ();
```

Returns

An `Output_DisableDeviceData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableCentroidData DisableCentroidData ()

Disable centroid data in the Vicon DataStream.

See Also: [IsCentroidDataEnabled\(\)](#), [EnableCentroidData\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableCentroidData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableCentroidData Output = MyClient.DisableCentroidData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableCentroidData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableCentroidData Output = MyClient.DisableCentroidData ();
```

Returns

An `Output_DisableCentroidData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableGreyscaleData DisableGreyscaleData ()

Disable greyscale data in the Vicon DataStream.

See Also: [IsGreyscaleDataEnabled\(\)](#), [EnableGreyscaleData\(\)](#)

C example

Not implemented

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableGreyscaleData Output = MyClient.DisableGreyscaleData();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableGreyscaleData Output = MyClient.DisableGreyscaleData ();
```

Returns

An Output_DisableGreyscaleData class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableVideoData DisableVideoData ()

Disable video data in the Vicon DataStream.

See Also: [IsVideoDataEnabled\(\)](#), [EnableVideoData\(\)](#)

C example

Not implemented

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableVideoData Output = MyClient.DisableVideoData();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableVideoData Output = MyClient.DisableVideoData ();
```

Returns

An Output_DisableVideoData class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_DisableDebugData DisableDebugData ()

Disable debug data in the Vicon DataStream.

See Also: [IsDebugEnabled\(\)](#), [EnableDebugData\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_DisableDebugData();
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_DisableDebugData Output = MyClient.DisableDebugData();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.DisableDebugData ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_DisableDebugData Output = MyClient.DisableDebugData ();
```

Returns

An `Output_DisableDebugData` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_IsSegmentDataEnabled IsSegmentDataEnabled () const

Return whether kinematic segment data is enabled in the Vicon DataStream.

See Also: [EnableSegmentData\(\)](#), [DisableSegmentData\(\)](#), [IsMarkerDataEnabled\(\)](#), [IsUnlabeled-MarkerDataEnabled\(\)](#), [IsDeviceDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsSegmentDataEnabled( pClient )
// Output == 0
Client_EnabledSegmentData( pClient );
CBool Output = Client_IsSegmentDataEnabled( pClient )
// Output == 1
Client_EnableUnlabeledMarkerData( pClient );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsSegmentDataEnabled Output = MyClient.IsSegmentDataEnabled();
// Output.Enabled == false
MyClient.EnableSegmentData();
Output_IsSegmentDataEnabled Output = MyClient.IsSegmentDataEnabled();
// Output.Enabled == true
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.IsSegmentDataEnabled(); % Output.Enabled == false
MyClient.EnableSegmentData();
Output = MyClient.IsSegmentDataEnabled(); % Output.Enabled == true
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsSegmentDataEnabled Output = MyClient.IsSegmentDataEnabled();
// Output.Enabled == false
MyClient.EnableSegmentData();
Output_IsSegmentDataEnabled Output = MyClient.IsSegmentDataEnabled();
// Output.Enabled == true
```

Returns

An Output_IsSegmentDataEnabled class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsMarkerDataEnabled IsMarkerDataEnabled () const

Return whether labeled reconstructed marker data is enabled in the DataStream.

See Also: [EnableMarkerData\(\)](#), [DisableMarkerData\(\)](#), [IsSegmentDataEnabled\(\)](#), [IsUnlabeled-MarkerDataEnabled\(\)](#), [IsDeviceDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsMarkerDataEnabled( pClient );
// Output = 0;
Client_EnableMarkerData( pClient );
CBool Output = Client_IsMarkerDataEnabled( pClient );
// Output = 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsMarkerDataEnabled Output = MyClient.IsMarkerDataEnabled();
// Output.Enabled == false
MyClient.EnableMarkerData();
Output_IsMarkerDataEnabled Output = MyClient.IsMarkerDataEnabled();
// Output.Enabled == true
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.IsMarkerDataEnabled(); % Output.Enabled == false
MyClient.EnableMarkerData();
Output = MyClient.IsMarkerDataEnabled(); % Output.Enabled == true
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new
ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsMarkerDataEnabled Output = MyClient.IsMarkerDataEnabled();
// Output.Enabled == false
MyClient.EnableMarkerData();
Output_IsMarkerDataEnabled Output = MyClient.IsMarkerDataEnabled();
// Output.Enabled == true
```

Returns

An Output_IsMarkerDataEnabled class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsUnlabeledMarkerDataEnabled IsUnlabeledMarkerDataEnabled () const

Return whether unlabeled marker data is enabled in the DataStream.

See Also: [EnableUnlabeledMarkerData\(\)](#), [DisableUnlabeledMarkerData\(\)](#), [IsSegmentDataEnabled\(\)](#), [IsMarkerDataEnabled\(\)](#), [IsDeviceDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsUnlabeledMarkerDataEnabled( pClient );
// Output = 0;
Client_EnableUnlabeledMarkerData( pClient );
CBool Output = Client_IsUnlabeledMarkerDataEnabled( pClient );
// Output = 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsUnlabeledMarkerDataEnabled Output = MyClient.IsUnlabeledMarkerDataEnabled();
// Output.Enabled == false
MyClient.EnableUnlabeledMarkerData();
Output_IsUnlabeledMarkerDataEnabled Output = MyClient.IsUnlabeledMarkerDataEnabled();
// Output.Enabled == true
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.IsUnlabeledMarkerDataEnabled(); % Output.Enabled == false
MyClient.EnableUnlabeledMarkerData();
Output = MyClient.IsUnlabeledMarkerDataEnabled(); % Output.Enabled == true
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsUnlabeledMarkerDataEnabled Output = MyClient.IsMarkerDataEnabled();
// Output.Enabled == false
MyClient.EnableUnlabeledMarkerData();
Output_IsUnlabeledMarkerDataEnabled Output = MyClient.IsUnlabeledMarkerDataEnabled();
// Output.Enabled == true
```

Returns

An `Output_IsUnlabeledMarkerDataEnabled` class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

ViconDataStreamSDK::CPP::Output_IsMarkerRayDataEnabled IsMarkerRayDataEnabled () const

Return whether marker ray data is enabled in the DataStream.

See Also: [EnableMarkerRayData\(\)](#), [DisableMarkerRayData\(\)](#), [IsSegmentDataEnabled\(\)](#), [IsMarkerDataEnabled\(\)](#), [IsDeviceDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsMarkerRayDataEnabled( pClient );
// Output = 0;
Client_EnableMarkerRayData( pClient );
CBool Output = Client_IsMarkerRayDataEnabled( pClient );
// Output = 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsMarkerRayDataEnabled Output = MyClient.IsMarkerRayDataEnabled();
// Output.Enabled == false
MyClient.EnableMarkerRayData();
Output_IsMarkerRayDataEnabled Output = MyClient.IsMarkerRayDataEnabled();
// Output.Enabled == true
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.IsMarkerRayDataEnabled(); % Output.Enabled == false
MyClient.EnableMarkerRayData();
Output = MyClient.IsMarkerRayDataEnabled(); % Output.Enabled == true
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new
ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsMarkerRayDataEnabled Output = MyClient.IsMarkerDataEnabled();
// Output.Enabled == false
MyClient.EnableMarkerRayData();
Output_IsMarkerRayDataEnabled Output = MyClient.IsMarkerRayDataEnabled();
// Output.Enabled == true
```

Returns

An `Output_IsMarkerRayDataEnabled` class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsDeviceDataEnabled IsDeviceDataEnabled () const

Return whether force plate, EMG, and other device data is enabled in the DataStream.

See Also: [EnableDeviceData\(\)](#), [DisableDeviceData\(\)](#), [IsSegmentDataEnabled\(\)](#), [IsMarkerDataEnabled\(\)](#), [IsUnlabeledMarkerDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsDeviceDataDataEnabled( pClient );
// Output = 0;
Client_EnableDeviceDataData( pClient );
CBool Output = Client_IsDeviceDataDataEnabled( pClient );
// Output = 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsDeviceDataEnabled Output = MyClient.IsDeviceDataEnabled();
// Output.Enabled == false
MyClient.EnableDeviceData();
Output_IsDeviceDataEnabled Output = MyClient.IsDeviceDataEnabled();
Output.Enabled == true
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.IsDeviceDataEnabled(); % Output.Enabled == false
MyClient.EnableDeviceData();
Output = MyClient.IsDeviceDataEnabled(); % Output.Enabled == true
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsDeviceDataEnabled Output = MyClient.IsDeviceDataEnabled();
// Output.Enabled == false
MyClient.EnableDeviceData();
Output_IsDeviceDataEnabled Output = MyClient.IsDeviceDataEnabled();
// Output.Enabled == true
```

Returns

An Output_IsDeviceDataEnabled class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsCentroidDataEnabled IsCentroidDataEnabled () const

Return whether Centroid data is enabled in the DataStream.

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsCentroidDataDataEnabled( pClient );
// Output = 0;
Client_EnableCentroidDataData( pClient );
CBool Output = Client_IsCentroidDataDataEnabled( pClient );
// Output = 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsCentroidDataEnabled Output = MyClient.IsCentroidDataEnabled ();
// Output.Enabled == false
MyClient.EnableCentroidData();
Output_IsCentroidDataEnabled Output = MyClient.IsCentroidDataEnabled ();
// Output.Enabled == true
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.IsCentroidDataEnabled (); % Output.Enabled == false
MyClient.EnableCentroidData();
Output = MyClient.IsCentroidDataEnabled (); % Output.Enabled == true
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsCentroidDataEnabled Output = MyClient.IsCentroidDataEnabled ();
// Output.Enabled == false
MyClient.EnableCentroidData();
Output_IsCentroidDataEnabled Output = MyClient.IsCentroidDataEnabled ();
// Output.Enabled == true
```

See Also: [EnableCentroidData\(\)](#), [DisableCentroidData\(\)](#)

Returns

An `Output_IsCentroidDataEnabled` class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsGreyscaleDataEnabled IsGreyscaleDataEnabled () const

Return whether greyscale data is enabled in the DataStream.

See Also: [EnableGreyscaleData\(\)](#), [DisableGreyscaleData\(\)](#)

C example

Not implemented

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsGreyscaleDataEnabled Output = MyClient.IsGreyscaleDataEnabled ();
// Output.Enabled == false
MyClient.EnableGreyscaleData();
Output_IsGreyscaleDataEnabled Output = MyClient.IsGreyscaleDataEnabled ();
// Output.Enabled == true
```

MATLAB example

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsGreyscaleDataEnabled Output = MyClient.IsGreyscaleDataEnabled ();
// Output.Enabled == false
MyClient.EnableGreyscaleData();
Output_IsGreyscaleDataEnabled Output = MyClient.IsGreyscaleDataEnabled ();
// Output.Enabled == true
```

Returns

An Output_IsGreyscaleDataEnabled class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsVideoDataEnabled IsVideoDataEnabled () const

Return whether video data is enabled in the DataStream.

See Also: [EnableVideoData\(\)](#), [DisableVideoData\(\)](#)

C example

Not implemented

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsVideoEnabled Output = MyClient.IsVideoDataEnabled ();
// Output.Enabled == false
MyClient.EnableVideoData();
Output_IsVideoDataEnabled Output = MyClient.IsVideoDataEnabled ();
// Output.Enabled == true
```

MATLAB example

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsVideoEnabled Output = MyClient.IsVideoDataEnabled ();
// Output.Enabled == false
MyClient.EnableVideoData();
Output_IsVideoDataEnabled Output = MyClient.IsVideoDataEnabled ();
// Output.Enabled == true
```

Returns

An Output_IsVideoDataEnabled class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

Output_IsDebugDataEnabled IsDebugDataEnabled () const

Return whether debug data is enabled in the DataStream.

See Also: [EnableDebugData\(\)](#), [DisableDebugData\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
CBool Output = Client_IsDebugDataEnabled( pClient );
// Output = 0;
Client_EnableDebugData( pClient );
CBool Output = Client_IsDebugDataEnabled( pClient );
// Output = 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_IsDebugDataEnabled Output = MyClient.IsDebugDataEnabled ();
// Output.Enabled == false
MyClient.EnableDebugData();
Output_IsDebugDataEnabled Output = MyClient.IsDebugDataEnabled ();
// Output.Enabled == true
```

MATLAB example

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_IsDebugDataEnabled Output = MyClient.IsDebugDataEnabled ();
// Output.Enabled == false
MyClient.EnableDebugData();
Output_IsDebugDataEnabled Output = MyClient.IsDebugDataEnabled ();
// Output.Enabled == true
```

Returns

An Output_IsDebugDataEnabled class containing the result of the operation.

- The Result will be:
 - Whether the data is enabled

void SetBufferSize (unsigned int BufferSize)

Set the number of frames that the client should buffer.

The default value is 1, which always supplies the latest frame. Choose higher values to reduce the risk of missing frames between calls.

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_SetBufferSize( 5 );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.SetBufferSize( 5 );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.SetBufferSize( 5 );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.SetBufferSize( 5 );
```

See Also: [GetFrame\(\)](#)

Parameters

BufferSize	The maximum number of frames to buffer.
------------	---

Returns

Nothing

Output_SetStreamMode SetStreamMode (const StreamMode::Enum Mode)

There are three modes that the SDK can operate in.

Each mode has a different impact on the [Client](#), Server, and network resources used.

- **ServerPush** In "ServerPush" mode, the Server pushes every new frame of data over the network to the [Client](#). The Server will try not to drop any frames. This results in the lowest latency that can be achieved. If the [Client](#) is unable to read data at the rate it is being sent, then it is buffered, firstly in the [Client](#), then on the TCP/IP connection, and then at the Server. When all the buffers are full then frames may be dropped at the Server and the performance of the Server may be affected. The [GetFrame\(\)](#) method returns the most recently received frame if available, or blocks the calling thread if the most recently received frame has already been processed.
- **ClientPull** In "ClientPull" mode, the [Client](#) waits for a call to [GetFrame\(\)](#), and then requests the latest frame of data from the Server. This increases latency, because a request must be sent over the network to the Server, the Server has to prepare the frame of data for the [Client](#), and then the data must be sent back over the network. Network bandwidth is kept to a minimum, because the Server only sends what you need. The buffers are very unlikely to be filled, and Server performance is unlikely to be affected. The [GetFrame\(\)](#) method blocks the calling thread until the frame has been received.
- **ClientPullPreFetch** "ClientPullPreFetch" is an enhancement to the "ClientPull" mode. A thread in the SDK continuously and preemptively does a "ClientPull" on your behalf, storing the latest requested frame in memory. When you next call [GetFrame\(\)](#), the SDK returns the last requested frame that was cached in memory. [GetFrame\(\)](#) does not need to block the calling thread. As with normal "ClientPull", buffers are unlikely to fill up, and Server performance is unlikely to be affected. Latency is slightly reduced, but network traffic may increase if you request frames on behalf of the [Client](#) which are never used. The stream defaults to "ClientPull" mode as this is considered the safest option. If performance is a problem, try "ClientPullPreFetch" followed by "ServerPush".

See Also: [GetFrame\(\)](#), [GetLatencyTotal\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_SetStreamMode( pClient, ServerPush );
Client_SetStreamMode( pClient, ClientPull );
Client_SetStreamMode( pClient, ClientPullPreFetch );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.SetStreamMode( ViconDataStreamSDK::CPP::StreamMode::ServerPush );
MyClient.SetStreamMode( ViconDataStreamSDK::CPP::StreamMode::ClientPull );
MyClient.SetStreamMode( ViconDataStreamSDK::CPP::StreamMode::ClientPullPreFetch );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.SetStreamMode( StreamMode.ServerPush );
MyClient.SetStreamMode( StreamMode.ClientPull );
MyClient.SetStreamMode( StreamMode.ClientPullPreFetch );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.SetStreamMode( ViconDataStreamSDK.DotNET.StreamMode.ServerPush );
MyClient.SetStreamMode( ViconDataStreamSDK.DotNET.StreamMode.ClientPull );
MyClient.SetStreamMode( ViconDataStreamSDK.DotNET.StreamMode.ClientPullPreFetch );
```

Parameters

Mode	Stream modes that the SDK can operate in
	<ul style="list-style-type: none"> • StreamMode.ServerPush • StreamMode.ClientPull • StreamMode.ClientPullPreFetch

Returns

An Output_SetStreamMode class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

ViconDataStreamSDK::CPP::Output_SetApexDeviceFeedback SetApexDeviceFeedback (const String & DeviceName, bool i_bOn)

Enable haptic feedback for the selected Apex device.

Apex device names may be obtained using GetDeviceCount, GetDeviceName

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
Client_SetApexDeviceFeedback( pClient, "ViconApex_01", true );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame()
Output_GetDeviceName DeviceName MyClient.GetDeviceName( 0 );
MyClient.SetApexDeviceFeedback( DeviceName.DeviceName, true );
```

MATLAB example

.NET example

Returns

An Output_SetApexDeviceFeedback class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidDeviceName
 - NullClient
 - HapticAlreadySet

Output_SetAxisMapping SetAxisMapping (const Direction::Enum XAxis, const Direction::Enum YAxis, const Direction::Enum ZAxis)

Remaps the 3D axis.

Vicon Data uses a right-handed coordinate system, with +X forward, +Y left, and +Z up. Other systems use different coordinate systems. The SDK can transform its data into any valid right-handed coordinate system by re-mapping each axis. Valid directions are "Up", "Down", "Left", "-Right", "Forward", and "Backward". Note that "Forward" means moving away from you, and "-Backward" is moving towards you. Common usages are Z-up: SetAxisMapping(Forward, Left, Up) Y-up: SetAxisMapping(Forward, Up, Right)

See Also: [GetAxisMapping\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_SetAxisMapping(pClient, Forward, Left, Up); // Z-up
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.SetAxisMapping( ViconDataStreamSDK::CPP::Direction::Forward,
ViconDataStreamSDK::CPP::Direction::Left,
ViconDataStreamSDK::CPP::Direction::Up );
```

MATLAB example

```
MyClient = Client();
MyClient.SetAxisMapping( Direction.Forward, Direction.Left, Direction.Up );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.SetAxisMapping( ViconDataStreamSDK.DotNET.Direction.Forward,
ViconDataStreamSDK.DotNET.Direction.Left,
ViconDataStreamSDK.DotNET.Direction.Up );
```

Parameters

XAxis	Specify the direction of your X axis relative to yourself as the observer.
YAxis	Specify the direction of your Y axis relative to yourself as the observer.
ZAxis	Specify the direction of your Z axis relative to yourself as the observer.

Returns

An Output_SetAxisMapping class containing the result of the operation.

- The Result will be:
 - Success
 - CoLinearAxes
 - LeftHandedAxes

Output_GetAxisMapping GetAxisMapping () const

Get the current Axis mapping.

See Also: [SetAxisMapping\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
COutput_GetAxisMapping _Output_GetAxisMapping;
Client_GetAxisMapping( pClient, &_Output_GetAxisMapping );
// _Output_GetAxisMapping.XAxis == Forward
// _Output_GetAxisMapping.YAxis == Left
// _Output_GetAxisMapping.ZAxis == Up
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_GetAxisMapping Output = MyClient.GetAxisMapping();
// Output.XAxis == ViconDataStreamSDK::CPP::Direction::Forward
// Output.YAxis == ViconDataStreamSDK::CPP::Direction::Left
// Output.ZAxis == ViconDataStreamSDK::CPP::Direction::Up
```

MATLAB example

```
MyClient = Client();
Output = MyClient.GetAxisMapping();
% Output.XAxis == Direction.Forward
% Output.YAxis == Direction.Left
% Output.ZAxis == Direction.Up
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_GetAxisMapping Output = MyClient.GetAxisMapping();
// Output.XAxis == ViconDataStreamSDK.DotNET.Direction.Forward
// Output.YAxis == ViconDataStreamSDK.DotNET.Direction.Left
// Output.ZAxis == ViconDataStreamSDK.DotNET.Direction.Up
```

Returns

An Output_GetAxisMapping class containing the result of the operation.

- The Result will be:
 - XAxis, YAxis, ZAxis

Output_GetFrame GetFrame ()

Request a new frame to be fetched from the Vicon DataStream Server.

See Also: [SetStreamMode\(\)](#)

C example

```
CClient * pClient = Client_Create();
CEnum Output = Client_GetFrame( pClient ); // Output == NotConnected
Client_Connect( pClient, "localhost" );
Output = Client_GetFrame( pClient ); // Output == Success
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_GetFrame Output;
Output = MyClient.GetFrame(); // Output.Result == NotConnected
MyClient.Connect( "localhost" );
Output = MyClient.GetFrame(); // Output.Result == Success
```

MATLAB example

```
MyClient = Client();
Output = MyClient.GetFrame(); // Output.Result == NotConnected
MyClient.Connect( "localhost" );
Output = MyClient.GetFrame(); // Output.Result == Success
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_GetFrame Output;
Output = MyClient.GetFrame(); // Output.Result == NotConnected
MyClient.Connect( "localhost" );
Output = MyClient.GetFrame(); // Output.Result == Success
```

Returns

An Output_GetFrame class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_GetFrameNumber GetFrameNumber () const

Return the number of the last frame retrieved from the DataStream.

See Also: [GetFrame\(\)](#), [GetTimecode\(\)](#)

C example

```
CClient * pClient = Client_Create();
COutput_GetFrameNumber _Output_GetFrameNumber;
Client_GetFrameNumber(pClient, &_Output_GetFrameNumber); // _Output_GetFrameNumber.FrameNumber == 0;
Client_Connect( pClient, "localhost" );
Client_GetFrameNumber(pClient, &_Output_GetFrameNumber); // _Output_GetFrameNumber.FrameNumber > 1;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_GetFrameNumber Output;
Output = MyClient.GetFrameNumber(); // Output.Result == NoFrame
// Output.FrameNumber == 0
MyClient.GetFrame();
Output = MyClient.GetFrameNumber(); // Output.Result == Success
// Output.FrameNumber >= 1
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Output = MyClient.GetFrameNumber(); % Output.Result == NoFrame
% Output.FrameNumber == 0
MyClient.GetFrame();
Output = MyClient.GetFrameNumber(); % Output.Result == Success
% Output.FrameNumber >= 1
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_GetFrameNumber Output;
Output = MyClient.GetFrameNumber(); // Output.Result == NoFrame
// Output.FrameNumber == 0
MyClient.GetFrame();
Output = MyClient.GetFrameNumber(); // Output.Result == Success
// Output.FrameNumber >= 1
```

Returns

An `Output_GetFrameNumber` class containing the result of the operation and the frame number.

- The Result will be:
 - Success
 - NotConnected

Output_GetTimecode GetTimecode () const

Return the timecode information for the last frame retrieved from the DataStream.

If the stream is valid but timecode is not available, the Output will be Result.Success and the Standard will be None.

See Also: [GetFrame\(\)](#), [GetFrameNumber\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetTimecode _Output_Timecode;
Client_GetTimecode( pClient, &_Output_Timecode );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetTimecode Output = MyClient.GetTimecode();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetTimecode();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetTimecode Output = MyClient.GetTimecode();
```

Returns

An Output_GetTimecode class containing the result of the operation and

- Hours
- Minutes
- Seconds
- Frames
- SubFrame
- FieldFlag
- Standard
- SubFramesPerFrame
- UserBits
- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetFrameRate GetFrameRate () const

Return the Vicon camera system frame rate (in Hz) at the time of the last frame retrieved from the DataStream.

See Also: [GetFrame\(\)](#), [GetFrameNumber\(\)](#), [GetTimecode\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetFrameRate Rate;
Client_GetFrameRate(pClient, &Rate);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRate Output = MyClient.GetFrameRate ();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetFrameRate ();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRate Output = MyClient.GetFrameRate ();
```

Returns

An Output_GetFrameRate class containing the result of the operation and the frame rate in hz.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetLatencySampleCount GetLatencySampleCount () const

Return the number of latency measurements that were taken at various stages of the real-time pipeline.

This value can be passed into [GetLatencySampleName\(\)](#).

See Also: [GetFrame\(\)](#), [GetTimecode\(\)](#), [GetLatencyTotal\(\)](#), [GetLatencySampleName\(\)](#), [GetLatencySampleValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetLatencySampleCount _Output_LatencySampleCount;
Client_GetLatencySampleCount( pClient, &_Output_LatencySampleCount );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencySampleCount Output = MyClient.GetLatencySampleCount();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetLatencySampleCount();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencySampleCount Output = MyClient.GetLatencySampleCount();
```

Returns

An `Output_GetLatencySampleCount` class containing the result of the operation and the number of samples taken.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetLatencySampleName GetLatencySampleName (const unsigned int LatencySampleIndex) const

Return the name of a latency sample.

This value can be passed into [GetLatencySampleValue\(\)](#).

See Also: [GetFrame\(\)](#), [GetTimecode\(\)](#), [GetLatencyTotal\(\)](#), [GetLatencySampleCount\(\)](#), [GetLatencySampleValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
char SampleName[128];
Client_GetLatencySampleName(pClient, 0, 128, SampleName);
// SampleName = "Data Collected"
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencySampleName Output = MyClient.GetLatencySampleName( 0 );
// Output.Name == "Data Collected"
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetLatencySampleName( 1 );
% Output.Name == 'Data Collected'
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencySampleName Output = MyClient.GetLatencySampleName( 0 );
Output.Name == "Data Collected"
```

Parameters

Latency-SampleIndex	The index of the name.
---------------------	------------------------

Returns

An `Output_GetLatencySampleName` class containing the result of the operation and the name of the latency sample.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetLatencySampleValue GetLatencySampleValue (const String & LatencySampleName) const

Return the duration of a named latency sample in seconds.

This value can be passed into [GetLatencySampleValue\(\)](#).

See Also: [GetFrame\(\)](#), [GetTimecode\(\)](#), [GetLatencyTotal\(\)](#), [GetLatencySampleCount\(\)](#), [GetLatencySampleValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetLatencySampleValue _Output_GetLatencySampleValue ;
Client_GetLatencySampleValue ( pClient, "Data Collected", &_Output_GetLatencySampleValue );
// _Output_GetLatencySampleValue.Value = 0.1
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencySampleValue Output =
MyClient.GetLatencySampleValue( "Data Collected" );
// Output.Value == 0.1
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetLatencySampleValue( 'Data Collected' );
% Output.Value == 0.1
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencySampleName Output =
MyClient.GetLatencySampleValue( "Data Collected" );
// Output.Value == 0.1
```

Parameters

Latency-SampleName	The name of the latency sample
--------------------	--------------------------------

Returns

An [Output_GetLatencySampleValue](#) class containing the result of the operation and the duration of the latency in seconds.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetLatencyTotal GetLatencyTotal () const

Return the total latency in seconds introduced at various stages of the real-time pipeline.

If no latency information is available then all latencies will be reported as o.o.

See Also: [GetFrame\(\)](#), [GetTimecode\(\)](#), [GetLatencySampleCount\(\)](#), [GetLatencySampleName\(\)](#), [GetLatencySampleValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetLatencyTotal _Output_GetLatencyTotal ;
Client_GetLatencyTotal ( pClient, &_Output_GetLatencyTotal );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencyTotal Output = MyClient.GetLatencyTotal();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetLatencyTotal();
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLatencyTotal Output = MyClient.GetLatencyTotal();
```

Returns

An `Output_GetLatencyTotal` class containing the result of the operation and the total latency in seconds made from summing the other latencies.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetHardwareFrameNumber GetHardwareFrameNumber () const

Returns the hardware frame number as used by the cameras.

This is not reset on synchronization.

See Also: [GetFrameNumber\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetHardwareFrameNumber _Output_GetHardwareFrameNumber ;
Client_GetHardwareFrameNumber ( pClient, &_Output_GetHardwareFrameNumber );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetHardwareFrameNumber Output = MyClient.GetHardwareFrameNumber();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetHardwareFrameNumber Output = MyClient.GetHardwareFrameNumber();
```

Returns

An `Output_GetHardwareFrameNumber` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_GetFrameRateCount GetFrameRateCount () const

Get the number of frame rate types that the server application reports.

See Also: [GetFrameRateName\(\)](#), [GetFrameRateValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetFrameRateCount _Output_GetFrameRateCount;
Client_GetFrameRateCount ( pClient, &_Output_GetFrameRateCount );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRateCount Output = MyClient.GetFrameRateCount();
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetFrameRateCount();
% Output.Count = 3
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRateCount Output = MyClient.GetFrameRateCount();
```

Returns

An Output_GetFrameRateCount class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_GetFrameRateName GetFrameRateName (const unsigned int FrameRateIndex) const

Get the name of a frame rate type at the specified index.

See Also: [GetFrameRateCount\(\)](#), [GetFrameRateValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
char FramerateName[128];
Client_GetFrameRateName(pClient, 0, 128, FramerateName);
Client_Destroy( pClient );
```

C++ example

```
A valid index is between 0 and GetFrameRateCount() - 1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRateCount Output = MyClient.GetFrameRateCount();
if( Output.Count > 0 )
{
    Output_GetFrameRateName NameOutput = MyClient.GetFrameRateIndex( 0 );
}
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetFrameRateName( 1 );
% Output.Name = 'name'
```

.NET example

```
A valid index is between 0 and GetFrameRateCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRateCount Output = MyClient.GetFrameRateCount();
if( Output.Count > 0 )
{
    Output_GetFrameRateName NameOutput = MyClient.GetFrameRateIndex( 0 );
}
```

Returns

An `Output_GetFrameRateName` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidIndex

Output_GetFrameRateValue GetFrameRateValue (const String & FrameRateName) const

Get the current value of the specified frame rate type.

See Also: [GetFrameRateCount\(\)](#), [GetFrameRateName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
char FramerateName[128];
Client_GetFrameRateName(pClient, 0, 128, FramerateName);
COutput_GetFrameRateValue FramerateValue;
Client_GetFrameRateValue(pClient, FramerateName, &FramerateValue);
Client_Destroy( pClient );
```

C++ example

```
A valid name is obtained from GetFrameRateName
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRateCount Output = MyClient.GetFrameRateCount();
Output_GetFrameRateName NameOutput = MyClient.GetFrameRateIndex( 0 );
Output_GetFrameRateValue ValueOutput = MyClient.GetFrameRateValue( NameOutput.Name );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
Output = MyClient.GetFrameRateName( 1 );
ValueOutput = MyClient.GetFrameRateValue( Output.Name );
% Output.Value = '200'
```

.NET example

```
A valid name is obtained from GetFrameRateName
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetFrameRateCount Output = MyClient.GetFrameRateCount();
Output_GetFrameRateName NameOutput = MyClient.GetFrameRateIndex( 0 );
Output_GetFrameRateValue ValueOutput = MyClient.GetFrameRateValue( NameOutput.Name );
```

Returns

An `Output_GetFrameRateValue` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidFrameRateName

Output_GetSubjectCount GetSubjectCount () const

Return the number of subjects in the DataStream.

This information can be used in conjunction with GetSubjectName.

See Also: [GetSubjectName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
COutput_GetSubjectCount SubjectCount;
Client_GetSubjectCount(pClient, &SubjectCount); // SubjectCount.Result == NoFrame
// SubjectCount.SubjectCount == 0;
Client_GetFrame( pClient );
Client_GetSubjectCount(pClient, &SubjectCount); // SubjectCount.Result == Success;
// SubjectCount.SubjectCount == 0;
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Output_GetSubjectCount Output;
Output = MyClient.GetSubjectCount(); // Output.Result == NoFrame
// Output.SubjectCount == 0
MyClient.GetFrame();
Output = MyClient.GetSubjectCount(); // Output.Result == Success
// Output.SubjectCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( 'localhost' );
Output = MyClient.GetSubjectCount(); % Output.Result == NoFrame
% Output.SubjectCount == 0
MyClient.GetFrame();
Output = MyClient.GetSubjectCount(); % Output.Result == Success
% Output.SubjectCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Output_GetSubjectCount Output;
Output = MyClient.GetSubjectCount(); // Output.Result == NoFrame
// Output.SubjectCount == 0
MyClient.GetFrame();
Output = MyClient.GetSubjectCount(); // Output.Result == Success
// Output.SubjectCount >= 0
```

Returns

An Output_GetSubjectCount class containing the result of the operation and the number of subjects.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetSubjectName GetSubjectName (const unsigned int SubjectIndex) const

Return the name of a subject.

This can be passed into segment and marker functions.

See Also: [GetSubjectCount\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
char SubjectName[128];
CEnum Output = Client_GetSubjectName(pClient, 0, 128, SubjectName);
// Output == Success
// SubjectName == "Al"
Output = Client_GetSubjectName(pClient, 1, 128, SubjectName);
// Output == Success
// SubjectName == "Bob"
Output = Client_GetSubjectName(pClient, 2, 128, SubjectName);
// Output == InvalidIndex
// SubjectName == ""

Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSubjectCount OutputGSC;
OutputGSC = MyClient.GetSubjectCount(); // OutputGSC.Result == Success
// OutputGSC.SubjectCount == 2
Output_GetSubjectName OutputGSN;
OutputGSN = MyClient.GetSubjectName(0); // OutputGSN.Result == Success
// OutputGSN.SubjectName == "Al"
OutputGSN = MyClient.GetSubjectName(1); // OutputGSN.Result == Success
// OutputGSN .SubjectName == "Bob"
OutputGSN = MyClient.GetSubjectName(2); // OutputGSN.Result == InvalidIndex
// OutputGSN.SubjectName == ""
```

MATLAB example

```
MyClient = Client;
MyClient.Connect( 'localhost' );
MyClient.GetFrame();
OutputGSC = MyClient.GetSubjectCount(); % OutputGSC.Result == Success
% OutputGSC.SubjectCount == 2
OutputGSN = MyClient.GetSubjectName(1); % OutputGSN.Result == Success
% OutputGSN.SubjectName == 'Al'
OutputGSN = MyClient.GetSubjectName(2); % OutputGSN.Result == Success
% OutputGSN .SubjectName == 'Bob'
OutputGSN = MyClient.GetSubjectName(3); % OutputGSN.Result == InvalidIndex
% OutputGSN.SubjectName == ''
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSubjectCount OutputGSC;
OutputGSC = MyClient.GetSubjectCount(); // OutputGSC.Result == Success
// OutputGSC.SubjectCount == 2
```

```
Output_GetSubjectName OutputGSN;
OutputGSN = MyClient.GetSubjectName(0); // OutputGSN.Result == Success
// OutputGSN.SubjectName == "A1"
OutputGSN = MyClient.GetSubjectName(1); // OutputGSN.Result == Success
// OutputGSN .SubjectName == "Bob"
OutputGSN = MyClient.GetSubjectName(2); // OutputGSN.Result == InvalidIndex
// OutputGSN.SubjectName == ""
```

Parameters

SubjectIndex	The index of the subject. A valid Subject Index is between 0 and GetSubjectCount() -1. Matlab: A valid Subject Index is between 1 and GetSubjectCount() .
--------------	---

Returns

An `Output_GetSubjectName` `GetSubjectName` class containing the result of the operation and the name of the subject.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetSubjectRootSegmentName GetSubjectRootSegmentName (const String & SubjectName) const

Return the name of the root segment for a specified subject.

This can be passed into segment functions. The root segment is the ancestor of all other segments in the subject.

See Also: [GetSegmentCount\(\)](#), [GetSegmentParentName\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableSegmentData( pClient );
Client_GetFrame( pClient );
char RootSegment[128];
CEnum Result = Client_GetSubjectRootSegmentName(pClient, "Bob", 128, RootSegment);
// Result == Success
// RootSegment == "Pelvis"
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSubjectRootSegmentName Output;
Output = MyClient.GetSubjectRootSegmentName( "Bob" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output = MyClient.GetSubjectRootSegmentName( "Bob" );
% Output.Result == Success
% Output.SegmentName == "Pelvis"
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSubjectRootSegmentName Output;
Output = MyClient.GetSubjectRootSegmentName( "Bob" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

Parameters

SubjectName	The name of the subject
-------------	-------------------------

Returns

An `Output_GetSubjectRootSegmentName` class containing the result of the operation and the name of the root segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetSegmentCount GetSegmentCount (const String & SubjectName) const

Return the number of segments for a specified subject in the DataStream.

This information can be used in conjunction with GetSegmentName.

See Also: [GetSubjectName\(\)](#), [GetSegmentName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
COutput_GetSegmentCount SegmentCount;
Client_GetSegmentCount( pClient, "Bob", &SegmentCount );
// SegmentCount.Result == NOFrame
// SegmentCount.Value == 0
Client_GetFrame( pClient );
Client_GetSegmentCount( pClient, "AI", &SegmentCount );
// SegmentCount.Result == InvalidSubjectName
// SegmentCount.Value == 0
Client_GetSegmentCount( pClient, "Bob", &SegmentCount );
// SegmentCount.Result == Success
// SegmentCount.Value >= 0

Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableSegmentData();
MyClient.Connect( "localhost" );
Output_GetSegmentCount Output;
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == NoFrame
// Output.SegmentCount == 0
MyClient.GetFrame();
Output = MyClient.GetSegmentCount( "AI" ); // Output.Result ==
// InvalidSubjectName
// Output.SegmentCount == 0
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == Success
// Output.SegmentCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableSegmentData();
MyClient.Connect( "localhost" );
Output = MyClient.GetSegmentCount( "Bob" ); % Output.Result == NoFrame
% Output.SegmentCount == 0
MyClient.GetFrame();
Output = MyClient.GetSegmentCount( "AI" ); % Output.Result ==
% InvalidSubjectName
% Output.SegmentCount == 0
Output = MyClient.GetSegmentCount( "Bob" ); % Output.Result == Success
% Output.SegmentCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableSegmentData();
MyClient.Connect( "localhost" );
Output_GetSegmentCount Output;
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == NoFrame
// Output.SegmentCount == 0
MyClient.GetFrame();
Output = MyClient.GetSegmentCount( "AI" ); // Output.Result ==
```

```
// InvalidSubjectName
// Output.SegmentCount == 0
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == Success
// Output.SegmentCount >= 0
```

Parameters

SubjectName	The name of the subject.
-------------	--------------------------

Returns

An Output_GetSegmentCount class containing the result of the operation and the number of segments.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetSegmentName GetSegmentName (const String & SubjectName, const unsigned int SegmentIndex) const

Return the name of a subject segment specified by index.

See Also: [GetSegmentCount\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#), [GetSubject-RootSegmentName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
char SegmentName[128];
// SegmentIndex must be between 0 and GetSegmentCount() - 1
Client_GetSegmentName(pClient, "Bob", 0, 128, SegmentName);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentName Output;
// SegmentIndex must be between 0 and GetSegmentCount() - 1
Output = MyClient.GetSegmentName( "Bob", 0 );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
% SegmentIndex must be between 1 and GetSegmentCount()
Output = MyClient.GetSegmentName( "Bob", 1 );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentParentName Output;
// SegmentIndex must be between 0 and GetSegmentCount() - 1
Output = MyClient.GetSegmentName( "Bob", 0 );
```

Parameters

SubjectName	The name of the subject
Segment-Index	The index of the segment

Returns

An Output_GetSegmentName class containing the result of the operation and the name of the parent segment or an empty string if it is the root segment.

- The Result will be:
 - Success

- NotConnected
- NoFrame
- InvalidIndex
- InvalidSubjectName

Output_GetSegmentChildCount GetSegmentChildCount (const String & SubjectName, const String & SegmentName) const

Return the number of child segment for a specified subject segment.

This can be passed into segment functions.

See Also: [GetSegmentCount\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentChildCount ChildCount;
Client_GetSegmentChildCount(pClient, "Bob", "Pelvis", &ChildCount);
// ChildCount.Result == Success
// ChildCount.SegmentCount == 2
Client_GetSegmentChildCount(pClient, "Alice", "Pelvis", &ChildCount);
// ChildCount.Result == InvalidSubjectName
// ChildCount.SegmentCount == 0

char SegmentName[128];
Client_GetSegmentName(pClient, "Bob", , 128, SegmentName);
Client_GetSegmentName(pClient, "Bob", &SegmentName);
// ChildCount.Result == Success
// ChildCount.SegmentCount == 2
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentChildCount OutputGSCC;
OutputGSCC = MyClient.GetSegmentChildCount( "Bob", "Pelvis" );
// OutputGSCC.Result == Success
// OutputGSCC.SegmentCount == 2
Output_GetSegmentChildName OutputGSCN;
OutputGSCN = MyClient.GetSegmentName( "Alice", 0 );
// OutputGSCN.Result == InvalidSubjectName
// OutputGSCN.SegmentName == ""
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 0 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "LFemur"
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 1 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "RFemur"
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 2 );
// OutputGSCN.Result == InvalidIndex
// OutputGSCN.SegmentName == ""
// (no third segment)
```

MATLAB example

```
A valid Segment Index is between 1 and GetSegmentChildCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
OutputGSCC = MyClient.GetSegmentChildCount( "Bob", "Pelvis" );
% OutputGSCC.Result == Success
% OutputGSCC.SegmentCount == 2
OutputGSCN = MyClient.GetSegmentChildName( "Alice", "Pelvis", 1 );
% OutputGSCN.Result == InvalidSubjectName
% OutputGSCN.SegmentName == ""
```

```
OutputGSCN = MyClient.GetSegmentChildName( "Bob", "Pelvis", 1 );
% OutputGSCN.Result == Success
% OutputGSCN.SegmentName == "LFemur"
OutputGSCN = MyClient.GetSegmentChildName( "Bob", "Pelvis", 2 );
% OutputGSCN.Result == Success
% OutputGSCN.SegmentName == "RFemur"
OutputGSCN = MyClient.GetSegmentChildName( "Bob", "Pelvis", 3 );
% OutputGSCN.Result == InvalidIndex
% OutputGSCN.SegmentName == ""
% (no third segment)
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentChildCount OutputGSCC;
OutputGSCC = MyClient.GetSegmentChildCount( "Bob", "Pelvis" );
// OutputGSCC.Result == Success
// OutputGSCC.SegmentCount == 2
Output_GetSegmentChildName OutputGSCN;
OutputGSCN = MyClient.GetSegmentChildName( "Alice", "Pelvis", 0 );
// OutputGSCN.Result == InvalidSubjectName
// OutputGSCN.SegmentName == ""
OutputGSCN = MyClient.GetSegmentChildName( "Bob", "Pelvis", 0 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "LFemur"
OutputGSCN = MyClient.GetSegmentChildName( "Bob", "Pelvis", 1 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "RFemur"
OutputGSCN = MyClient.GetSegmentChildName( "Bob", "Pelvis", 2 );
// OutputGSCN.Result == InvalidIndex
// OutputGSCN.SegmentName == ""
// (no third segment)
```

Parameters

SubjectName	The name of the subject
Segment- Name	The name of the segment

Returns

An `Output_GetSegmentChildCount` class containing the result of the operation and the number of child segments.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentChildName GetSegmentChildName (const String & SubjectName, const String & SegmentName, const unsigned int SegmentIndex) const

Return the name of the child segment for a specified subject segment and index.

See Also: [GetSegmentCount\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#), [GetSubject-RootSegmentName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableSegmentData( pClient );
Client_GetFrame( pClient );
char SegmentChildName[128];
// Segment index must be between 0 and Client_GetSegmentChildCount() - 1
Client_GetSegmentChildName( pClient, "Bob", "Pelvis", 0, 128, SegmentChildName );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentChildName Output;
// Segment index must be between 0 and GetSegmentChildCount() - 1
Output = MyClient.GetSegmentChildName( "Bob", "Pelvis", 0 );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
// Segment index must be between 1 and GetSegmentChildCount()
Output = MyClient.GetSegmentChildName( "Bob", "Pelvis", 1 );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentChildName Output;
// Segment index must be between 0 and GetSegmentChildCount() - 1
Output = MyClient.GetSegmentChildName( "Bob", "Pelvis", 0 );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment
Segment-Index	The index of the child segment. A valid Segment Index is between 0 and GetSegmentChildCount() -1.

Returns

An `Output_GetSegmentChildName` class containing the result of the operation and the name of the child segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentParentName GetSegmentParentName (const String & SubjectName, const String & SegmentName) const

Return the name of the parent segment for a specified subject segment.

If the specified segment is the root segment of the subject then it will return an empty string.

See Also: [GetSegmentCount\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#), [GetSubject-RootSegmentName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
char SegmentParentName[128];
CEnum Result = Client_GetSegmentParentName(pClient, "Bob", "Pelvis", 128, SegmentParentName);
// Result == Success
// SegmentParentName = ""
// This is the root segment
Result = Client_GetSegmentParentName(pClient, "Bob", "LFemur", 128, SegmentParentName);
// Result == Success
// SegmentParentName = "Pelvis"
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentParentName Output;
Output = MyClient.GetSegmentParentName( "Bob", "Pelvis" );
// Output.Result == Success
// Output.SegmentName == ""
// This is the root segment
Output = MyClient.GetSegmentParentName( "Bob", "LFemur" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output = MyClient.GetSegmentParentName( "Bob", "Pelvis" );
% Output.Result == Success
% Output.SegmentCount == ""
% This is the root segment
Output = MyClient.GetSegmentParentName( "Bob", "LFemur" );
% Output.Result == Success
% Output.SegmentCount == "Pelvis"
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentParentName Output;
Output = MyClient.GetSegmentParentName( "Bob", "Pelvis" );
// Output.Result == Success
// Output.SegmentName == ""
// This is the root segment
Output = MyClient.GetSegmentParentName( "Bob", "LFemur" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

Parameters

SubjectName	The name of the subject
Segment- Name	The name of the segment

Returns

An `Output_GetSegmentParentName` class containing the result of the operation and the name of the parent segment or an empty string if it is the root segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticTranslation GetSegmentStaticTranslation (const String & SubjectName, const String & SegmentName) const

Return the static pose translation of a subject segment.

The static translation of the segment corresponds to the PRE-POSITION element of the segment in the subject vsk. It is the base position of the segment, and is included in the value returned by GetLocalTranslation. If you are required to calculate the amount a segment has moved from its base position, subtract this value from the local translation.

See Also: [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegmentStaticRotationQuaternion\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentStaticTranslation _Output_GetSegmentStaticTranslation;
Client_GetSegmentStaticTranslation(pClient, "Alice", "Pelvis", &_Output_GetSegmentStaticTranslation);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentStaticTranslation Output =
MyClient.GetSegmentStaticTranslation( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output = MyClient.GetSegmentStaticTranslation( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStramSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentStaticTranslation Output =
MyClient.GetSegmentStaticTranslations( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An Output_GetSegmentStaticTranslation class containing the result of the operation and the translation of the segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticRotationHelical GetSegmentStaticRotationHelical (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment in helical coordinates.

The helical coordinates represent a vector whose length is the amount of rotation in radians, and the direction is the axis about which to rotate.

The static rotation of the segment corresponds to the PRE-ORIENTATION element of the segment in the subject vsk. It is the base rotation of the segment, and is included in the value returned by GetLocalRotation*. If you are required to calculate the amount a segment has rotated from its base position, subtract this value from the local rotation.

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegment-StaticRotationQuaternion\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation](#), [GetSegmentLocalRotationHelical](#), [GetSegmentLocalRotationMatrix](#), [GetSegmentLocalRotation-Quaternion](#), [GetSegmentLocalRotationEulerXYZ](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentStaticRotationHelical _Output_GetSegmentStaticRotationHelical;
Client_GetSegmentStaticRotationHelical(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationHelical);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationHelical Output =
MyClient.GetSegmentStaticRotationHelical( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetSegmentStaticRotationHelical( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationHelical Output =
MyClient.GetSegmentStaticRotationHelical( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An `Output_GetSegmentStaticRotationHelical` class containing the result of the operation and the rotation of the segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticRotationMatrix GetSegmentStaticRotationMatrix (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment as a 3x3 row-major matrix.

The static rotation of the segment corresponds to the PRE-ORIENTATION element of the segment in the subject vsk. It is the base rotation of the segment, and is included in the value returned by GetLocalRotation*. If you are required to calculate the amount a segment has rotated from its base position, subtract this value from the local rotation.

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationQuaternion\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentStaticRotationMatrix _Output_GetSegmentStaticRotationMatrix;
Client_GetSegmentStaticRotationMatrix(pClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationMatrix);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationMatrix Output =
MyClient.GetSegmentStaticRotationMatrix( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetSegmentStaticRotationMatrix( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationMatrix Output =
MyClient.GetSegmentStaticRotationMatrix( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An Output_GetSegmentStaticRotationMatrix class containing the result of the operation and the rotation of the segment.

- The Result will be:
 - Success

- NotConnected
- NoFrame
- InvalidSubjectName
- InvalidSegmentName

Output_GetSegmentStaticRotationQuaternion GetSegmentStaticRotationQuaternion (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment in quaternion coordinates.

The quaternion is of the form (x, y, z, w) where w is the real component and x, y and z are the imaginary components. N.B. This is different from that used in many other applications, which use (w, x, y, z).

The static rotation of the segment corresponds to the PRE-ORIENTATION element of the segment in the subject vsk. It is the base rotation of the segment, and is included in the value returned by GetLocalRotation*. If you are required to calculate the amount a segment has rotated from its base position, subtract this value from the local rotation.

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentStaticRotationQuaternion _Output_GetSegmentStaticRotationQuaternion;
Client_GetSegmentStaticRotationQuaternion(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationQuaternion);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationQuaternion Output =
MyClient.GetSegmentStaticRotationQuaternion( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetSegmentStaticRotationQuaternion( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationQuaternion Output =
MyClient.GetSegmentStaticRotationQuaternion( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An `Output_GetSegmentStaticRotationQuaternion` class containing the result of the operation and the rotation of the segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticRotationEulerXYZ GetSegmentStaticRotationEulerXYZ (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment in Euler XYZ coordinates.

The static rotation of the segment corresponds to the PRE-ORIENTATION element of the segment in the subject vsk. It is the base rotation of the segment, and is included in the value returned by GetLocalRotation*. If you are required to calculate the amount a segment has rotated from its base position, subtract this value from the local rotation.

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegmentStaticRotationQuaternion\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#).

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentStaticRotationEulerXYZ _Output_GetSegmentStaticRotationEulerXYZ;
Client_GetSegmentStaticRotationEulerXYZ(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationEulerXYZ);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationEulerXYZ Output;
Output = MyClient.GetSegmentStaticRotationEulerXYZ( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetSegmentStaticRotationEulerXYZ( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationEulerXYZ Output =
MyClient.GetSegmentStaticRotationEulerXYZ( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentStaticRotationEulerXYZ class containing the result of the request and the rotation of the segment (x,y,z).

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentGlobalTranslation GetSegmentGlobalTranslation (const String & SubjectName, const String & SegmentName) const

Return the translation of a subject segment in global coordinates.

The translation is of the form (x, y, z) where x, y and z are in millimeters with respect to the global origin.

See Also: [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentGlobalTranslation _Output_GetSegmentGlobalTranslation;
Client_GetSegmentGlobalTranslation(pClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalTranslation);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentGlobalTranslation Output =
MyClient.GetSegmentGlobalTranslation( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output = MyClient.GetSegmentGlobalTranslation( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentGlobalTranslation Output =
MyClient.GetSegmentGlobalTranslations( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An `Output_GetSegmentGlobalTranslation` class containing the result of the operation, the translation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the translation will be [0,0,0].

Output_GetSegmentGlobalRotationHelical GetSegmentGlobalRotationHelical (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in global helical coordinates.

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentGlobalRotationHelical _Output_GetSegmentGlobalRotationHelical;
Client_GetSegmentGlobalRotationHelical(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationHelical);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationHelical Output =
MyClient.GetSegmentGlobalRotationHelical( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentGlobalRotationHelical( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationHelical Output =
MyClient.GetSegmentGlobalRotationHelical( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationHelical class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case, the rotation will be [0,0,0].

Output_GetSegmentGlobalRotationMatrix GetSegmentGlobalRotationMatrix (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment as a 3x3 row-major matrix in global coordinates.

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentGlobalRotationMatrix _Output_GetSegmentGlobalRotationMatrix;
Client_GetSegmentGlobalRotationMatrix(pClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationMatrix);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationMatrix Output =
MyClient.GetSegmentGlobalRotationMatrix( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentGlobalRotationMatrix( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationMatrix Output =
MyClient.GetSegmentGlobalRotationMatrix( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment- Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationMatrix Class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame.

Output_GetSegmentGlobalRotationQuaternion GetSegmentGlobalRotationQuaternion (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in global quaternion coordinates.

The quaternion is of the form (x, y, z, w) where w is the real component and x, y and z are the imaginary components. N.B. This is different from that used in many other applications, which use (w, x, y, z).

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
Output_GetSegmentGlobalRotationQuaternion _Output_GetSegmentGlobalRotationQuaternion;
Client_GetSegmentGlobalRotationQuaternion(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationQuaternion);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationQuaternion Output =
MyClient.GetSegmentGlobalRotationQuaternion( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentGlobalRotationQuaternion( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationQuaternion Output =
MyClient.GetSegmentGlobalRotationQuaternion( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An `Output_GetSegmentGlobalRotationQuaternion` class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the Rotation will be [1,0,0,0].

Output_GetSegmentGlobalRotationEulerXYZ GetSegmentGlobalRotationEulerXYZ (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in global Euler XYZ coordinates.

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentGlobalRotationEulerXYZ _Output_GetSegmentGlobalRotationEulerXYZ;
Client_GetSegmentGlobalRotationEulerXYZ(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationEulerXYZ);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationEulerXYZ Output =
MyClient.GetSegmentGlobalRotationEulerXYZ( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentGlobalRotationEulerXYZ( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationEulerXYZ Output =
MyClient.GetSegmentGlobalRotationEulerXYZ( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationEulerXYZ class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success

- NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the rotation will be [o,o,o].

Output_GetSegmentLocalTranslation GetSegmentLocalTranslation (const String & SubjectName, const String & SegmentName) const

Return the translation of a subject segment in local coordinates relative to its parent segment.

See Also: [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentLocalTranslation _Output_GetSegmentLocalTranslation;
Client_GetSegmentLocalTranslation(pClient, "Alice", "Pelvis", &_Output_GetSegmentLocalTranslation);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentLocalTranslation Output =
MyClient.GetSegmentLocalTranslation( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output = MyClient.GetSegmentLocalTranslation( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentLocalTranslation Output =
MyClient.GetSegmentLocalTranslations( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An `Output_GetSegmentLocalTranslation` class containing the result of the operation, the translation of the segment, and whether the segment is occluded.

- The Result will be:

- Success
- NotConnected
- NoFrame
- InvalidSubjectName
- InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the translation will be [0,0,0].

Output_GetSegmentLocalRotationHelical GetSegmentLocalRotationHelical (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in local helical coordinates relative to its parent segment.

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentLocalRotationHelical _Output_GetSegmentLocalRotationHelical;
Client_GetSegmentLocalRotationHelical(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationHelical);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationHelical Output =
MyClient.GetSegmentLocalRotationHelical( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentLocalRotationHelical( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationHelical Output =
MyClient.GetSegmentLocalRotationHelical( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationHelical class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success

- NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the Rotation will be [o,o,o].

Output_GetSegmentLocalRotationMatrix GetSegmentLocalRotationMatrix (const String & SubjectName, const String & SegmentName) const

Return the rotation row-major matrix of a subject segment in local coordinates relative to its parent segment.

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#) , [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentLocalRotationMatrix _Output_GetSegmentLocalRotationMatrix;
Client_GetSegmentLocalRotationMatrix(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationMatrix);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationMatrix Output =
MyClient.GetSegmentLocalRotationMatrix( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentLocalRotationMatrix( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationMatrix Output =
MyClient.GetSegmentLocalRotationMatrix( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationMatrix class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success

- NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame.

Output_GetSegmentLocalRotationQuaternion GetSegmentLocalRotationQuaternion (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in local quaternion coordinates relative to its parent segment.

The quaternion is of the form (x, y, z, w) where w is the real component and x, y and z are the imaginary components. N.B. This is different from that used in many other applications, which use (w, x, y, z).

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentLocalRotationQuaternion _Output_GetSegmentLocalRotationQuaternion;
Client_GetSegmentLocalRotationQuaternion(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationQuaternion);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationQuaternion Output =
MyClient.GetSegmentLocalRotationQuaternion( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentLocalRotationQuaternion( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationQuaternion Output =
MyClient.GetSegmentLocalRotationQuaternion( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An `Output_GetSegmentLocalRotationQuaternion` class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be `True` if the segment was absent at this frame. In this case the rotation will be `[1,0,0,0]`.

Output_GetSegmentLocalRotationEulerXYZ GetSegmentLocalRotationEulerXYZ (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in local Euler XYZ coordinates relative to its parent segment.

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#) , [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetSegmentLocalRotationEulerXYZ _Output_GetSegmentLocalRotationEulerXYZ;
Client_GetSegmentLocalRotationEulerXYZ(
    pClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationEulerXYZ);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationEulerXYZ Output =
MyClient.GetSegmentLocalRotationEulerXYZ( "Alice", "Pelvis" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output = MyClient.GetSegmentLocalRotationEulerXYZ( "Alice", "Pelvis" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.GetFrame();
Output_GetSegmentLocalRotationEulerXYZ Output =
MyClient.GetSegmentLocalRotationEulerXYZ( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationEulerXYZ class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success

- NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the rotation will be [o,o,o].

Output_GetObjectQuality GetObjectQuality (const String & ObjectName) const

Return the quality score for a specified Object (Subject).

This is only implemented by Tracker.

See Also: [GetSubjectCount\(\)](#), [GetSubjectName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_EnableSegmentData( pClient );
Client_Connect( pClient, "localhost" );
COutput_GetObjectQuality _Output_GetObjectQuality;
Client_GetObjectQuality(pClient, "Object", &_Output_GetObjectQuality);
// _output_GetObjectQuality.Result = NoFrame
// _output_GetObjectQuality.Quality = 0
Client_GetFrame( pClient );
Client_GetObjectQuality(pClient, "Object", &_Output_GetObjectQuality);
// _output_GetObjectQuality.Result = Success
// _output_GetObjectQuality.Quality >= 0.0 && _output_GetObjectQuality.Quality <= 1.0
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableSegmentData();
MyClient.Connect( "localhost" );
Output_GetObjectQuality Output;
Output = MyClient.GetObjectQuality( "Object" );
// Output.Result == NoFrame
// Output.Quality == 0
MyClient.GetFrame();
Output = MyClient.GetMarkerCount( "Camera" );
// Output.Result == InvalidSubjectName
// Output.Quality == 0
// (no "Camera")
Output = MyClient.GetMarkerCount( "Object" );
// Output.Result == Success
// Output.Quality >= 0.0 && Output.Quality <= 1.0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableSegmentData ();
MyClient.Connect( "localhost" );
Output = MyClient.GetObjectQuality( "Object" );
% Output.Result == NoFrame
% Output.Quality == 0
MyClient.GetFrame();
Output = MyClient.GetObjectQuality( "Camera" );
% Output.Result == InvalidSubjectName
% Output.Quality == 0
% (no "Camera")
Output = MyClient.GetObjectQuality( "Object" );
% Output.Result == Success
% Output.Quality >= 0 && Output.Quality >= 1.0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableSegmentData ();
MyClient.Connect( "localhost" );
Output_GetMarkerCount Output;
Output = MyClient.GetObjectQuality( "Object" );
```

```
// Output.Result == NoFrame
// Output.Quality == 0
MyClient.GetFrame();
Output = MyClient.GetObjectQuality( "Camera" );
// Output.Result == InvalidSubjectName
// Output.Quality == 0
// (no "Camera")
Output = MyClient.GetObjectQuality( "Object" );
// Output.Result == Success
// Output.Quality >= 0 && Output.Quality >= 1.0
```

Parameters

ObjectName	The name of the subject.
------------	--------------------------

Returns

An `Output_GetObjectQuality` class containing the result of the operation and the quality score of the object.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName

Output_GetMarkerCount GetMarkerCount (const String & SubjectName) const

Return the number of markers for a specified subject in the DataStream.

This information can be used in conjunction with GetMarkerName.

See Also: [GetSubjectName\(\)](#), [GetMarkerName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
COutput_GetMarkerCount MarkerCount;
Client_GetMarkerCount( pClient, "Bob", &MarkerCount);
// Output.Result = NoFrame
// Output.MarkerCount = 0
Client_GetFrame( pClient );
Client_GetMarkerCount( pClient, "Bob", &MarkerCount);
// Output.Result = Success
// Output.MarkerCount >= 0
Client_GetMarkerCount( pClient, "Alice", &MarkerCount);
// (no "Alice")
// Output.Result = InvalidSubjectName
// Output.MarkerCount == 0
Client_Destroy( pClient );
```

C++ example

```
CPP::Client MyClient;
MyClient.EnableMarkerData();
MyClient.Connect( "localhost" );
Output_GetMarkerCount Output;
Output = MyClient.GetMarkerCount( "Bob" ); // Output.Result == NoFrame
// Output.MarkerCount == 0
MyClient.GetFrame();
Output = MyClient.GetMarkerCount( "Alice" );
// Output.Result == InvalidSubjectName
// Output.MarkerCount == 0
// (no "Alice")
Output = MyClient.GetMarkerCount( "Bob" ); // Output.Result == Success
// Output.MarkerCount >= 0
```

MATLAB example

```
// MyClient = Client();
MyClient.EnableMarkerData();
MyClient.Connect( "localhost" );
Output = MyClient.GetMarkerCount( "Bob" ); % Output.Result == NoFrame
% Output.MarkerCount == 0
MyClient.GetFrame();
Output = MyClient.GetMarkerCount( "Alice" );
% Output.Result == InvalidSubjectName
% Output.MarkerCount == 0
% (no "Alice")
Output = MyClient.GetMarkerCount( "Bob" ); % Output.Result == Success
% Output.MarkerCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableMarkerData();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
```

```
Output_GetMarkerCount Output;
Output = MyClient.GetMarkerCount( "Bob" ); // Output.Result == NoFrame
// Output.MarkerCount == 0
MyClient.GetFrame();
Output = MyClient.GetMarkerCount( "Alice" );
// Output.Result == InvalidSubjectName
// Output.MarkerCount == 0
// (no "Alice")
Output = MyClient.GetMarkerCount( "Bob" ); // Output.Result == Success
// Output.MarkerCount >= 0
```

Parameters

SubjectName	The name of the subject.
-------------	--------------------------

Returns

An `Output_GetMarkerCount` class containing the result of the operation, and the number of markers.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName

Output_GetMarkerName GetMarkerName (const String & SubjectName, const unsigned int MarkerIndex) const

Return the name of a marker for a specified subject.

This can be passed into GetMarkerGlobalTranslation.

See Also: [GetMarkerCount\(\)](#), [GetMarkerGlobalTranslation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetMarkerCount MarkerCount;
Client_GetMarkerCount(pClient, "Bob", &MarkerCount);
// MarkerCount.Result == Success
// MarkerCount.MarkerCount == 2
A valid Marker Index is between 0 and GetMarkerCount()-1
char MarkerName[128];
Client_GetMarkerName(pClient, "Alice", 0, 128, MarkerName);
// MarkerName.Result == InvalidSubjectName
// MarkerName.MarkerName == ""
// (no "Alice")
Client_GetMarkerName(pClient, "Bob", 0, 128, MarkerName);
// MarkerName.Result == Success
// MarkerName.MarkerName == "LASI"
Client_GetMarkerName(pClient, "Bob", 1, 128, MarkerName);
// MarkerName.Result == Success
// MarkerName.MarkerName == "RASI"
Client_GetMarkerName(pClient, "Bob", 2, 128, MarkerName);
// MarkerName.Result == InvalidIndex
// MarkerName.MarkerName == ""
// (no third marker)
Client_Destroy( pClient );
```

C++ example

```
A valid Marker Index is between 0 and GetMarkerCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetMarkerCount OutputGMC;
OutputGMC = MyClient.GetMarkerCount( "Bob" );
// OutputGMC.Result == Success
// OutputGMC.MarkerCount == 2
Output_GetMarkerName OutputGMN;
OutputGMN = MyClient.GetMarkerName( "Alice", 0 );
// OutputGMN.Result == InvalidSubjectName
// OutputGMN.MarkerName == ""
// (no "Alice")
OutputGMN = MyClient.GetMarkerName( "Bob", 0 );
// OutputGMN.Result == Success
// OutputGMN.MarkerName == "LASI"
OutputGMN = MyClient.GetMarkerName( "Bob", 1 );
// OutputGMN.Result == Success
// OutputGMN.MarkerName == "RASI"
OutputGMN = MyClient.GetMarkerName( "Bob", 2 );
// OutputGMN.Result == InvalidIndex
// OutputGMN.MarkerName == ""
// (no third marker)
```

MATLAB example

```
A valid Marker Index is between 1 and GetMarkerCount()
```

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
OutputGMC = MyClient.GetMarkerCount( "Bob" );
// OutputGMC.Result == Success
// OutputGMC.MarkerCount == 2
OutputGMN = MyClient.GetMarkerName( "Alice", 1 );
// OutputGMN.Result == InvalidSubjectName
// OutputGMN.MarkerName == ""
// (no "Alice")
OutputGMN = MyClient.GetMarkerName( "Bob", 1 );
// OutputGMN.Result == Success
// OutputGMN.MarkerName == "LASI"
OutputGMN = MyClient.GetMarkerName( "Bob", 2 );
// OutputGMN.Result == Success
// OutputGMN.MarkerName == "RASI"
OutputGMN = MyClient.GetMarkerName( "Bob", 3 );
// OutputGMN.Result == InvalidIndex
// OutputGMN.MarkerName == ""
// (no third marker)
```

.NET example

```
A valid Marker Index is between 0 and GetMarkerCount()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetMarkerCount OutputGMC;
OutputGMC = MyClient.GetMarkerCount( "Bob" );
// OutputGMC.Result == Success
// OutputGMC.MarkerCount == 2
Output_GetMarkerName OutputGMN;
OutputGMN = MyClient.GetMarkerName( "Alice", 0 );
// OutputGMN.Result == InvalidSubjectName
// OutputGMN.MarkerName == ""
// (no "Alice")
OutputGMN = MyClient.GetMarkerName( "Bob", 0 );
// OutputGMN.Result == Success
// OutputGMN.MarkerName == "LASI"
OutputGMN = MyClient.GetMarkerName( "Bob", 1 );
// OutputGMN.Result == Success
// OutputGMN.MarkerName == "RASI"
OutputGMN = MyClient.GetMarkerName( "Bob", 2 );
// OutputGMN.Result == InvalidIndex
// OutputGMN.MarkerName == ""
// (no third marker)
```

Parameters

SubjectName	The name of the subject.
MarkerIndex	The index of the marker.

Returns

An `Output_GetMarkerName` class containing the result of the operation and the name of the marker.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

- InvalidSubjectName
- InvalidIndex

Output_GetMarkerParentName GetMarkerParentName (const String & SubjectName, const String & MarkerName) const

Return the name of the segment that is the parent of this marker.

See Also: [GetMarkerCount\(\)](#), [GetMarkerName\(\)](#), [GetMarkerGlobalTranslation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
Client_GetFrame( pClient );
char MarkerParentName[128];
CEnum Result = Client_GetMarkerParentName(pClient, "Bob", "LFHD", 128, MarkerParentName);
// Result == Success
// MarkerParentName == "Head"
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetMarkerParentName Output;
Output = MyClient.GetMarkerParentName( "Bob", "LFHD" );
// Output.Result == Success
// Output.SegmentName == "Head"
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output = MyClient.GetMarkerParentName( "Bob", "LFHD" );
// Output.Result == Success
// Output.SegmentName == "Head"
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetMarkerParentName Output;
Output = MyClient.GetMarkerParentName( "Bob", "LFHD" );
// Output.Result == Success
// Output.SegmentName == "Head"
```

Parameters

SubjectName	The name of the subject.
MarkerName	The name of the marker.

Returns

An `Output_GetMarkerParentName` class containing the result of the operation and the name of the parent segment.

- The Result will be:

- Success
- NotConnected
- NoFrame
- InvalidSubjectName
- InvalidMarkerName

Output_GetMarkerGlobalTranslation GetMarkerGlobalTranslation (const String & SubjectName, const String & MarkerName) const

Return the translation of a subject marker in global coordinates.

The Translation is of the form (x, y, z) where x, y and z are in millimeters with respect to the global origin.

See Also: [GetMarkerName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetMarkerGlobalTranslation _Output_GetMarkerGlobalTranslation;
Client_GetMarkerGlobalTranslation(pClient, "Alice", "LASI", &_Output_GetMarkerGlobalTranslation);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetMarkerGlobalTranslation Output =
MyClient.GetMarkerGlobalTranslation( "Alice", "LASI" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output = MyClient.GetMarkerGlobalTranslation( "Alice", "LASI" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetMarkerGlobalTranslation Output =
MyClient.GetMarkerGlobalTranslation( "Alice", "LASI" );
```

Parameters

SubjectName	The name of the subject.
MarkerName	The name of the marker.

Returns

An Output_GetMarkerGlobalTranslation class containing the result of the operation, the translation of the marker, and whether the marker is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

- InvalidSubjectName
 - InvalidMarkerName
- Occluded will be true if the marker was absent at this frame. In this case the Translation will be [0,0,0].

ViconDataStreamSDK::CPP::Output_GetMarkerRayContributionCount GetMarkerRayContributionCount (const String & SubjectName, const String & MarkerName) const

Return the number of rays that are contributing to a labeled marker in the DataStream.

This information can be used in conjunction with GetMarkerRayContribution.

See Also: [GetMarkerRayContribution\(\)](#), [EnableMarkerRayData\(\)](#), [DisableMarkerRayData\(\)](#), [IsMarkerRayDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerRayData( pClient );
Client_GetFrame( pClient );
COutput_GetMarkerRayContributionCount _Output_GetMarkerRayContributionCount;
Client_GetMarkerRayContributionCount( pClient, "Alice", "LASI", &_Output_GetMarkerRayContributionCount );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableMarkerRayData();
MyClient.GetFrame();
Output_GetMarkerRayContributionCount Output =
MyClient.GetMarkerRayContributionCount ( "Alice", "LASI" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerRayData();
MyClient.GetFrame();
Output = MyClient.GetMarkerRayContributionCount ( "Alice", "LASI" );
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerRayData();
MyClient.GetFrame();
Output_GetMarkerRayContributionCount Output =
MyClient.GetMarkerRayContributionCount( "Alice", "LASI" );
```

Parameters

SubjectName	The name of the subject.
MarkerName	The name of the marker.

Returns

An Output_GetMarkerRayContributionCount class containing the result of the operation and the number of rays.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
- InvalidSubjectName
- InvalidMarkerName

ViconDataStreamSDK::CPP::Output_GetMarkerRayContribution GetMarkerRayContribution (const String & SubjectName, const String & MarkerName, unsigned int MarkerRayContributionIndex) const

Return the camera ID for an indexed ray that is contributing to a labeled marker in the DataStream.

This information can be used in conjunction with GetMarkerRayContributionCount.

See Also: [GetMarkerRayContributionCount\(\)](#), [EnableMarkerRayData\(\)](#), [DisableMarkerRayData\(\)](#), [IsMarkerRayDataEnabled\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetMarkerRayContribution _Output_GetMarkerRayContribution;
Client_GetMarkerRayContribution(pClient, "Alice", "LASI", 0, &_Output_GetMarkerRayContribution);
Client_Destroy( pClient );
```

C++ example

```
A valid Ray Index is between 0 and GetMarkerRayContributionCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableMarkerRayData();
MyClient.GetFrame();
Output_GetMarkerRayContribution Output =
MyClient.GetMarkerRayContribution( "Alice", "LASI", 0 );
```

MATLAB example

```
A valid Ray Index is between 1 and GetMarkerRayContributionCount()
MarkerRayContributionIndex )
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableMarkerRayData();
MyClient.GetFrame();
Output = MyClient.GetMarkerRayContribution ( "Alice", "LASI", 1 );
```

.NET example

```
A valid Ray Index is between 0 and GetMarkerRayContributionCount()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableMarkerRayData();
MyClient.GetFrame();
Output_GetMarkerRayContribution Output =
MyClient.GetMarkerRayContribution( "Alice", "LASI", 0 );
```

Parameters

SubjectName	The name of the subject.
MarkerName	The name of the marker.
MarkerRay-Contribution-Index	The index of the ray required.

Returns

An `Output_GetMarkerRayContribution` class containing the result of the operation, the camera ID of the camera producing the ray and the index of the centroid resulting from the ray.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidMarkerName

Output_GetUnlabeledMarkerCount GetUnlabeledMarkerCount () const

Return the number of unlabeled markers in the DataStream.

This information can be used in conjunction with GetGlobalUnlabeledMarkerTranslation

See Also: GetGlobalUnlabeledMarkerTranslation()

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableUnlabeledMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetUnlabeledMarkerCount UnlabeledMarkerCount;
Client_GetUnlabeledMarkerCount(pClient, &UnlabeledMarkerCount);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableUnlabeledMarkerData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetUnlabeledMarkerCount Output =
MyClient.GetUnlabeledMarkerCount(); // Output.Result == Success
// Output.MarkerCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableUnlabeledMarkerData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetUnlabeledMarkerCount(); // Output.Result == Success
// Output.MarkerCount >= 0
```

.NET example

```
MyClient = Client();
MyClient.EnableUnlabeledMarkerData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetUnlabeledMarkerCount(); // Output.Result == Success
// Output.MarkerCount >= 0
```

Returns

An Output_GetUnlabeledMarkerCount class containing the result of the operation and the number of markers.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetUnlabeledMarkerGlobalTranslation GetUnlabeledMarkerGlobalTranslation (const unsigned int MarkerIndex) const

Return the translation of an unlabeled marker in global coordinates.

The Translation is of the form (x, y, z) where x, y and z are in millimeters with respect to the global origin.

See Also: [GetUnlabeledMarkerCount\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableUnlabeledMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetUnlabeledMarkerGlobalTranslation _Output_GetUnlabeledMarkerGlobalTranslation;
Client_GetUnlabeledMarkerGlobalTranslation( pClient, 0, &_Output_GetUnlabeledMarkerGlobalTranslation );
Client_Destroy( pClient );
```

C++ example

```
A valid Marker Index is between 0 and GetUnlabeledMarkerCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableUnlabeledMarkerData();
MyClient.GetFrame();
Output_GetUnlabeledMarkerGlobalTranslation Output =
MyClient.GetUnlabeledMarkerGlobalTranslation( 0 );
```

MATLAB example

```
A valid Marker Index is between 1 and GetUnlabeledMarkerCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableUnlabeledMarkerData();
MyClient.GetFrame();
Output = MyClient.GetUnlabeledMarkerGlobalTranslation( 1 );
```

.NET example

```
A valid Marker Index is between 0 and GetUnlabeledMarkerCount()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableUnlabeledMarkerData();
MyClient.GetFrame();
Output_GetUnlabeledMarkerGlobalTranslation Output =
MyClient.GetUnlabeledMarkerGlobalTranslation( 0 );
```

Parameters

MarkerIndex	The index of the marker
-------------	-------------------------

Returns

An Output_GetUnlabeledMarkerGlobalTranslation class containing the result of the operation and the translation of the marker.

- The Result will be:
 - Success

- NotConnected
- NoFrame

Output_GetLabeledMarkerCount GetLabeledMarkerCount () const

Returns the number of all labeled markers in the datastream across all subjects.

This may be used to determine marker index range for use with [GetLabeledMarkerGlobalTranslation\(\)](#).

See Also: [GetLabeledMarkerGlobalTranslation\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetLabeledMarkerCount LabeledMarkerCount;
Client_GetLabeledMarkerCount( pClient, &LabeledMarkerCount );
// LabeledMarkerCount.Result == Success
// LabeledMarkerCount.Markercount >= 0
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableMarkerData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetLabeledMarkerCount Output =
MyClient.GetLabeledMarkerCount();
// Output.Result == Success
// Output.MarkerCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableMarkerData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetLabeledMarkerCount(); // Output.Result == Success
// Output.MarkerCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableMarkerData();
MyClient.Connect("localhost");
MyClient.GetFrame();
Output_GetLabeledMarkerCount Output = MyClient.GetLabeledMarkerCount();
// Output.Result == Success
// Output.MarkerCount >= 0
```

Returns

An [Output_GetLabeledMarkerCount](#) class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetLabeledMarkerGlobalTranslation GetLabeledMarkerGlobalTranslation (const unsigned int MarkerIndex) const

Return the translation of a labeled marker in global coordinates.

The Translation is of the form (x, y, z) where x, y and z are in millimeters with respect to the global origin.

See Also: [GetLabeledMarkerCount\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableMarkerData( pClient );
Client_GetFrame( pClient );
COutput_GetLabeledMarkerGlobalTranslation LabeledMarkerGlobalTranslation;
Client_GetLabeledMarkerGlobalTranslation( pClient, &LabeledMarkerGlobalTranslation );
Client_Destroy( pClient );
```

C++ example

```
A valid Marker Index is between 0 and GetLabeledMarkerCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output_GetLabeledMarkerGlobalTranslation Output =
MyClient.GetLabeledMarkerGlobalTranslation( 0 );
```

MATLAB example

```
A valid Marker Index is between 1 and GetUnlabeledMarkerCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableMarkerData();
MyClient.GetFrame();
Output = MyClient.GetLabeledMarkerGlobalTranslation( 1 );    ///
```

.NET example

```
A valid Marker Index is between 0 and GetLabeledMarkerCount()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableLabeledMarkerData();
MyClient.GetFrame();
Output_GetLabeledMarkerGlobalTranslation Output =
MyClient.GetLabeledMarkerGlobalTranslation( 0 );
```

Returns

An Output_GetLabeledMarkerGlobalTranslation class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetDeviceCount GetDeviceCount () const

Return the number of force plates, EMGs, and other devices in the DataStream.

This information can be used in conjunction with [GetDeviceName](#).

See Also: [GetDeviceName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetDeviceCount DeviceCount;
Client_GetDeviceCount( pClient, &DeviceCount );
// DeviceCount.Result == Success
// DeviceCount.DeviceCount >= 0
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetDeviceCount Output = MyClient.GetDeviceCount();
// Output.Result == Success
// Output.DeviceCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetDeviceCount(); // Output.Result == Success
// Output.DeviceCount >= 0
```

.NET example

```
ViconDataStreamSDK::DotNET::Client MyClient;
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetDeviceCount Output = MyClient.GetDeviceCount();
// Output.Result == Success
// Output.DeviceCount >= 0
```

Returns

An [Output_GetDeviceCount](#) class containing the result of the operation and the number of devices.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetDeviceName GetDeviceName (const unsigned int DeviceIndex) const

Return the name and type of a device.

This name can be passed into device functions.

See Also: [GetDeviceCount\(\)](#), [GetDeviceOutputCount\(\)](#), [GetDeviceOutputValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetDeviceCount DeviceCount;
Client_GetDeviceCount( pClient, &DeviceCount );
// DeviceCount.Result == Success
// DeviceCount.DeviceCount == 2
char DeviceName[128];
CEnum DeviceType;
CEnum Result = Client_GetDeviceName( pClient, 0, 128, DeviceName, &DeviceType );
// Result == Success
// DeviceName == "ZeroWire"
// DeviceType == Unknown
Result = Client_GetDeviceName( pClient, 1, 128, DeviceName, &DeviceType );
// Result == Success
// DeviceName == "AMTI #1"
// DeviceType == ForcePlate
Result = Client_GetDeviceName( pClient, 2, 128, DeviceName, &DeviceType );
// Result == InvalidIndex
// DeviceName == ""
// DeviceType == Unknown
Client_Destroy( pClient );
```

C++ example

```
A valid Device Index is between 0 and GetDeviceCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceCount OutputGDC;
OutputGDC = MyClient.GetDeviceCount( DeviceCount );
// OutputGDC.Result == Success
// OutputGDC.DeviceCount == 2
Output_GetDeviceName OutputGDN;
OutputGDN = MyClient.GetDeviceName( 0 );
// OutputGDN.Result == Success
// OutputGDN.DeviceName == "ZeroWire"
// OutputGDN.DeviceType == Unknown
OutputGDN = MyClient.GetDeviceName( 1 );
// OutputGDN.Result == Success
// OutputGDN.DeviceName == "AMTI #1"
// OutputGDN.DeviceType == ForcePlate
OutputGDN = MyClient.GetDeviceName( 2 );
// OutputGDN.Result == InvalidIndex
// OutputGDN.DeviceName == ""
// OutputGDN.DeviceType == Unknown
```

MATLAB example

```
A valid Device Index is between 1 and GetDeviceCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
```

```

OutputGDC = MyClient.GetDeviceCount( DeviceCount );
% OutputGDC.Result == Success
% OutputGDC.DeviceCount == 2
OutputGDN = MyClient.GetDeviceName( 1 );
% OutputGDN.Result == Success
% OutputGDN.DeviceName == "ZeroWire"
% OutputGDN.DeviceType == Unknown
OutputGDN = MyClient.GetDeviceName( 2 );
% OutputGDN.Result == Success
% OutputGDN.DeviceName == "AMTI #1"
% OutputGDN.DeviceType == ForcePlate
OutputGDN = MyClient.GetDeviceName( 3 );
% OutputGDN.Result == InvalidIndex
% OutputGDN.DeviceName == ""
% OutputGDN.DeviceType == Unknown

```

.NET example

```

A valid Device Index is between 0 and GetDeviceCount()-1
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceCount OutputGDC;
OutputGDC = MyClient.GetDeviceCount( DeviceCount );
// OutputGDC.Result == Success
// OutputGDC.DeviceCount == 2
Output_GetDeviceName OutputGDN;
OutputGDN = MyClient.GetDeviceName( 0 );
// OutputGDN.Result == Success
// OutputGDN.DeviceName == "ZeroWire"
// OutputGDN.DeviceType == Unknown
OutputGDN = MyClient.GetDeviceName( 1 );
// OutputGDN.Result == Success
// OutputGDN.DeviceName == "AMTI #1"
// OutputGDN.DeviceType == ForcePlate
OutputGDN = MyClient.GetDeviceName( 2 );
// OutputGDN.Result == InvalidIndex
// OutputGDN.DeviceName == ""
// OutputGDN.DeviceType == Unknown

```

Parameters

DeviceIndex	The index of the device.
-------------	--------------------------

Returns

An `Output_GetDeviceName` class containing the result of the operation, the name of the device, and the device type.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex The Device Type will be:
 - Unknown
 - ForcePlate

Output_GetDeviceOutputCount GetDeviceOutputCount (const String & DeviceName) const

Return the number of outputs for a device in the DataStream.

This information can be used in conjunction with [GetDeviceOutputName](#).

See Also: [GetDeviceName\(\)](#), [GetDeviceOutputName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetDeviceOutputCount DeviceOutputCount;
Client_GetDeviceOutputCount(pClient, "DataGlove", &DeviceOutputCount);
// DeviceOutputCount.Result == InvalidDeviceName
// DeviceOutputCount.DeviceOutputCount == 0
// (no "DataGlove" device)
Client_GetDeviceOutputCount(pClient, "ZeroWire", &DeviceOutputCount);
// DeviceOutputCount.Result == Success
// DeviceOutputCount.DeviceOutputCount == 6
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputCount Output;
Output = MyClient.GetDeviceOutputCount( "DataGlove" );
// Output.Result == InvalidDeviceName
// Output.DeviceOutputCount == 0
// (no "DataGlove" device)
Output = MyClient.GetDeviceOutputCount( "ZeroWire" );
// Output.Result == Success
// Output.DeviceOutputCount == 6
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output = MyClient.GetDeviceOutputCount( "DataGlove" );
// Output.Result == InvalidDeviceName
// Output.DeviceOutputCount == 0
// (no "DataGlove" device)
Output = MyClient.GetDeviceOutputCount( "ZeroWire" );
// Output.Result == Success
// Output.DeviceOutputCount == 6
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputCount Output;
Output = MyClient.GetDeviceOutputCount( "DataGlove" );
// Output.Result == InvalidDeviceName
// Output.DeviceOutputCount == 0
// (no "DataGlove" device)
Output = MyClient.GetDeviceOutputCount( "ZeroWire" );
// Output.Result == Success
// Output.DeviceOutputCount == 6
```

Parameters

DeviceName	The device name
------------	-----------------

Returns

An Output_GetDeviceOutputCount class containing the result of the operation and the number of device outputs.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidDeviceName

Output_GetDeviceOutputName GetDeviceOutputName (const String & DeviceName, const unsigned int DeviceOutputIndex) const

Return the name and SI unit of a device output.

This name can be passed into GetDeviceOutputValue.

See Also: [GetDeviceCount\(\)](#), [GetDeviceOutputCount\(\)](#), [GetDeviceOutputValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData();
Client_GetFrame( pClient );
char DeviceOutputName[128];
CEnum DeviceOutputUnit;
CEnum Result = Client_GetDeviceOutputName(pClient, "AMTI", 0, 128, DeviceOutputName, &DeviceOutputUnit);
// Result == Success
// DeviceOutputName == "Fx"
// DeviceOutputUnit == Newton
Client_Destroy( pClient );
```

C++ example

```
A valid Device Output Index is between 0 and GetDeviceOutputCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputName Output =
MyClient.GetDeviceOutputName( "AMTI", 0 );
// Output.Result == Success
// Output.DeviceOutputName == "Fx"
// Output.DeviceOutputUnit == Newton
```

MATLAB example

```
A valid Device Output Index is between 1 and GetDeviceOutputCount()
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output = MyClient.GetDeviceOutputName( "AMTI", 0 );
% Output.Result == Success
% Output.DeviceOutputName == "Fx"
% Output.DeviceOutputUnit == Newton
```

.NET example

```
A valid Device Output Index is between 0 and GetDeviceOutputCount()-1
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputName Output =
MyClient.GetDeviceOutputName( "AMTI", 0 );
// Output.Result == Success
// Output.DeviceOutputName == "Fx"
// Output.DeviceOutputUnit == Newton
```


Parameters

DeviceName	The device name
Device-OutputIndex	The index of the device output

Returns

An Output_GetDeviceOutputName class containing the result of the operation, the name of the device output and the unit of the device output.

- The Result will be:
 - Success
 - NotConnected
- The DeviceOutputName could be:
 - "Fx" - Force X
 - "Fy" - Force Y
 - "Fz" - Force Z
 - "Mx" - Moment X
 - "My" - Moment Y
 - "Mz" - Moment Z
 - "Cx" - Center Of Pressure X
 - "Cy" - Center Of Pressure Y
 - "Cz" - Center Of Pressure Z
 - "Pin1" - Analog Input 1
 - "Pin2" - Analog Input 2 - The Device Output Unit will be:
 - Unit.Unknown
 - Unit.Volt
 - Unit.Newton
 - Unit.NewtonMeter
 - Unit.Meter
 - Unit.Kilogram
 - Unit.Second
 - Unit.Ampere
 - Unit.Kelvin
 - Unit.Mole
 - Unit.Candela
 - Unit.Radian
 - Unit.Steradian
 - Unit.MeterSquared
 - Unit.MeterCubed
 - Unit.MeterPerSecond
 - Unit.MeterPerSecondSquared
 - Unit.RadianPerSecond

- Unit.RadianPerSecondSquared
- Unit.Hertz
- Unit.Joule
- Unit.Watt
- Unit.Pascal
- Unit.Lumen
- Unit.Lux
- Unit.Coulomb
- Unit.Ohm
- Unit.Farad
- Unit.Weber
- Unit.Tesla
- Unit.Henry
- Unit.Siemens
- Unit.Becquerel
- Unit.Gray
- Unit.Sievert
- Unit.Katal

Output_GetDeviceOutputValue GetDeviceOutputValue (const String & DeviceName, const String & DeviceOutputName) const

Return the value of a device output.

If there are multiple samples for a frame, then the first sample is returned. The force plate data provided in the individual device channels is in a coordinate system local to the force plate aligned Z upwards, Y towards the front of the force plate. This coordinate system is located at the center of the top surface of the force plate. Any plate origin offset has been accounted for in the moment data. These are forces not reactions.

See Also: [GetDeviceCount\(\)](#), [GetDeviceOutputCount\(\)](#), [GetDeviceOutputName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetDeviceOutputValue _Output_GetDeviceOutputValue;
Client_GetDeviceOutputValue( pClient, "AMTI", "Fx", &_Output_GetDeviceOutputValue );
// _OutputGetDeviceOutputValue.Result == Success
// _OutputGetDeviceOutputValue.Value == ?
// _OutputGetDeviceOutputValue.Value.Occluded = ?
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputValue Output =
MyClient.GetDeviceOutputValue( "AMTI", "Fx" );
// Output.Result == Success
// Output.Value == ?
// Output.Occluded = ?
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output = MyClient.GetDeviceOutputValue( "AMTI", "Fx" );
// Output.Result == Success
// Output.Value == ?
// Output.Occluded = ?
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputValue Output =
MyClient.GetDeviceOutputValue( "AMTI", "Fx" );
// Output.Result == Success
// Output.Value == ?
// Output.Occluded = ?
```

Parameters

DeviceName	The device name
Device- OutputName	The name of the device output

Returns

An Output_GetDeviceOutputValue class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidDeviceName
 - InvalidDeviceOutputName

Output_GetDeviceOutputSubsamples GetDeviceOutputSubsamples (const String & DeviceName, const String & DeviceOutputName) const

Return the number of samples available for the specified device at the current frame.

If an analog device is sampling at 1000 Hz and the system is running at 100 Hz then this function will return 10. The samples can be accessed by supplying the subsample index to `GetDeviceOutputValue`. See below.

See Also: [GetDeviceOutputCount\(\)](#), [GetDeviceOutputValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetDeviceOutputSubsamples DeviceOutputSubsamples;
Client_GetDeviceOutputSubsamples( pClient, "AMTI", "Fx", &DeviceOutputSubsamples );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputSubsamples Output =
MyClient.GetDeviceOutputSubsamples ( "AMTI", "Fx" );
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output = MyClient.GetDeviceOutputSubsamples ( "AMTI", "Fx" );
// Output.Result == Success
// Output.DeviceOutputSubsamples == ?
// Output.Occluded = ?
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient =
new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputSubsamples Output =
MyClient.GetDeviceOutputSubsamples( "AMTI", "Fx" );
// Output.Result == Success
// Output.DeviceOutputSubsamples == ?
// Output.Occluded = ?
```

Parameters

DeviceName	The device name
Device-OutputName	The name of the device output

Returns

An `Output_GetDeviceOutputSubsamples` class containing the result of the operation, the number of subsamples for this device output, and whether the device is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidDeviceName
 - InvalidDeviceOutputName
- Occluded will be true if the value was absent at this frame. In this case the value will be 0.

Output_GetDeviceOutputValue GetDeviceOutputValue (const String & DeviceName, const String & DeviceOutputName, const unsigned int Subsample) const

Return the value of a device output.

This override allows access to the individual subsamples for the current frame of data. See [GetDeviceOutputValue](#) for information about the meaning of the force plate channels.

See Also: [GetDeviceOutputSubsamples\(\)](#), [GetDeviceOutputValue\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetDeviceOutputValue _Output_GetDeviceOutputValue;
Client_GetDeviceOutputValueForSubsample( pClient, "AMTI", "Fx", 6, &_Output_GetDeviceOutputValue);
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputValue Output =
MyClient.GetDeviceOutputValue( "AMTI", "Fx", 6 );
// Output.Result == Success
// Output.Value == ?
// Output.Occluded = ?
```

MATLAB example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputValue Output =
MyClient.GetDeviceOutputValue( "AMTI", "Fx", 6 );
// Output.Result == Success
// Output.Value == ?
// Output.Occluded = ?
// Output.Value == ?
// Output.Occluded = ?
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData();
MyClient.GetFrame();
Output_GetDeviceOutputValue Output =
MyClient.GetDeviceOutputValue( "AMTI", "Fx", 6 );
// Output.Result == Success
// Output.Value == ?
// Output.Occluded = ?
```

Parameters

DeviceName	The device name
Device-OutputName	The name of the device output

Returns

An `Output_GetDeviceOutputValue` class containing the result of the operation, the value of the device output, and whether the device is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidDeviceName
 - InvalidDeviceIndex
 - InvalidDeviceOutputName

Output_GetForcePlateCount GetForcePlateCount () const

Return the number of force plates available in the DataStream.

See Also: [GetGlobalForceVector\(\)](#), [GetGlobalMomentVector\(\)](#), [GetGlobalCentreOfPressure\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_EnableDeviceData( pClient );
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetForcePlateCount ForcePlateCount;
Client_GetForcePlateCount( pClient, &ForcePlateCount );
// ForcePlateCount.Result == Success
// ForcePlateCount.ForcePlateCount >= 0
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetForcePlateCount Output = MyClient.GetForcePlateCount ();
// Output.Result == Success
// Output.ForcePlateCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetForcePlateCount(); // Output.Result == Success
// Output.ForcePlateCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetForcePlateCount Output = MyClient.GetForcePlateCount();
// Output.Result == Success
// Output.ForcePlateCount >= 0
```

Returns

An `Output_GetForcePlateCount` class containing the result of the operation and the number of force plates.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetGlobalForceVector GetGlobalForceVector (const unsigned int ForcePlateIndex) const

Return the force vector for the force plate in global coordinates.

The vector is in Newtons and is with respect to the global coordinate system regardless of the orientation of the force plate. The vector represents the force exerted upon the force plate, not the reaction force. If multiple subsamples are available this function returns the first subsample. See the alternate version of this function to access all of the analog data.

See Also: [GetGlobalMomentVector\(\)](#), [GetGlobalCentreOfPressure\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData ( pClient );
Client_GetFrame( pClient );
COutput_GetGlobalForceVector _Output_GetForceVector;
Client_GetGlobalForceVector( pClient, 0, &_Output_GetForceVector);
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetGlobalForceVector Output = MyClient.GetGlobalForceVector( 0 );
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output = MyClient.GetGlobalForceVector( 1 );
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableUnlabeledMarkerData();
MyClient.GetFrame();
Output_GetGlobalForceVector Output = MyClient.GetGlobalForceVector( 0 );
```

Parameters

ForcePlate-Index	The index of the force plate
------------------	------------------------------

Returns

An Output_GetGlobalForceVector class containing the result of the operation and the force on the force plate

- The Result will be:
 - Success

- NotConnected
- NoFrame
- InvalidIndex

Output_GetGlobalMomentVector GetGlobalMomentVector (const unsigned int ForcePlateIndex) const

Return the moment vector for the force plate in global coordinates.

The vector is in Newton-meters and is with respect to the global coordinate system regardless of the orientation of the force plate. The vector represents the moment exerted upon the force plate, not the reaction moment. Any force plate origin offset is accounted for in the moments so they are acting about the exact center of the top surface of the force plate. If multiple subsamples are available this function returns the first subsample. See the alternate version of this function to access all of the analog data.

See Also: [GetGlobalForceVector\(\)](#), [GetGlobalCentreOfPressure\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData ( pClient );
Client_GetFrame( pClient );
COutput_GetGlobalMomentVector _Output_GetMomentVector;
Client_GetGlobalMomentVector( pClient, 0, &_Output_GetMomentVector );
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetGlobalMomentVector Output = MyClient.GetGlobalMomentVector( 0 );
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output = MyClient.GetGlobalMomentVector( 1 );
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetGlobalMomentVector Output = MyClient.GetGlobalMomentVector( 0 );
```

Parameters

ForcePlate-Index	The index of the force plate
------------------	------------------------------

Returns

An Output_GetGlobalMomentVector class containing the result of the operation and the moment exerted on the force plate

- The Result will be:

- Success
- NotConnected
- NoFrame
- InvalidIndex

Output_GetGlobalCentreOfPressure GetGlobalCentreOfPressure (const unsigned int ForcePlateIndex) const

Return the center of pressure for the force plate in global coordinates.

The position is in millimeters and is with respect to the global coordinate system. If multiple subsamples are available this function returns the first subsample. See the alternate version of this function to access all of the analog data.

See Also: [GetGlobalForceVector\(\)](#), [GetGlobalMomentVector\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_EnableDeviceData ( pClient );
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetGlobalCentreOfPressure _Output_GetCentreOfPressure;
Client_GetGlobalCentreOfPressure( pClient, 0, &_Output_GetCentreOfPressure );
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetGlobalCentreOfPressure Output = MyClient.GetGlobalCentreOfPressure( 0 );
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output = MyClient.GetGlobalCentreOfPressure( 1 );
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetGlobalCentreOfPressure Output = MyClient.GetGlobalCentreOfPressure( 0 );
```

Parameters

ForcePlate-Index	The index of the force plate
------------------	------------------------------

Returns

An Output_GetGlobalCentreOfPressure class containing the result of the operation and the center of pressure.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
- InvalidIndex

Output_GetForcePlateSubsamples GetForcePlateSubsamples (const unsigned int ForcePlateIndex) const

Return the number of subsamples available for a specified plate in the current frame.

Additional versions of GetGlobalForceVector, GetGlobalMomentVector, and GetGlobalCentreOfPressure take the subsample index to allow access to all the force plate data.

See Also: [GetGlobalForceVector\(\)](#), [GetGlobalMomentVector\(\)](#), [GetGlobalCentreOfPressure\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData ( pClient );
Client_GetFrame( pClient );
COutput_GetForcePlateSubsamples ForcePlateSubsamples;
Client_GetForcePlateSubsamples( pClient, 0, &ForcePlateSubsamples );
// ForcePlateSubsamples.Result == Success
// ForcePlateSubsamples.ForcePlateSubsamples >= 0
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetForcePlateSubsamples Output = MyClient.GetForcePlateSubsamples ( 0 );
// Output.Result == Success
// Output.ForcePlateSubsamples >= 0
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
MyClient = Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetForcePlateSubsamples( 1 );
// Output.Result == Success
// Output.ForcePlateSubsamples >= 0
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetForcePlateSubsamples Output = MyClient.GetForcePlateSubsamples ( 0 );
// Output.Result == Success
// Output.ForcePlateSubsamples >= 0
```

Parameters

ForcePlate-Index	The index of the force plate
------------------	------------------------------

Returns

An `Output_GetForcePlateSubsamples` class containing the result of the operation and the number of subsamples.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetGlobalForceVector GetGlobalForceVector (const unsigned int ForcePlateIndex, const unsigned int Subsample) const

Return the force vector for the plate in global coordinates.

This version takes a subsample index that allows access to all of the force information. The vector is in Newtons and is with respect to the global coordinate system regardless of the orientation of the plate. The vector represents the force exerted upon the plate, not the reaction force.

See Also: [GetGlobalMomentVector\(\)](#), [GetGlobalCentreOfPressure\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData ( pClient );
Client_GetFrame( pClient );
unsigned int Index(0);
COutput_GetForcePlateSubsamples ForcePlateSubsamples;
Client_GetForcePlateSubsamples( pClient, Index, &ForcePlateSubsamples );
for ( unsigned int ForcePlateSubsample = 0;
      ForcePlateSubsample < ForcePlateSubsamples.ForcePlateSubsamples; ++ForcePlateSubsample)
{
    COutput_GetGlobalForceVector _Output_GetForceVector;
    Client_GetGlobalForceVectorForSubsample(
        pClient, Index, ForcePlateSubsample, &_Output_GetForceVector );
}
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
A valid Subsample is between 0 and GetForcePlateSubsamples()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
const unsigned int Index(0);
const unsigned int Samples = MyClient.GetForcePlateSubsamples( index ).ForcePlateSubsamples;
for( unsigned int Sample = 0; Sample < Samples; ++ Sample)
{
    Output_GetGlobalForceVector Output = MyClient.GetGlobalForceVector( Index, Sample );
}
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
A valid Subsample is between 1 and GetForcePlateSubsamples()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Index = 0;
Output_GetForcePlateSubsamples = MyClient.GetForcePlateSubsamples(Index );
for Sample = 1:Output_GetForcePlateSubsamples.ForcePlateSubsamples
    Output = MyClient.GetGlobalForceVector( Index, Sample );
end
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
A valid Subsample is between 0 and GetForcePlateSubsamples()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableUnlabeledMarkerData();
MyClient.GetFrame();
```

```
uint Index = 0;
uint Samples = MyClient.GetForcePlateSubsamples(ForcePlateIndex).ForcePlateSubsamples;
for (uint Sample = 0; Sample < Samples; ++ Sample)
{
    Output_GetGlobalForceVector Output = MyClient.GetGlobalForceVector( Index, Sample );
}
```

Parameters

ForcePlate- Index	The index of the force plate
Subsample	The subsample to access

Returns

An Output_GetGlobalForceVector class containing the result of the operation and the force on the plate.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetGlobalMomentVector GetGlobalMomentVector (const unsigned int ForcePlateIndex, const unsigned int Subsample) const

Return the moment vector for the plate in global coordinates.

This version takes a subsample index that allows access to all of the force information. The vector is in Newton-meters and is with respect to the global coordinate system regardless of the orientation of the plate. The vector represents the moment exerted upon the plate, not the reaction moment. Any force plate origin offset is accounted for in the moments so they are acting about the exact center of the top surface of the plate.

See Also: [GetGlobalForceVector\(\)](#), [GetGlobalCentreOfPressure\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_EnableDeviceData ( pClient );
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
unsigned int Index(0);
COutput_GetForcePlateSubsamples ForcePlateSubsamples;
Client_GetForcePlateSubsamples( pClient, Index, &ForcePlateSubsamples );
for ( unsigned int ForcePlateSubsample = 0;
      ForcePlateSubsample < ForcePlateSubsamples.ForcePlateSubsamples; ++ForcePlateSubsample)
{
    COutput_GetGlobalMomentVector _Output_GetMomentVector;
    Client_GetGlobalMomentVectorForSubsample(
        pClient, Index, ForcePlateSubsample, &_Output_GetMomentVector);
}
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
A valid Subsample is between 0 and GetForcePlateSubsamples()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
const unsigned int Index(0);
const unsigned int Samples = MyClient.GetForcePlateSubsamples( index ).ForcePlateSubsamples;
for( unsigned int Sample = 0; Sample < Samples; ++ Sample)
{
    Output_GetGlobalMomentVector Output = MyClient.GetGlobalMomentVector( Index, Sample );
}
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
A valid Subsample is between 1 and GetForcePlateSubsamples()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Index = 0;
Output_GetForcePlateSubsamples = MyClient.GetForcePlateSubsamples( Index );
for Sample = 1:Output_GetForcePlateSubsamples.ForcePlateSubsamples
    Output = MyClient.GetGlobalMomentVector ( Index, Sample );
end
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount() - 1
A valid Subsample is between 0 and GetForcePlateSubsamples()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
```

```
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
uint Index = 0;
uint Samples = MyClient.GetForcePlateSubsamples(ForcePlateIndex).ForcePlateSubsamples;
for (uint Sample = 0; Sample < Samples; ++ Sample)
{
    Output_GetGlobalMomentVector Output = MyClient.GetGlobalMomentVector( Index, Sample );
}
```

Parameters

ForcePlate-Index	The index of the force plate
Subsample	The subsample to access

Returns

An `Output_GetGlobalMomentVector` class containing the result of the operation and the moment exerted on the plate.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetGlobalCentreOfPressure GetGlobalCentreOfPressure (const unsigned int ForcePlateIndex, const unsigned int Subsample) const

Return the center of pressure for the plate in global coordinates.

This version takes a subsample index that allows access to all of the force information. The position is in millimeters and is with respect to the global coordinate system.

See Also: [GetGlobalForceVector\(\)](#), [GetGlobalMomentVector\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData ( pClient );
Client_GetFrame( pClient );
unsigned int Index(0);
COutput_GetForcePlateSubsamples ForcePlateSubsamples;
Client_GetForcePlateSubsamples( pClient, Index, &ForcePlateSubsamples );
for ( unsigned int ForcePlateSubsample = 0;
      ForcePlateSubsample < ForcePlateSubsamples.ForcePlateSubsamples; ++ForcePlateSubsample)
{
    COutput_GetGlobalCentreOfPressure _Output_GetCentreOfPressure;
    Client_GetGlobalCentreOfPressureForSubsample(
        pClient, Index, ForcePlateSubsample, &_Output_GetCentreOfPressure);
}
Client_Destroy( pClient );
```

C++ example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
A valid Subsample is between 0 and GetForcePlateSubsamples()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
const unsigned int Index(0);
const unsigned int Samples = MyClient.GetForcePlateSubsamples( index ).ForcePlateSubsamples;
for( unsigned int Sample = 0; Sample < Samples; ++ Sample)
{
    Output_GetGlobalCentreOfPressure Output = MyClient.GetGlobalCentreOfPressure(Index, Sample);
}
```

MATLAB example

```
A valid ForcePlateIndex is between 1 and GetForcePlateCount()
A valid Subsample is between 1 and GetForcePlateSubsamples()
MyClient = Client();
MyClient.Connect( "localhost" );
Client_GetFrame( pClient );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Index = 0;
Output_GetForcePlateSubsamples = MyClient.GetForcePlateSubsamples( Index );
for Sample = 1:Output_GetForcePlateSubsamples.ForcePlateSubsamples
    Output = MyClient.GetGlobalCentreOfPressure( Index, Sample );
end
```

.NET example

```
A valid ForcePlateIndex is between 0 and GetForcePlateCount()-1
A valid Subsample is between 0 and GetForcePlateSubsamples()-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableDeviceData ();
MyClient.GetFrame();
```

```
uint Index = 0;
uint Samples = MyClient.GetForcePlateSubsamples (ForcePlateIndex).ForcePlateSubsamples;
for (uint Sample = 0; Sample < Samples; ++ Sample)
{
    Output_GetGlobalCentreOfPressure Output = MyClient.GetGlobalCentreOfPressure (Index,Sample);
}
```

Parameters

ForcePlate- Index	The index of the force plate
Subsample	The subsample to access

Returns

An Output_GetGlobalCentreOfPressure class containing the result of the operation the center of pressure

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetEyeTrackerCount GetEyeTrackerCount () const

Return the number of eye trackers available in the DataStream.

See Also: [GetEyeTrackerGlobalGazeVector\(\)](#), [GetEyeTrackerGlobalGazeVector\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_EnableDeviceData( pClient );
Client_Connect( pClient, "localhost" );
Client_GetFrame( pClient );
COutput_GetEyeTrackerCount EyeTrackerCount;
Client_GetEyeTrackerCount( pClient, &EyeTrackerCount );
// EyeTrackerCount.Result == Success
// EyeTrackerCount.EyeTrackerCount >= 0
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetDeviceCount Output = MyClient.GetEyeTrackerCount ();
// Output.Result == Success
// Output.EyeTrackerCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output = MyClient.GetEyeTrackerCount();
// Output.Result == Success
// Output.EyeTrackerCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.EnableDeviceData();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetEyeTrackerCount Output = MyClient.GetEyeTrackerCount();
// Output.Result == Success
// Output.EyeTrackerCount >= 0
```

Returns

An `Output_GetEyeTrackerCount` class containing the result of the operation and the number of eye trackers.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetEyeTrackerGlobalPosition GetEyeTrackerGlobalPosition (const unsigned int EyeTrackerIndex) const

Return the location of the eye.

The position is in millimeters with respect to the global origin. The segment and device data need to be enabled to get the position.

See Also: [GetEyeTrackerCount\(\)](#), [GetEyeTrackerGlobalGazeVector\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetEyeTrackerGlobalPosition _Output_GetEyeTrackerGlobalPosition;
Client_GetEyeTrackerGlobalPosition(pClient, 0, &_Output_GetEyeTrackerGlobalPosition);
Client_Destroy( pClient );
```

C++ example

```
A valid EyeTrackerIndex is between 0 and GetEyeTrackerCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData ();
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetEyeTrackerGlobalPosition Output = MyClient.GetEyeTrackerGlobalPosition ( 0 );
```

MATLAB example

```
A valid EyeTrackerIndex is between 1 and GetEyeTrackerCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData ();
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output = MyClient.GetEyeTrackerGlobalPosition ( 1 );
```

.NET example

```
A valid EyeTrackerIndex is between 0 and GetEyeTrackerCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData ();
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetEyeTrackerGlobalPosition Output = MyClient.GetEyeTrackerGlobalPosition ( 0 );
```

Parameters

EyeTracker-Index	The index of the eye tracker
------------------	------------------------------

Returns

An Output_GetEyeTrackerGlobalPosition class containing the result of the operation, the eye position and whether the eyetracker is occluded.

- The Result will be:
 - Success

- NotConnected
 - NoFrame
 - InvalidIndex
- Occluded will be true if the segment that has the eye tracker attached is not visible. If true the position will be (0,0,0).

Output_GetEyeTrackerGlobalGazeVector GetEyeTrackerGlobalGazeVector (const unsigned int EyeTrackerIndex) const

Return the gaze direction as a unit vector in global coordinates.

The gaze vector will be marked as occluded if the segment that has the eye tracker attached is not visible, the eye tracker is not calibrated or the pupil is not found. The segment and device data need to be enabled to get the gaze vector.

See Also: [GetEyeTrackerCount\(\)](#), [GetEyeTrackerGlobalPosition\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableDeviceData( pClient );
Client_GetFrame( pClient );
COutput_GetEyeTrackerGlobalGazeVector _Output_GetEyeTrackerGlobalGazeVector;
Client_GetEyeTrackerGlobalGazeVector(pClient, 0, &_Output_GetEyeTrackerGlobalGazeVector);
Client_Destroy( pClient );
```

C++ example

```
A valid EyeTrackerIndex is between 0 and GetEyeTrackerCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData ();
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetEyeTrackerGlobalPosition Output = MyClient.GetEyeTrackerGlobalGazeVector ( 0 );
```

MATLAB example

```
A valid EyeTrackerIndex is between 1 and GetEyeTrackerCount()
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData ();
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output = MyClient.GetEyeTrackerGlobalGazeVector ( 1 );
```

.NET example

```
A valid EyeTrackerIndex is between 0 and GetEyeTrackerCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData ();
MyClient.EnableDeviceData ();
MyClient.GetFrame();
Output_GetEyeTrackerGlobalPosition Output = MyClient.GetEyeTrackerGlobalPosition ( 0 );
```

Parameters

EyeTracker-Index	The index of the eye tracker
------------------	------------------------------

Returns

An Output_GetEyeTrackerGlobalGazeVector class containing the result of the operation, the gaze direction vector, and whether the eye tracker is occluded.

- The Result will be:

- Success
 - NotConnected
 - NoFrame
 - InvalidIndex
- Occluded will be true if the gaze vector could not be calculated. If true, the position will be (0,0,0).

Output_GetCameraCount GetCameraCount () const

Return the number of cameras available in the DataStream.

See Also: [GetCameraName\(\)](#), [GetCentroidCount\(\)](#), [GetCentroidPosition\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount( pClient, &CameraCount );
// CameraCount.Result == Success
// CameraCount.CameraCount >= 0
Client_GetFrame( pClient );
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount Output = MyClient.GetCameraCount();
// Output.Result == Success
// Output.CameraCount >= 0
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData();
MyClient.GetFrame();
Output = MyClient.GetCameraCount();
% Output.Result == Success, Output.CameraCount >= 0
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount Output = MyClient.GetCameraCount();
// Output.Result == Success
// Output.CameraCount >= 0
```

Returns

An Output_GetCameraCount class containing the result of the operation and the number of cameras.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetCameraName GetCameraName (unsigned int CameraIndex) const

Return the name of a camera.

This name can be passed into centroid functions.

See Also: [GetCameraCount\(\)](#), [GetCentroidCount\(\)](#), [GetCentroidPosition\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
// CamerCount.Result == Success
// CameraCount.CameraCount == 1
char CameraName[128];
Client_GetCameraName(pClient, 0, 128, CameraName);
Client_Destroy( pClient );
```

C++ example

```
A valid CameraIndex is between 0 and GetCameraCount()-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
// OutputGCC.Result == Success
// OutputGCC.CameraCount == 1
Output_GetCameraName OutputGCN;
OutputGCN = MyClient.GetCameraName( 0 )
```

MATLAB example

```
A valid CameraIndex is between 1 and GetCameraCount()
% [Output] = GetCameraName ( CameraIndex )
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
OutputGCC = MyClient.GetCameraCount ( 1 );
% OutputGCC.Result == Success
% OutputGCC.CameraCount == 1
OutputGCN = MyClient.GetCameraName( 1 );
```

.NET example

```
A valid CameraIndex is between 0 and GetCameraCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
// OutputGCC.Result == Success
// OutputGCC.CameraCount == 1
Output_GetCameraName OutputGCN;
OutputGCN = MyClient.GetCameraName( 0 )
```

Parameters

CameraIndex	The index of the camera
-------------	-------------------------

Returns

An `Output_GetCameraName` class containing the result of the operation and the name of the camera.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetCameraId GetCameraId (const std::string & CameraName) const

Returns the internal ID of the camera with the specified name.

See Also: [GetCameraName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        COutput_GetCameraId CameraId;
        Client_GetCameraId(pClient, CameraName, &CameraId );
    }
}
Client_GetFrame( pClient );
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraId Output_GCI = MyClient.GetCameraId( OutputGCN.CameraName );
    }
}
```

MATLAB example

Not implemented

.NET example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraId Output_GCI = MyClient.GetCameraId( OutputGCN.CameraName );
    }
}
```


Returns

An `Output_GetCameraId` class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetCameraUserId GetCameraUserId (const std::string & CameraName) const

Returns the user-assigned ID of the camera with the specified name.

See Also: [GetCameraName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        COutput_GetCameraUserId CameraId;
        Client_GetCameraUserId(pClient, CameraName, &CameraUserId );
    }
}
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraUserId Output_GCI = MyClient.GetCameraUserId( OutputGCN.CameraName );
    }
}
```

MATLAB example

Not implemented

.NET example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraUserId Output_GCI = MyClient.GetCameraUserId( OutputGCN.CameraName );
    }
}
```

Returns

An Output_GetCameraUserId class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetCameraType GetCameraType (const std::string & CameraName) const

Returns the type of the camera with the specified name.

The type returned is an internal type string.

See Also: [GetCameraName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        char CameraType[128];
        CEnum Result = Client_GetCameraType( pClient, CameraName, 128, CameraType );
    }
}
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraType Output_GCT = MyClient.GetCameraType( OutputGCN.CameraName );
    }
}
```

MATLAB example

Not implemented

.NET example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraType Output_GCT = MyClient.GetCameraType( OutputGCN.CameraName );
    }
}
```

Returns

An Output_ class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetCameraDisplayName GetCameraDisplayName (const std::string & CameraName) const

Returns the name of of the camera type as a string suitable for display to a user.

See Also: [GetCameraName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        char CameraDisplayName[128];
        CEnum Result = Client_GetCameraDisplayName( pClient, CameraName, 128, CameraDisplayName );
    }
}
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( Output_GCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraDisplayName Output_GCD = MyClient.GetCameraDisplayName( OutputGCN.CameraName );
    }
}
```

MATLAB example

Not implemented

.NET example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( Output_GCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {

```

```
Output_GetCameraDisplayName Output_GCD = MyClient.GetCameraDisplayName( OutputGCN.CameraName );  
}  
}
```

Returns

An Output_ class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetCameraResolution GetCameraResolution (const std::string & CameraName) const

Returns the sensor resolution of the camera with the specified name.

See Also: [GetCameraName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        COutput_GetCameraResolution CameraResolution;
        Client_GetCameraResolution(pClient, CameraName, &CameraResolution );
    }
}
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraResolution Output_GCR = MyClient.GetCameraResolution( OutputGCN.CameraName );
    }
}
```

MATLAB example

Not implemented

.NET example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetCameraResolution Output_GCR = MyClient.GetCameraResolution( OutputGCN.CameraName );
    }
}
```


Returns

An Output_ class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetIsVideoCamera GetIsVideoCamera (const std::string & CameraName) const

Returns whether the camera with the specified name is a video camera.

See Also: [GetCameraName\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        COutput_GetIsVideoCamera IsVideoCamera;
        Client_GetIsVideoCamera(pClient, CameraName, &IsVideoCamera );
    }
}
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetIsVideoCamera Output_GCV = MyClient.GetIsVideoCamera( OutputGCN.CameraName );
    }
}
```

MATLAB example

Not implemented

.NET example

```
A valid CameraName may be obtained from GetCameraName()
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
if( OutputGCC.Result == Success && OutputGCC.CameraCount > 0 )
{
    Output_GetCameraName OutputGCN;
    OutputGCN = MyClient.GetCameraName( 0 );
    if( OutputGCN.Result == Success )
    {
        Output_GetIsVideoCamera Output_GCV = MyClient.GetIsVideoCamera( OutputGCN.CameraName );
    }
}
```

Returns

An Output_ class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetCentroidCount GetCentroidCount (const std::string & CameraName) const

Return the number of centroids reported by a named camera.

The centroid data needs to be enabled to get the number of centroids.

See Also: [GetCameraCount\(\)](#), [GetCameraName\(\)](#), [GetCentroidPosition\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
COutput_GetCameraCount CameraCount;
Client_GetCameraCount(pClient, &CameraCount);
if( CameraCount.Result == Success && CameraCount.CameraCount > 0 )
{
    char CameraName[128];
    CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
    if ( Output == Success )
    {
        COutput_GetCentroidCount CentroidCount;
        Client_GetCentroidCount(pClient, CameraName, &CentroidCount );
    }
}
Client_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
for( unsigned int CameraIndex = 0; CameraIndex < OutputGCC.CameraCount; ++CameraIndex )
{
    Output_GetCameraName OutputGCN = MyClient.GetCameraName( CameraIndex );
    Output_GetCentroidCount OutputGCeC = MyClient.GetCentroidCount( OutputGCN.CameraName );
    // OutputGCeC.Result == Success
    // OutputGCeC.CentroidCount >= 0
}
```

MATLAB example

```
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData();
MyClient.GetFrame();
OutputGCC = MyClient.GetCameraCount();
for CameraIndex = 1:OutputGCC.CameraCount
    OutputGCN = MyClient.GetCameraName( CameraIndex );
    OutputGCeC = MyClient.GetCentroidCount( OutputGCN.CameraName )
    % OutputGCeC.Result == Success
    % OutputGCeC.CentroidCount >= 0
End
```

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraCount OutputGCC = MyClient.GetCameraCount();
for( unsigned int CameraIndex = 0; CameraIndex < OutputGCC.CameraCount; ++CameraIndex )
```

```
{
    OutputGCN = MyClient.GetCameraName( CameraIndex );
    OutputGCeC = MyClient.GetCentroidCount( OutputGCN.CameraName )
    // OutputGCeC.Result == Success
    // OutputGCeC.CentroidCount >= 0
}
```

Parameters

CameraName	The name of the camera.
------------	-------------------------

Returns

An Output_GetCentroidCount class containing the result of the operation and the number of centroids.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidCameraName

Output_GetCentroidPosition GetCentroidPosition (const std::string & CameraName, const unsigned int CentroidIndex) const

Return the position and radius of the centroid in camera coordinates.

The centroid data needs to be enabled to get the centroid position and radius.

See Also: [GetCameraCount\(\)](#), [GetCameraName\(\)](#), [GetCentroidCount\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
char CameraName[128];
CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
COutput_GetCentroidPosition CentroidPosition;
Client_GetCentroidPosition(pClient, CameraName, 0, &CentroidPosition );
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName is obtained from GetCameraName( CameraIndex )
A valid CentroidIndex is between 0 and GetCentroidCount( CameraName )-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraName OutputGCN = MyClient.GetCameraName( 0 );
Output_GetCentroidPosition Output = MyClient.GetCentroidPosition( OutputGCN.CameraName, 0 );
```

MATLAB example

```
A valid CameraName is obtained from GetCameraName( CameraIndex )
A valid CentroidIndex is between 1 and GetCentroidCount( CameraName )
% [Output] = GetCentroidPosition( CameraName, CentroidIndex )
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
OutputGCN = MyClient.GetCameraName( 1 );
Output = MyClient.GetCentroidPosition( OutputGCN.CameraName, 1 );
```

.NET example

```
A valid CameraName is obtained from GetCameraName( CameraIndex )
A valid CentroidIndex is between 0 and GetCentroidCount( CameraName )-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraName OutputGCN = MyClient.GetCameraName( 0 );
Output_GetCentroidPosition Output = MyClient.GetCentroidPosition( OutputGCN.CameraName, 0 );
```

Parameters

CameraName	The name of the camera.
CentroidIndex	The index of the centroid.

Returns

An `Output_GetCentroidPosition` class containing the result of the operation, the position of the centroid and the radius of the centroid.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidCameraName
 - InvalidIndex

Output_GetCentroidWeight GetCentroidWeight (const std::string & CameraName, const unsigned int CentroidIndex) const

Return the weight of the centroid.

The centroid data needs to be enabled to get the centroid weight. Only supported by Tracker - weights will be 1.0 for all centroids if Low Jitter mode is not enabled.

See Also: [GetCameraCount\(\)](#), [GetCameraName\(\)](#), [GetCentroidCount\(\)](#)

C example

```
CClient * pClient = Client_Create();
Client_Connect( pClient, "localhost" );
Client_EnableCentroidData ( pClient );
Client_GetFrame( pClient );
char CameraName[128];
CEnum Output = Client_GetCameraName(pClient, 0, 128, CameraName);
COutput_GetCentroidWeight CentroidWeight;
Client_GetCentroidWeight(pClient, CameraName, 0, &CentroidWeight );
Client_Destroy( pClient );
```

C++ example

```
A valid CameraName is obtained from GetCameraName( CameraIndex )
A valid CentroidIndex is between 0 and GetCentroidCount( CameraName )-1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraName OutputGCN = MyClient.GetCameraName( 0 );
Output_GetCentroidWeight Output = MyClient.GetCentroidWeight( OutputGCN.CameraName, 0 );
```

MATLAB example

```
A valid CameraName is obtained from GetCameraName( CameraIndex )
A valid CentroidIndex is between 1 and GetCentroidCount( CameraName )
% [Output] = GetCentroidWeight( CameraName, CentroidIndex )
MyClient = Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
OutputGCN = MyClient.GetCameraName( 1 );
Output = MyClient.GetCentroidWeight( OutputGCN.CameraName, 1 );
```

.NET example

```
A valid CameraName is obtained from GetCameraName( CameraIndex )
A valid CentroidIndex is between 0 and GetCentroidCount( CameraName )-1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableCentroidData ();
MyClient.GetFrame();
Output_GetCameraName OutputGCN = MyClient.GetCameraName( 0 );
Output_GetCentroidWeight Output = MyClient.GetCentroidWeight( OutputGCN.CameraName, 0 );
```

Parameters

CameraName	The name of the camera.
CentroidIndex	The index of the centroid.

Returns

An `Output_GetCentroidWeight` class containing the result of the operation and the weight of the centroid.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidCameraName
 - InvalidIndex

Output_GetGreyscaleBlobCount GetGreyscaleBlobCount (const std::string & CameraName) const

Obtain the number of greyscale blobs that are available for the specified camera.

See Also: [GetGreyscaleBlob\(\)](#), [EnableGreyscaleData\(\)](#)

C example

Not implemented

C++ example

```
A valid camera name may be obtained from GetCameraName( CameraIndex )
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableGreyscaleData ();
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetGreyscaleBlobCount Output = MyClient.GetGreyscaleBlobCount( CameraName.CameraName );
```

MATLAB example

Not implemented

.NET example

```
A valid camera name may be obtained from GetCameraName( CameraIndex )
A valid blob index is between 0 and GetGreyscaleBlobCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableGreyscaleData ();
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetGreyscaleBlob GreyscaleData = MyClient.GetGreyscaleBlob( CameraName.CameraName, 0 );
```

Returns

An Output_GetGreyscaleBlobCount class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_GetGreyscaleBlob GetGreyscaleBlob (const std::string & CameraName, const unsigned int i_BlobIndex) const

Obtains greyscale blob data for the specified camera and blob index.

See Also: [GetGreyscaleBlobCount\(\)](#), [EnableGreyscaleData\(\)](#)

C example

Not implemented

C++ example

```
A valid camera name may be obtained from GetCameraName( CameraIndex )
A valid blob index is between 0 and GetGreyscaleBlobCount() - 1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableGreyscaleData ();
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetGreyscaleBlob GreyscaleData = MyClient.GetGreyscaleBlob( CameraName.CameraName, 0 );
```

MATLAB example

Not implemented

.NET example

```
A valid camera name may be obtained from GetCameraName( CameraIndex )
A valid blob index is between 0 and GetGreyscaleBlobCount() - 1
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableGreyscaleData ();
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetGreyscaleBlob GreyscaleData = MyClient.GetGreyscaleBlob( CameraName.CameraName, 0 );
```

Returns

An Output_GetGreyscaleBlob class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName
 - InvalidIndex

Output_GetVideoFrame GetVideoFrame (const std::string & CameraName) const

Obtains video data for the specified camera.

See Also: -

C example

Not implemented

C++ example

```
A valid camera name may be obtained from GetCameraName( CameraIndex )
A valid blob index is between 0 and GetGreyscaleBlobCount() - 1
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableVideoData ();
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetVideoFrame VideoData = MyClient.GetVideoFrame( CameraName.CameraName );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.EnableVideoData ();
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetVideoFrame VideoData = MyClient.GetVideoFrame( CameraName.CameraName ); /// -----
```

Returns

An Output_GetVideoFrame class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected
 - InvalidCameraName

Output_SetCameraFilter SetCameraFilter (const std::vector< unsigned int > & CameraIdsForCentroids, const std::vector< unsigned int > & CameraIdsForBlobs, const std::vector< unsigned int > & CameraIdsForVideo)

Add a filter to allow centroid, blob or video data being transmitted only for the specified cameras.

See Also: [GetGreyscaleBlobCount\(\)](#), [GetGreyscaleBlob\(\)](#), [GetCentroidCount\(\)](#), [GetCentroid-Position\(\)](#), [GetCentroidWeight\(\)](#)

C example

Not implemented

C++ example

```
A valid camera name may be obtained from GetCameraName( CameraIndex )
A valid camera id may be obtained from GetCameraId( CameraName )
ViconDataStreamSDK::CPP::Client MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetCameraId CameraId = MyClient.GetCameraName( CameraName.CameraName );
std::vector< unsigned int > ReceiveCentroids;
ReceiveCentroids.push_back( CameraId.CameraId );
std::vector< unsigned int > ReceiveBlobs;
ReceiveBlobs.push_back( CameraId.CameraId );
std::vector< unsigned int > ReceiveVideo;
ReceiveVideo.push_back( CameraId.CameraId );
Output_SetCameraFilter FilterResults =
    MyClient.SetCameraFilter( ReceiveCentroids, ReceiveBlobs, ReceiveVideo );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetCameraName CameraName = MyClient.GetCameraName( 0 );
Output_GetCameraId CameraId = MyClient.GetCameraName( CameraName.CameraName );
List< unsigned int >^ ReceiveCentroids = gcnew List< unsigned int >();
ReceiveCentroids.Add( CameraId.CameraId );
List< unsigned int >^ ReceiveBlobs = gcnew List< unsigned int >();
ReceiveBlobs.Add( CameraId.CameraId );
List< unsigned int >^ ReceiveVideo = gcnew List< unsigned int >();
ReceiveVideo.Add( CameraId.CameraId );
Output_SetCameraFilter FilterResults =
    MyClient.SetCameraFilter( ReceiveCentroids, ReceiveBlobs, ReceiveVideo );    /// -----
```

Returns

An Output_SetCameraFilter class containing the result of the operation.

- The Result will be:
 - Success

The documentation for this class was generated from the following files:

- DataStreamClient.h
- DataStreamClient.cpp

RetimingClient Class Reference

Detailed Description

The re-timing client class for C++.

Vicon DataStream SDK Re-Timing Client

Intended uses

The Vicon DataStream re-timing client provides calls to obtain subject data from the DataStream with minimal latency and temporal jitter. When [UpdateFrame\(\)](#) is called, the client uses re-timed data that has been linearly interpolated from an internal buffer to predict the position of each segment to the current time.

The system and network latencies are used when determining the amount of prediction required. If additional prediction is required, for example for use in a VR system where an additional latency is present due to rendering and display latency; this may be requested in the call to [UpdateFrame\(\)](#).

The user will either call [UpdateFrame\(\)](#), which will update the current frame state to the time of calling and return immediately. This is intended for use in systems where you require subject data positions at times driven by an external clock.

If you do not have an external clock, and require behavior similar to that of the standard DataStream client running in ServerPush streaming mode, then the system may be configured to provide frame data at a consistent frame rate by providing a frame rate to the [Connect\(\)](#) call. The user will then call [WaitForFrame\(\)](#), which will block in a similar method to [Client::GetFrame\(\)](#), but using retimed data in order to keep the frame period very consistent.

Examples of use

If you are using the client in a situation where you need to obtain the position of subjects in

```
ViconDataStreamSDK::CPP::RetimingClient _MyClient;
_MyClient.Connect( "localhost" );

// example render method. Real code would probably cache the subject and segment names and bind
// them to a model, so this code would iterate over the model and update the joint positions.
void render()
{
    _MyClient.UpdateFrame();

    Output_GetSubjectCount SubjectCount = _MyClient.GetSubjectCount();
    if (SubjectCount.Result == Result::Success)
    {
        for (unsigned int SubjectIndex = 0; SubjectIndex < SubjectCount.SubjectCount; ++SubjectIndex)
        {
            Output_GetSubjectName SubjectName = _MyClient.GetSubjectName(SubjectIndex);
```

```

if (SubjectName.Result == Result::Success)
{
    Output_GetSegmentCount SegmentCount = _MyClient.GetSegmentCount (SubjectName.SubjectName);
    if (SegmentCount.Result == Result::Success)
    {
        for (unsigned int SegmentIndex = 0; SegmentIndex < SegmentCount.SegmentCount; ++SegmentIndex)
        {
            Output_GetSegmentName SegmentName =
                _MyClient.GetSegmentName (SubjectName.SubjectName, SegmentIndex);
            if (SegmentName.Result == Result::Success)
            {
                Output_GetSegmentGlobalRotationQuaternion SegmentRotation =
                    _MyClient.GetSegmentGlobalRotationQuaternion
                        (SubjectName.SubjectName, SegmentName.SegmentName);
                if (SegmentRotation.Result == Result::Success && !SegmentRotation.Occluded)
                {
                    // use the segment rotation
                }
            }
        }
    }
}
}
}
}

```

If using the client where there is no render call and you require your own timing.

```

ViconDataStreamSDK::CPP::RetimingClient _MyClient;
// Request a retimed update frame rate of 90Hz.
_MyClient.Connect( "localhost", 90 );
while( _MyClient.IsConnected() )
{
    Output_WaitForFrame WaitOutput = _MyClient.WaitForFrame();
    if( WaitOutput.Result == Result::Success )
    {
        // iterate over subjects and segments and obtain the joint positions and rotations as above.
    }
}
}

```

For a more detailed example, see the `ViconDataStreamSDK_CPPRetimingTest` example. The `SimpleViewer` application also provides an example of re-timing client use in a practical context.

Public Member Functions

- [RetimingClient \(\)](#)
Construction.
- [virtual ~RetimingClient \(\)](#)
Destruction.
- [Output_GetVersion](#) [GetVersion \(\)](#) const
Get the version of the Vicon DataStream SDK.
- [Output_Connect](#) [Connect](#) (const String &HostName, double FrameRate=o.o)
Establish a dedicated connection to a Vicon DataStream Server.
- [Output_Disconnect](#) [Disconnect \(\)](#)
Disconnect from the Vicon DataStream Server.
- [Output_IsConnected](#) [IsConnected \(\)](#) const
Discover whether client is connected to the Vicon DataStream Server.
- [Output_SetAxisMapping](#) [SetAxisMapping](#) (const Direction::Enum XAxis, const Direction::Enum YAxis, const Direction::Enum ZAxis)
Remaps the 3D axis.

- Output_GetAxisMapping [GetAxisMapping](#) () const
Get the current Axis mapping.
- Output_UpdateFrame [UpdateFrame](#) (double Offset=0.0)
Update the current frame state to represent the position of all active subjects at the current time.
- Output_WaitForFrame [WaitForFrame](#) ()
Used when running the retiming client with a specified frame rate.
- Output_GetSubjectCount [GetSubjectCount](#) () const
Return the number of subjects in the DataStream.
- Output_GetSubjectName [GetSubjectName](#) (const unsigned int SubjectIndex) const
Return the name of a subject.
- Output_GetSubjectRootSegmentName [GetSubjectRootSegmentName](#) (const String &SubjectName) const
Return the name of the root segment for a specified subject.
- Output_GetSegmentCount [GetSegmentCount](#) (const String &SubjectName) const
Return the number of segments for a specified subject in the DataStream.
- Output_GetSegmentName [GetSegmentName](#) (const String &SubjectName, const unsigned int SegmentIndex) const
Return the name of a subject segment specified by index.
- Output_GetSegmentChildCount [GetSegmentChildCount](#) (const String &SubjectName, const String &SegmentName) const
Return the number of child segments for a specified subject segment.
- Output_GetSegmentChildName [GetSegmentChildName](#) (const String &SubjectName, const String &SegmentName, const unsigned int SegmentIndex) const
Return the name of the child segment for a specified subject segment and index.
- Output_GetSegmentParentName [GetSegmentParentName](#) (const String &SubjectName, const String &SegmentName) const
Return the name of the parent segment for a specified subject segment.
- Output_GetSegmentStaticTranslation [GetSegmentStaticTranslation](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose translation of a subject segment.
- Output_GetSegmentStaticRotationHelical [GetSegmentStaticRotationHelical](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment in helical coordinates.
- Output_GetSegmentStaticRotationMatrix [GetSegmentStaticRotationMatrix](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment as a 3x3 row-major matrix.
- Output_GetSegmentStaticRotationQuaternion [GetSegmentStaticRotationQuaternion](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment in quaternion coordinates.
- Output_GetSegmentStaticRotationEulerXYZ [GetSegmentStaticRotationEulerXYZ](#) (const String &SubjectName, const String &SegmentName) const
Return the static pose rotation of a subject segment in Euler XYZ coordinates.
- Output_GetSegmentGlobalTranslation [GetSegmentGlobalTranslation](#) (const String &SubjectName, const String &SegmentName) const
Return the translation of a subject segment in global coordinates.
- Output_GetSegmentGlobalRotationHelical [GetSegmentGlobalRotationHelical](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in global helical coordinates.

- Output_GetSegmentGlobalRotationMatrix [GetSegmentGlobalRotationMatrix](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment as a 3x3 row-major matrix in global coordinates.
- Output_GetSegmentGlobalRotationQuaternion [GetSegmentGlobalRotationQuaternion](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in global quaternion coordinates.
- Output_GetSegmentGlobalRotationEulerXYZ [GetSegmentGlobalRotationEulerXYZ](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in global Euler XYZ coordinates.
- Output_GetSegmentLocalTranslation [GetSegmentLocalTranslation](#) (const String &SubjectName, const String &SegmentName) const
Return the translation of a subject segment in local coordinates relative to its parent segment.
- Output_GetSegmentLocalRotationHelical [GetSegmentLocalRotationHelical](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in local helical coordinates relative to its parent segment.
- Output_GetSegmentLocalRotationMatrix [GetSegmentLocalRotationMatrix](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation row-major matrix of a subject segment in local coordinates relative to its parent segment.
- Output_GetSegmentLocalRotationQuaternion [GetSegmentLocalRotationQuaternion](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in local quaternion coordinates relative to its parent segment.
- Output_GetSegmentLocalRotationEulerXYZ [GetSegmentLocalRotationEulerXYZ](#) (const String &SubjectName, const String &SegmentName) const
Return the rotation of a subject segment in local Euler XYZ coordinates relative to its parent segment.
- void [SetMaximumPrediction](#) (double MaxPrediction)
Sets the maximum amount by which the interpolation engine will predict later than the latest received frame.
- double [MaximumPrediction](#) () const
Returns the maximum prediction value currently in use.

Constructor & Destructor Documentation

[RetimingClient](#) ()

Construction.

Instances of the Vicon Data Stream [RetimingClient](#) create a [DataStreamClient](#) internally that manages the connection to the data stream.

The [RetimingClient](#) will set the underlying client up to receive the required data from the stream and to set the correct data delivery mode, so it is not necessary to set this up manually.

C example

```
// The C version uses explicit creation methods

CClient * pClient = RetimingClient_Create();
// C Client functions take the client as a parameter
CBool ok = RetimingClient_SomeFunction( pClient, Args );
// The C client needs to be explicitly destroyed
RetimingClient_Destroy( pClient );
```

C++ example

```
// The C++ version of the SDK is object oriented, so use the class constructor.

{
    ViconDataStreamSDK::CPP::RetimingClient StackRetimingClient;
    Output_SomeFunction Output = StackRetimingClient.SomeFunction();
    // ...
}
// Client is implicitly destroyed as it goes out of scope.

// Alternatively the Client can be made on the heap.

ViconDataStreamSDK::CPP::RetimingClient * pHeapRetimingClient
= new ViconDataStreamSDK::CPP::RetimingClient();
Output_SomeFunction Output = pHeapRetimingClient->SomeFunction( Input );
```

MATLAB example

Not implemented

.NET example

```
// .NET is object oriented, so use the class constructor.

// Because objects are lazily garbage collected, your instance may outlive the
// last reference to it for some time.

// If the instance is pre-fetching frame data for you, then it can still use CPU
// and network bandwidth.

// Consider explicitly disconnecting prior to destruction.

ViconDataStreamSDK.DotNET.RetimingClient pHeapClient
    = new ViconDataStreamSDK.DotNET.RetimingClient();
Output_SomeFunction Output = pHeapClient.SomeFunction(InputParam);
// Signal to the garbage collector that it can clean up
pHeapClient.Disconnect();
pHeapClient = null;
```

~RetimingClient () [virtual]

Destruction.

Destruction will Disconnect if required.

See [RetimingClient::RetimingClient](#) for an example.

Member Function Documentation

Output_GetVersion GetVersion () const

Get the version of the Vicon DataStream SDK.

- Major When this number increases, we break backward compatibility with previous major versions.
- Minor When this number increases, we have probably added new functionality to the SDK without breaking backward compatibility with previous versions.

- Point When this number increases, we have introduced a bug fix or performance enhancement without breaking backward compatibility with previous versions.

The function can be called without the client being connected.

C example

```
CRetimingClient * pClient = RetimingClient_Create();  
COutput_GetVersion Output = RetimingClient_GetVersion( pClient );  
RetimingClient_Destroy( pClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;  
Output_GetVersion Output = MyClient.GetVersion();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();  
Output_GetVersion Output = MyClient.GetVersion();
```

Returns

Output_GetVersion class containing the version information.

Output_Connect Connect (const String & HostName, double FrameRate = 0.0)

Establish a dedicated connection to a Vicon DataStream Server.

See Also: [Disconnect\(\)](#), [IsConnected\(\)](#).

The function defaults to connecting on port 801. You can specify an alternate port number after a colon. This is for future compatibility: current products serve data on port 801 only.

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
COutput_Connect Output = RetimingClient_Connect( pRetimingClient, "localhost");
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
Output_Connect Output = MyClient.Connect( "localhost" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
Output_Connect Output = MyClient.Connect( "localhost" );
// Connect with alternative FrameRate parameter
Output_Connect Output = MyClient.Connect( "localhost", 90.0 );
```

Parameters

HostName	The DNS-identifiable name, or IP address of the PC hosting the DataStream server. For example: <ul style="list-style-type: none"> • "localhost" • "MyViconPC:801" • "10.0.0.2"
FrameRate	An optional parameter - if specified, the re-timing client's internal frame output clock will be active. This is implemented by a separate overloaded method on .NET

Returns

An Output_Connect class containing the result of the connect operation.

- The Result will be:
 - Success
 - InvalidHostName
 - ClientAlreadyConnected
 - ClientConnectionFailed

Output_Disconnect Disconnect ()

Disconnect from the Vicon DataStream Server.

See Also: [Connect\(\)](#), [IsConnected\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
COutput_Disconnect Output = RetimingClient_Disconnect( pRetimingClient );
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
Output_Disconnect Output = MyClient.Disconnect();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
Output_Disconnect Output = MyClient.Disconnect();
```

Returns

An Output_Disconnect class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_IsConnected IsConnected () const

Discover whether client is connected to the Vicon DataStream Server.

See Also: [Connect\(\)](#), [Disconnect\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
CBool Output = RetimingClient_IsConnected( pRetimingClient );
// Output == 0
RetimingClient_Connect( pRetimingClient, "localhost" );
Output = RetimingClient_IsConnected( pRetimingClient );
// Output == 1
COutput_Disconnect Output = RetimingClient_Disconnect( pRetimingClient );
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::Client MyClient;
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == false
MyClient.Connect( "localhost" );
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == true
// (assuming localhost is serving)
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == false
MyClient.Connect( "localhost" );
Output_IsConnected Output = MyClient.IsConnected()
// Output.Connected == true
// (assuming localhost is serving)
```

Returns

An Output_IsConnected class containing a true value for Connected if you are connected to the stream, otherwise false.

Output_SetAxisMapping SetAxisMapping (const Direction::Enum XAxis, const Direction::Enum YAxis, const Direction::Enum ZAxis)

Remaps the 3D axis.

Vicon Data uses a right-handed coordinate system, with +X forward, +Y left, and +Z up. Other systems use different coordinate systems. The SDK can transform its data into any valid right-handed coordinate system by re-mapping each axis. Valid directions are "Up", "Down", "Left", "-Right", "Forward", and "Backward". Note that "Forward" means moving away from you, and "-Backward" is moving towards you. Common usages are Z-up: SetAxisMapping(Forward, Left, Up) Y-up: SetAxisMapping(Forward, Up, Right)

See Also: [GetAxisMapping\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_SetAxisMapping(pRetimingClient, Forward, Left, Up); // Z-up
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.SetAxisMapping( ViconDataStreamSDK::CPP::Direction::Forward,
ViconDataStreamSDK::CPP::Direction::Left,
ViconDataStreamSDK::CPP::Direction::Up );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
MyClient.SetAxisMapping( ViconDataStreamSDK.DotNET.Direction.Forward,
ViconDataStreamSDK.DotNET.Direction.Left,
ViconDataStreamSDK.DotNET.Direction.Up );
```

Parameters

XAxis	Specify the direction of your X axis relative to yourself as the observer.
YAxis	Specify the direction of your Y axis relative to yourself as the observer.
ZAxis	Specify the direction of your Z axis relative to yourself as the observer.

Returns

An Output_SetAxisMapping class containing the result of the operation.

- The Result will be:
 - Success
 - CoLinearAxes
 - LeftHandedAxes

Output_GetAxisMapping GetAxisMapping () const

Get the current Axis mapping.

See Also: [SetAxisMapping\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_SetAxisMapping(pRetimingClient, Forward, Left, Up); // Z-up
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
Output_GetAxisMapping Output = MyClient.GetAxisMapping();
// Output.XAxis == ViconDataStreamSDK::CPP::Direction::Forward
// Output.YAxis == ViconDataStreamSDK::CPP::Direction::Left
// Output.ZAxis == ViconDataStreamSDK::CPP::Direction::Up
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.Client MyClient = new ViconDataStreamSDK.DotNET.Client();
Output_GetAxisMapping Output = MyClient.GetAxisMapping();
// Output.XAxis == ViconDataStreamSDK.DotNET.Direction.Forward
// Output.YAxis == ViconDataStreamSDK.DotNET.Direction.Left
// Output.ZAxis == ViconDataStreamSDK.DotNET.Direction.Up
```

Returns

An Output_GetAxisMapping class containing the result of the operation.

- The Result will be:
 - XAxis, YAxis, ZAxis

Output_UpdateFrame UpdateFrame (double Offset = 0.0)

Update the current frame state to represent the position of all active subjects at the current time.

The position of each segment is estimated by predicting forwards from the most recent frames received from the DataStream, taking into account the latency reported by the system to determine the amount of prediction required.

The results of calls which return details about the current frame state such as [GetSubjectCount\(\)](#) and [GetSegmentGlobalRotationQuaternion\(\)](#) will all return the stream contents and position at the time that this call was made.

If no call to [UpdateFrame\(\)](#) is made, calls querying the stream state will return NoFrame

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
CEnum Output = RetimingClient_GetFrame(); // Output == NotConnected
RetimingClient_Connect( pRetimingClient, "localhost" );
Output = RetimingClient_UpdateFrame(); // Output == Success
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
Output_UpdateFrame Output;
Output = MyClient.UpdateFrame(); // Output.Result == NotConnected
MyClient.Connect( "localhost" );
Output = MyClient.UpdateFrame(); // Output.Result == Success
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
Output_UpdateFrame Output;
Output = MyClient.UpdateFrame(); // Output.Result == NotConnected
MyClient.Connect( "localhost" );
Output = MyClient.UpdateFrame(); // Output.Result == Success
Output = MyClient.UpdateFrame(20); // Output.Result == Success
```

Parameters

Offset	An additional offset that will be applied to the time at which which the predicted position is calculated. This may be used to compensate for additional delays that are in the users system, such as render delay. This is implemented in a separate overloaded method in .NET.
--------	--

Returns

An Output_UpdateFrame class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_WaitForFrame WaitForFrame ()

Used when running the retiming client with a specified frame rate.

This call will block until the next frame is available, as driven by an internal clock running at the frame rate specified by Connect(Host, FrameRate). The frame data is re-timed to the correct time point

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
CEnum Output = RetimingClient_GetFrame(); // Output == NotConnected
RetimingClient_ConnectAndStart( pRetimingClient, "localhost", 200 );
Output = RetimingClient_WaitForFrame(); // Output == Success
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost", 200 );
Output = MyClient.WaitForFrame(); // Output.Result == Success
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost", 200 );
Output = MyClient.WaitForFrame(); // Output.Result == Success
```

Returns

An Output_WaitForFrame class containing the result of the operation.

- The Result will be:
 - Success
 - NotConnected

Output_GetSubjectCount GetSubjectCount () const

Return the number of subjects in the DataStream.

This information can be used in conjunction with GetSubjectName.

See Also: [GetSubjectName\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
COutput_GetSubjectCount SubjectCount;
RetimingClient_GetSubjectCount( pRetimingClient, &SubjectCount); // SubjectCount.Result == NoFrame
// SubjectCount.SubjectCount == 0;
RetimingClient_GetFrame( pRetimingClient );
RetimingClient_GetSubjectCount( pRetimingClient, &SubjectCount); // SubjectCount.Result == Success;
// SubjectCount.SubjectCount == 0;
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
Output_GetSubjectCount Output;
Output = MyClient.GetSubjectCount(); // Output.Result == NoFrame
// Ooutput.SubjectCount == 0
MyClient.GetFrame();
Output = MyClient.GetSubjectCount(); // Output.Result == Success
// Output.SubjectCount >= 0
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
Output_GetSubjectCount Output;
Output = MyClient.GetSubjectCount(); // Output.Result == NoFrame
// Ooutput.SubjectCount == 0
MyClient.UpdateFrame();
Output = MyClient.GetSubjectCount(); // Output.Result == Success
// Output.SubjectCount >= 0
```

Returns

An Output_GetSubjectCount class containing the result of the operation and the number of subjects.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame

Output_GetSubjectName GetSubjectName (const unsigned int SubjectIndex) const

Return the name of a subject.

This can be passed into segment and marker functions.

See Also: [GetSubjectCount\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
char SubjectName[128];
CEnum Output = RetimingClient_GetSubjectName(pRetimingClient, 0, 128, SubjectName);
// Output == Success
// SubjectName == "Al"
Output = RetimingClient_GetSubjectName(pRetimingClient, 1, 128, SubjectName);
// Output == Success
// SubjectName == "Bob"
Output = RetimingClient_GetSubjectName(pRetimingClient, 2, 128, SubjectName);
// Output == InvalidIndex
// SubjectName == ""

RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSubjectCount OutputGSC;
OutputGSC = MyClient.GetSubjectCount(); // OutputGSC.Result == Success
// OutputGSC.SubjectCount == 2
Output_GetSubjectName OutputGSN;
OutputGSN = MyClient.GetSubjectName(0); // OutputGSN.Result == Success
// OutputGSN.SubjectName == "Al"
OutputGSN = MyClient.GetSubjectName(1); // OutputGSN.Result == Success
// OutputGSN .SubjectName == "Bob"
OutputGSN = MyClient.GetSubjectName(2); // OutputGSN.Result == InvalidIndex
// OutputGSN.SubjectName == ""
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSubjectCount OutputGSC;
OutputGSC = MyClient.GetSubjectCount(); // OutputGSC.Result == Success
// OutputGSC.SubjectCount == 2
Output_GetSubjectName OutputGSN;
OutputGSN = MyClient.GetSubjectName(0); // OutputGSN.Result == Success
// OutputGSN.SubjectName == "Al"
OutputGSN = MyClient.GetSubjectName(1); // OutputGSN.Result == Success
// OutputGSN .SubjectName == "Bob"
OutputGSN = MyClient.GetSubjectName(2); // OutputGSN.Result == InvalidIndex
// OutputGSN.SubjectName == ""
```

Parameters

SubjectIndex	The index of the subject. A valid Subject Index is between 0 and GetSubjectCount() -1. Matlab: A valid Subject Index is between 1 and GetSubjectCount() .
--------------	---

Returns

An `Output_GetSubjectName` `GetSubjectName` class containing the result of the operation and the name of the subject.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetSubjectRootSegmentName GetSubjectRootSegmentName (const String & SubjectName) const

Return the name of the root segment for a specified subject.

This can be passed into segment functions. The root segment is the ancestor of all other segments in the subject.

See Also: [GetSegmentCount\(\)](#), [GetSegmentParentName\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_EnableSegmentData( pRetimingClient );
RetimingClient_GetFrame( pRetimingClient );
char RootSegment[128];
CEnum Result = RetimingClient_GetSubjectRootSegmentName(pRetimingClient, "Bob", 128, RootSegment);
// Result == Success
// RootSegment == "Pelvis"
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSubjectRootSegmentName Output;
Output = MyClient.GetSubjectRootSegmentName( "Bob" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSubjectRootSegmentName Output;
Output = MyClient.GetSubjectRootSegmentName( "Bob" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

Parameters

SubjectName	The name of the subject
-------------	-------------------------

Returns

An Output_GetSubjectRootSegmentName class containing the result of the operation and the name of the root segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetSegmentCount GetSegmentCount (const String & SubjectName) const

Return the number of segments for a specified subject in the DataStream.

This information can be used in conjunction with GetSegmentName.

See Also: [GetSubjectName\(\)](#), [GetSegmentName\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
COutput_GetSegmentCount SegmentCount;
RetimingClient_GetSegmentCount( pRetimingClient, "Bob", &SegmentCount );
// SegmentCount.Result == NOFrame
// SegmentCount.Value == 0
RetimingClient_GetFrame( pRetimingClient );
RetimingClient_GetSegmentCount( pRetimingClient, "Al", &SegmentCount );
// SegmentCount.Result == InvalidSubjectName
// SegmentCount.Value == 0
RetimingClient_GetSegmentCount( pRetimingClient, "Bob", &SegmentCount );
// SegmentCount.Result == Success
// SegmentCount.Value >= 0
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.EnableSegmentData();
MyClient.Connect( "localhost" );
Output_GetSegmentCount Output;
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == NoFrame
// Output.SegmentCount == 0
MyClient.GetFrame();
Output = MyClient.GetSegmentCount( "Al" ); // Output.Result ==
// InvalidSubjectName
// Output.SegmentCount == 0
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == Success
// Output.SegmentCount >= 0
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
Output_GetSegmentCount Output;
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == NoFrame
// Output.SegmentCount == 0
MyClient.UpdateFrame();
Output = MyClient.GetSegmentCount( "Al" ); // Output.Result ==
// InvalidSubjectName
// Output.SegmentCount == 0
Output = MyClient.GetSegmentCount( "Bob" ); // Output.Result == Success
// Output.SegmentCount >= 0
```

Parameters

SubjectName	The name of the subject.
-------------	--------------------------

Returns

An `Output_GetSegmentCount` class containing the result of the operation and the number of segments.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex

Output_GetSegmentName GetSegmentName (const String & SubjectName, const unsigned int SegmentIndex) const

Return the name of a subject segment specified by index.

See Also: [GetSegmentCount\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#), [GetSubject-RootSegmentName\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
COutput_GetSegmentCount SegmentCount;
RetimingClient_GetSegmentCount( pRetimingClient, "Bob", &SegmentCount );
// SegmentCount.Result == NOFrame
// SegmentCount.Value == 0
RetimingClient_GetFrame( pRetimingClient );
RetimingClient_GetSegmentCount( pRetimingClient, "AI", &SegmentCount );
// SegmentCount.Result == InvalidSubjectName
// SegmentCount.Value == 0
RetimingClient_GetSegmentCount( pRetimingClient, "Bob", &SegmentCount );
// SegmentCount.Result == Success
// SegmentCount.Value >= 0
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentName Output;
// SegmentIndex must be between 0 and GetSegmentCount() - 1
Output = MyClient.GetSegmentName( "Bob", 0 );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentName Output;
// SegmentIndex must be between 0 and GetSegmentCount() - 1
Output = MyClient.GetSegmentName( "Bob", 0 );
```

Parameters

SubjectName	The name of the subject
Segment-Index	The index of the segment

Returns

An Output_GetSegmentName class containing the result of the operation and the name of the parent segment or an empty string if it is the root segment.

- The Result will be:
 - Success

- NotConnected
- NoFrame
- InvalidIndex
- InvalidSubjectName

Output_GetSegmentChildCount GetSegmentChildCount (const String & SubjectName, const String & SegmentName) const

Return the number of child segments for a specified subject segment.

This can be passed into segment functions.

See Also: [GetSegmentCount\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentChildCount ChildCount;
RetimingClient_GetSegmentChildCount(pRetimingClient, "Bob", "Pelvis", &ChildCount);
// ChildCount.Result == Success
// ChildCount.SegmentCount == 2
RetimingClient_GetSegmentChildCount(pRetimingClient, "Alice", "Pelvis", &ChildCount);
// ChildCount.Result == InvalidSubjectName
// ChildCount.SegmentCount == 0
char SegmentName[128];
RetimingClient_GetSegmentName(pRetimingClient, "Bob", , 128, SegmentName);
RetimingClient_GetSegmentName(pRetimingClient, "Bob", &SegmentName);
// ChildCount.Result == Success
// ChildCount.SegmentCount == 2
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentChildCount OutputGSCC;
OutputGSCC = MyClient.GetSegmentChildCount( "Bob", "Pelvis" );
// OutputGSCC.Result == Success
// OutputGSCC.SegmentCount == 2
Output_GetSegmentChildName OutputGSCN;
OutputGSCN = MyClient.GetSegmentName( "Alice", 0 );
// OutputGSCN.Result == InvalidSubjectName
// OutputGSCN.SegmentName == ""
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 0 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "LFemur"
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 1 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "RFemur"
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 2 );
// OutputGSCN.Result == InvalidIndex
// OutputGSCN.SegmentName == ""
// (no third segment)
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentChildCount OutputGSCC;
OutputGSCC = MyClient.GetSegmentChildCount( "Bob", "Pelvis" );
// OutputGSCC.Result == Success
// OutputGSCC.SegmentCount == 2
Output_GetSegmentChildName OutputGSCN;
```

```
OutputGSCN = MyClient.GetSegmentName( "Alice", 0 );
// OutputGSCN.Result == InvalidSubjectName
// OutputGSCN.SegmentName == ""
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 0 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "LFemur"
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 1 );
// OutputGSCN.Result == Success
// OutputGSCN.SegmentName == "RFemur"
OutputGSCN = MyClient.GetSegmentName( "Bob", "Pelvis", 2 );
// OutputGSCN.Result == InvalidIndex
// OutputGSCN.SegmentName == ""
// (no third segment)
```

Parameters

SubjectName	The name of the subject
Segment- Name	The name of the segment

Returns

An `Output_GetSegmentChildCount` class containing the result of the operation and the number of child segments.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidIndex
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentChildName GetSegmentChildName (const String & SubjectName, const String & SegmentName, const unsigned int SegmentIndex) const

Return the name of the child segment for a specified subject segment and index.

See Also: [GetSegmentCount\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#), [GetSubject-RootSegmentName\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_EnableSegmentData( pRetimingClient );
RetimingClient_GetFrame( pRetimingClient );
char SegmentChildName[128];
// Segment index must be between 0 and RetimingClient_GetSegmentChildCount() - 1
RetimingClient_GetSegmentChildName( pRetimingClient, "Bob", "Pelvis", 0, 128, SegmentChildName );
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentChildName Output;
// Segment index must be between 0 and GetSegmentChildCount() - 1
Output = MyClient.GetSegmentChildName( "Bob", "Pelvis", 0 );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentChildName Output;
// Segment index must be between 0 and GetSegmentChildCount() - 1
Output = MyClient.GetSegmentChildName( "Bob", "Pelvis", 0 );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment
Segment-Index	The index of the child segment. A valid Segment Index is between 0 and GetSegmentChildCount() -1.

Returns

An `Output_GetSegmentChildName` class containing the result of the operation and the name of the child segment.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
- InvalidIndex
- InvalidSubjectName
- InvalidSegmentName

Output_GetSegmentParentName GetSegmentParentName (const String & SubjectName, const String & SegmentName) const

Return the name of the parent segment for a specified subject segment.

If the specified segment is the root segment of the subject then it will return an empty string.

See Also: [GetSegmentCount\(\)](#), [GetSegmentChildCount\(\)](#), [GetSegmentChildName\(\)](#), [GetSubject-RootSegmentName\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
char SegmentParentName[128];
CEnum Result = RetimingClient_GetSegmentParentName(
    pRetimingClient, "Bob", "Pelvis", 128, SegmentParentName);
// Result == Success
// SegmentParentName = ""
// This is the root segment
Result = RetimingClient_GetSegmentParentName(pRetimingClient, "Bob", "LFemur", 128, SegmentParentName);
// Result == Success
// SegmentParentName = "Pelvis"
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentParentName Output;
Output = MyClient.GetSegmentParentName( "Bob", "Pelvis" );
// Output.Result == Success
// Output.SegmentName == ""
// This is the root segment
Output = MyClient.GetSegmentParentName( "Bob", "LFemur" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentParentName Output;
Output = MyClient.GetSegmentParentName( "Bob", "Pelvis" );
// Output.Result == Success
// Output.SegmentName == ""
// This is the root segment
Output = MyClient.GetSegmentParentName( "Bob", "LFemur" );
// Output.Result == Success
// Output.SegmentName == "Pelvis"
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An `Output_GetSegmentParentName` class containing the result of the operation and the name of the parent segment or an empty string if it is the root segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticTranslation GetSegmentStaticTranslation (const String & SubjectName, const String & SegmentName) const

Return the static pose translation of a subject segment.

See Also: [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegmentStaticRotationQuaternion\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentStaticTranslation _Output_GetSegmentStaticTranslation;
RetimingClient_GetSegmentStaticTranslation(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentStaticTranslation);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentStaticTranslation Output =
MyClient.GetSegmentStaticTranslation( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentStaticTranslation Output =
MyClient.GetSegmentStaticTranslation( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An Output_GetSegmentStaticTranslation class containing the result of the operation and the translation of the segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticRotationHelical GetSegmentStaticRotationHelical (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment in helical coordinates.

The helical coordinates represent a vector whose length is the amount of rotation in radians, and the direction is the axis about which to rotate.

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentStaticRotationHelical _Output_GetSegmentStaticRotationHelical;
RetimingClient_GetSegmentStaticRotationHelical(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationHelical);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationHelical Output =
MyClient.GetSegmentStaticRotationHelical( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentStaticRotationHelical Output =
MyClient.GetSegmentStaticRotationHelical( "Alice", "Pelvis" );
```

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegment-StaticRotationQuaternion\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation](#), [GetSegmentLocalRotationHelical](#), [GetSegmentLocalRotationMatrix](#), [GetSegmentLocalRotation-Quaternion](#), [GetSegmentLocalRotationEulerXYZ](#)

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An Output_GetSegmentStaticRotationHelical class containing the result of the operation and the rotation of the segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticRotationMatrix GetSegmentStaticRotationMatrix (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment as a 3x3 row-major matrix.

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationQuaternion\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentStaticRotationMatrix _Output_GetSegmentStaticRotationMatrix;
RetimingClient_GetSegmentStaticRotationMatrix(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationMatrix);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationMatrix Output =
MyClient.GetSegmentStaticRotationMatrix( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentStaticRotationMatrix Output =
MyClient.GetSegmentStaticRotationMatrix( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An Output_GetSegmentStaticRotationMatrix class containing the result of the operation and the rotation of the segment.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentStaticRotationQuaternion GetSegmentStaticRotationQuaternion (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment in quaternion coordinates.

The quaternion is of the form (x, y, z, w) where w is the real component and x, y and z are the imaginary components. N.B. This is different from that used in many other applications, which use (w, x, y, z).

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegmentStaticRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentStaticRotationQuaternion _Output_GetSegmentStaticRotationQuaternion;
RetimingClient_GetSegmentStaticRotationQuaternion(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationQuaternion);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationQuaternion Output =
MyClient.GetSegmentStaticRotationQuaternion( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentStaticRotationQuaternion Output =
MyClient.GetSegmentStaticRotationQuaternion( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject
Segment-Name	The name of the segment

Returns

An Output_GetSegmentStaticRotationQuaternion class containing the result of the operation and the rotation of the segment.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
- InvalidSubjectName
- InvalidSegmentName

Output_GetSegmentStaticRotationEulerXYZ GetSegmentStaticRotationEulerXYZ (const String & SubjectName, const String & SegmentName) const

Return the static pose rotation of a subject segment in Euler XYZ coordinates.

See Also: [GetSegmentStaticTranslation\(\)](#), [GetSegmentStaticRotationHelical\(\)](#), [GetSegmentStaticRotationMatrix\(\)](#), [GetSegmentStaticRotationQuaternion\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#).

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentStaticRotationEulerXYZ _Output_GetSegmentStaticRotationEulerXYZ;
RetimingClient_GetSegmentStaticRotationEulerXYZ(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentStaticRotationEulerXYZ);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentStaticRotationEulerXYZ Output;
Output = MyClient.GetSegmentStaticRotationEulerXYZ( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentStaticRotationEulerXYZ Output;
Output = MyClient.GetSegmentStaticRotationEulerXYZ( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentStaticRotationEulerXYZ class containing the result of the request and the rotation of the segment (x, y, z).

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

Output_GetSegmentGlobalTranslation GetSegmentGlobalTranslation (const String & SubjectName, const String & SegmentName) const

Return the translation of a subject segment in global coordinates.

The translation is of the form (x, y, z) where x, y and z are in millimeters with respect to the global origin.

See Also: [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentGlobalTranslation _Output_GetSegmentGlobalTranslation;
RetimingClient_GetSegmentGlobalTranslation(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalTranslation);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentGlobalTranslation Output =
MyClient.GetSegmentGlobalTranslation( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentGlobalTranslation Output =
MyClient.GetSegmentGlobalTranslation( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalTranslation class containing the result of the operation, the translation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName

- InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the translation will be [o,o,o].

Output_GetSegmentGlobalRotationHelical GetSegmentGlobalRotationHelical (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in global helical coordinates.

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentGlobalRotationHelical _Output_GetSegmentGlobalRotationHelical;
RetimingClient_GetSegmentGlobalRotationHelical(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationHelical);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationHelical Output =
MyClient.GetSegmentGlobalRotationHelical( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentGlobalRotationHelical Output =
MyClient.GetSegmentGlobalRotationHelical( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationHelical class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case, the rotation will be [o,o,o].

Output_GetSegmentGlobalRotationMatrix GetSegmentGlobalRotationMatrix (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment as a 3x3 row-major matrix in global coordinates.

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentGlobalRotationMatrix _Output_GetSegmentGlobalRotationMatrix;
RetimingClient_GetSegmentGlobalRotationMatrix(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationMatrix);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationMatrix Output =
MyClient.GetSegmentGlobalRotationMatrix( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentGlobalRotationMatrix Output =
MyClient.GetSegmentGlobalRotationMatrix( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationMatrix Class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame.

Output_GetSegmentGlobalRotationQuaternion GetSegmentGlobalRotationQuaternion (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in global quaternion coordinates.

The quaternion is of the form (x, y, z, w) where w is the real component and x, y and z are the imaginary components. N.B. This is different from that used in many other applications, which use (w, x, y, z).

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentGlobalRotationQuaternion _Output_GetSegmentGlobalRotationQuaternion;
RetimingClient_GetSegmentGlobalRotationQuaternion(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationQuaternion);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationQuaternion Output =
MyClient.GetSegmentGlobalRotationQuaternion( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentGlobalRotationQuaternion Output =
MyClient.GetSegmentGlobalRotationQuaternion( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationQuaternion class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the Rotation will be [1,0,0,0].

Output_GetSegmentGlobalRotationEulerXYZ GetSegmentGlobalRotationEulerXYZ (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in global Euler XYZ coordinates.

See Also: [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentGlobalRotationEulerXYZ _Output_GetSegmentGlobalRotationEulerXYZ;
RetimingClient_GetSegmentGlobalRotationEulerXYZ(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentGlobalRotationEulerXYZ);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentGlobalRotationEulerXYZ Output =
MyClient.GetSegmentGlobalRotationEulerXYZ( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentGlobalRotationEulerXYZ Output =
MyClient.GetSegmentGlobalRotationEulerXYZ( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentGlobalRotationEulerXYZ class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

- Occluded will be True if the segment was absent at this frame. In this case the rotation will be [0,0,0].

Output_GetSegmentLocalTranslation GetSegmentLocalTranslation (const String & SubjectName, const String & SegmentName) const

Return the translation of a subject segment in local coordinates relative to its parent segment.

See Also: [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentLocalTranslation _Output_GetSegmentLocalTranslation;
RetimingClient_GetSegmentLocalTranslation(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentLocalTranslation);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.EnableSegmentData();
MyClient.GetFrame();
Output_GetSegmentLocalTranslation Output =
MyClient.GetSegmentLocalTranslation( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentLocalTranslation Output =
MyClient.GetSegmentLocalTranslation( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalTranslation class containing the result of the operation, the translation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

- Occluded will be True if the segment was absent at this frame. In this case the translation will be [0,0,0].

Output_GetSegmentLocalRotationHelical GetSegmentLocalRotationHelical (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in local helical coordinates relative to its parent segment.

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentLocalRotationHelical _Output_GetSegmentLocalRotationHelical;
RetimingClient_GetSegmentLocalRotationHelical(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationHelical);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentLocalRotationHelical Output =
MyClient.GetSegmentLocalRotationHelical( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentLocalRotationHelical Output =
MyClient.GetSegmentLocalRotationHelical( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationHelical class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

- Occluded will be True if the segment was absent at this frame. In this case the Rotation will be [0,0,0].

Output_GetSegmentLocalRotationMatrix GetSegmentLocalRotationMatrix (const String & SubjectName, const String & SegmentName) const

Return the rotation row-major matrix of a subject segment in local coordinates relative to its parent segment.

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#) , [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentLocalRotationMatrix _Output_GetSegmentLocalRotationMatrix;
RetimingClient_GetSegmentLocalRotationMatrix(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationMatrix);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentLocalRotationMatrix Output =
MyClient.GetSegmentLocalRotationMatrix( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentLocalRotationMatrix Output =
MyClient.GetSegmentLocalRotationMatrix( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationMatrix class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame.

Output_GetSegmentLocalRotationQuaternion GetSegmentLocalRotationQuaternion (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in local quaternion coordinates relative to its parent segment.

The quaternion is of the form (x, y, z, w) where w is the real component and x, y and z are the imaginary components. N.B. This is different from that used in many other applications, which use (w, x, y, z).

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationEulerXYZ\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#), [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentLocalRotationQuaternion _Output_GetSegmentLocalRotationQuaternion;
RetimingClient_GetSegmentLocalRotationQuaternion(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationQuaternion);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentLocalRotationQuaternion Output =
MyClient.GetSegmentLocalRotationQuaternion( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentLocalRotationQuaternion Output =
MyClient.GetSegmentLocalRotationQuaternion( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationQuaternion class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected

- NoFrame
 - InvalidSubjectName
 - InvalidSegmentName
- Occluded will be True if the segment was absent at this frame. In this case the rotation will be [1,0,0,0].

Output_GetSegmentLocalRotationEulerXYZ GetSegmentLocalRotationEulerXYZ (const String & SubjectName, const String & SegmentName) const

Return the rotation of a subject segment in local Euler XYZ coordinates relative to its parent segment.

See Also: [GetSegmentLocalTranslation\(\)](#), [GetSegmentLocalRotationHelical\(\)](#), [GetSegmentLocalRotationMatrix\(\)](#), [GetSegmentLocalRotationQuaternion\(\)](#), [GetSegmentGlobalTranslation\(\)](#), [GetSegmentGlobalRotationHelical\(\)](#), [GetSegmentGlobalRotationMatrix\(\)](#) , [GetSegmentGlobalRotationQuaternion\(\)](#), [GetSegmentGlobalRotationEulerXYZ\(\)](#)

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
COutput_GetSegmentLocalRotationEulerXYZ _Output_GetSegmentLocalRotationEulerXYZ;
RetimingClient_GetSegmentLocalRotationEulerXYZ(
    pRetimingClient, "Alice", "Pelvis", &_Output_GetSegmentLocalRotationEulerXYZ);
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.Connect( "localhost" );
MyClient.GetFrame();
Output_GetSegmentLocalRotationEulerXYZ Output =
MyClient.GetSegmentLocalRotationEulerXYZ( "Alice", "Pelvis" );
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
Output_GetSegmentLocalRotationEulerXYZ Output =
MyClient.GetSegmentLocalRotationEulerXYZ( "Alice", "Pelvis" );
```

Parameters

SubjectName	The name of the subject.
Segment-Name	The name of the segment.

Returns

An Output_GetSegmentLocalRotationEulerXYZ class containing the result of the operation, the rotation of the segment, and whether the segment is occluded.

- The Result will be:
 - Success
 - NotConnected
 - NoFrame
 - InvalidSubjectName
 - InvalidSegmentName

- Occluded will be True if the segment was absent at this frame. In this case the rotation will be [0,0,0].

void SetMaximumPrediction (double MaxPrediction)

Sets the maximum amount by which the interpolation engine will predict later than the latest received frame.

If required to predict by more than this amount, the result LateDataRequested will be returned.

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_SetMaximumPrediction( pRetimingClient, 30 );
RetimingClient_Connect( pRetimingClient, "localhost" );
RetimingClient_GetFrame( pRetimingClient );
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.SetMaximumPrediction( 30 );
MyClient.Connect( "localhost" );
MyClient.GetFrame();
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();
MyClient.SetMaximumPrediction( 30 );
MyClient.Connect( "localhost" );
MyClient.UpdateFrame();
```

Parameters

Max-Prediction	The maximum amount of prediction required in milliseconds
----------------	---

double MaximumPrediction () const

Returns the maximum prediction value currently in use.

The default value is 100 ms.

C example

```
CRetimingClient * pRetimingClient = RetimingClient_Create();
RetimingClient_SetMaximumPrediction( pRetimingClient, 30 );
RetimingClient_MaximumPrediction( pRetimingClient ); // Returns 30
RetimingClient_Destroy( pRetimingClient );
```

C++ example

```
ViconDataStreamSDK::CPP::RetimingClient MyClient;
MyClient.SetMaximumPrediction( 30 );
MyClient.MaximumPrediction(); // Returns 30
```

MATLAB example

Not implemented

.NET example

```
ViconDataStreamSDK.DotNET.RetimingClient MyClient = new ViconDataStreamSDK.DotNET.RetimingClient();  
MyClient.SetMaximumPrediction( 30 );  
MyClient.MaximumPrediction(); // Returns 30
```

Returns

The maximum prediction allowed in milliseconds

The documentation for this class was generated from the following files:

- DataStreamRetimingClient.h
- DataStreamRetimingClient.cpp

Index

- ~Client
 - Client, [15](#)
- ~RetimingClient
 - RetimingClient, [197](#)
- Client, [8](#)
 - ~Client, [15](#)
 - Client, [14](#)
 - Connect, [17](#)
 - ConnectToMulticast, [18](#)
 - DisableCentroidData, [38](#)
 - DisableDebugData, [41](#)
 - DisableDeviceData, [37](#)
 - DisableGreyscaleData, [39](#)
 - DisableMarkerData, [34](#)
 - DisableMarkerRayData, [36](#)
 - DisableSegmentData, [33](#)
 - DisableUnlabeledMarkerData, [35](#)
 - DisableVideoData, [40](#)
 - Disconnect, [20](#)
 - EnableCentroidData, [29](#)
 - EnableDebugData, [32](#)
 - EnableDeviceData, [28](#)
 - EnableGreyscaleData, [30](#)
 - EnableMarkerData, [25](#)
 - EnableMarkerRayData, [27](#)
 - EnableSegmentData, [24](#)
 - EnableUnlabeledMarkerData, [26](#)
 - EnableVideoData, [31](#)
 - GetAxisMapping, [56](#)
 - GetCameraCount, [168](#)
 - GetCameraDisplayName, [177](#)
 - GetCameraId, [171](#)
 - GetCameraName, [169](#)
 - GetCameraResolution, [179](#)
 - GetCameraType, [175](#)
 - GetCameraUserId, [173](#)
 - GetCentroidCount, [183](#)
 - GetCentroidPosition, [185](#)
 - GetCentroidWeight, [187](#)
 - GetDeviceCount, [134](#)
 - GetDeviceName, [135](#)
 - GetDeviceOutputCount, [137](#)
 - GetDeviceOutputName, [139](#)
 - GetDeviceOutputSubsamples, [144](#)
 - GetDeviceOutputValue, [142, 146](#)
 - GetEyeTrackerCount, [163](#)
 - GetEyeTrackerGlobalGazeVector, [166](#)
 - GetEyeTrackerGlobalPosition, [164](#)
 - GetForcePlateCount, [148](#)
 - GetForcePlateSubsamples, [155](#)
 - GetFrame, [57](#)
 - GetFrameNumber, [58](#)
 - GetFrameRate, [60](#)
 - GetFrameRateCount, [66](#)
 - GetFrameRateName, [67](#)
 - GetFrameRateValue, [68](#)
 - GetGlobalCentreOfPressure, [153, 161](#)
 - GetGlobalForceVector, [149, 157](#)
 - GetGlobalMomentVector, [151, 159](#)
 - GetGreyscaleBlob, [190](#)
 - GetGreyscaleBlobCount, [189](#)
 - GetHardwareFrameNumber, [65](#)
 - GetIsVideoCamera, [181](#)
 - GetLabeledMarkerCount, [132](#)
 - GetLabeledMarkerGlobalTranslation, [133](#)
 - GetLatencySampleCount, [61](#)
 - GetLatencySampleName, [62](#)
 - GetLatencySampleValue, [63](#)
 - GetLatencyTotal, [64](#)
 - GetMarkerCount, [116](#)
 - GetMarkerGlobalTranslation, [123](#)
 - GetMarkerName, [118](#)
 - GetMarkerParentName, [121](#)
 - GetMarkerRayContribution, [127](#)
 - GetMarkerRayContributionCount, [125](#)
 - GetObjectQuality, [114](#)
 - GetSegmentChildCount, [78](#)
 - GetSegmentChildName, [80](#)
 - GetSegmentCount, [74](#)
 - GetSegmentGlobalRotationEulerXYZ, [102](#)
 - GetSegmentGlobalRotationHelical, [96](#)
 - GetSegmentGlobalRotationMatrix, [98](#)
 - GetSegmentGlobalRotationQuaternion, [100](#)
 - GetSegmentGlobalTranslation, [94](#)
 - GetSegmentLocalRotationEulerXYZ, [112](#)
 - GetSegmentLocalRotationHelical, [106](#)
 - GetSegmentLocalRotationMatrix, [108](#)
 - GetSegmentLocalRotationQuaternion, [110](#)
 - GetSegmentLocalTranslation, [104](#)
 - GetSegmentName, [76](#)

[GetSegmentParentName, 82](#)
[GetSegmentStaticRotationEulerXYZ, 92](#)
[GetSegmentStaticRotationHelical, 86](#)
[GetSegmentStaticRotationMatrix, 88](#)
[GetSegmentStaticRotationQuaternion, 90](#)
[GetSegmentStaticRotationTranslation, 84](#)
[GetSubjectCount, 69](#)
[GetSubjectName, 70](#)
[GetSubjectRootSegmentName, 72](#)
[GetTimecode, 59](#)
[GetUnlabeledMarkerCount, 129](#)
[GetUnlabeledMarkerGlobalTranslation, 130](#)
[GetVersion, 15](#)
[GetVideoFrame, 191](#)
[IsCentroidDataEnabled, 47](#)
[IsConnected, 21](#)
[IsDebugEnabled, 50](#)
[IsDeviceDataEnabled, 46](#)
[IsGreyscaleDataEnabled, 48](#)
[IsMarkerDataEnabled, 43](#)
[IsMarkerRayDataEnabled, 45](#)
[IsSegmentDataEnabled, 42](#)
[IsUnlabeledMarkerDataEnabled, 44](#)
[IsVideoDataEnabled, 49](#)
[SetApexDeviceFeedback, 54](#)
[SetAxisMapping, 55](#)
[SetBufferSize, 51](#)
[SetCameraFilter, 192](#)
[SetStreamMode, 52](#)
[StartTransmittingMulticast, 22](#)
[StopTransmittingMulticast, 23](#)
 Connect
 Client, [17](#)
 RetimingClient, [199](#)
 ConnectToMulticast
 Client, [18](#)

 DisableCentroidData
 Client, [38](#)
 DisableDebugData
 Client, [41](#)
 DisableDeviceData
 Client, [37](#)
 DisableGreyscaleData
 Client, [39](#)
 DisableMarkerData
 Client, [34](#)
 DisableMarkerRayData
 Client, [36](#)
 DisableSegmentData
 Client, [33](#)
 DisableUnlabeledMarkerData
 Client, [35](#)
 DisableVideoData
 Client, [40](#)

 Disconnect
 Client, [20](#)
 RetimingClient, [200](#)

 EnableCentroidData
 Client, [29](#)
 EnableDebugData
 Client, [32](#)
 EnableDeviceData
 Client, [28](#)
 EnableGreyscaleData
 Client, [30](#)
 EnableMarkerData
 Client, [25](#)
 EnableMarkerRayData
 Client, [27](#)
 EnableSegmentData
 Client, [24](#)
 EnableUnlabeledMarkerData
 Client, [26](#)
 EnableVideoData
 Client, [31](#)

 GetAxisMapping
 Client, [56](#)
 RetimingClient, [203](#)
 GetCameraCount
 Client, [168](#)
 GetCameraDisplayName
 Client, [177](#)
 GetCameraId
 Client, [171](#)
 GetCameraName
 Client, [169](#)
 GetCameraResolution
 Client, [179](#)
 GetCameraType
 Client, [175](#)
 GetCameraUserId
 Client, [173](#)
 GetCentroidCount
 Client, [183](#)
 GetCentroidPosition
 Client, [185](#)
 GetCentroidWeight
 Client, [187](#)
 GetDeviceCount
 Client, [134](#)
 GetDeviceName
 Client, [135](#)
 GetDeviceOutputCount
 Client, [137](#)
 GetDeviceOutputName
 Client, [139](#)
 GetDeviceOutputSubsamples

Client, 144	GetMarkerName
GetDeviceOutputValue	Client, 118
Client, 142 , 146	GetMarkerParentName
GetEyeTrackerCount	Client, 121
Client, 163	GetMarkerRayContribution
GetEyeTrackerGlobalGazeVector	Client, 127
Client, 166	GetMarkerRayContributionCount
GetEyeTrackerGlobalPosition	Client, 125
Client, 164	GetObjectQuality
GetForcePlateCount	Client, 114
Client, 148	GetSegmentChildCount
GetForcePlateSubsamples	Client, 78
Client, 155	RetimingClient, 214
GetFrame	GetSegmentChildName
Client, 57	Client, 80
GetFrameNumber	RetimingClient, 216
Client, 58	GetSegmentCount
GetFrameRate	Client, 74
Client, 60	RetimingClient, 210
GetFrameRateCount	GetSegmentGlobalRotationEulerXYZ
Client, 66	Client, 102
GetFrameRateName	RetimingClient, 232
Client, 67	GetSegmentGlobalRotationHelical
GetFrameRateValue	Client, 96
Client, 68	RetimingClient, 228
GetGlobalCentreOfPressure	GetSegmentGlobalRotationMatrix
Client, 153 , 161	Client, 98
GetGlobalForceVector	RetimingClient, 229
Client, 149 , 157	GetSegmentGlobalRotationQuaternion
GetGlobalMomentVector	Client, 100
Client, 151 , 159	RetimingClient, 230
GetGreyscaleBlob	GetSegmentGlobalTranslation
Client, 190	Client, 94
GetGreyscaleBlobCount	RetimingClient, 226
Client, 189	GetSegmentLocalRotationEulerXYZ
GetHardwareFrameNumber	Client, 112
Client, 65	RetimingClient, 241
GetIsVideoCamera	GetSegmentLocalRotationHelical
Client, 181	Client, 106
GetLabeledMarkerCount	RetimingClient, 236
Client, 132	GetSegmentLocalRotationMatrix
GetLabeledMarkerGlobalTranslation	Client, 108
Client, 133	RetimingClient, 238
GetLatencySampleCount	GetSegmentLocalRotationQuaternion
Client, 61	Client, 110
GetLatencySampleName	RetimingClient, 239
Client, 62	GetSegmentLocalTranslation
GetLatencySampleValue	Client, 104
Client, 63	RetimingClient, 234
GetLatencyTotal	GetSegmentName
Client, 64	Client, 76
GetMarkerCount	RetimingClient, 212
Client, 116	GetSegmentParentName
GetMarkerGlobalTranslation	Client, 82
Client, 123	RetimingClient, 218

- GetSegmentStaticRotationEulerXYZ
 - Client, [92](#)
 - RetimingClient, [225](#)
- GetSegmentStaticRotationHelical
 - Client, [86](#)
 - RetimingClient, [221](#)
- GetSegmentStaticRotationMatrix
 - Client, [88](#)
 - RetimingClient, [222](#)
- GetSegmentStaticRotationQuaternion
 - Client, [90](#)
 - RetimingClient, [223](#)
- GetSegmentStaticTranslation
 - Client, [84](#)
 - RetimingClient, [220](#)
- GetSubjectCount
 - Client, [69](#)
 - RetimingClient, [206](#)
- GetSubjectName
 - Client, [70](#)
 - RetimingClient, [207](#)
- GetSubjectRootSegmentName
 - Client, [72](#)
 - RetimingClient, [209](#)
- GetTimecode
 - Client, [59](#)
- GetUnlabeledMarkerCount
 - Client, [129](#)
- GetUnlabeledMarkerGlobalTranslation
 - Client, [130](#)
- GetVersion
 - Client, [15](#)
 - RetimingClient, [197](#)
- GetVideoFrame
 - Client, [191](#)
- IsCentroidDataEnabled
 - Client, [47](#)
- IsConnected
 - Client, [21](#)
 - RetimingClient, [201](#)
- IsDebugEnabled
 - Client, [50](#)
- IsDeviceDataEnabled
 - Client, [46](#)
- IsGreyscaleDataEnabled
 - Client, [48](#)
- IsMarkerDataEnabled
 - Client, [43](#)
- IsMarkerRayDataEnabled
 - Client, [45](#)
- IsSegmentDataEnabled
 - Client, [42](#)
- IsUnlabeledMarkerDataEnabled
 - Client, [44](#)
- IsVideoDataEnabled
 - Client, [49](#)
- MaximumPrediction
 - RetimingClient, [243](#)
- RetimingClient, [193](#)
 - ~RetimingClient, [197](#)
 - Connect, [199](#)
 - Disconnect, [200](#)
 - GetAxisMapping, [203](#)
 - GetSegmentChildCount, [214](#)
 - GetSegmentChildName, [216](#)
 - GetSegmentCount, [210](#)
 - GetSegmentGlobalRotationEulerXYZ, [232](#)
 - GetSegmentGlobalRotationHelical, [228](#)
 - GetSegmentGlobalRotationMatrix, [229](#)
 - GetSegmentGlobalRotationQuaternion, [230](#)
 - GetSegmentGlobalTranslation, [226](#)
 - GetSegmentLocalRotationEulerXYZ, [241](#)
 - GetSegmentLocalRotationHelical, [236](#)
 - GetSegmentLocalRotationMatrix, [238](#)
 - GetSegmentLocalRotationQuaternion, [239](#)
 - GetSegmentLocalTranslation, [234](#)
 - GetSegmentName, [212](#)
 - GetSegmentParentName, [218](#)
 - GetSegmentStaticRotationEulerXYZ, [225](#)
 - GetSegmentStaticRotationHelical, [221](#)
 - GetSegmentStaticRotationMatrix, [222](#)
 - GetSegmentStaticRotationQuaternion, [223](#)
 - GetSegmentStaticTranslation, [220](#)
 - GetSubjectCount, [206](#)
 - GetSubjectName, [207](#)
 - GetSubjectRootSegmentName, [209](#)
 - GetVersion, [197](#)
 - IsConnected, [201](#)
 - MaximumPrediction, [243](#)
 - RetimingClient, [196](#)
 - RetimingClient, [196](#)
 - SetAxisMapping, [202](#)
 - SetMaximumPrediction, [243](#)
 - UpdateFrame, [204](#)
 - WaitForFrame, [205](#)
- SetApexDeviceFeedback
 - Client, [54](#)
- SetAxisMapping
 - Client, [55](#)
 - RetimingClient, [202](#)
- SetBufferSize
 - Client, [51](#)
- SetCameraFilter
 - Client, [192](#)

SetMaximumPrediction
 RetimingClient, [243](#)
SetStreamMode
 Client, [52](#)
StartTransmittingMulticast
 Client, [22](#)
StopTransmittingMulticast
 Client, [23](#)

UpdateFrame
 RetimingClient, [204](#)

WaitForFrame
 RetimingClient, [205](#)