



RC5 is a symmetric block cipher known for its simplicity and flexibility in key and block sizes.

Encryption



Decryption



RC5 Block Diagram:

- Input: The plaintext is divided into two words (w bits each)
- Initial Key Addition: The input words are combined with a portion of the expanded key.

- Mixing / Circular-shifts: These operations (XOR and Rotations) are applied iteratively in multiple rounds.

- Key Schedule: Generates the expanded key from the secret key.

- Output: The result of the final round is the ciphertext (two w-bit words).

Modes of operations:

i) ECB (Electronic Codebook):

The simplest mode, encrypting each block independently. Suitable for short, random data but can reveal patterns in non-random.

ii) CBC (Cipher Block Chaining):

Each block is XORed with the previous ciphertext block before encryption. Providing better security than ECB.

iii) OFB (Output Feedback):

Uses the previous ciphertext block to generate the key stream, making it suitable for noisy channel.

iv) CFB (Cipher Feedback):

Converts the block cipher into a stream cipher by feeding back previous ciphertext blocks.

v) Counter (CTR):

Uses a counter to generate the key stream allowing for parallel encryption and decryption.

Java implementation of RC5

```
import java.nio.ByteBuffer;
import java.util.Arrays;

public class RC5 {
    private final int w = 32;
    private final int r = 12;
    private final int b = 16;
    private final int[] S;
    private final int Pw = 0xb7e15163, Qw = 0x9e3779b9;

    public RC5(byte[] key) {
        int c = (key.length + 3) / 4;
        int[] L = new int[c];

        for (int i = 0; i < key.length; i++) {
            L[i/4] = ((key[i] & 0xFF) << (8 * (i/4))) >> (32 - 8);
        }

        int t = 2 * (r + 1);
        S = new int[t];
        S[0] = Pw;

        for (int i = 1; i < t; i++) {
            S[i] = S[i-1] + Qw;
        }
    }
}
```

```

int A=0, B=0, i=0, j=0;
int v=3 * (Math.max(C,4));
for (int s=0; s<v; s++) {
    A = s[i] = Integer.rotateLeft((s[i]+A+B), 3);
    B = L[s] = Integer.rotateLeft((L[s]+A+B), (A+B));
    i = (i+1) % v;
    j = (j+1) % v;
}
}

```

```

public int[] encrypt (int[] p) {
    int A = p[0] + s[0];
    int B = p[1] + s[1];
    for (int i=1; i<v; i++) {
        A = Integer.rotateLeft(A^B, B) + s[2*i];
        B = Integer.rotateLeft(B^A, A) + s[2*i+1];
    }
    return new int[] {A, B};
}

```

```

public int[] decrypt (int[] c) {
    int A = c[0];
    int B = c[1];
    for (i=v; i>1; i--) {

```

```
B = Integer.rotateRight(B - S[2 * i + 1], A) ^ A;
```

```
A = Integer.rotateRight(A - S[2 * i], B) ^ B; }
```

```
A -= S[0];
```

```
B -= S[1];
```

```
return new int[] { A, B }; }
```

```
public static void main(String[] args) {
```

```
byte[] key = "MySecretKey12345".getBytes();
```

```
RCS rcs = new RCS(key);
```

```
int[] plaintext = { 0x12345678, 0x9ABCDEF0 };
```

```
System.out.printf("Plaintext: %08x %08x\n",  
    plaintext[0], plaintext[1]);
```

```
int[] ciphertext = rcs.encrypt(plaintext);
```

```
System.out.printf("Encrypted: %08x %08x\n",  
    ciphertext[0], ciphertext[1]);
```

```
int[] decrypted = rcs.decrypt(ciphertext);
```

```
System.out.printf("Decrypted: %08x %08x\n",  
    decrypted[0], decrypted[1]); }
```

Sample output:

plaintext: 12345678 9ABCDEF0

Encrypted: E2C3456 5E91A7B9

Decrypted: 12345678 9ABCDEF0