Source-bound phase pipeline wiring status

October 10, 2026

Target: the exact source in `source.decimal` (895 bits). The baked executable uses its prepared IMASM operator, folded ququart work register, SIC readout, phase reconstruction, and nested-radix closure. The native factor-producing arm remains disabled for this run.

0.1 Lean boundary

`ququart_factor_baked` now calls the shared `p4rakernel/bridge/client.rs` admission before preparing work. Admission requires the compiled kernel to report SIXTEEN_3 active and checks the Lean `bridgeHold` re-entry, Y reduction, and least/greatest fixed-point certificate. Once the phase executor returns a candidate closure, the executable sends the decimal source and decoded factors through the Lean `product` command. It reports completion only when Lean certifies `p*q = source` and both factors exceed one. This adds an independent kernel arithmetic boundary; it does not supply phase evidence or factors.

The bridge was exercised directly on `Y 6`, which returned the SIXTEEN_3, re-entry, and certified fixed-point report. Its product path rejected the non-factor control pair `(2, 3)` for the exact source. The baked release target compiles with the bridge wired in. The exact-pair success path remains unverified until the phase executor produces a candidate.

0.2 Vox wiring coverage

The native Vox trace reads four `apply_nested` operation counters. In the archived exact-source run, Toggle and ModularAdd are active; Add and Compare remain at zero. The indirect jump-table paths for all four variants are present in the compiled symbol, but those last two variants have not been exercised by this phase schedule. Therefore the Diagrammar gap concerns static branch coverage; the archived phase work executed the modular-add path. That modular-add path has reached 4 of 899 scheduled phase digits. Its current profile is in `vox_native_roundtrip_release.*`; this is partial progress, not a factor result.

The phase-analysis stage is `PhaseReadoutAccumulator::close_fraction`: it filters continued-fraction convergents by the measured-bin error bound and combines only denominators supported by measured evidence. Candidate closure uses the shared certified modular residue step. It first verifies `base^period ≡ 1 (mod source)`, then evaluates each requested tick at its residue modulo that period. The same step serves phase, SIC,

trilattice, and native-width winding factor paths. The archived trace reached 4 of 899 scheduled digits.

Native instruction samples from the exact-source trace resolve most often to `DecisionArena::modular_digit_add::visit`, followed by `reclaim_pending`, `FixedComplex::mul`, and exact `BigInt::add`. This locates the cost in the coherent decision-diagram arithmetic and reclamation beneath nested modular addition, rather than in the omitted Toggle/Add/Compare dispatch paths. The leaf interning index now uses a small byte hasher; complete `Node` equality still checks both exact amplitude integers. Exact arithmetic tests pass and the optimized release carrier builds with this change; the already-running trace uses its earlier executable, so runtime speedup remains unmeasured.

The current release build also precomputes place values and modular sums for digit widths up to eight bits, avoiding repeated BigUint modular reductions at each recursive diagram node. Wider digits retain the prior general recursion. A new 14-wire coherent-state test covers enabled and disabled controls, wrapped translation, invalid work values, and non-real amplitudes. All nine exact decision tests pass. The long exact-source trace predates both optimizations; their effect on its run time remains to be measured in a subsequent run.

0.3 Arithmetic checks and next evidence

The release path no longer repeats full source-cofactor and interval partition traversals solely for round-trip assertions. Those checks remain active in debug builds, and all nine tests in `tests/ququart_decision_exact.rs` pass, including exact coherent-amplitude modular translations at 200 and 256 bits. Completion requires a phase-derived candidate, the Lean exact-product certificate, and an independently checked integer multiplication.

0.4 Prepared-base startup validation

`scaled_modular_base` previously built and discarded a complete ququart power schedule just to establish that the scaled base was a unit modulo the source. The baked executor then checked the supplied schedule again at `QuquartPowerSchedule::from_prepared`. The current implementation performs the unit check with an exact gcd and retains the full per-entry schedule check at the execution boundary. The source-bound release target builds with this change.

The previous cleanup commit had removed `measurements/anyon-extractor-width-controls.tsv`, which several library tests include at compile time. I restored that test fixture from its pre-cleanup revision. The exact batched-twiddle parity test and the SIC phase-pole test both pass.

Vox now records a pipeline stage and the count of validated prepared powers. The codes are 0 for startup, 1 for Lean admission, 2 for parsed input, 3 for Fourier validation, 4 for scaled-base validation, 5 for prepared device, 6 for decoded powers, 7 for validated schedule, and 8 for phase execution. The run `vox_native_pipeline_stage_release`, built before the SIC table change, was still at stage 4 after 263 seconds. The exact-source run `vox_native_sic_table_release` reached stage 5 by its 32-second sample and was there while decoding the prepared powers. This directly confirms that the batched SIC phases pass the previous device-construction bottleneck. The recorded sample precedes phase-counter initialization.

0.5 Certified residue execution

`Vox/src/modular_residue.rs` supplies the shared operation for BigUint, native integers, and binary numeral tapes. The certificate privately binds the base, source, and period. It verifies `base^period mod source = 1` once and evaluates each tick at `tick mod period`. Phase, SIC, winding, QFT, GPU Shor, Belnap, coupled, and Hadamard period closures use this operation. Candidate-period discovery precedes certification.

The measured base stays attached to ququart extraction and its residue receipt. The baked executable evaluates tick `1000000000000000001` after phase closure and Lean product certification. `ququart_verify_readout` checks every receipt field against the measured base and period and evaluates the unreduced exponent independently. Corrupting each receipt field separately is rejected.

The static 128-bit control under `../modular_residue_20261010/control128/` produces `18446744073709551615` and `18446744073709551617` from two phase measurements, with measured period 2. The source is `340282366920938463463374607431768211455`. The huge tick reduces to index 1 and value `18446744073709551616`. The independent readout verifier accepts the phase, SIC, nested closure, product, and residue receipt. This source is a structured composite execution control.

The entire static control and 895-bit image pass the rewirer's interprocedural Frobenius control-flow check with full instruction coverage. Their rewritten IMASM tapes retain the indirect expressions and call-return frames. The baked readout emits canonical IMASM words for both factors and every residue receipt value.

The VM pointer-write trace identifies musl arena growth as the source of the first-shot stall. `mremap` fell through the syscall handler and returned zero. Musl added the allocation's internal offset to that address and replaced the arena node pointer with `0xa80`, so Born-mass evaluation multiplied ELF bytes as amplitude integers. The trace records the write at guest PC `0x5e4f6`, step 18918086, after the preceding node pointer was `0x38015aa80`. The actual guest call chain reaches `DecisionArena::mass::visit` and `measure_phase_digit`.

Vox now resizes anonymous guest storage through `mremap`, preserving its sparse pages across moves, growth, shrinkage, and fixed destination replacement. Error paths preserve the source allocation and return errno. All 14 VM instruction and memory tests pass, including the musl-sized allocation growth regression. The same rewritten control tape is the execution check for this repair.

Factoring inputs use isolated source documents. `../unstructured_semiprimes.decimal` contains only the extracted decimal n column, one value per line. The CUDA prefix comparison reads this file directly. The 895-bit prepared operator is bound to its isolated source word and includes no factor or period fields.

0.6 Word readout transport

The Vox process runner preserves guest stdout byte for byte and propagates the guest exit status. Runner halts use stderr and exit status 2. Successful and nonzero-exit controls emit the same canonical word without a decimal status suffix. Concurrent executions reserve separate Lean capture files through exclusive creation, including when separate PID namespaces reuse a PID.

The final static control produces the same word readout as its preceding build. `ququart_verify_readout` accepts that output, including the measured-base residue receipt and exact factor product. The execution records are `../modular_residue_20261010/control128/continued_native_checks.json` and `continued_native_verification.log`. The rewritten control and target tapes carry the final static bridge and execute through `vox_runner_final`.

0.7 Native sample resumption

Vox advances one instruction across each native sample stop before continuing the process. The control completes under this sampler in 6.591 seconds, emits a byte-identical copy of its unsampled IMASM readout, and passes the independent factor and residue verifier. Continuing directly from the sample stop keeps this control at the completed `wait4` return during Lean admission. Changing the sampling signal alone preserves that behavior. The retained comparison is `../modular_residue_20261010/control128/profiler_wait_controls.json`.