

Specifications	ASA A1KA Dual Chassis HA Pair	ASA A20 Single Chassis HA Pair	ASA A30 Single Chassis HA Pair
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Storage Limits			
Max Number of Drives (Total)	240	48	72
Internal Drives count	N/A	Max: 24 per Chassis;	Max: 24 per Chassis;
Max number of Capacity Flash NVMe SSD Drives	N/A	N/A	N/A
Max number of NVMe SSD Drives	Max: 240 per HA Pair;	Max: 48 per HA Pair;	Max: 72 per HA Pair;
Max number of FS4483 shelves	N/A	N/A	N/A
Max number of NS224 shelves	10 external	1 internal + 1 external	1 internal + 2 external
Max number of NS224 w/ NSM100B shelves	10 external	1 external	2 external
Capacity Limits			
Marketing Maximum Raw Capacity (GB)			
Node	4,298,000	1,473,600	2,210,400
HA Pair	4,298,000	1,473,600	2,210,400
Core Cluster Limits			
Maximum Number of VLANs			
Node	512	512	512
Maximum IPsec Policies			
SVM	N/A	N/A	N/A
Cluster	N/A	N/A	N/A
Maximum IPsec Policies (If using HW Offload)			
SVM	N/A	40	40
Cluster	N/A	40	40
Maximum IPsec Policies (If not using HW Offload)			
SVM	N/A	256	256
Cluster	N/A	1,500	1,500
Maximum number of Intercluster LIFs			
Node	N/A	8	8
Maximum Number of IPspaces			
Cluster	N/A	512	512
System Maximums and Limits			
Max Nodes per Cluster (NAS / SAN)	Not Supported / 12	Not Supported / 6	Not Supported / 8
Max FabricPool Size	Not Supported	Not Supported	Not Supported
Max FlexGroup Data Constituent Size	Not Supported	Not Supported	Not Supported
Max Infinite Volume Data Constituent Size	Not Supported	Not Supported	Not Supported
Min Root Volume Size	-	-	-
NetApp Volume Encryption	Dual-layer Encryption	Dual-layer Encryption	Dual-layer Encryption
Processor			
Processor Model	64-bit 52-Core 1.7GHz	64-bit 8-core 2.1 GHz	64-bit 16-core 2.0 GHz
Processor Architecture	64 bit	64 bit	64 bit
Processor Speed	1.70 Ghz	2.10 Ghz	2.00 Ghz
Processor Count (Per Node)	2	1	1
Processor Count (Per Config)	4	2	2
Processor Cores (Per CPU)	52	8	16
Processor Cores (Per Node)	104	8	16
Processor Cores (Per Config)	208	16	32
Memory			
NVMEM (Per Node)	N/A	8 GB	8 GB
NVMEM (Per Config)	N/A	16 GB	16 GB
NVRAM (Per Node)	64 GB	N/A	N/A

	ASA A1KA Dual Chassis HA Pair	ASA A20 Single Chassis HA Pair	ASA A30 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
NVRAM (Per Config)	128 GB	N/A	N/A
RAM (Per Node)	1024 GB	64 GB	64 GB
RAM (Per Config)	2048 GB	128 GB	128 GB
Onboard Ports			
Ethernet Ports	-	-	-
UTA2 Ports	-	-	-
Expansion Slots	9 x IO Module (per Chassis) 18 x IO Module (per System)	8 x IO Module (per System)	8 x IO Module (per System)
SAS Ports	-	-	-
Physical Characteristics			
Rack Units	4	2	2
Chassis Height	3.5" (8.89 cm)	3.43" (8.7 cm)	3.43" (8.7 cm)
Chassis Width with Mounting Flanges	19.02" (48.3 cm)	19.02" (48.3 cm)	19.02" (48.3 cm)
Chassis Width without Mounting Flanges	17.68" (44.9 cm)	17.6" (44.7 cm)	17.6" (44.7 cm)
Chassis Depth with Cable Mgmt	35.24" (89.5 cm)	-	-
Chassis Depth without Cable Mgmt	30.04" (76.3 cm)	22.05" (56 cm)	22.05" (56 cm)
Chassis Weight			
System Clearance Dimensions			
Front Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Front Clearance (Maintenance)	31.99" (81.2 cm)	24.03" (61 cm)	24.03" (61 cm)
Rear Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Rear Clearance (Maintenance)	11.03" (28 cm)	16.94" (43 cm)	16.94" (43 cm)
Environmental Requirements			
Operating Temperature Range	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C
Storage Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Transit Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Operating Relative Humidity	8 to 80 %	8 to 80 %	8 to 80 %
Storage Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Transit Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Operating Altitude Range	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m
Storage Altitude Range	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m
Transit Altitude Range	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m
Acoustic Noise - Sound Power	8.5 Bels	8 Bels	8 Bels
Acoustic Noise - Sound Pressure	67.7 dBA	70.5 dBA	70.5 dBA
Input Power Voltage	40 to 48; 200 to 240;	40 to 48; 100 to 120; 200 to 240;	40 to 48; 200 to 240;
Storage OS Requirements (for selected major version)			
Recommended Version	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2
Minimum OS	9.19.1RC1	9.19.1RC1	9.19.1RC1
Maximum OS	9.19.1P2	9.19.1P2	9.19.1P2
Software and Firmware * indicates that firmware is bundled with Storage OS Version			
BIOS	20.8*	21.4.1, 21.3*	21.4.1, 21.3*
BMC	18.6*	19.4*	19.4*
Product Standards Compliance			
Certifications EMC/EMI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI

	ASA A1KA Dual Chassis HA Pair	ASA A20 Single Chassis HA Pair	ASA A30 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Certifications safety	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS
Certifications Safety/EMC/EMI	EAC, UKRSEPRO	EAC, UKRSEPRO	EAC, UKRSEPRO
Certifications Safety/EMC/EMI/RoHS	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC
Standards EMC/EMI	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835
Standards Safety	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)
System Availability & Support			
Release Date	Sep 2024	Feb 2025	Feb 2025
End of Availability (EOA)	-	-	-
End of Support (EOS)	-	-	-
WAFL Cluster Limits			
Maximum character length for Snapshot copy names			
Snapshot	N/A	255	255
Maximum number of LUN Snapshot Copies			
Consistency group	1,023	1,023	1,023
Node	1,023,000	1,023,000	1,023,000
HA Pair	2,046,000	2,046,000	2,046,000
Quality of Service Cluster Limits			
Maximum number of Policy Groups			
Cluster	N/A	12,000	12,000
Maximum number of QoS user workloads			
Cluster	N/A	40,000	40,000
Data Protection Cluster Limits			
Maximum fan-out from source for DP mirror			
Volume	N/A	8	8
Maximum number of clusters that can be peered			
Cluster	N/A	400	400
Maximum number of concurrent Snap Mirror or SnapVault transfers			
Node	N/A	100	100
Maximum number of data protection (DP) mirrors and/or SnapVault relationships			
Volume	N/A	1	1
Node	N/A	500	500
HA Pair	N/A	1,000	1,000
Cluster	N/A	2,000	2,000
Maximum number of SnapMirror Synchronous relationships			
Volume	N/A	1	1
Node	N/A	400	400
HA Pair	N/A	400	400

	ASA A1KA Dual Chassis HA Pair	ASA A20 Single Chassis HA Pair	ASA A30 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Number of storage virtual machine disaster recovery (SVM DR) relationship			
Cluster	128	N/A	N/A
Maximum Number of FlexGroups and/or Consistency Groups supported in (SVM DR) relationship			
Cluster	32	N/A	N/A
Maximum Number of Concurrent SnapDiff Sessions			
Node	64	64	64
HA Pair	128	128	128
Consistency Groups			
Maximum Number of Consistency Groups			
Cluster	N/A	1,600	1,600
Maximum Number of Consistency Groups and Parent Consistency Groups			
Cluster	N/A	1,600	1,600
Maximum Number of Parent Consistency Groups			
Cluster	N/A	1,600	1,600
Maximum Number of Child Consistency Groups in a Parent Consistency Group			
Parent consistency group	N/A	5	5
Storage Availability Zone			
Cluster Limits			
Maximum FC queue depth available (SAZ)			
Port	2,048	2,048	2,048
Maximum I/O queue count available - NVMe/FC (SAZ)			
Regular Priority Controller	4	4	4
High Priority Controller	8	6	6
Maximum I/O queue count available - NVMe/TCP (SAZ)			
Regular Priority Controller	2	2	2
High Priority Controller	8	4	4
Maximum I/O queue depth available - NVMe/FC (SAZ)			
Regular Priority Queue	32	32	32
High Priority Queue	64	32	32
Maximum I/O queue depth available - NVMe/TCP (SAZ)			
Regular Priority Queue	128	128	128
High Priority Queue	128	128	128
Maximum number of controllers - NVMe/FC (SAZ)			
Port	256	256	256
Maximum number of controllers - NVMe/TCP (SAZ)			
Node	2,048	128	128
Maximum number of igroups (SAZ)			
Node	4,096	2,048	2,048
HA Pair	8,192	4,096	4,096
Cluster	32,768	12,288	16,384

	ASA A1KA Dual Chassis HA Pair	ASA A20 Single Chassis HA Pair	ASA A30 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum number of IP Data Lifs (iSCSI + NVMe/TCP)			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	512	512	512
Cluster	4,096	3,072	4,096
Maximum number of iSCSI sessions (SAZ)			
Node	8,192	4,096	4,096
HA Pair	16,384	8,192	8,192
Cluster	65,536	24,576	32,768
Maximum number of iSCSI/FCP initiators			
igroup	256	256	256
Node	4,096	2,048	2,048
HA Pair	8,192	4,096	4,096
Cluster	32,768	12,288	16,384
Maximum number of LIFS - FCP (SAZ)			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	1,024	1,024	1,024
Cluster	4,096	3,072	4,096
Maximum number of LIFS - NVMe/FC			
Port	16	16	16
SVM	24	24	24
Node	32	32	32
HA Pair	32	32	32
Cluster	32	32	32
Maximum number of LUN mappings (SAZ)			
igroup	4,096	4,096	4,096
Node	5,000	500	500
HA Pair	10,000	1,000	1,000
Cluster	30,000	3,000	4,000
Maximum number of namespace mappings (SAZ)			
Subsystem	1,024	1,024	1,024
Node	5,000	500	500
HA Pair	10,000	1,000	1,000
Cluster	30,000	3,000	4,000
Maximum number of NVMe/oF hosts			
Subsystem	64	64	64
Maximum number of portsets (SAZ)			
Node	4,096	2,048	2,048
HA Pair	8,192	4,096	4,096
Cluster	32,768	12,288	16,384
Maximum Number of SAN (iSCSI/FCP) Hosts (ITNs)			
Port	512	512	512
Node	8,192	4,096	4,096
HA Pair	16,384	8,192	8,192
Cluster	65,536	24,576	32,768
Maximum number of Storage Units			
Node	5,000	500	500
HA Pair	10,000	1,000	1,000
Cluster	30,000	3,000	4,000

	ASA A1KA Dual Chassis HA Pair	ASA A20 Single Chassis HA Pair	ASA A30 Single Chassis HA Pair
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum number of storage virtual machines (SVMs)			
Cluster	256	256	256
Maximum number of subsystems (SAZ)			
SVM	8,192	8,192	8,192
Cluster	8,192	8,192	8,192
Maximum Storage Unit size (TiB)			
Storage Unit	128	128	128
SnapMirror Active Sync (symmetric active/active)			
Maximum Number of Nodes in SnapMirror Active Sync relationships for NVMe			
Node	2	2	2
Maximum Number of NS Maps			
Consistency group	256	256	256
Maximum Number of Subsystem			
Consistency group	16	16	16
Maximum Number of Unique Namespaces Supported			
Node	400	400	400
Maximum Number of Nodes in SnapMirror Active Sync relationships			
Cluster	4	4	4
Maximum number of constituent LUNs in SnapMirror Active Sync relationships (Constituent LUNs)			
Consistency group	80	80	80
HA Pair (Non-Scalable)	400	400	400
Maximum number of Consistency Groups in SnapMirror Active Sync relationships			
HA Pair (Non-Scalable)	50	50	50
Maximum Number of LUN Maps in SnapMirror Active Sync relationships			
Node	4,096	4,096	4,096
Maximum Number of LUNs in SnapMirror Active Sync relationships			
Volume	512	512	512
Maximum Number of SAN LIFs in SnapMirror Active Sync relationships			
Vserver	128	128	128

Specifications	ASA A50 Single Chassis HA Pair	ASA A70 Single Chassis HA Pair	ASA A90 Single Chassis HA Pair VER2
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Storage Limits			
Max Number of Drives (Total)	120	240	240
Internal Drives count	Max: 24 per Chassis;	Max: 48 per Chassis;	Max: 48 per Chassis;
Max number of Capacity Flash NVMe SSD Drives	N/A	N/A	N/A
Max number of NVMe SSD Drives	Max: 120 per HA Pair;	Max: 240 per HA Pair;	Max: 240 per HA Pair;
Max number of FS4483 shelves	N/A	1 internal	1 internal
Max number of NS224 shelves	1 internal + 4 external	8 external	8 external
Max number of NS224 w/ NSM100B shelves	4 external	8 external	8 external
Capacity Limits			
Marketing Maximum Raw Capacity (GB)			
Node	3,684,000	4,298,000	4,298,000
HA Pair	3,684,000	4,298,000	4,298,000
Core Cluster Limits			
Maximum Number of VLANs			
Node	512	512	512
Maximum IPsec Policies			
SVM	256	256	256
Cluster	1,500	1,500	1,500
Maximum IPsec Policies (If using HW Offload)			
SVM	N/A	N/A	N/A
Cluster	N/A	N/A	N/A
Maximum IPsec Policies (If not using HW Offload)			
SVM	N/A	N/A	N/A
Cluster	N/A	N/A	N/A
Maximum number of Intercluster LIFs			
Node	8	8	8
Maximum Number of IPspaces			
Cluster	512	512	512
System Maximums and Limits			
Max Nodes per Cluster (NAS / SAN)	Not Supported / 12	Not Supported / 12	Not Supported / 12
Max FabricPool Size	Not Supported	Not Supported	Not Supported
Max FlexGroup Data Constituent Size	Not Supported	Not Supported	Not Supported
Max Infinite Volume Data Constituent Size	Not Supported	Not Supported	Not Supported
Min Root Volume Size	-	-	-
NetApp Volume Encryption	Dual-layer Encryption	Dual-layer Encryption	Dual-layer Encryption
Processor			
Processor Model	64-bit 24-core 1.9 GHz	64-bit 16-Core 2.0GHz	64-bit 32-Core 2.0GHz
Processor Architecture	64 bit	64 bit	64 bit
Processor Speed	1.90 Ghz	2.00 Ghz	2.00 Ghz
Processor Count (Per Node)	1	2	2
Processor Count (Per Config)	2	4	4
Processor Cores (Per CPU)	24	16	32
Processor Cores (Per Node)	24	32	64
Processor Cores (Per Config)	48	64	128
Memory			
NVMEM (Per Node)	16 GB	N/A	N/A
NVMEM (Per Config)	32 GB	N/A	N/A
NVRAM (Per Node)	N/A	32 GB	64 GB

Specifications	ASA A50 Single Chassis HA Pair	ASA A70 Single Chassis HA Pair	ASA A90 Single Chassis HA Pair VER2
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
NVRAM (Per Config)	N/A	64 GB	128 GB
RAM (Per Node)	128 GB	128 GB	1024 GB
RAM (Per Config)	256 GB	256 GB	2048 GB
Onboard Ports			
Ethernet Ports	-	-	-
UTA2 Ports	-	-	-
Expansion Slots	8 x IO Module (per System)	18 x IO Module (per System)	18 x IO Module (per System)
SAS Ports	-	-	-
Physical Characteristics			
Rack Units	2	4	4
Chassis Height	3.43" (8.7 cm)	6.89" (17.5 cm)	6.89" (17.5 cm)
Chassis Width with Mounting Flanges	19.02" (48.3 cm)	19.02" (48.3 cm)	19.02" (48.3 cm)
Chassis Width without Mounting Flanges	17.6" (44.7 cm)	17.6" (44.7 cm)	17.6" (44.7 cm)
Chassis Depth with Cable Mgmt	-	38.27" (97.2 cm)	38.27" (97.2 cm)
Chassis Depth without Cable Mgmt	22.05" (56 cm)	34.49" (87.6 cm)	34.49" (87.6 cm)
Chassis Weight			
System Clearance Dimensions			
Front Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Front Clearance (Maintenance)	24.03" (61 cm)	36.41" (92.4 cm)	36.41" (92.4 cm)
Rear Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)	6.03" (15.3 cm)
Rear Clearance (Maintenance)	16.94" (43 cm)	36.01" (91.4 cm)	36.01" (91.4 cm)
Environmental Requirements			
Operating Temperature Range	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C
Storage Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Transit Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Operating Relative Humidity	8 to 80 %	8 to 80 %	8 to 80 %
Storage Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Transit Relative Humidity	10 to 95 %	10 to 95 %	10 to 95 %
Operating Altitude Range	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m
Storage Altitude Range	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m
Transit Altitude Range	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m
Acoustic Noise - Sound Power	8 Bels	8.6 Bels	8.6 Bels
Acoustic Noise - Sound Pressure	70.5 dBA	71.6 dBA	71.6 dBA
Input Power Voltage	40 to 48; 200 to 240;	40 to 48; 200 to 240;	40 to 48; 200 to 240;
Storage OS Requirements (for selected major version)			
Recommended Version	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2
Minimum OS	9.19.1RC1	9.19.1RC1	9.19.1RC1
Maximum OS	9.19.1P2	9.19.1P2	9.19.1P2
Software and Firmware * indicates that firmware is bundled with Storage OS Version			
BIOS	21.4.1, 21.3*	20.8*	20.8*
BMC	19.4*	18.6*	18.6*
Product Standards Compliance			
Certifications EMC/EMI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI

	ASA A50 Single Chassis HA Pair	ASA A70 Single Chassis HA Pair	ASA A90 Single Chassis HA Pair VER2
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Certifications safety	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS
Certifications Safety/EMC/EMI	EAC, UKRSEPRO	EAC, UKRSEPRO	EAC, UKRSEPRO
Certifications Safety/EMC/EMI/RoHS	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC
Standards EMC/EMI	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835
Standards Safety	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)
System Availability & Support			
Release Date	Feb 2025	Sep 2024	May 2026
End of Availability (EOA)	-	-	-
End of Support (EOS)	-	-	-
WAFL Cluster Limits			
Maximum character length for Snapshot copy names			
Snapshot	255	255	255
Maximum number of LUN Snapshot Copies			
Consistency group	1,023	1,023	1,023
Node	1,023,000	1,023,000	1,023,000
HA Pair	2,046,000	2,046,000	2,046,000
Quality of Service Cluster Limits			
Maximum number of Policy Groups			
Cluster	12,000	12,000	12,000
Maximum number of QoS user workloads			
Cluster	40,000	40,000	40,000
Data Protection Cluster Limits			
Maximum fan-out from source for DP mirror			
Volume	8	20	20
Maximum number of clusters that can be peered			
Cluster	400	400	400
Maximum number of concurrent Snap Mirror or SnapVault transfers			
Node	100	250	250
Maximum number of data protection (DP) mirrors and/or SnapVault relationships			
Volume	1	1	1
Node	500	1,000	1,000
HA Pair	1,000	2,000	2,000
Cluster	2,000	6,000	6,000
Maximum number of SnapMirror Synchronous relationships			
Volume	1	1	1
Node	400	400	400
HA Pair	400	400	400

	ASA A50 Single Chassis HA Pair	ASA A70 Single Chassis HA Pair	ASA A90 Single Chassis HA Pair VER2
Specifications			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Number of storage virtual machine disaster recovery (SVM DR) relationship			
Cluster	N/A	128	128
Maximum Number of FlexGroups and/or Consistency Groups supported in (SVM DR) relationship			
Cluster	N/A	32	32
Maximum Number of Concurrent SnapDiff Sessions			
Node	64	64	64
HA Pair	128	128	128
Consistency Groups			
Maximum Number of Consistency Groups			
Cluster	1,600	1,600	1,600
Maximum Number of Consistency Groups and Parent Consistency Groups			
Cluster	1,600	1,600	1,600
Maximum Number of Parent Consistency Groups			
Cluster	1,600	1,600	1,600
Maximum Number of Child Consistency Groups in a Parent Consistency Group			
Parent consistency group	5	5	5
Storage Availability Zone Cluster Limits			
Maximum FC queue depth available (SAZ)			
Port	2,048	2,048	2,048
Maximum I/O queue count available - NVMe/FC (SAZ)			
Regular Priority Controller	4	4	4
High Priority Controller	6	6	8
Maximum I/O queue count available - NVMe/TCP (SAZ)			
Regular Priority Controller	2	2	2
High Priority Controller	4	4	8
Maximum I/O queue depth available - NVMe/FC (SAZ)			
Regular Priority Queue	32	32	32
High Priority Queue	32	32	64
Maximum I/O queue depth available - NVMe/TCP (SAZ)			
Regular Priority Queue	128	128	128
High Priority Queue	128	128	128
Maximum number of controllers - NVMe/FC (SAZ)			
Port	256	256	256
Maximum number of controllers - NVMe/TCP (SAZ)			
Node	256	512	2,048
Maximum number of igroups (SAZ)			
Node	4,096	4,096	4,096
HA Pair	8,192	8,192	8,192
Cluster	32,768	32,768	32,768

Specifications	ASA A50 Single Chassis HA Pair	ASA A70 Single Chassis HA Pair	ASA A90 Single Chassis HA Pair VER2
			
	ONTAP 9.19.1	ONTAP 9.19.1	ONTAP 9.19.1
Maximum number of IP Data Lifs (iSCSI + NVMe/TCP)			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	512	512	512
Cluster	4,096	4,096	4,096
Maximum number of iSCSI sessions (SAZ)			
Node	8,192	8,192	8,192
HA Pair	16,384	16,384	16,384
Cluster	65,536	65,536	65,536
Maximum number of iSCSI/FCP initiators			
igroup	256	256	256
Node	4,096	4,096	4,096
HA Pair	8,192	8,192	8,192
Cluster	32,768	32,768	32,768
Maximum number of LIFS - FCP (SAZ)			
Port	32	32	32
Portset	32	32	32
SVM	256	256	256
Node	512	512	512
HA Pair	1,024	1,024	1,024
Cluster	4,096	4,096	4,096
Maximum number of LIFS - NVMe/FC			
Port	16	16	16
SVM	24	24	24
Node	32	32	32
HA Pair	32	32	32
Cluster	32	32	32
Maximum number of LUN mappings (SAZ)			
igroup	4,096	4,096	4,096
Node	2,500	2,500	5,000
HA Pair	5,000	5,000	10,000
Cluster	30,000	30,000	30,000
Maximum number of namespace mappings (SAZ)			
Subsystem	1,024	1,024	1,024
Node	2,500	2,500	5,000
HA Pair	5,000	5,000	10,000
Cluster	30,000	30,000	30,000
Maximum number of NVMe/oF hosts			
Subsystem	64	64	64
Maximum number of portsets (SAZ)			
Node	4,096	4,096	4,096
HA Pair	8,192	8,192	8,192
Cluster	32,768	32,768	32,768
Maximum Number of SAN (iSCSI/FCP) Hosts (ITNs)			
Port	512	512	512
Node	8,192	8,192	8,192
HA Pair	16,384	16,384	16,384
Cluster	65,536	65,536	65,536
Maximum number of Storage Units			
Node	2,500	2,500	5,000
HA Pair	5,000	5,000	10,000
Cluster	30,000	30,000	30,000

Specifications	ASA A50 Single Chassis HA Pair		ASA A70 Single Chassis HA Pair		ASA A90 Single Chassis HA Pair VER2	
						
	ONTAP 9.19.1		ONTAP 9.19.1		ONTAP 9.19.1	
Maximum number of storage virtual machines (SVMs)						
Cluster		256	256	256		
Maximum number of subsystems (SAZ)						
SVM		8,192	8,192	8,192	8,192	
Cluster		8,192	8,192	8,192	8,192	
Maximum Storage Unit size (TiB)						
Storage Unit		128	128	128		
SnapMirror Active Sync (symmetric active/active)						
Maximum Number of Nodes in SnapMirror Active Sync relationships for NVMe						
Node		2	2	2		
Maximum Number of NS Maps						
Consistency group		256	256	256		
Maximum Number of Subsystem						
Consistency group		16	16	16		
Maximum Number of Unique Namespaces Supported						
Node		400	400	400		
Maximum Number of Nodes in SnapMirror Active Sync relationships						
Cluster		4	4	4		
Maximum number of constituent LUNs in SnapMirror Active Sync relationships (Constituent LUNs)						
Consistency group		80	80	80		
HA Pair (Non-Scalable)		400	400	400		
Maximum number of Consistency Groups in SnapMirror Active Sync relationships						
HA Pair (Non-Scalable)		50	50	50		
Maximum Number of LUN Maps in SnapMirror Active Sync relationships						
Node		4,096	4,096	4,096		
Maximum Number of LUNs in SnapMirror Active Sync relationships						
Volume		512	512	512		
Maximum Number of SAN LIFs in SnapMirror Active Sync relationships						
Vserver		128	128	128		

Specifications	ASA A90 Single Chassis HA Pair	ASA C30 Single Chassis HA Pair
		
	ONTAP 9.19.1	ONTAP 9.19.1
Storage Limits		
Max Number of Drives (Total)	240	48
Internal Drives count	Max: 48 per Chassis;	Max: 24 per Chassis;
Max number of Capacity Flash NVMe SSD Drives	N/A	Max: 48 per HA Pair;
Max number of NVMe SSD Drives	Max: 240 per HA Pair;	N/A
Max number of FS4483 shelves	1 internal	N/A
Max number of NS224 shelves	8 external	1 internal + 1 external
Max number of NS224 w/ NSM100B shelves	8 external	1 external
Capacity Limits		
Marketing Maximum Raw Capacity (GB)		
Node	4,298,000	1,473,600
HA Pair	4,298,000	1,473,600
Core Cluster Limits		
Maximum Number of VLANs		
Node	512	512
Maximum IPsec Policies		
SVM	256	N/A
Cluster	1,500	N/A
Maximum IPsec Policies (If using HW Offload)		
SVM	N/A	40
Cluster	N/A	40
Maximum IPsec Policies (If not using HW Offload)		
SVM	N/A	256
Cluster	N/A	1,500
Maximum number of Intercluster LIFs		
Node	8	8
Maximum Number of IPspaces		
Cluster	512	512
System Maximums and Limits		
Max Nodes per Cluster (NAS / SAN)	Not Supported / 12	Not Supported / 8
Max FabricPool Size	Not Supported	Not Supported
Max FlexGroup Data Constituent Size	Not Supported	Not Supported
Max Infinite Volume Data Constituent Size	Not Supported	Not Supported
Min Root Volume Size	-	-
NetApp Volume Encryption	Dual-layer Encryption	Dual-layer Encryption
Processor		
Processor Model	64-bit 32-Core 2.0GHz	64-bit 10-core 1.30 GHz
Processor Architecture	64 bit	64 bit
Processor Speed	2.00 Ghz	1.30 Ghz
Processor Count (Per Node)	2	1
Processor Count (Per Config)	4	2
Processor Cores (Per CPU)	32	10
Processor Cores (Per Node)	64	10
Processor Cores (Per Config)	128	20
Memory		
NVMEM (Per Node)	N/A	8 GB
NVMEM (Per Config)	N/A	16 GB
NVRAM (Per Node)	64 GB	N/A

	ASA A90 Single Chassis HA Pair	ASA C30 Single Chassis HA Pair
Specifications		
	ONTAP 9.19.1	ONTAP 9.19.1
NVRAM (Per Config)	128 GB	N/A
RAM (Per Node)	1024 GB	64 GB
RAM (Per Config)	2048 GB	128 GB
Onboard Ports		
Ethernet Ports	-	-
UTA2 Ports	-	-
Expansion Slots	18 x IO Module (per System)	8 x IO Module (per System)
SAS Ports	-	-
Physical Characteristics		
Rack Units	4	2
Chassis Height	6.89" (17.5 cm)	3.43" (8.7 cm)
Chassis Width with Mounting Flanges	19.02" (48.3 cm)	19.02" (48.3 cm)
Chassis Width without Mounting Flanges	17.6" (44.7 cm)	17.6" (44.7 cm)
Chassis Depth with Cable Mgmt	38.27" (97.2 cm)	-
Chassis Depth without Cable Mgmt	34.49" (87.6 cm)	22.05" (56 cm)
Chassis Weight		
System Clearance Dimensions		
Front Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)
Front Clearance (Maintenance)	36.41" (92.4 cm)	24.03" (61 cm)
Rear Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)
Rear Clearance (Maintenance)	36.01" (91.4 cm)	16.94" (43 cm)
Environmental Requirements		
Operating Temperature Range	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C
Storage Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Transit Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Operating Relative Humidity	8 to 80 %	8 to 80 %
Storage Relative Humidity	10 to 95 %	10 to 95 %
Transit Relative Humidity	10 to 95 %	10 to 95 %
Operating Altitude Range	Up to 10000.0 ft Up to 3048.0 m	Up to 10000.0 ft Up to 3048.0 m
Storage Altitude Range	Up to 40000.0 ft Up to 12192.0 m	Up to 40000.0 ft Up to 12192.0 m
Transit Altitude Range	Up to 39989.8 ft Up to 12192 m	Up to 39989.8 ft Up to 12192 m
Acoustic Noise - Sound Power	8.6 Bels	8 Bels
Acoustic Noise - Sound Pressure	71.6 dBA	70.5 dBA
Input Power Voltage	40 to 48; 200 to 240;	40 to 48; 200 to 240;
Storage OS Requirements (for selected major version)		
Recommended Version	9.19.1, 9.19.1P2	9.19.1, 9.19.1P2
Minimum OS	9.19.1RC1	9.19.1RC1
Maximum OS	9.19.1P2	9.19.1P2
Software and Firmware * indicates that firmware is bundled with Storage OS Version		
BIOS	20.8*	21.4.1, 21.3*
BMC	18.6*	19.4*
Product Standards Compliance		
Certifications EMC/EMI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI

	ASA A90 Single Chassis HA Pair	ASA C30 Single Chassis HA Pair
Specifications		
	ONTAP 9.19.1	ONTAP 9.19.1
Certifications safety	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K U-SoR, IRAM, NOM, NRCS, SONCAP, TBS
Certifications Safety/EMC/EMI	EAC, UKRSEPRO	EAC, UKRSEPRO
Certifications Safety/EMC/EMI/RoHS	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC
Standards EMC/EMI	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55032, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835
Standards Safety	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 15598-1, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)
System Availability & Support		
Release Date	Sep 2024	May 2025
End of Availability (EOA)	-	-
End of Support (EOS)	-	-
WAFL Cluster Limits		
Maximum character length for Snapshot copy names		
Snapshot	255	255
Maximum number of LUN Snapshot Copies		
Consistency group	1,023	1,023
Node	1,023,000	1,023,000
HA Pair	2,046,000	2,046,000
Quality of Service Cluster Limits		
Maximum number of Policy Groups		
Cluster	12,000	12,000
Maximum number of QoS user workloads		
Cluster	40,000	40,000
Data Protection Cluster Limits		
Maximum fan-out from source for DP mirror		
Volume	20	8
Maximum number of clusters that can be peered		
Cluster	400	400
Maximum number of concurrent Snap Mirror or SnapVault transfers		
Node	250	100
Maximum number of data protection (DP) mirrors and/or SnapVault relationships		
Volume	1	1
Node	1,000	500
HA Pair	2,000	1,000
Cluster	6,000	2,000
Maximum number of SnapMirror Synchronous relationships		
Volume	1	1
Node	400	400
HA Pair	400	400

	ASA A90 Single Chassis HA Pair	ASA C30 Single Chassis HA Pair
Specifications		
	ONTAP 9.19.1	ONTAP 9.19.1
Maximum Number of storage virtual machine disaster recovery (SVM DR) relationship		
Cluster	128	N/A
Maximum Number of FlexGroups and/or Consistency Groups supported in (SVM DR) relationship		
Cluster	32	N/A
Maximum Number of Concurrent SnapDiff Sessions		
Node	64	64
HA Pair	128	128
Consistency Groups		
Maximum Number of Consistency Groups		
Cluster	1,600	1,600
Maximum Number of Consistency Groups and Parent Consistency Groups		
Cluster	1,600	1,600
Maximum Number of Parent Consistency Groups		
Cluster	1,600	1,600
Maximum Number of Child Consistency Groups in a Parent Consistency Group		
Parent consistency group	5	5
Storage Availability Zone Cluster Limits		
Maximum FC queue depth available (SAZ)		
Port	2,048	2,048
Maximum I/O queue count available - NVMe/FC (SAZ)		
Regular Priority Controller	4	4
High Priority Controller	8	6
Maximum I/O queue count available - NVMe/TCP (SAZ)		
Regular Priority Controller	2	2
High Priority Controller	8	4
Maximum I/O queue depth available - NVMe/FC (SAZ)		
Regular Priority Queue	32	32
High Priority Queue	64	32
Maximum I/O queue depth available - NVMe/TCP (SAZ)		
Regular Priority Queue	128	128
High Priority Queue	128	128
Maximum number of controllers - NVMe/FC (SAZ)		
Port	256	256
Maximum number of controllers - NVMe/TCP (SAZ)		
Node	2,048	128
Maximum number of igroups (SAZ)		
Node	4,096	2,048
HA Pair	8,192	4,096
Cluster	32,768	16,384

	ASA A90 Single Chassis HA Pair	ASA C30 Single Chassis HA Pair
Specifications		
	ONTAP 9.19.1	ONTAP 9.19.1
Maximum number of IP Data Lifs (iSCSI + NVMe/TCP)		
Port	32	32
Portset	32	32
SVM	256	256
Node	512	512
HA Pair	512	512
Cluster	4,096	4,096
Maximum number of iSCSI sessions (SAZ)		
Node	8,192	4,096
HA Pair	16,384	8,192
Cluster	65,536	32,768
Maximum number of iSCSI/FCP initiators		
igroup	256	256
Node	4,096	2,048
HA Pair	8,192	4,096
Cluster	32,768	16,384
Maximum number of LIFS - FCP (SAZ)		
Port	32	32
Portset	32	32
SVM	256	256
Node	512	512
HA Pair	1,024	1,024
Cluster	4,096	4,096
Maximum number of LIFS - NVMe/FC		
Port	16	16
SVM	24	24
Node	32	32
HA Pair	32	32
Cluster	32	32
Maximum number of LUN mappings (SAZ)		
igroup	4,096	4,096
Node	5,000	500
HA Pair	10,000	1,000
Cluster	30,000	4,000
Maximum number of namespace mappings (SAZ)		
Subsystem	1,024	1,024
Node	5,000	500
HA Pair	10,000	1,000
Cluster	30,000	4,000
Maximum number of NVMe/oF hosts		
Subsystem	64	64
Maximum number of portsets (SAZ)		
Node	4,096	2,048
HA Pair	8,192	4,096
Cluster	32,768	16,384
Maximum Number of SAN (iSCSI/FCP) Hosts (ITNs)		
Port	512	512
Node	8,192	4,096
HA Pair	16,384	8,192
Cluster	65,536	32,768
Maximum number of Storage Units		
Node	5,000	500
HA Pair	10,000	1,000
Cluster	30,000	4,000

Specifications	ASA A90 Single Chassis HA Pair		ASA C30 Single Chassis HA Pair	
				
	ONTAP 9.19.1		ONTAP 9.19.1	
Maximum number of storage virtual machines (SVMs)				
Cluster	256		256	
Maximum number of subsystems (SAZ)				
SVM	8,192		8,192	
Cluster	8,192		8,192	
Maximum Storage Unit size (TiB)				
Storage Unit	128		128	
SnapMirror Active Sync (symmetric active/active)				
Maximum Number of Nodes in SnapMirror Active Sync relationships for NVMe				
Node	2		2	
Maximum Number of NS Maps				
Consistency group	256		256	
Maximum Number of Subsystem				
Consistency group	16		16	
Maximum Number of Unique Namespaces Supported				
Node	400		400	
Maximum Number of Nodes in SnapMirror Active Sync relationships				
Cluster	4		4	
Maximum number of constituent LUNs in SnapMirror Active Sync relationships (Constituent LUNs)				
Consistency group	80		80	
HA Pair (Non-Scalable)	400		400	
Maximum number of Consistency Groups in SnapMirror Active Sync relationships				
HA Pair (Non-Scalable)	50		50	
Maximum Number of LUN Maps in SnapMirror Active Sync relationships				
Node	4,096		4,096	
Maximum Number of LUNs in SnapMirror Active Sync relationships				
Volume	512		512	
Maximum Number of SAN LIFs in SnapMirror Active Sync relationships				
Vserver	128		128	

Specifications
Storage Limits
Max Number of Drives (Total)
Internal Drives count
Max number of Capacity Flash NVMe SSD Drives
Max number of NVMe SSD Drives
Max number of FS4483 shelves
Max number of NS224 shelves
Max number of NS224 w/ NSM100B shelves
Capacity Limits
Marketing Maximum Raw Capacity (GB)
Node
HA Pair
Core Cluster Limits
Maximum Number of VLANs
Node
Maximum IPsec Policies
SVM
Cluster
Maximum IPsec Policies (If using HW Offload)
SVM
Cluster
Maximum IPsec Policies (If not using HW Offload)
SVM
Cluster
Maximum number of Intercluster LIFs
Node
Maximum Number of IPspaces
Cluster
System Maximums and Limits
Max Nodes per Cluster (NAS / SAN)
Max FabricPool Size
Max FlexGroup Data Constituent Size
Max Infinite Volume Data Constituent Size
Min Root Volume Size
NetApp Volume Encryption
Processor
Processor Model
Processor Architecture
Processor Speed
Processor Count (Per Node)
Processor Count (Per Config)
Processor Cores (Per CPU)
Processor Cores (Per Node)
Processor Cores (Per Config)
Memory
NVMEM (Per Node)
NVMEM (Per Config)
NVRAM (Per Node)

Specifications
NVRAM (Per Config)
RAM (Per Node)
RAM (Per Config)
Onboard Ports
Ethernet Ports
UTA2 Ports
Expansion Slots
SAS Ports
Physical Characteristics
Rack Units
Chassis Height
Chassis Width with Mounting Flanges
Chassis Width without Mounting Flanges
Chassis Depth with Cable Mgmt
Chassis Depth without Cable Mgmt
Chassis Weight
System Clearance Dimensions
Front Clearance (Cooling)
Front Clearance (Maintenance)
Rear Clearance (Cooling)
Rear Clearance (Maintenance)
Environmental Requirements
Operating Temperature Range
Storage Temperature Range
Transit Temperature Range
Operating Relative Humidity
Storage Relative Humidity
Transit Relative Humidity
Operating Altitude Range
Storage Altitude Range
Transit Altitude Range
Acoustic Noise - Sound Power
Acoustic Noise - Sound Pressure
Input Power Voltage
Storage OS Requirements (for selected major version)
Recommended Version
Minimum OS
Maximum OS
Software and Firmware * indicates that firmware is bundled with Storage OS Version
BIOS
BMC
Product Standards Compliance
Certifications EMC/EMI

Specifications
Certifications safety
Certifications Safety/EMC/EMI
Certifications Safety/EMC/EMI/RoHS
Standards EMC/EMI
Standards Safety
System Availability & Support
Release Date
End of Availability (EOA)
End of Support (EOS)
WAFL Cluster Limits
Maximum character length for Snapshot copy names
Snapshot
Maximum number of LUN Snapshot Copies
Consistency group
Node
HA Pair
Quality of Service Cluster Limits
Maximum number of Policy Groups
Cluster
Maximum number of QoS user workloads
Cluster
Data Protection Cluster Limits
Maximum fan-out from source for DP mirror
Volume
Maximum number of clusters that can be peered
Cluster
Maximum number of concurrent Snap Mirror or SnapVault transfers
Node
Maximum number of data protection (DP) mirrors and/or SnapVault relationships
Volume
Node
HA Pair
Cluster
Maximum number of SnapMirror Synchronous relationships
Volume
Node
HA Pair

Specifications
Maximum Number of storage virtual machine disaster recovery (SVM DR) relationship
Cluster
Maximum Number of FlexGroups and/or Consistency Groups supported in (SVM DR) relationship
Cluster
Maximum Number of Concurrent SnapDiff Sessions
Node
HA Pair
Consistency Groups
Maximum Number of Consistency Groups
Cluster
Maximum Number of Consistency Groups and Parent Consistency Groups
Cluster
Maximum Number of Parent Consistency Groups
Cluster
Maximum Number of Child Consistency Groups in a Parent Consistency Group
Parent consistency group
Storage Availability Zone
Cluster Limits
Maximum FC queue depth available (SAZ)
Port
Maximum I/O queue count available - NVMe/FC (SAZ)
Regular Priority Controller
High Priority Controller
Maximum I/O queue count available - NVMe/TCP (SAZ)
Regular Priority Controller
High Priority Controller
Maximum I/O queue depth available - NVMe/FC (SAZ)
Regular Priority Queue
High Priority Queue
Maximum I/O queue depth available - NVMe/TCP (SAZ)
Regular Priority Queue
High Priority Queue
Maximum number of controllers - NVMe/FC (SAZ)
Port
Maximum number of controllers - NVMe/TCP (SAZ)
Node
Maximum number of igroups (SAZ)
Node
HA Pair
Cluster

Specifications
Maximum number of IP Data Lifs (iSCSI + NVMe/TCP)
Port
Portset
SVM
Node
HA Pair
Cluster
Maximum number of iSCSI sessions (SAZ)
Node
HA Pair
Cluster
Maximum number of iSCSI/FCP initiators
igroup
Node
HA Pair
Cluster
Maximum number of LIFS - FCP (SAZ)
Port
Portset
SVM
Node
HA Pair
Cluster
Maximum number of LIFS - NVMe/FC
Port
SVM
Node
HA Pair
Cluster
Maximum number of LUN mappings (SAZ)
igroup
Node
HA Pair
Cluster
Maximum number of namespace mappings (SAZ)
Subsystem
Node
HA Pair
Cluster
Maximum number of NVMe/oF hosts
Subsystem
Maximum number of portsets (SAZ)
Node
HA Pair
Cluster
Maximum Number of SAN (iSCSI/FCP) Hosts (ITNs)
Port
Node
HA Pair
Cluster
Maximum number of Storage Units
Node
HA Pair
Cluster

Specifications
Maximum number of storage virtual machines (SVMs)
Cluster
Maximum number of subsystems (SAZ)
SVM
Cluster
Maximum Storage Unit size (TiB)
Storage Unit
SnapMirror Active Sync (symmetric active/active)
Maximum Number of Nodes in SnapMirror Active Sync relationships for NVMe
Node
Maximum Number of NS Maps
Consistency group
Maximum Number of Subsystem
Consistency group
Maximum Number of Unique Namespaces Supported
Node
Maximum Number of Nodes in SnapMirror Active Sync relationships
Cluster
Maximum number of constituent LUNs in SnapMirror Active Sync relationships (Consituent LUNs)
Consistency group
HA Pair (Non-Scalable)
Maximum number of Consistency Groups in SnapMirror Active Sync relationships
HA Pair (Non-Scalable)
Maximum Number of LUN Maps in SnapMirror Active Sync relationships
Node
Maximum Number of LUNs in SnapMirror Active Sync relationships
Volume
Maximum Number of SAN LIFs in SnapMirror Active Sync relationships
Vserver