

Specifications	EF50 Duplex 100GbE All-Flash	EF80 Duplex 100GbE All-Flash
		
	SANtricity OS 12.00R1	SANtricity OS 12.00R1
Storage Limits		
Full Storage Limit Matrix	Supported Shelves/Drives	Supported Shelves/Drives
Max Number of Drives (Total)	24	24
Internal Drives count	Min: 6 per Chassis; Max: 24 per Chassis;	Min: 6 per Chassis; Max: 24 per Chassis;
Max number of Capacity Flash NVMe SSD Drives	Max: 24 per HA Pair;	Max: 24 per HA Pair;
Max number of NVMe SSD Drives	Max: 24 per HA Pair;	Max: 24 per HA Pair;
Max number of NE224 shelves	1 internal	1 internal
Capacity Limits		
Marketing Maximum Raw Capacity (GB)		
Node	1,473,600	1,473,600
HA Pair	1,473,600	1,473,600
System Maximums and Limits		
Max Volume Size (EB)	-	-
Max Volume Count	-	-
Max Drives per Disk Pool	240	420
Max Disk Pool Volumes	2048	2048
Max Vol size for a Disk Pool volume (TB)	4096	4096
Max Disk Pools	20	20
Max Partitions	512	512
Max Volumes per Partition	256	256
Flash Read Cache (GB) (Min/Max)	SSD (400/5120)	SSD (400/8192)
Max Destaging Cache-to-Flash Size (GB)	12	12
Processor		
Processor Model	64-bit 8-core 2.00 Ghz	64-bit 16-core 2.0 GHz
Processor Architecture	64 bit	64 bit
Processor Speed	2.00 Ghz	2.00 Ghz
Processor Count (Per Node)	1	1
Processor Count (Per Config)	2	2
Processor Cores (Per CPU)	8	16
Processor Cores (Per Node)	8	16
Processor Cores (Per Config)	16	32
Technical Specifications		
System Memory	64 GB DDR4	128 GB DDR4
PCI Interface	PCIe4	PCIe5
Controller Count	2	2
Full Disk Encryption Support	yes	yes
Data Assurance (T10 PI) Support	yes	yes
Base board Host Interface (per Controller)	-	-
OOB Management Port Interface (per Controller)	1 x Ethernet (1 Gbps)	1 x Ethernet (1 Gbps)
DDP Support	yes	yes
SSD support in a Disk Pool	YES	YES
Flash Device/OS/De-Stage (GB)	-	-
Physical Characteristics		
Rack Units	2	2
Height	3.43" (8.7 cm)	3.43" (8.7 cm)
Width with Mounting Flanges	19.02" (48.3 cm)	19.02" (48.3 cm)
Width without Mounting Flanges	17.6" (44.7 cm)	17.6" (44.7 cm)

Specifications	EF50 Duplex 100GbE All-Flash	EF80 Duplex 100GbE All-Flash
		
	SANtricity OS 12.00R1	SANtricity OS 12.00R1
Depth With Cable Mgmt	-	-
Depth Without Cable Mgmt	21.38" (54.3 cm)	21.38" (54.3 cm)
Weight	60.08 lb (27.25 kg)	60.72 lb (27.54 kg)
System Clearance Dimensions		
Front Clearance (Cooling)	6.03" (15.3 cm)	6.03" (15.3 cm)
Front Clearance (Maintenance)	24.03" (61 cm)	24.03" (61 cm)
Rear Clearance (Cooling)	24.03" (61 cm)	24.03" (61 cm)
Rear Clearance (Maintenance)	36.01" (91.4 cm)	36.01" (91.4 cm)
Environmental Requirements		
Operating Temperature Range	50 to 95 deg F 10 to 35 deg C	50 to 95 deg F 10 to 35 deg C
Storage Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Transit Temperature Range	-40 to 158 deg F -40 to 70 deg C	-40 to 158 deg F -40 to 70 deg C
Operating Relative Humidity	20 to 80 %	20 to 80 %
Storage Relative Humidity	5 to 95 %	5 to 95 %
Transit Relative Humidity	10 to 95 %	10 to 95 %
Operating Altitude Range	0.0 to 10000.0 ft 0.0 to 3048.0 m	0.0 to 10000.0 ft 0.0 to 3048.0 m
Storage Altitude Range	-1000.0 to 40000.0 ft -304.8 to 12192.0 m	-1000.0 to 40000.0 ft -304.8 to 12192.0 m
Transit Altitude Range	-	-
Acoustic Noise - Sound Power	-	-
Acoustic Noise - Sound Pressure	-	-
Input Power Voltage	200 to 240;	200 to 240;
Storage OS Requirements (for selected major version)		
Recommended Version	12.00R0, 12.00R1	12.00R0, 12.00R1
Minimum OS	12.00R0	12.00R0
Maximum OS	12.00R1	12.00R1
Product Standards Compliance		
Certifications EMC/EMI	AMCA, FCC, ICES, KC, Morocco, VCCI	AMCA, FCC, ICES, KC, Morocco, VCCI
Certifications safety	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS	BIS, CB, CSA, G_K_U-SoR, IRAM, NOM, NRCS, SONCAP, TBS
Certifications Safety/EMC/EMI	EAC, UKRSEPRO	EAC, UKRSEPRO
Certifications Safety/EMC/EMI/RoHS	BSMI, CE DoC, UKCA DoC	BSMI, CE DoC, UKCA DoC
Standards EMC/EMI	BS-EN-55024, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835	BS-EN-55024, BS-EN55035, CISPR 32, EN55022, EN55024, EN55032, EN55035, EN61000-3-2, EN61000-3-3, FCC Part 15 Class A, ICES-003, KS C 9832, KS C 9835
Standards Safety	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 14336, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)	ANSI/UL60950-1, ANSI/UL62368-1, BS-EN62368-1, CAN/CSA C22.2 No. 60950-1, CAN/CSA C22.2 No. 62368-1, CNS 14336, EN60825-1, EN62368-1, IEC 62368-1, IEC60950-1, IS 13252(part 1)
System Availability & Support		
Release Date	Mar 2026	Mar 2026
End of Availability (EOA)	-	-
End of Support (EOS)	-	-